



Python Telegram Bot Documentation

Release 13.1

Leandro Toledo

Dec 31, 2020

1	Guides and tutorials	1
2	Examples	3
3	Reference	5
3.1	telegram.ext package	5
3.1.1	telegram.ext.Updater	5
3.1.2	telegram.ext.Dispatcher	8
3.1.3	telegram.ext.DispatcherHandlerStop	12
3.1.4	telegram.ext.filters Module	12
3.1.5	telegram.ext.Job	27
3.1.6	telegram.ext.JobQueue	28
3.1.7	telegram.ext.MessageQueue	32
3.1.8	telegram.ext.DelayQueue	33
3.1.9	telegram.ext.CallbackContext	34
3.1.10	telegram.ext.Defaults	36
3.1.11	Handlers	37
3.1.12	Persistence	70
3.2	telegram package	77
3.2.1	telegram.Animation	77
3.2.2	telegram.Audio	79
3.2.3	telegram.Bot	80
3.2.4	telegram.BotCommand	133
3.2.5	telegram.CallbackQuery	134
3.2.6	telegram.Chat	138
3.2.7	telegram.ChatAction	146
3.2.8	telegram.ChatLocation	146
3.2.9	telegram.ChatMember	147
3.2.10	telegram.ChatPermissions	150
3.2.11	telegram.ChatPhoto	151
3.2.12	telegram.constants Module	152
3.2.13	telegram.Contact	157
3.2.14	telegram.Dice	158
3.2.15	telegram.Document	159
3.2.16	telegram.error module	160
3.2.17	telegram.File	161
3.2.18	telegram.ForceReply	162
3.2.19	telegram.InlineKeyboardButton	163
3.2.20	telegram.InlineKeyboardMarkup	164
3.2.21	telegram.InputFile	165
3.2.22	telegram.InputMedia	166

3.2.23	telegram.InputMediaAnimation	166
3.2.24	telegram.InputMediaAudio	168
3.2.25	telegram.InputMediaDocument	169
3.2.26	telegram.InputMediaPhoto	170
3.2.27	telegram.InputMediaVideo	171
3.2.28	telegram.KeyboardButton	173
3.2.29	telegram.KeyboardButtonPollType	173
3.2.30	telegram.Location	174
3.2.31	telegram.LoginUrl	175
3.2.32	telegram.Message	176
3.2.33	telegram.MessageId	194
3.2.34	telegram.MessageEntity	195
3.2.35	telegram.ParseMode	196
3.2.36	telegram.PhotoSize	197
3.2.37	telegram.Poll	198
3.2.38	telegram.PollAnswer	200
3.2.39	telegram.PollOption	201
3.2.40	telegram.ProximityAlertTriggered	201
3.2.41	telegram.ReplyKeyboardRemove	202
3.2.42	telegram.ReplyKeyboardMarkup	202
3.2.43	telegram.ReplyMarkup	205
3.2.44	telegram.TelegramObject	205
3.2.45	telegram.Update	206
3.2.46	telegram.User	208
3.2.47	telegram.UserProfilePhotos	213
3.2.48	telegram.Venue	214
3.2.49	telegram.Video	215
3.2.50	telegram.VideoNote	216
3.2.51	telegram.Voice	218
3.2.52	telegram.WebhookInfo	219
3.2.53	Stickers	220
3.2.54	Inline Mode	223
3.2.55	Payments	261
3.2.56	Games	268
3.2.57	Passport	270
3.3	telegram.utils package	283
3.3.1	telegram.utils.helpers Module	283
3.3.2	telegram.utils.promise.Promise	287
3.3.3	telegram.utils.request.Request	288
3.3.4	telegram.utils.types Module	289
3.4	Changelog	290
3.4.1	Changelog	290

Python Module Index	313
----------------------------	------------

Index	315
--------------	------------

CHAPTER 1

Guides and tutorials

If you're just starting out with the library, we recommend following our “[Your first Bot](#)” tutorial that you can find on our [wiki](#). On our wiki you will also find guides like how to use handlers, webhooks, emoji, proxies and much more.

CHAPTER 2

Examples

A great way to learn is by looking at examples. Ours can be found at our [github](#) in the examples folder.

Below you can find a reference of all the classes and methods in python-telegram-bot. Apart from the *telegram.ext* package the objects should reflect the types defined in the [official telegram bot api documentation](#).

3.1 telegram.ext package

3.1.1 telegram.ext.Updater

```
class telegram.ext.Updater(token: str = None, base_url: str = None, workers: int = 4,
                           bot: telegram.bot.Bot = None, private_key: bytes = None, private_key_password: bytes = None, user_sig_handler: Callable = None, request_kwargs: Dict[str, Any] = None, persistence: BasePersistence = None, defaults: Defaults = None, use_context: bool = True, dispatcher: telegram.ext.dispatcher.Dispatcher = None, base_file_url: str = None)
```

Bases: object

This class, which employs the *telegram.ext.Dispatcher*, provides a frontend to *telegram.Bot* to the programmer, so they can focus on coding the bot. Its purpose is to receive the updates from Telegram and to deliver them to said dispatcher. It also runs in a separate thread, so the user can interact with the bot, for example on the command line. The dispatcher supports handlers for different kinds of data: Updates from Telegram, basic text commands and even arbitrary types. The updater can be started as a polling service or, for production, use a webhook to receive updates. This is achieved using the *WebhookServer* and *WebhookHandler* classes.

bot

The bot used with this Updater.

Type *telegram.Bot*

user_sig_handler

Optional. Function to be called when a signal is received.

Type function

update_queue

Queue for the updates.

Type Queue

job_queue

Jobqueue for the updater.

Type `telegram.ext.JobQueue`

dispatcher

Dispatcher that handles the updates and dispatches them to the handlers.

Type `telegram.ext.Dispatcher`

running

Indicates if the updater is running.

Type `bool`

persistence

Optional. The persistence class to store data that should be persistent over restarts.

Type `telegram.ext.BasePersistence`

use_context

Optional. True if using context based callbacks.

Type `bool`

Parameters

- **token** (`str`, optional) – The bot’s token given by the @BotFather.
- **base_url** (`str`, optional) – Base_url for the bot.
- **base_file_url** (`str`, optional) – Base_file_url for the bot.
- **workers** (`int`, optional) – Amount of threads in the thread pool for functions decorated with `@run_async` (ignored if *dispatcher* argument is used).
- **bot** (`telegram.Bot`, optional) – A pre-initialized bot instance (ignored if *dispatcher* argument is used). If a pre-initialized bot is used, it is the user’s responsibility to create it using a *Request* instance with a large enough connection pool.
- **dispatcher** (`telegram.ext.Dispatcher`, optional) – A pre-initialized dispatcher instance. If a pre-initialized dispatcher is used, it is the user’s responsibility to create it with proper arguments.
- **private_key** (`bytes`, optional) – Private key for decryption of telegram passport data.
- **private_key_password** (`bytes`, optional) – Password for above private key.
- **user_sig_handler** (`function`, optional) – Takes *signum*, *frame* as positional arguments. This will be called when a signal is received, defaults are (SIGINT, SIGTERM, SIGABRT) settable with *idle*.
- **request_kwargs** (`dict`, optional) – Keyword args to control the creation of a *telegram.utils.request.Request* object (ignored if *bot* or *dispatcher* argument is used). The *request_kwargs* are very useful for the advanced users who would like to control the default timeouts and/or control the proxy used for http communication.
- **use_context** (`bool`, optional) – If set to `True` uses the context based callback API (ignored if *dispatcher* argument is used). Defaults to `True`. **New users:** set this to `True`.
- **persistence** (`telegram.ext.BasePersistence`, optional) – The persistence class to store data that should be persistent over restarts (ignored if *dispatcher* argument is used).
- **defaults** (`telegram.ext.Defaults`, optional) – An object containing default values to be used if not set explicitly in the bot methods.

Note:

- You must supply either a `bot` or a `token` argument.
 - If you supply a `bot`, you will need to pass defaults to *both* the bot and the `telegram.ext.Updater`.
-

Raises `ValueError` – If both `token` and `bot` are passed or none of them.

idle (`stop_signals: Union[List[T], Tuple] = (<Signals.SIGINT: 2>, <Signals.SIGTERM: 15>, <Signals.SIGABRT: 6>)`) → `None`

Blocks until one of the signals are received and stops the updater.

Parameters `stop_signals` (`list` | `tuple`) – List containing signals from the signal module that should be subscribed to. `Updater.stop()` will be called on receiving one of those signals. Defaults to (`SIGINT`, `SIGTERM`, `SIGABRT`).

start_polling (`poll_interval: float = 0.0`, `timeout: float = 10`, `clean: bool = False`, `bootstrap_retries: int = -1`, `read_latency: float = 2.0`, `allowed_updates: List[str] = None`) → `Optional[queue.Queue]`

Starts polling updates from Telegram.

Parameters

- **poll_interval** (`float`, optional) – Time to wait between polling updates from Telegram in seconds. Default is `0.0`.
- **timeout** (`float`, optional) – Passed to `telegram.Bot.get_updates`.
- **clean** (`bool`, optional) – Whether to clean any pending updates on Telegram servers before actually starting to poll. Default is `False`.
- **bootstrap_retries** (`int`, optional) – Whether the bootstrapping phase of the `Updater` will retry on failures on the Telegram server.
 - `< 0` - retry indefinitely (default)
 - `0` - no retries
 - `> 0` - retry up to X times
- **allowed_updates** (`List[str]`, optional) – Passed to `telegram.Bot.get_updates`.
- **read_latency** (`float` | `int`, optional) – Grace time in seconds for receiving the reply from server. Will be added to the `timeout` value and used as the read timeout from server (Default: `2`).

Returns The update queue that can be filled from the main thread.

Return type `Queue`

start_webhook (`listen: str = '127.0.0.1'`, `port: int = 80`, `url_path: str = ''`, `cert: str = None`, `key: str = None`, `clean: bool = False`, `bootstrap_retries: int = 0`, `webhook_url: str = None`, `allowed_updates: List[str] = None`, `force_event_loop: bool = False`) → `Optional[queue.Queue]`

Starts a small http server to listen for updates via webhook. If `cert` and `key` are not provided, the webhook will be started directly on `http://listen:port/url_path`, so SSL can be handled by another application. Else, the webhook will be started on `https://listen:port/url_path`

Note: Due to an incompatibility of the Tornado library PTB uses for the webhook with Python 3.8+ on Windows machines, PTB will attempt to set the event loop to `asyncio.SelectorEventLoop` and raise an exception, if an incompatible event loop has already been specified. See this [thread](#) for more details. To suppress the exception, set `force_event_loop` to `True`.

Parameters

- **listen** (*str*, optional) – IP-Address to listen on. Default `127.0.0.1`.
- **port** (*int*, optional) – Port the bot should be listening on. Default `80`.
- **url_path** (*str*, optional) – Path inside url.
- **cert** (*str*, optional) – Path to the SSL certificate file.
- **key** (*str*, optional) – Path to the SSL key file.
- **clean** (*bool*, optional) – Whether to clean any pending updates on Telegram servers before actually starting the webhook. Default is `False`.
- **bootstrap_retries** (*int*, optional) – Whether the bootstrapping phase of the *Updater* will retry on failures on the Telegram server.
 - `< 0` - retry indefinitely (default)
 - `0` - no retries
 - `> 0` - retry up to X times
- **webhook_url** (*str*, optional) – Explicitly specify the webhook url. Useful behind NAT, reverse proxy, etc. Default is derived from *listen*, *port* & *url_path*.
- **allowed_updates** (*List[str]*, optional) – Passed to `telegram.Bot.set_webhook`.
- **force_event_loop** (*bool*, optional) – Force using the current event loop. See above note for details. Defaults to `False`

Returns The update queue that can be filled from the main thread.

Return type `Queue`

stop() → `None`

Stops the polling/webhook thread, the dispatcher and the job queue.

3.1.2 telegram.ext.Dispatcher

```
class telegram.ext.Dispatcher (bot: Bot, update_queue: queue.Queue, workers:
                                int = 4, exception_event: threading.Event = None,
                                job_queue: JobQueue = None, persistence: tele-
                                gram.ext.basepersistence.BasePersistence = None,
                                use_context: bool = True)
```

Bases: `object`

This class dispatches all kinds of updates to its registered handlers.

bot

The bot object that should be passed to the handlers.

Type `telegram.Bot`

update_queue

The synchronized queue that will contain the updates.

Type `Queue`

job_queue

Optional. The `telegram.ext.JobQueue` instance to pass onto handler callbacks.

Type `telegram.ext.JobQueue`

workers

Number of maximum concurrent worker threads for the `@run_async` decorator and `run_async()`.

Type `int`, optional

user_data

A dictionary handlers can use to store data for the user.

Type `defaultdict`

chat_data

A dictionary handlers can use to store data for the chat.

Type `defaultdict`

bot_data

A dictionary handlers can use to store data for the bot.

Type `dict`

persistence

Optional. The persistence class to store data that should be persistent over restarts.

Type `telegram.ext.BasePersistence`

Parameters

- **bot** (`telegram.Bot`) – The bot object that should be passed to the handlers.
- **update_queue** (`Queue`) – The synchronized queue that will contain the updates.
- **job_queue** (`telegram.ext.JobQueue`, optional) – The `telegram.ext.JobQueue` instance to pass onto handler callbacks.
- **workers** (`int`, optional) – Number of maximum concurrent worker threads for the `@run_async` decorator and `run_async()`. Defaults to 4.
- **persistence** (`telegram.ext.BasePersistence`, optional) – The persistence class to store data that should be persistent over restarts.
- **use_context** (`bool`, optional) – If set to `True` uses the context based callback API (ignored if `dispatcher` argument is used). Defaults to `True`. **New users:** set this to `True`.

add_error_handler (`callback: Callable[[Any, telegram.ext.callbackcontext.CallbackContext], None]`, `run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>`) → `None`

Registers an error handler in the Dispatcher. This handler will receive every error which happens in your bot.

Note: Attempts to add the same callback multiple times will be ignored.

Warning: The errors handled within these handlers won't show up in the logger, so you need to make sure that you reraise the error.

Parameters

- **callback** (callable) – The callback function for this error handler. Will be called when an error is raised. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The error that happened will be present in `context.error`.
- **run_async** (`bool`, optional) – Whether this handlers callback should be run asynchronously using `run_async()`. Defaults to `False`.

Note: See <https://git.io/fxJuV> for more info about switching to context based API.

add_handler (*handler*: *telegram.ext.handler.Handler*, *group*: *int* = 0) → None
Register a handler.

TL;DR: Order and priority counts. 0 or 1 handlers per group will be used. End handling of update with *telegram.ext.DispatcherHandlerStop*.

A handler must be an instance of a subclass of *telegram.ext.Handler*. All handlers are organized in groups with a numeric value. The default group is 0. All groups will be evaluated for handling an update, but only 0 or 1 handler per group will be used. If *telegram.ext.DispatcherHandlerStop* is raised from one of the handlers, no further handlers (regardless of the group) will be called.

The priority/order of handlers is determined as follows:

- Priority of the group (lower group number == higher priority)
- The first handler in a group which should handle an update (see *telegram.ext.Handler.check_update*) will be used. Other handlers from the group will not be used. The order in which handlers were added to the group defines the priority.

Parameters

- **handler** (*telegram.ext.Handler*) – A Handler instance.
- **group** (*int*, optional) – The group identifier. Default is 0.

dispatch_error (*update*: *Union[str, Update, None]*, *error*: *Exception*, *promise*: *telegram.utils.promise.Promise* = None) → None
Dispatches an error.

Parameters

- **update** (*str* | *telegram.Update* | None) – The update that caused the error
- **error** (*Exception*) – The error that was raised.
- **promise** (*telegram.utils.Promise*, optional) – The promise whose pooled function raised the error.

error_handlers = None

A dict, where the keys are error handlers and the values indicate whether they are to be run asynchronously.

Type Dict[callable, bool]

classmethod get_instance () → *telegram.ext.dispatcher.Dispatcher*

Get the singleton instance of this class.

Returns *telegram.ext.Dispatcher*

Raises *RuntimeError*

groups = None

A list with all groups.

Type List[int]

handlers = None

Holds the handlers per group.

Type Dict[int, List[*telegram.ext.Handler*]]

process_update (*update*: *Union[str, telegram.update.Update, telegram.error.TelegramError]*) → None
Processes a single update.

Parameters **update** (`str` | `telegram.Update` | `telegram.TelegramError`) – The update to process.

remove_error_handler (`callback: Callable[[Any, telegram.ext.callbackcontext.CallbackContext], None]`) → `None`
Removes an error handler.

Parameters **callback** (`callable`) – The error handler to remove.

remove_handler (`handler: telegram.ext.handler.Handler`, `group: int = 0`) → `None`
Remove a handler from the specified group.

Parameters

- **handler** (`telegram.ext.Handler`) – A Handler instance.
- **group** (`object`, optional) – The group identifier. Default is 0.

run_async (`func: Callable[[...], Any]`, `*args`, `update: Union[str, Update] = None`, `**kwargs`) → `telegram.utils.promise.Promise`
Queue a function (with given args/kwags) to be run asynchronously. Exceptions raised by the function will be handled by the error handlers registered with `add_error_handler()`.

Warning:

- If you're using `@run_async/run_async()` you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.
- Calling a function through `run_async()` from within an error handler can lead to an infinite error handling loop.

Parameters

- **func** (`callable`) – The function to run in the thread.
- ***args** (`tuple`, optional) – Arguments to `func`.
- **update** (`telegram.Update`, optional) – The update associated with the functions call. If passed, it will be available in the error handlers, in case an exception is raised by `func`.
- ****kwargs** (`dict`, optional) – Keyword arguments to `func`.

Returns `Promise`

running = None
Indicates if this dispatcher is running.

Type `bool`

start (`ready: threading.Event = None`) → `None`
Thread target of thread 'dispatcher'.

Runs in background and processes the update queue.

Parameters **ready** (`threading.Event`, optional) – If specified, the event will be set once the dispatcher is ready.

stop () → `None`
Stops the thread.

update_persistence (`update: Union[str, Update] = None`) → `None`
Update `user_data`, `chat_data` and `bot_data` in `persistence`.

Parameters

- **update** (`telegram.Update`, optional) – The update to process. If passed, only the

- **user_data** and **chat_data** will be updated. (corresponding) –

3.1.3 telegram.ext.DispatcherHandlerStop

class telegram.ext.DispatcherHandlerStop (state: object = None)

Bases: Exception

Raise this in handler to prevent execution any other handler (even in different group).

In order to use this exception in a *telegram.ext.ConversationHandler*, pass the optional state parameter instead of returning the next state:

```
def callback(update, context):  
    ...  
    raise DispatcherHandlerStop(next_state)
```

state

Optional. The next state of the conversation.

Type object

Parameters **state** (object, optional) – The next state of the conversation.

3.1.4 telegram.ext.filters Module

This module contains the Filters for use with the MessageHandler class.

class telegram.ext.filters.Filters

Bases: object

Predefined filters for use as the filter argument of *telegram.ext.MessageHandler*.

Examples

Use `MessageHandler(Filters.video, callback_method)` to filter all video messages. Use `MessageHandler(Filters.contact, callback_method)` for all contacts. etc.

all = Filters.all

All Messages.

animation = Filters.animation

Messages that contain *telegram.Animation*.

audio = Filters.audio

Messages that contain *telegram.Audio*.

caption = Filters.caption

Messages with a caption. If a list of strings is passed, it filters messages to only allow those whose caption is appearing in the given list.

Examples

`MessageHandler(Filters.caption, callback_method)`

Parameters **update** (List[str] | Tuple[str], optional) – Which captions to allow. Only exact matches are allowed. If not specified, will allow any message with a caption.

```
class caption_entity(entity_type: str)
```

Bases: `telegram.ext.filters.MessageFilter`

Filters media messages to only allow those which have a `telegram.MessageEntity` where their `type` matches `entity_type`.

Examples

```
Example MessageHandler(Filters.caption_entity("hashtag"),
callback_method)
```

Parameters `entity_type` – Caption Entity type to check for. All types can be found as constants in `telegram.MessageEntity`.

```
class caption_regex(pattern: Union[str, Pattern[AnyStr]])
```

Bases: `telegram.ext.filters.MessageFilter`

Filters updates by searching for an occurrence of `pattern` in the message caption.

This filter works similarly to `Filters.regex`, with the only exception being that it applies to the message caption instead of the text.

Examples

```
Use MessageHandler(Filters.photo & Filters.caption_regex(r'help'),
callback) to capture all photos with caption containing the word 'help'.
```

Note: This filter will not work on simple text messages, but only on media with caption.

Parameters `pattern` (`str` | `Pattern`) – The regex pattern.

```
class chat(chat_id: Union[int, List[int], Tuple[int, ...]] = None, username: Union[str, List[str],
    Tuple[str, ...]] = None, allow_empty: bool = False)
```

Bases: `telegram.ext.filters._ChatUserBaseFilter`

Filters messages to allow only those which are from a specified chat ID or username.

Examples

```
MessageHandler(Filters.chat(-1234), callback_method)
```

Warning: `chat_ids` will give a copy of the saved chat ids as `frozenset`. This is to ensure thread safety. To add/remove a chat, you should use `add_usernames()`, `add_chat_ids()`, `remove_usernames()` and `remove_chat_ids()`. Only update the entire set by `filter.chat_ids/usernames = new_set`, if you are entirely sure that it is not causing race conditions, as this will completely replace the current set of allowed chats.

chat_ids

Which chat ID(s) to allow through.

Type `set(int)`, optional

usernames

Which username(s) (without leading '@') to allow through.

Type `set(str)`, optional

allow_empty

Whether updates should be processed, if no chat is specified in *chat_ids* and *usernames*.

Type bool, optional

Parameters

- **chat_id** (telegram.utils.types.SLT[int], optional) – Which chat ID(s) to allow through.
- **username** (telegram.utils.types.SLT[str], optional) – Which username(s) to allow through. Leading '@' s in usernames will be discarded.
- **allow_empty** (bool, optional) – Whether updates should be processed, if no chat is specified in *chat_ids* and *usernames*. Defaults to False

Raises RuntimeError – If chat_id and username are both present.

add_chat_ids (*chat_id: Union[int, List[int], Tuple[int, ...]]*) → None

Add one or more chats to the allowed chat ids.

Parameters **chat_id** (telegram.utils.types.SLT[int], optional) – Which chat ID(s) to allow through.

add_usernames (*username: Union[str, List[str], Tuple[str, ...]]*) → None

Add one or more chats to the allowed usernames.

Parameters **username** (telegram.utils.types.SLT[str], optional) – Which username(s) to allow through. Leading '@' s in usernames will be discarded.

remove_chat_ids (*chat_id: Union[int, List[int], Tuple[int, ...]]*) → None

Remove one or more chats from allowed chat ids.

Parameters **chat_id** (telegram.utils.types.SLT[int], optional) – Which chat ID(s) to disallow through.

remove_usernames (*username: Union[str, List[str], Tuple[str, ...]]*) → None

Remove one or more chats from allowed usernames.

Parameters **username** (telegram.utils.types.SLT[str], optional) – Which username(s) to disallow through. Leading '@' s in usernames will be discarded.

chat_type = Filters.chat_type

Subset for filtering the type of chat.

Examples

Use these filters like: `Filters.chat_type.channel` or `Filters.chat_type.supergroup` etc. Or use just `Filters.chat_type` for all chat types.

channel

Updates from channel

group

Updates from group

supergroup

Updates from supergroup

groups

Updates from group *or* supergroup

private

Updates sent in private chat

command = Filters.command

Messages with a *telegram.MessageEntity.BOT_COMMAND*. By default only allows messages

starting with a bot command. Pass `False` to also allow messages that contain a bot command *anywhere* in the text.

Examples:

```
MessageHandler(Filters.command, command_at_start_callback)
MessageHandler(Filters.command(False), command_anywhere_callback)
```

Note: `Filters.text` also accepts messages containing a command.

Parameters `update` (`bool`, optional) – Whether to only allow messages that *start* with a bot command. Defaults to `True`.

contact = `Filters.contact`

Messages that contain `telegram.Contact`.

dice = `Filters.dice`

Dice Messages. If an integer or a list of integers is passed, it filters messages to only allow those whose dice value is appearing in the given list.

Examples

To allow any dice message, simply use `MessageHandler(Filters.dice, callback_method)`. To allow only dice with value 6, use `MessageHandler(Filters.dice(6), callback_method)`. To allow only dice with value 5 *or* 6, use `MessageHandler(Filters.dice([5, 6]), callback_method)`.

Parameters `update` (`telegram.utils.types.SLT[int]`, optional) – Which values to allow. If not specified, will allow any dice message.

Note: Dice messages don't have text. If you want to filter either text or dice messages, use `Filters.text | Filters.dice`.

dice

Dice messages with the emoji . Passing a list of integers is supported just as for `Filters.dice`.

darts

Dice messages with the emoji . Passing a list of integers is supported just as for `Filters.dice`.

basketball

Dice messages with the emoji . Passing a list of integers is supported just as for `Filters.dice`.

football

Dice messages with the emoji . Passing a list of integers is supported just as for `Filters.dice`.

slot_machine

Dice messages with the emoji . Passing a list of integers is supported just as for `Filters.dice`.

document = `Filters.document`

Subset for messages containing a document/file.

Examples

Use these filters like: `Filters.document.mp3`, `Filters.document.mime_type("text/plain")` etc. Or use just `Filters.document` for all document messages.

category

Filters documents by their category in the mime-type attribute

Note: This Filter only filters by the mime_type of the document, it doesn't check the validity of the document. The user can manipulate the mime-type of a message and send media with wrong types that don't fit to this handler.

Example

`Filters.documents.category('audio/')` filters all types of audio sent as file, for example 'audio/mpeg' or 'audio/x-wav'.

application

Same as `Filters.document.category("application")`.

audio

Same as `Filters.document.category("audio")`.

image

Same as `Filters.document.category("image")`.

video

Same as `Filters.document.category("video")`.

text

Same as `Filters.document.category("text")`.

mime_type

Filters documents by their mime-type attribute

Note: This Filter only filters by the mime_type of the document, it doesn't check the validity of document.

The user can manipulate the mime-type of a message and send media with wrong types that don't fit to this handler.

Example

`Filters.documents.mime_type('audio/mpeg')` filters all audio in mp3 format.

apk

Same as `Filters.document.mime_type("application/vnd.android.package-archive")`-

doc

Same as `Filters.document.mime_type("application/msword")`-

docx

Same as `Filters.document.mime_type("application/vnd.openxmlformats-officedocument.wordprocessingml.document")`-

exe

Same as `Filters.document.mime_type("application/x-ms-dos-executable")`-

gif

Same as `Filters.document.mime_type("video/mp4")`-

jpg

Same as `Filters.document.mime_type("image/jpeg")`-

mp3

Same as `Filters.document.mime_type("audio/mpeg")` -

pdf

Same as `Filters.document.mime_type("application/pdf")` -

py

Same as `Filters.document.mime_type("text/x-python")` -

svg

Same as `Filters.document.mime_type("image/svg+xml")` -

txt

Same as `Filters.document.mime_type("text/plain")` -

targz

Same as `Filters.document.mime_type("application/x-compressed-tar")` -

wav

Same as `Filters.document.mime_type("audio/x-wav")` -

xml

Same as `Filters.document.mime_type("application/xml")` -

zip

Same as `Filters.document.mime_type("application/zip")` -

file_extension

This filter filters documents by their file ending/extension.

Note:

- This Filter only filters by the file ending/extension of the document, it doesn't check the validity of document.
 - The user can manipulate the file extension of a document and send media with wrong types that don't fit to this handler.
 - Case insensitive by default, you may change this with the flag `case_sensitive=True`.
 - Extension should be passed without leading dot unless it's a part of the extension.
 - Pass `None` to filter files with no extension, i.e. without a dot in the filename.
-

Example

- `Filters.document.file_extension("jpg")` filters files with extension `".jpg"`.
 - `Filters.document.file_extension(".jpg")` filters files with extension `"...jpg"`.
 - `Filters.document.file_extension("Dockerfile", case_sensitive=True)` filters files with extension `".Dockerfile"` minding the case.
 - `Filters.document.file_extension(None)` filters files without a dot in the filename.
-

class `entity(entity_type: str)`

Bases: `telegram.ext.filters.MessageFilter`

Filters messages to only allow those which have a `telegram.MessageEntity` where their `type` matches `entity_type`.

Examples

Example `MessageHandler(Filters.entity("hashtag"), callback_method)`

Parameters `entity_type` – Entity type to check for. All types can be found as constants in `telegram.MessageEntity`.

forwarded = Filters.forwarded

Messages that are forwarded.

game = Filters.game

Messages that contain `telegram.Game`.

group = Filters.group

Messages sent in a group or a supergroup chat.

Note: DEPRECATED. Use `telegram.ext.Filters.chat_type.groups` instead.

invoice = Filters.invoice

Messages that contain `telegram.Invoice`.

class language (*lang: Union[str, List[str], Tuple[str, ...]]*)

Bases: `telegram.ext.filters.MessageFilter`

Filters messages to only allow those which are from users with a certain language code.

Note: According to official Telegram API documentation, not every single user has the `language_code` attribute. Do not count on this filter working on all users.

Examples

```
MessageHandler(Filters.language("en"), callback_method)
```

Parameters `lang` (`telegram.utils.types.SLT[str]`) – Which language code(s) to allow through. This will be matched using `.startswith` meaning that ‘en’ will match both ‘en_US’ and ‘en_GB’.

location = Filters.location

Messages that contain `telegram.Location`.

passport_data = Filters.passport_data

Messages that contain a `telegram.PassportData`

photo = Filters.photo

Messages that contain `telegram.PhotoSize`.

poll = Filters.poll

Messages that contain a `telegram.Poll`.

private = Filters.private

Messages sent in a private chat.

Note: DEPRECATED. Use `telegram.ext.Filters.chat_type.private` instead.

class regex (*pattern: Union[str, Pattern[AnyStr]]*)

Bases: `telegram.ext.filters.MessageFilter`

Filters updates by searching for an occurrence of `pattern` in the message text. The `re.search()` function is used to determine whether an update should be filtered.

Refer to the documentation of the `re` module for more information.

To get the groups and groupdict matched, see `telegram.ext.CallbackContext.matches`.

Examples

Use `MessageHandler(Filters.regex(r'help'), callback)` to capture all messages that contain the word 'help'. You can also use `MessageHandler(Filters.regex(re.compile(r'help', re.IGNORECASE)), callback)` if you want your pattern to be case insensitive. This approach is recommended if you need to specify flags on your pattern.

Note: Filters use the same short circuiting logic as python's *and*, *or* and *not*. This means that for example:

```
>>> Filters.regex(r'(a?x)') | Filters.regex(r'(b?x)')
```

With a message.text of *x*, will only ever return the matches for the first filter, since the second one is never evaluated.

Parameters `pattern` (`str` | `Pattern`) – The regex pattern.

reply = Filters.reply

Messages that are a reply to another message.

class sender_chat (`chat_id: Union[int, List[int], Tuple[int, ...]] = None, username: Union[str, List[str], Tuple[str, ...]] = None, allow_empty: bool = False`)

Bases: `telegram.ext.filters._ChatUserBaseFilter`

Filters messages to allow only those which are from a specified sender chats chat ID or username.

Examples

- To filter for messages forwarded from a channel with ID -1234, use `MessageHandler(Filters.sender_chat(-1234), callback_method)`.
 - To filter for messages of anonymous admins in a super group with username @anonymous, use `MessageHandler(Filters.sender_chat(username='anonymous'), callback_method)`.
 - To filter for messages forwarded from *any* channel, use `MessageHandler(Filters.sender_chat.channel, callback_method)`.
 - To filter for messages of anonymous admins in *any* super group, use `MessageHandler(Filters.sender_chat.super_group, callback_method)`.
-

Warning: `chat_ids` will return a *copy* of the saved chat ids as `frozenset`. This is to ensure thread safety. To add/remove a chat, you should use `add_usernames()`, `add_chat_ids()`, `remove_usernames()` and `remove_chat_ids()`. Only update the entire set by filter. `chat_ids/usernames = new_set`, if you are entirely sure that it is not causing race conditions, as this will complete replace the current set of allowed chats.

chat_ids

Which sender chat chat ID(s) to allow through.

Type `set(int)`, optional

usernames

Which sender chat username(s) (without leading '@') to allow through.

Type `set(str)`, optional

allow_empty

Whether updates should be processed, if no sender chat is specified in `chat_ids` and `usernames`.

Type `bool`, optional

super_group

Messages whose sender chat is a super group.

Examples

```
Filters.sender_chat.supergroup
```

channel

Messages whose sender chat is a channel.

Examples

```
Filters.sender_chat.channel
```

Parameters

- **chat_id** (`telegram.utils.types.SLT[int]`, optional) – Which sender chat ID(s) to allow through.
- **username** (`telegram.utils.types.SLT[str]`, optional) – Which sender chat sername(s) to allow through. Leading '@' s in usernames will be discarded.
- **allow_empty** (`bool`, optional) – Whether updates should be processed, if no sender chat is specified in `chat_ids` and `usernames`. Defaults to `False`

Raises `RuntimeError` – If `chat_id` and `username` are both present.

add_chat_ids (`chat_id: Union[int, List[int], Tuple[int, ...]]`) → `None`

Add one or more sender chats to the allowed chat ids.

Parameters **chat_id** (`telegram.utils.types.SLT[int]`, optional) – Which sender chat ID(s) to allow through.

add_usernames (`username: Union[str, List[str], Tuple[str, ...]]`) → `None`

Add one or more sender chats to the allowed usernames.

Parameters **username** (`telegram.utils.types.SLT[str]`, optional) – Which sender chat username(s) to allow through. Leading '@' s in usernames will be discarded.

remove_chat_ids (`chat_id: Union[int, List[int], Tuple[int, ...]]`) → `None`

Remove one or more sender chats from allowed chat ids.

Parameters **chat_id** (`telegram.utils.types.SLT[int]`, optional) – Which sender chat ID(s) to disallow through.

remove_usernames (`username: Union[str, List[str], Tuple[str, ...]]`) → `None`

Remove one or more sender chats from allowed usernames.

Parameters **username** (`telegram.utils.types.SLT[str]`, optional) – Which sender chat username(s) to disallow through. Leading '@' s in usernames will be discarded.

status_update = Filters.status_update

Subset for messages containing a status update.

Examples

Use these filters like: `Filters.status_update.new_chat_members` etc. Or use just `Filters.status_update` for all status update messages.

chat_created

Messages that contain `telegram.Message.group_chat_created`, `telegram.Message.supergroup_chat_created` or `telegram.Message.channel_chat_created`.

connected_website

Messages that contain `telegram.Message.connected_website`.

delete_chat_photo

Messages that contain `telegram.Message.delete_chat_photo`.

left_chat_member

Messages that contain `telegram.Message.left_chat_member`.

migrate

Messages that contain `telegram.Message.migrate_from_chat_id` or :attr: `telegram.Message.migrate_from_chat_id`.

new_chat_members

Messages that contain `telegram.Message.new_chat_members`.

new_chat_photo

Messages that contain `telegram.Message.new_chat_photo`.

new_chat_title

Messages that contain `telegram.Message.new_chat_title`.

pinned_message

Messages that contain `telegram.Message.pinned_message`.

proximity_alert_triggered

Messages that contain `telegram.Message.proximity_alert_triggered`.

sticker = Filters.sticker

Messages that contain `telegram.Sticker`.

successful_payment = Filters.successful_payment

Messages that confirm a `telegram.SuccessfulPayment`.

text = Filters.text

Text Messages. If a list of strings is passed, it filters messages to only allow those whose text is appearing in the given list.

Examples

To allow any text message, simply use `MessageHandler(Filters.text, callback_method)`.

A simple use case for passing a list is to allow only messages that were sent by a custom `telegram.ReplyKeyboardMarkup`:

```
buttons = ['Start', 'Settings', 'Back']
markup = ReplyKeyboardMarkup.from_column(buttons)
...
MessageHandler(Filters.text(buttons), callback_method)
```

Note:

- Dice messages don't have text. If you want to filter either text or dice messages, use `Filters.text | Filters.dice`.

- Messages containing a command are accepted by this filter. Use `Filters.text & (~Filters.command)`, if you want to filter only text messages without commands.
-

Parameters `update` (`List[str] | Tuple[str]`, optional) – Which messages to allow. Only exact matches are allowed. If not specified, will allow any text message.

update = `Filters.update`

Subset for filtering the type of update.

Examples

Use these filters like: `Filters.update.message` or `Filters.update.channel_posts` etc. Or use just `Filters.update` for all types.

message

Updates with `telegram.Update.message`

edited_message

Updates with `telegram.Update.edited_message`

messages

Updates with either `telegram.Update.message` or `telegram.Update.edited_message`

channel_post

Updates with `telegram.Update.channel_post`

edited_channel_post

Updates with `telegram.Update.edited_channel_post`

channel_posts

Updates with either `telegram.Update.channel_post` or `telegram.Update.edited_channel_post`

class `user` (`user_id: Union[int, List[int], Tuple[int, ...]] = None`, `username: Union[str, List[str], Tuple[str, ...]] = None`, `allow_empty: bool = False`)

Bases: `telegram.ext.filters._ChatUserBaseFilter`

Filters messages to allow only those which are from specified user ID(s) or username(s).

Examples

`MessageHandler(Filters.user(1234), callback_method)`

Warning: `user_ids` will give a *copy* of the saved user ids as `frozenset`. This is to ensure thread safety. To add/remove a user, you should use `add_usernames()`, `add_user_ids()`, `remove_usernames()` and `remove_user_ids()`. Only update the entire set by `filter.user_ids/usernames = new_set`, if you are entirely sure that it is not causing race conditions, as this will completely replace the current set of allowed users.

user_ids

Which user ID(s) to allow through.

Type `set(int)`, optional

usernames

Which username(s) (without leading '@') to allow through.

Type `set(str)`, optional

allow_empty

Whether updates should be processed, if no user is specified in *user_ids* and *usernames*.

Type bool, optional

Parameters

- **user_id** (telegram.utils.types.SLT[int], optional) – Which user ID(s) to allow through.
- **username** (telegram.utils.types.SLT[str], optional) – Which username(s) to allow through. Leading '@'s in usernames will be discarded.
- **allow_empty** (bool, optional) – Whether updates should be processed, if no user is specified in *user_ids* and *usernames*. Defaults to False

Raises RuntimeError – If user_id and username are both present.

add_user_ids (*user_id*: Union[int, List[int], Tuple[int, ...]]) → None

Add one or more users to the allowed user ids.

Parameters **user_id** (telegram.utils.types.SLT[int], optional) – Which user ID(s) to allow through.

add_usernames (*username*: Union[str, List[str], Tuple[str, ...]]) → None

Add one or more users to the allowed usernames.

Parameters **username** (telegram.utils.types.SLT[str], optional) – Which username(s) to allow through. Leading '@'s in usernames will be discarded.

remove_user_ids (*user_id*: Union[int, List[int], Tuple[int, ...]]) → None

Remove one or more users from allowed user ids.

Parameters **user_id** (telegram.utils.types.SLT[int], optional) – Which user ID(s) to disallow through.

remove_usernames (*username*: Union[str, List[str], Tuple[str, ...]]) → None

Remove one or more users from allowed usernames.

Parameters **username** (telegram.utils.types.SLT[str], optional) – Which username(s) to disallow through. Leading '@'s in usernames will be discarded.

venue = Filters.venue

Messages that contain *telegram.Venue*.

class via_bot (*bot_id*: Union[int, List[int], Tuple[int, ...]] = None, *username*: Union[str, List[str], Tuple[str, ...]] = None, *allow_empty*: bool = False)

Bases: telegram.ext.filters._ChatUserBaseFilter

Filters messages to allow only those which are from specified via_bot ID(s) or username(s).

Examples

```
MessageHandler(Filters.via_bot(1234), callback_method)
```

Warning: *bot_ids* will give a copy of the saved bot ids as frozenset. This is to ensure thread safety. To add/remove a bot, you should use *add_usernames()*, *add_bot_ids()*, *remove_usernames()* and *remove_bot_ids()*. Only update the entire set by filter. *bot_ids/usernames* = *new_set*, if you are entirely sure that it is not causing race conditions, as this will completely replace the current set of allowed bots.

bot_ids

Which bot ID(s) to allow through.

Type set(int), optional

usernames

Which username(s) (without leading '@') to allow through.

Type `set(str)`, optional

allow_empty

Whether updates should be processed, if no bot is specified in `bot_ids` and `usernames`.

Type `bool`, optional

Parameters

- **bot_id** (`telegram.utils.types.SLT[int]`, optional) – Which bot ID(s) to allow through.
- **username** (`telegram.utils.types.SLT[str]`, optional) – Which username(s) to allow through. Leading '@'s in usernames will be discarded.
- **allow_empty** (`bool`, optional) – Whether updates should be processed, if no user is specified in `bot_ids` and `usernames`. Defaults to `False`

Raises `RuntimeError` – If `bot_id` and `username` are both present.

add_bot_ids (`bot_id: Union[int, List[int], Tuple[int, ...]]`) → `None`

Add one or more users to the allowed user ids.

Parameters **bot_id** (`telegram.utils.types.SLT[int]`, optional) – Which bot ID(s) to allow through.

add_usernames (`username: Union[str, List[str], Tuple[str, ...]]`) → `None`

Add one or more users to the allowed usernames.

Parameters **username** (`telegram.utils.types.SLT[str]`, optional) – Which username(s) to allow through. Leading '@'s in usernames will be discarded.

remove_bot_ids (`bot_id: Union[int, List[int], Tuple[int, ...]]`) → `None`

Remove one or more users from allowed user ids.

Parameters **bot_id** (`telegram.utils.types.SLT[int]`, optional) – Which bot ID(s) to disallow through.

remove_usernames (`username: Union[str, List[str], Tuple[str, ...]]`) → `None`

Remove one or more users from allowed usernames.

Parameters **username** (`telegram.utils.types.SLT[str]`, optional) – Which username(s) to disallow through. Leading '@'s in usernames will be discarded.

video = **Filters.video**

Messages that contain `telegram.Video`.

video_note = **Filters.video_note**

Messages that contain `telegram.VideoNote`.

voice = **Filters.voice**

Messages that contain `telegram.Voice`.

class `telegram.ext.filters.BaseFilter`

Bases: `abc.ABC`

Base class for all Filters.

Filters subclassing from this class can combined using bitwise operators:

And:

```
>>> (Filters.text & Filters.entity(MENTION))
```

Or:

```
>>> (Filters.audio | Filters.video)
```

Exclusive Or:

```
>>> (Filters.regex('To Be') ^ Filters.regex('Not 2B'))
```

Not:

```
>>> ~ Filters.command
```

Also works with more than two filters:

```
>>> (Filters.text & (Filters.entity(URL) | Filters.entity(TEXT_LINK)))
>>> Filters.text & (~ Filters.forwarded)
```

Note: Filters use the same short circuiting logic as python's *and*, *or* and *not*. This means that for example:

```
>>> Filters.regex(r'(a?x)') | Filters.regex(r'(b?x)')
```

With `message.text == x`, will only ever return the matches for the first filter, since the second one is never evaluated.

If you want to create your own filters create a class inheriting from either `MessageFilter` or `UpdateFilter` and implement a `:meth:filter` method that returns a boolean: `True` if the message should be handled, `False` otherwise. Note that the filters work only as class instances, not actual class objects (so remember to initialize your filter classes).

By default the filters name (what will get printed when converted to a string for display) will be the class name. If you want to overwrite this assign a better name to the `name` class variable.

name

Name for this filter. Defaults to the type of filter.

Type `str`

data_filter

Whether this filter is a data filter. A data filter should return a dict with lists. The dict will be merged with `telegram.ext.CallbackContext`'s internal dict in most cases (depends on the handler).

Type `bool`

class `telegram.ext.filters.MessageFilter`

Bases: `telegram.ext.filters.BaseFilter`, `abc.ABC`

Base class for all Message Filters. In contrast to `UpdateFilter`, the object passed to `filter()` is `update.effective_message`.

Please see `telegram.ext.BaseFilter` for details on how to create custom filters.

name

Name for this filter. Defaults to the type of filter.

Type `str`

data_filter

Whether this filter is a data filter. A data filter should return a dict with lists. The dict will be merged with `telegram.ext.CallbackContext`'s internal dict in most cases (depends on the handler).

Type `bool`

filter (`message: telegram.message.Message`) $\rightarrow$ `Union[bool, Dict[KT, VT], None]`

This method must be overwritten.

Parameters `message` (`telegram.Message`) – The message that is tested.

Returns `dict` or `bool`

class telegram.ext.filters.**UpdateFilter**

Bases: *telegram.ext.filters.BaseFilter*, abc.ABC

Base class for all Update Filters. In contrast to *UpdateFilter*, the object passed to *filter()* is *update*, which allows to create filters like *Filters.update.edited_message*.

Please see *telegram.ext.BaseFilter* for details on how to create custom filters.

name

Name for this filter. Defaults to the type of filter.

Type str

data_filter

Whether this filter is a data filter. A data filter should return a dict with lists. The dict will be merged with *telegram.ext.CallbackContext*'s internal dict in most cases (depends on the handler).

Type bool

filter (*update*: *telegram.update.Update*) → Union[bool, Dict[KT, VT], None]

This method must be overwritten.

Parameters *update* (*telegram.Update*) – The update that is tested.

Returns dict or bool.

class telegram.ext.filters.**InvertedFilter** (*f*: *telegram.ext.filters.BaseFilter*)

Bases: *telegram.ext.filters.UpdateFilter*

Represents a filter that has been inverted.

Parameters *f* – The filter to invert.

filter (*update*: *telegram.update.Update*) → bool

This method must be overwritten.

Parameters *update* (*telegram.Update*) – The update that is tested.

Returns dict or bool.

class telegram.ext.filters.**MergedFilter** (*base_filter*: *telegram.ext.filters.BaseFilter*,
and_filter: *telegram.ext.filters.BaseFilter* =
None, *or_filter*: *telegram.ext.filters.BaseFilter*
= *None*)

Bases: *telegram.ext.filters.UpdateFilter*

Represents a filter consisting of two other filters.

Parameters

- **base_filter** – Filter 1 of the merged filter.
- **and_filter** – Optional filter to “and” with *base_filter*. Mutually exclusive with *or_filter*.
- **or_filter** – Optional filter to “or” with *base_filter*. Mutually exclusive with *and_filter*.

filter (*update*: *telegram.update.Update*) → Union[bool, Dict[KT, VT]]

This method must be overwritten.

Parameters *update* (*telegram.Update*) – The update that is tested.

Returns dict or bool.

class telegram.ext.filters.**XORFilter** (*base_filter*: *telegram.ext.filters.BaseFilter*,
xor_filter: *telegram.ext.filters.BaseFilter*)

Bases: *telegram.ext.filters.UpdateFilter*

Convenience filter acting as wrapper for *MergedFilter* representing the an XOR gate for two filters

Parameters

- **base_filter** – Filter 1 of the merged filter.
- **xor_filter** – Filter 2 of the merged filter.

filter (*update*: *telegram.update.Update*) → Union[bool, Dict[KT, VT], None]
This method must be overwritten.

Parameters **update** (*telegram.Update*) – The update that is tested.

Returns dict or bool.

3.1.5 telegram.ext.Job

```
class telegram.ext.Job (callback: Callable[[CallbackContext], None], context: object = None,  
                        name: str = None, job_queue: telegram.ext.jobqueue.JobQueue = None,  
                        job: Optional[telegram.ext.jobqueue.Job] = None)
```

Bases: object

This class is a convenience wrapper for the jobs held in a *telegram.ext.JobQueue*. With the current backend APScheduler, *job* holds a *apscheduler.job.Job* instance.

Note:

- All attributes and instance methods of *job* are also directly available as attributes/methods of the corresponding *telegram.ext.Job* object.
 - Two instances of *telegram.ext.Job* are considered equal, if their corresponding *job* attributes have the same *id*.
 - If *job* isn't passed on initialization, it must be set manually afterwards for this *telegram.ext.Job* to be useful.
-

callback

The callback function that should be executed by the new job.

Type callable

context

Optional. Additional data needed for the callback function.

Type object

name

Optional. The name of the new job.

Type str

job_queue

Optional. The JobQueue this job belongs to.

Type *telegram.ext.JobQueue*

job

Optional. The APS Job this job is a wrapper for.

Type *apscheduler.job.Job*

Parameters

- **callback** (callable) – The callback function that should be executed by the new job. Callback signature for context based API:

```
def callback(CallbackContext)
```

a *context.job* is the *telegram.ext.Job* instance. It can be used to access its *job.context* or change it to a repeating job.

- **context** (object, optional) – Additional data needed for the callback function. Can be accessed through `job.context` in the callback. Defaults to `None`.
- **name** (str, optional) – The name of the new job. Defaults to `callback.__name__`.
- **job_queue** (`telegram.ext.JobQueue`, optional) – The `JobQueue` this job belongs to. Only optional for backward compatibility with `JobQueue.put()`.
- **job** (`apscheduler.job.Job`, optional) – The APS Job this job is a wrapper for.

enabled

Whether this job is enabled.

Type `bool`

next_t

Datetime for the next job execution. Datetime is localized according to `tzinfo`. If job is removed or already ran it equals to `None`.

Type `datetime.datetime`

removed

Whether this job is due to be removed.

Type `bool`

run (*dispatcher: Dispatcher*) → `None`

Executes the callback function independently of the jobs schedule.

schedule_removal () → `None`

Schedules this job for removal from the `JobQueue`. It will be removed without executing its callback function again.

3.1.6 telegram.ext.JobQueue

class `telegram.ext.JobQueue`

Bases: `object`

This class allows you to periodically perform tasks with the bot. It is a convenience wrapper for the APScheduler library.

scheduler

The APScheduler

Type `apscheduler.schedulers.background.BackgroundScheduler`

bot

The bot instance that should be passed to the jobs. DEPRECATED: Use `set_dispatcher` instead.

Type `telegram.Bot`

get_jobs_by_name (*name: str*) → `Tuple[telegram.ext.jobqueue.Job, ...]`

Returns a tuple of all *pending/scheduled* jobs with the given name that are currently in the `JobQueue`

jobs () → `Tuple[telegram.ext.jobqueue.Job, ...]`

Returns a tuple of all *pending/scheduled* jobs that are currently in the `JobQueue`.

run_custom (*callback: Callable[[CallbackContext], None]*, *job_kwargs: Dict[str, Any]*, *context: object = None*, *name: str = None*) → `telegram.ext.jobqueue.Job`

Creates a new customly defined `Job`.

Parameters

- **callback** (callable) – The callback function that should be executed by the new job. Callback signature for context based API:

```
def callback(CallbackContext)
```

`context.job` is the `telegram.ext.Job` instance. It can be used to access its `job.context` or change it to a repeating job.

- **job_kwargs** (dict) – Arbitrary keyword arguments. Used as arguments for `scheduler.add_job`.
- **context** (object, optional) – Additional data needed for the callback function. Can be accessed through `job.context` in the callback. Defaults to `None`.
- **name** (str, optional) – The name of the new job. Defaults to `callback.__name__`.

Returns The new `Job` instance that has been added to the job queue.

Return type `telegram.ext.Job`

run_daily (*callback: Callable[[CallbackContext], None]*, *time: datetime.time*, *days: Tuple[int, ...] = (0, 1, 2, 3, 4, 5, 6)*, *context: object = None*, *name: str = None*, *job_kwargs: Dict[str, Any] = None*) → `telegram.ext.jobqueue.Job`

Creates a new `Job` that runs on a daily basis and adds it to the queue.

Parameters

- **callback** (callable) – The callback function that should be executed by the new job. Callback signature for context based API:

```
def callback(CallbackContext)
```

`context.job` is the `telegram.ext.Job` instance. It can be used to access its `job.context` or change it to a repeating job.
- **time** (`datetime.time`) – Time of day at which the job should run. If the timezone (`time.tzinfo`) is `None`, the default timezone of the bot will be used.
- **days** (`Tuple[int]`, optional) – Defines on which days of the week the job should run. Defaults to `EVERY_DAY`.
- **context** (object, optional) – Additional data needed for the callback function. Can be accessed through `job.context` in the callback. Defaults to `None`.
- **name** (str, optional) – The name of the new job. Defaults to `callback.__name__`.
- **job_kwargs** (dict, optional) – Arbitrary keyword arguments to pass to the `scheduler.add_job()`.

Returns The new `Job` instance that has been added to the job queue.

Return type `telegram.ext.Job`

Note: For a note about DST, please see the documentation of [APScheduler](#).

run_monthly (*callback: Callable[[CallbackContext], None]*, *when: datetime.time*, *day: int*, *context: object = None*, *name: str = None*, *day_is_strict: bool = True*, *job_kwargs: Dict[str, Any] = None*) → `telegram.ext.jobqueue.Job`

Creates a new `Job` that runs on a monthly basis and adds it to the queue.

Parameters

- **callback** (callable) – The callback function that should be executed by the new job. Callback signature for context based API:

```
def callback(CallbackContext)
```

`context.job` is the `telegram.ext.Job` instance. It can be used to access its `job.context` or change it to a repeating job.

- **when** (`datetime.time`) – Time of day at which the job should run. If the timezone (`when.tzinfo`) is `None`, the default timezone of the bot will be used.
- **day** (`int`) – Defines the day of the month whereby the job would run. It should be within the range of 1 and 31, inclusive.
- **context** (`object`, optional) – Additional data needed for the callback function. Can be accessed through `job.context` in the callback. Defaults to `None`.
- **name** (`str`, optional) – The name of the new job. Defaults to `callback.__name__`.
- **day_is_strict** (`bool`, optional) – If `False` and `day > month.days`, will pick the last day in the month. Defaults to `True`.
- **job_kwargs** (`dict`, optional) – Arbitrary keyword arguments to pass to the `scheduler.add_job()`.

Returns The new `Job` instance that has been added to the job queue.

Return type `telegram.ext.Job`

run_once (`callback: Callable[[CallbackContext], None]`, `when: Union[float, datetime.timedelta, datetime.datetime, datetime.time]`, `context: object = None`, `name: str = None`, `job_kwargs: Dict[str, Any] = None`) → `telegram.ext.jobqueue.Job`
Creates a new `Job` that runs once and adds it to the queue.

Parameters

- **callback** (`callable`) – The callback function that should be executed by the new job. Callback signature for context based API:

```
def callback(CallbackContext)
```

`context.job` is the `telegram.ext.Job` instance. It can be used to access its `job.context` or change it to a repeating job.
- **when** (`int | float | datetime.timedelta | datetime.datetime | datetime.time`) – Time in or at which the job should run. This parameter will be interpreted depending on its type.
 - `int` or `float` will be interpreted as “seconds from now” in which the job should run.
 - `datetime.timedelta` will be interpreted as “time from now” in which the job should run.
 - `datetime.datetime` will be interpreted as a specific date and time at which the job should run. If the timezone (`datetime.tzinfo`) is `None`, the default timezone of the bot will be used.
 - `datetime.time` will be interpreted as a specific time of day at which the job should run. This could be either today or, if the time has already passed, tomorrow. If the timezone (`time.tzinfo`) is `None`, the default timezone of the bot will be used.
- **context** (`object`, optional) – Additional data needed for the callback function. Can be accessed through `job.context` in the callback. Defaults to `None`.
- **name** (`str`, optional) – The name of the new job. Defaults to `callback.__name__`.
- **job_kwargs** (`dict`, optional) – Arbitrary keyword arguments to pass to the `scheduler.add_job()`.

Returns The new `Job` instance that has been added to the job queue.

Return type `telegram.ext.Job`

run_repeating(*callback*: Callable[[CallbackContext], None], *interval*: Union[float, datetime.timedelta], *first*: Union[float, datetime.timedelta, datetime.datetime, datetime.time] = None, *last*: Union[float, datetime.timedelta, datetime.datetime, datetime.time] = None, *context*: object = None, *name*: str = None, *job_kwargs*: Dict[str, Any] = None) → telegram.ext.jobqueue.Job

Creates a new Job that runs at specified intervals and adds it to the queue.

Parameters

- **callback** (callable) – The callback function that should be executed by the new job. Callback signature for context based API:

```
def callback(CallbackContext)
```

`context.job` is the `telegram.ext.Job` instance. It can be used to access its `job.context` or change it to a repeating job.

- **interval** (int | float | datetime.timedelta) – The interval in which the job will run. If it is an int or a float, it will be interpreted as seconds.
- **first** (int | float | datetime.timedelta | datetime.datetime | datetime.time, optional) – Time in or at which the job should run. This parameter will be interpreted depending on its type.
 - int or float will be interpreted as “seconds from now” in which the job should run.
 - datetime.timedelta will be interpreted as “time from now” in which the job should run.
 - datetime.datetime will be interpreted as a specific date and time at which the job should run. If the timezone (`datetime.tzinfo`) is None, the default timezone of the bot will be used.
 - datetime.time will be interpreted as a specific time of day at which the job should run. This could be either today or, if the time has already passed, tomorrow. If the timezone (`time.tzinfo`) is None, the default timezone of the bot will be used.

Defaults to `interval`

- **last** (int | float | datetime.timedelta | datetime.datetime | datetime.time, optional) – Latest possible time for the job to run. This parameter will be interpreted depending on its type. See `first` for details.

If `last` is `datetime.datetime` or `datetime.time` type and `last.tzinfo` is None, the default timezone of the bot will be assumed.

Defaults to None.

- **context** (object, optional) – Additional data needed for the callback function. Can be accessed through `job.context` in the callback. Defaults to None.
- **name** (str, optional) – The name of the new job. Defaults to `callback.__name__`.
- **job_kwargs** (dict, optional) – Arbitrary keyword arguments to pass to the `scheduler.add_job()`.

Returns The new Job instance that has been added to the job queue.

Return type `telegram.ext.Job`

Note: *interval* is always respected “as-is”. That means that if DST changes during that interval, the job might not run at the time one would expect. It is always recommended to pin servers to UTC time, then time related behaviour can always be expected.

set_dispatcher (*dispatcher: Dispatcher*) → None

Set the dispatcher to be used by this JobQueue. Use this instead of passing a *telegram.Bot* to the JobQueue, which is deprecated.

Parameters **dispatcher** (*telegram.ext.Dispatcher*) – The dispatcher.

start () → None

Starts the job_queue thread.

stop () → None

Stops the thread.

3.1.7 telegram.ext.MessageQueue

```
class telegram.ext.MessageQueue (all_burst_limit: int = 30, all_time_limit_ms: int = 1000,  
                                group_burst_limit: int = 20, group_time_limit_ms: int =  
                                60000, exc_route: Callable[[Exception], None] = None,  
                                autostart: bool = True)
```

Bases: object

Implements callback processing with proper delays to avoid hitting Telegram’s message limits. Contains two DelayQueue, for group and for all messages, interconnected in delay chain. Callables are processed through *group* DelayQueue, then through *all* DelayQueue for group-type messages. For non-group messages, only the *all* DelayQueue is used.

Parameters

- **all_burst_limit** (int, optional) – Number of maximum *all-type* callbacks to process per time-window defined by *all_time_limit_ms*. Defaults to 30.
- **all_time_limit_ms** (int, optional) – Defines width of *all-type* time-window used when each processing limit is calculated. Defaults to 1000 ms.
- **group_burst_limit** (int, optional) – Number of maximum *group-type* callbacks to process per time-window defined by *group_time_limit_ms*. Defaults to 20.
- **group_time_limit_ms** (int, optional) – Defines width of *group-type* time-window used when each processing limit is calculated. Defaults to 60000 ms.
- **exc_route** (callable, optional) – A callable, accepting one positional argument; used to route exceptions from processor threads to main thread; is called on `Exception` subclass exceptions. If not provided, exceptions are routed through dummy handler, which re-raises them.
- **autostart** (bool, optional) – If `True`, processors are started immediately after object’s creation; if `False`, should be started manually by *start* method. Defaults to `True`.

__call__ (*promise: Callable, is_group_msg: bool = False*) → Callable

Processes callables in throughput-limiting queues to avoid hitting limits (specified with *burst_limit* and *time_limit*).

Parameters

- **promise** (callable) – Mainly the `telegram.utils.promise.Promise` (see Notes for other callables), that is processed in delay queues.
- **is_group_msg** (bool, optional) – Defines whether *promise* would be processed in `group*+*all*DelayQueue`s` (if set to `:obj: `True``), or only through `*all* ``DelayQueue` (if set to `False`), resulting in needed delays to avoid hitting specified limits. Defaults to `False`.

Note: Method is designed to accept `telegram.utils.promise.Promise` as *promise* argument, but other callables could be used too. For example, lambdas or simple functions could be used

to wrap original func to be called with needed args. In that case, be sure that either wrapper func does not raise outside exceptions or the proper `exc_route` handler is provided.

Returns Used as `promise` argument.

Return type `callable`

__init__ (*all_burst_limit: int = 30, all_time_limit_ms: int = 1000, group_burst_limit: int = 20, group_time_limit_ms: int = 60000, exc_route: Callable[[Exception], None] = None, autostart: bool = True*)
Initialize self. See `help(type(self))` for accurate signature.

__weakref__
list of weak references to the object (if defined)

start () → None
Method is used to manually start the `MessageQueue` processing.

stop (*timeout: float = None*) → None
Used to gently stop processor and shutdown its thread.

Parameters **timeout** (`float`) – Indicates maximum time to wait for processor to stop and its thread to exit. If timeout exceeds and processor has not stopped, method silently returns. `is_alive` could be used afterwards to check the actual status. `timeout` set to `None`, blocks until processor is shut down. Defaults to `None`.

3.1.8 telegram.ext.DelayQueue

class `telegram.ext.DelayQueue` (*queue: queue.Queue = None, burst_limit: int = 30, time_limit_ms: int = 1000, exc_route: Callable[[Exception], None] = None, autostart: bool = True, name: str = None*)

Bases: `threading.Thread`

Processes callbacks from queue with specified throughput limits. Creates a separate thread to process callbacks with delays.

burst_limit
Number of maximum callbacks to process per time-window.

Type `int`

time_limit
Defines width of time-window used when each processing limit is calculated.

Type `int`

exc_route
A callable, accepting 1 positional argument; used to route exceptions from processor thread to main thread;

Type `callable`

name
Thread's name.

Type `str`

Parameters

- **queue** (`Queue`, optional) – Used to pass callbacks to thread. Creates `Queue` implicitly if not provided.
- **burst_limit** (`int`, optional) – Number of maximum callbacks to process per time-window defined by `time_limit_ms`. Defaults to 30.

- **time_limit_ms** (*int*, optional) – Defines width of time-window used when each processing limit is calculated. Defaults to 1000.
- **exc_route** (*callable*, optional) – A callable, accepting 1 positional argument; used to route exceptions from processor thread to main thread; is called on *Exception* subclass exceptions. If not provided, exceptions are routed through dummy handler, which re-raises them.
- **autostart** (*bool*, optional) – If *True*, processor is started immediately after object's creation; if *False*, should be started manually by *start* method. Defaults to *True*.
- **name** (*str*, optional) – Thread's name. Defaults to 'DelayQueue-N', where N is sequential number of object created.

__call__ (*func: Callable, *args, **kwargs*) → *None*

Used to process callbacks in throughput-limiting thread through queue.

Parameters

- **func** (*callable*) – The actual function (or any callable) that is processed through queue.
- ***args** (*list*) – Variable-length *func* arguments.
- ****kwargs** (*dict*) – Arbitrary keyword-arguments to *func*.

__init__ (*queue: queue.Queue = None, burst_limit: int = 30, time_limit_ms: int = 1000, exc_route: Callable[[Exception], None] = None, autostart: bool = True, name: str = None*)

This constructor should always be called with keyword arguments. Arguments are:

group should be *None*; reserved for future extension when a *ThreadGroup* class is implemented.

target is the callable object to be invoked by the *run()* method. Defaults to *None*, meaning nothing is called.

name is the thread name. By default, a unique name is constructed of the form “Thread-N” where N is a small decimal number.

args is the argument tuple for the target invocation. Defaults to *()*.

kwargs is a dictionary of keyword arguments for the target invocation. Defaults to *{}*.

If a subclass overrides the constructor, it must make sure to invoke the base class constructor (*Thread.__init__()*) before doing anything else to the thread.

run () → *None*

Do not use the method except for unthreaded testing purposes, the method normally is automatically called by *autostart* argument.

stop (*timeout: float = None*) → *None*

Used to gently stop processor and shutdown its thread.

Parameters **timeout** (*float*) – Indicates maximum time to wait for processor to stop and its thread to exit. If timeout exceeds and processor has not stopped, method silently returns. *is_alive* could be used afterwards to check the actual status. *timeout* set to *None*, blocks until processor is shut down. Defaults to *None*.

3.1.9 telegram.ext.CallbackContext

class *telegram.ext.CallbackContext* (*dispatcher: Dispatcher*)

This is a context object passed to the callback called by *telegram.ext.Handler* or by the *telegram.ext.Dispatcher* in an error handler added by *telegram.ext.Dispatcher.add_error_handler* or to the callback of a *telegram.ext.Job*.

Note: `telegram.ext.Dispatcher` will create a single context for an entire update. This means that if you got 2 handlers in different groups and they both get called, they will get passed the same *CallbackContext* object (of course with proper attributes like `.matches` differing). This allows you to add custom attributes in a lower handler group callback, and then subsequently access those attributes in a higher handler group callback. Note that the attributes on *CallbackContext* might change in the future, so make sure to use a fairly unique name for the attributes.

Warning: Do not combine custom attributes and `@run_async/telegram.ext.Dispatcher.run_async()`. Due to how `run_async` works, it will almost certainly execute the callbacks for an update out of order, and the attributes that you think you added will not be present.

bot_data

Optional. A dict that can be used to keep any data in. For each update it will be the same dict.

Type dict

chat_data

Optional. A dict that can be used to keep any data in. For each update from the same chat id it will be the same dict.

Warning: When a group chat migrates to a supergroup, its chat id will change and the `chat_data` needs to be transferred. For details see our [wiki page](#).

Type dict

user_data

Optional. A dict that can be used to keep any data in. For each update from the same user it will be the same dict.

Type dict

matches

Optional. If the associated update originated from a regex-supported handler or had a `Filters.regex`, this will contain a list of match objects for every pattern where `re.search(pattern, string)` returned a match. Note that filters short circuit, so combined regex filters will not always be evaluated.

Type List[re match object]

args

Optional. Arguments passed to a command if the associated update is handled by `telegram.ext.CommandHandler`, `telegram.ext.PrefixHandler` or `telegram.ext.StringCommandHandler`. It contains a list of the words in the text after the command, using any whitespace string as a delimiter.

Type List[str]

error

Optional. The error that was raised. Only present when passed to a error handler registered with `telegram.ext.Dispatcher.add_error_handler`.

Type telegram.TelegramError

async_args

Optional. Positional arguments of the function that raised the error. Only present when the raising function was run asynchronously using `telegram.ext.Dispatcher.run_async()`.

Type List[object]

async_kwargs

Optional. Keyword arguments of the function that raised the error. Only present when the raising function was run asynchronously using `telegram.ext.Dispatcher.run_async()`.

Type Dict[str, object]

job

Optional. The job which originated this callback. Only present when passed to the callback of `telegram.ext.Job`.

Type `telegram.ext.Job`

bot

The bot associated with this context.

Type `telegram.Bot`

dispatcher

The dispatcher associated with this context.

Type `telegram.ext.Dispatcher`

job_queue

The JobQueue used by the `telegram.ext.Dispatcher` and (usually) the `telegram.ext.Updater` associated with this context.

Type `telegram.ext.JobQueue`

match

The first match from `matches`. Useful if you are only filtering using a single regex filter. Returns `None` if `matches` is empty.

Type *Regex match type*

update_queue

The Queue instance used by the `telegram.ext.Dispatcher` and (usually) the `telegram.ext.Updater` associated with this context.

Type `queue.Queue`

3.1.10 telegram.ext.Defaults

```
class telegram.ext.Defaults(parse_mode: str = None, disable_notification: bool =  
None, disable_web_page_preview: bool = None, time-  
out: Union[float, telegram.utils.helpers.DefaultValue] = <tele-  
gram.utils.helpers.DefaultValue object>, quote: bool = None, tz-  
info: pytz.tzinfo.BaseTzInfo = <UTC>, run_async: bool = False,  
allow_sending_without_reply: bool = None)
```

Bases: `object`

Convenience Class to gather all parameters with a (user defined) default value

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or URLs in your bot's message.

Type `str`

disable_notification

Optional. Sends the message silently. Users will receive a notification with no sound.

Type `bool`

disable_web_page_preview

Optional. Disables link previews for links in this message.

Type `bool`

allow_sending_without_reply

Optional. Pass `True`, if the message should be sent even if the specified replied-to message is not found.

Type `bool`

timeout

Optional. If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

Type `int|float`

quote

Optional. If set to `True`, the reply is sent as an actual reply to the message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: `True` in group chats and `False` in private chats.

Type `bool`

tzinfo

A timezone to be used for all `date(time)` objects appearing throughout PTB.

Type `tzinfo`

run_async

Optional. Default setting for the `run_async` parameter of handlers and error handlers registered through `Dispatcher.add_handler()` and `Dispatcher.add_error_handler()`.

Type `bool`

Parameters

- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or URLs in your bot's message.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **disable_web_page_preview** (`bool`, optional) – Disables link previews for links in this message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **timeout** (`int|float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **quote** (`bool`, optional) – If set to `True`, the reply is sent as an actual reply to the message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: `True` in group chats and `False` in private chats.
- **tzinfo** (`tzinfo`, optional) – A timezone to be used for all `date(time)` inputs appearing throughout PTB, i.e. if a timezone naive `date(time)` object is passed somewhere, it will be assumed to be in `tzinfo`. Must be a timezone provided by the `pytz` module. Defaults to UTC.
- **run_async** (`bool`, optional) – Default setting for the `run_async` parameter of handlers and error handlers registered through `Dispatcher.add_handler()` and `Dispatcher.add_error_handler()`. Defaults to `False`.

3.1.11 Handlers

telegram.ext.Handler

```
class telegram.ext.Handler (callback: Callable[[Union[str, Update], CallbackContext], RT],
                             pass_update_queue: bool = False, pass_job_queue: bool = False,
                             pass_user_data: bool = False, pass_chat_data: bool = False,
                             run_async: Union[bool, telegram.utils.helpers.DefaultValue] =
                             <telegram.utils.helpers.DefaultValue object>)
```

Bases: `abc.ABC`

The base class for all update handlers. Create custom handlers by inheriting from it.

callback

The callback function for this handler.

Type callable

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type bool

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type bool

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type bool

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Note: `pass_user_data` and `pass_chat_data` determine whether a dict you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same dict.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance

used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.

- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Union[str, Update]*) → Union[bool, object, None]

This method is called to determine if an update should be handled by this handler instance. It should always be overridden.

Parameters *update* (str | `telegram.Update`) – The update to be tested.

Returns Either `None` or `False` if the update should not be handled. Otherwise an object that will be passed to `handle_update()` and `collect_additional_context()` when the update gets handled.

collect_additional_context (*context: CallbackContext, update: Union[str, Update], dispatcher: Dispatcher, check_result: Any*) → None

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (`telegram.ext.CallbackContext`) – The context object.
- **update** (`telegram.Update`) – The update to gather chat/user id from.
- **dispatcher** (`telegram.ext.Dispatcher`) – The calling dispatcher.
- **check_result** – The result (return value) from `check_update`.

collect_optional_args (*dispatcher: Dispatcher, update: Union[str, Update] = None, check_result: Any = None*) → Dict[str, Any]

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (`telegram.ext.Dispatcher`) – The dispatcher.
- **update** (`telegram.Update`) – The update to gather chat/user id from.
- **check_result** – The result from `check_update`

handle_update (*update: Union[str, Update], dispatcher: Dispatcher, check_result: object, context: CallbackContext = None*) → Union[RT, telegram.utils.promise.Promise]

This method is called if it was determined that an update should indeed be handled by this instance. Calls `callback` along with its respectful arguments. To work with the `telegram.ext.ConversationHandler`, this method returns the value returned from `callback`. Note that it can be overridden if needed by the subclassing handler.

Parameters

- **update** (`str` | `telegram.Update`) – The update to be handled.
- **dispatcher** (`telegram.ext.Dispatcher`) – The calling dispatcher.
- **check_result** (`obj`) – The result from `check_update`.
- **context** (`telegram.ext.CallbackContext`, optional) – The context as provided by the dispatcher.

telegram.ext.CallbackQueryHandler

```
class telegram.ext.CallbackQueryHandler(callback: Callable[[Union[str, Update], CallbackContext], RT], pass_update_queue: bool = False, pass_job_queue: bool = False, pattern: Union[str, Pattern[AnyStr]] = None, pass_groups: bool = False, pass_groupdict: bool = False, pass_user_data: bool = False, pass_chat_data: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: `telegram.ext.handler.Handler`

Handler class to handle Telegram callback queries. Optionally based on a regex.

Read the documentation of the `re` module for more information.

callback

The callback function for this handler.

Type `callable`

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type `bool`

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type `bool`

pattern

Optional. Regex pattern to test `telegram.CallbackQuery.data` against.

Type `str` | `Pattern`

pass_groups

Determines whether `groups` will be passed to the callback function.

Type `bool`

pass_groupdict

Determines whether `groupdict`. will be passed to the callback function.

Type `bool`

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type `bool`

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context:
    CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pattern** (str | *Pattern*, optional) – Regex pattern. If not `None`, `re.match` is used on `telegram.CallbackQuery.data` to determine if an update should be handled by this handler.
- **pass_groups** (bool, optional) – If the callback should be passed the result of `re.match(pattern, data).groups()` as a keyword argument called `groups`. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_groupdict** (bool, optional) – If the callback should be passed the result of `re.match(pattern, data).groupdict()` as a keyword argument called `groupdict`. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update*: Union[str, Update]) → Union[bool, object, None]

Determines whether an update should be passed to this handlers *callback*.

Parameters *update* (*telegram.Update*) – Incoming telegram update.

Returns bool

collect_additional_context (*context*: CallbackContext, *update*: Union[str, Update],
dispatcher: Dispatcher, *check_result*: Union[bool,
Match[AnyStr]]) → None

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (*telegram.ext.CallbackContext*) – The context object.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **dispatcher** (*telegram.ext.Dispatcher*) – The calling dispatcher.
- **check_result** – The result (return value) from *check_update*.

collect_optional_args (*dispatcher*: Dispatcher, *update*: Union[str, Update] = None,
check_result: Union[bool, Match[AnyStr]] = None) → Dict[str,
Any]

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (*telegram.ext.Dispatcher*) – The dispatcher.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **check_result** – The result from *check_update*

telegram.ext.ChosenInlineResultHandler

```
class telegram.ext.ChosenInlineResultHandler (callback: Callable[[Union[str, Update], CallbackContext], RT],  
pass_update_queue: bool = False,  
pass_job_queue: bool = False,  
pass_user_data: bool = False,  
pass_chat_data: bool = False,  
run_async: Union[bool, telegram.utils.helpers.DefaultValue] =  
<telegram.utils.helpers.DefaultValue object>)
```

Bases: telegram.ext.handler.Handler

Handler class to handle Telegram updates that contain a chosen inline result.

callback

The callback function for this handler.

Type callable

pass_update_queue

Determines whether *update_queue* will be passed to the callback function.

Type bool

pass_job_queue

Determines whether *job_queue* will be passed to the callback function.

Type bool

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type bool

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (`update: Union[str, Update]`) → Union[bool, object, None]

Determines whether an update should be passed to this handlers `callback`.

Parameters `update` (`telegram.Update`) – Incoming telegram update.

Returns `bool`

`telegram.ext.ConversationHandler`

```
class telegram.ext.ConversationHandler (entry_points: List[telegram.ext.handler.Handler],
                                       states: Dict[object,
                                       List[telegram.ext.handler.Handler]], fall-
                                       backs: List[telegram.ext.handler.Handler],
                                       allow_reentry: bool = False, per_chat: bool
                                       = True, per_user: bool = True, per_message:
                                       bool = False, conversation_timeout: int = None,
                                       name: str = None, persistent: bool = False,
                                       map_to_parent: Dict[object, object] = None)
```

Bases: `telegram.ext.handler.Handler`

A handler to hold a conversation with a single user by managing four collections of other handlers.

The first collection, a list named `entry_points`, is used to initiate the conversation, for example with a `telegram.ext.CommandHandler` or `telegram.ext.MessageHandler`.

The second collection, a dict named `states`, contains the different conversation steps and one or more associated handlers that should be used if the user sends a message when the conversation with them is currently in that state. Here you can also define a state for `TIMEOUT` to define the behavior when `conversation_timeout` is exceeded, and a state for `WAITING` to define behavior when a new update is received while the previous `@run_async` decorated handler is not finished.

The third collection, a list named `fallbacks`, is used if the user is currently in a conversation but the state has either no associated handler or the handler that is associated to the state is inappropriate for the update, for example if the update contains a command, but a regular text message is expected. You could use this for a `/cancel` command or to let the user know their message was not recognized.

To change the state of conversation, the callback function of a handler must return the new state after responding to the user. If it does not return anything (returning `None` by default), the state will not change. If an entry point callback function returns `None`, the conversation ends immediately after the execution of this callback function. To end the conversation, the callback function must return `END` or `-1`. To handle the conversation timeout, use handler `TIMEOUT` or `-2`. Finally, `telegram.ext.DispatcherHandlerStop` can be used in conversations as described in the corresponding documentation.

Note: In each of the described collections of handlers, a handler may in turn be a `ConversationHandler`. In that case, the nested `ConversationHandler` should have the attribute `map_to_parent` which allows to return to the parent conversation at specified states within the nested conversation.

Note that the keys in `map_to_parent` must not appear as keys in `states` attribute or else the latter will be ignored. You may map `END` to one of the parents states to continue the parent conversation after this has ended or even map a state to `END` to end the *parent* conversation from within the nested one. For an example on nested `ConversationHandler`s, see our [examples](#).

entry_points

A list of `Handler` objects that can trigger the start of the conversation.

Type `List[telegram.ext.Handler]`

states

A dict that defines the different states of conversation a user can be in and one or more associated `Handler` objects that should be used in that state.

Type `Dict[object, List[telegram.ext.Handler]]`

fallbacks

A list of handlers that might be used if the user is in a conversation, but every handler for their current state returned `False` on `check_update`.

Type `List[telegram.ext.Handler]`

allow_reentry

Determines if a user can restart a conversation with an entry point.

Type `bool`

per_chat

If the conversationkey should contain the Chat's ID.

Type `bool`

per_user

If the conversationkey should contain the User's ID.

Type `bool`

per_message

If the conversationkey should contain the Message's ID.

Type `bool`

conversation_timeout

Optional. When this handler is inactive more than this timeout (in seconds), it will be automatically ended. If this value is 0 (default), there will be no timeout. When it's triggered, the last received update and the corresponding `context` will be handled by ALL the handler's who's `check_update` method returns `True` that are in the state `ConversationHandler.TIMEOUT`.

Type `float|datetime.timedelta`

name

Optional. The name for this conversationhandler. Required for persistence

Type `str`

persistent

Optional. If the conversations dict for this handler should be saved. Name is required and persistence has to be set in `telegram.ext.Updater`

Type `bool`

map_to_parent

Optional. A `dict` that can be used to instruct a nested conversationhandler to transition into a mapped state on its parent conversationhandler in place of a specified nested state.

Type `Dict[object, object]`

Parameters

- **entry_points** (`List[telegram.ext.Handler]`) – A list of Handler objects that can trigger the start of the conversation. The first handler which `check_update` method returns `True` will be used. If all return `False`, the update is not handled.
- **states** (`Dict[object, List[telegram.ext.Handler]]`) – A dict that defines the different states of conversation a user can be in and one or more associated Handler objects that should be used in that state. The first handler which `check_update` method returns `True` will be used.
- **fallbacks** (`List[telegram.ext.Handler]`) – A list of handlers that might be used if the user is in a conversation, but every handler for their current state returned `False` on `check_update`. The first handler which `check_update` method returns `True` will be used. If all return `False`, the update is not handled.
- **allow_reentry** (`bool`, optional) – If set to `True`, a user that is currently in a conversation can restart the conversation by triggering one of the entry points.

- **per_chat** (bool, optional) – If the conversationkey should contain the Chat’s ID. Default is True.
- **per_user** (bool, optional) – If the conversationkey should contain the User’s ID. Default is True.
- **per_message** (bool, optional) – If the conversationkey should contain the Message’s ID. Default is False.
- **conversation_timeout** (float | datetime.timedelta, optional) – When this handler is inactive more than this timeout (in seconds), it will be automatically ended. If this value is 0 or None (default), there will be no timeout. The last received update and the corresponding context will be handled by ALL the handler’s who’s `check_update` method returns True that are in the state `ConversationHandler.TIMEOUT`.
- **name** (str, optional) – The name for this conversationhandler. Required for persistence.
- **persistent** (bool, optional) – If the conversations dict for this handler should be saved. Name is required and persistence has to be set in `telegram.ext.Updater`
- **map_to_parent** (Dict[object, object], optional) – A dict that can be used to instruct a nested conversationhandler to transition into a mapped state on its parent conversationhandler in place of a specified nested state.

Raises ValueError

END = -1

Used as a constant to return when a conversation is ended.

Type int

TIMEOUT = -2

Used as a constant to handle state when a conversation is timed out.

Type int

WAITING = -3

Used as a constant to handle state when a conversation is still waiting on the previous `@run_sync` decorated running handler to finish.

Type int

check_update (update: Union[str, Update]) → Optional[Tuple[Tuple[int, ...], telegram.ext.handler.Handler, object]]

Determines whether an update should be handled by this conversationhandler, and if so in which state the conversation currently is.

Parameters update (`telegram.Update`) – Incoming telegram update.

Returns bool

handle_update (update: Union[str, Update], dispatcher: Dispatcher, check_result: Optional[Tuple[Tuple[int, ...], telegram.ext.handler.Handler, object]], context: telegram.ext.callbackcontext.CallbackContext = None) → Optional[object]

Send the update to the callback for the current state and Handler

Parameters

- **check_result** – The result from check_update. For this handler it’s a tuple of key, handler, and the handler’s check result.
- **update** (`telegram.Update`) – Incoming telegram update.
- **dispatcher** (`telegram.ext.Dispatcher`) – Dispatcher that originated the Update.

- **context** (*telegram.ext.CallbackContext*, optional) – The context as provided by the dispatcher.

telegram.ext.CommandHandler

```
class telegram.ext.CommandHandler(command: Union[str, List[str], Tuple[str, ...]],
                                  callback: Callable[[Union[str, Update], CallbackContext], RT],
                                  filters: telegram.ext.filters.BaseFilter = None,
                                  allow_edited: bool = None,
                                  pass_args: bool = False,
                                  pass_update_queue: bool = False,
                                  pass_job_queue: bool = False,
                                  pass_user_data: bool = False,
                                  pass_chat_data: bool = False,
                                  run_async: Union[bool, telegram.utils.helpers.DefaultValue] =
                                  <telegram.utils.helpers.DefaultValue object>)
```

Bases: `telegram.ext.handler.Handler`

Handler class to handle Telegram commands.

Commands are Telegram messages that start with /, optionally followed by an @ and the bot's name and/or some additional text. The handler will add a `list` to the *CallbackContext* named *CallbackContext.args*. It will contain a list of strings, which is the text following the command split on single or consecutive whitespace characters.

By default the handler listens to messages as well as edited messages. To change this behavior use `~Filters.update.edited_message` in the filter argument.

Note: *telegram.ext.CommandHandler* does *not* handle (edited) channel posts.

command

The command or list of commands this handler should listen for. Limitations are the same as described here <https://core.telegram.org/bots#commands>

Type `telegram.utils.types.SLT[str]`

callback

The callback function for this handler.

Type `callable`

filters

Optional. Only allow updates with these Filters.

Type `telegram.ext.BaseFilter`

allow_edited

Determines whether the handler should also accept edited messages.

Type `bool`

pass_args

Determines whether the handler should be passed `args`.

Type `bool`

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type `bool`

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type `bool`

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type `bool`

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **command** (`telegram.utils.types.SLT[str]`) – The command or list of commands this handler should listen for. Limitations are the same as described here <https://core.telegram.org/bots#commands>
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.
- **filters** (`telegram.ext.BaseFilter`, optional) – A filter inheriting from `telegram.ext.filters.BaseFilter`. Standard filters can be found in `telegram.ext.filters.Filters`. Filters can be combined using bitwise operators (`&` for and, `|` for or, `~` for not).
- **allow_edited** (`bool`, optional) – Determines whether the handler should also accept edited messages. Default is `False`. DEPRECATED: Edited is allowed by default. To change this behavior use `~Filters.update.edited_message`.
- **pass_args** (`bool`, optional) – Determines whether the handler should be passed the arguments passed to the command as a keyword argument called `args`. It will contain a list of strings, which is the text following the command split on single or consecutive whitespace characters. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_update_queue** (`bool`, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.

- **pass_job_queue** (*bool*, optional) – If set to *True*, a keyword argument called *job_queue* will be passed to the callback function. It will be a *telegram.ext.JobQueue* instance created by the *telegram.ext.Updater* which can be used to schedule new jobs. Default is *False*. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (*bool*, optional) – If set to *True*, a keyword argument called *user_data* will be passed to the callback function. Default is *False*. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (*bool*, optional) – If set to *True*, a keyword argument called *chat_data* will be passed to the callback function. Default is *False*. DEPRECATED: Please switch to context based callbacks.
- **run_async** (*bool*) – Determines whether the callback will run asynchronously. Defaults to *False*.

Raises *ValueError* - when command is too long or has illegal chars.

check_update (*update: Union[str, Update]*) → *Union[bool, Tuple[List[str], Union[bool, Dict[KT, VT], None]], None]*

Determines whether an update should be passed to this handlers *callback*.

Parameters *update* (*telegram.Update*) – Incoming telegram update.

Returns The list of args for the handler.

Return type *list*

collect_additional_context (*context: CallbackContext, update: Union[str, Update], dispatcher: Dispatcher, check_result: Union[bool, Tuple[List[str], Optional[bool]], None]*) → *None*

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (*telegram.ext.CallbackContext*) – The context object.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **dispatcher** (*telegram.ext.Dispatcher*) – The calling dispatcher.
- **check_result** – The result (return value) from *check_update*.

collect_optional_args (*dispatcher: Dispatcher, update: Union[str, Update] = None, check_result: Union[bool, Tuple[List[str], Optional[bool]], None] = None*) → *Dict[str, Any]*

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (*telegram.ext.Dispatcher*) – The dispatcher.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **check_result** – The result from *check_update*

telegram.ext.InlineQueryHandler

```
class telegram.ext.InlineQueryHandler(callback: Callable[[Union[str, Update], CallbackContext], RT], pass_update_queue: bool = False, pass_job_queue: bool = False, pattern: Union[str, Pattern[AnyStr]] = None, pass_groups: bool = False, pass_groupdict: bool = False, pass_user_data: bool = False, pass_chat_data: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: telegram.ext.handler.Handler

Handler class to handle Telegram inline queries. Optionally based on a regex. Read the documentation of the `re` module for more information.

callback

The callback function for this handler.

Type callable

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type bool

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type bool

pattern

Optional. Regex pattern to test `telegram.InlineQuery.query` against.

Type str|Pattern

pass_groups

Determines whether `groups` will be passed to the callback function.

Type bool

pass_groupdict

Determines whether `groupdict` will be passed to the callback function.

Type bool

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type bool

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Note: `pass_user_data` and `pass_chat_data` determine whether a dict you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same dict.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pattern** (str | Pattern, optional) – Regex pattern. If not `None`, `re.match` is used on `telegram.InlineQuery.query` to determine if an update should be handled by this handler.
- **pass_groups** (bool, optional) – If the callback should be passed the result of `re.match(pattern, data).groups()` as a keyword argument called `groups`. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_groupdict** (bool, optional) – If the callback should be passed the result of `re.match(pattern, data).groupdict()` as a keyword argument called `groupdict`. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Union[str, Update]*) → Union[bool, Match[AnyStr], None]

Determines whether an update should be passed to this handlers `callback`.

Parameters *update* (`telegram.Update`) – Incoming telegram update.

Returns bool

collect_additional_context (*context: CallbackContext, update: Union[str, Update], dispatcher: Dispatcher, check_result: Union[bool, Match[AnyStr], None]*) → None

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (`telegram.ext.CallbackContext`) – The context object.

- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **dispatcher** (*telegram.ext.Dispatcher*) – The calling dispatcher.
- **check_result** – The result (return value) from *check_update*.

collect_optional_args (*dispatcher: Dispatcher, update: Union[str, Update] = None, check_result: Union[bool, Match[AnyStr], None] = None*) → Dict[str, Any]

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (*telegram.ext.Dispatcher*) – The dispatcher.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **check_result** – The result from *check_update*

telegram.ext.MessageHandler

```
class telegram.ext.MessageHandler (filters: telegram.ext.filters.BaseFilter, callback: Callable[[Union[str, Update], CallbackContext], RT], pass_update_queue: bool = False, pass_job_queue: bool = False, pass_user_data: bool = False, pass_chat_data: bool = False, message_updates: bool = None, channel_post_updates: bool = None, edited_updates: bool = None, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: *telegram.ext.handler.Handler*

Handler class to handle telegram messages. They might contain text, media or status updates.

filters

Only allow updates with these Filters. See *telegram.ext.filters* for a full list of all available filters.

Type Filter

callback

The callback function for this handler.

Type callable

pass_update_queue

Determines whether *update_queue* will be passed to the callback function.

Type bool

pass_job_queue

Determines whether *job_queue* will be passed to the callback function.

Type bool

pass_user_data

Determines whether *user_data* will be passed to the callback function.

Type bool

pass_chat_data

Determines whether *chat_data* will be passed to the callback function.

Type bool

message_updates

Should “normal” message updates be handled? Default is `None`.

Type `bool`

channel_post_updates

Should channel posts updates be handled? Default is `None`.

Type `bool`

edited_updates

Should “edited” message updates be handled? Default is `None`.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **filters** (`telegram.ext.BaseFilter`, optional) – A filter inheriting from `telegram.ext.filters.BaseFilter`. Standard filters can be found in `telegram.ext.filters.Filters`. Filters can be combined using bitwise operators (& for and, | for or, ~ for not). Default is `telegram.ext.filters.Filters.update`. This defaults to all `message_type` updates being: `message`, `edited_message`, `channel_post` and `edited_channel_post`. If you don’t want or need any of those pass `~Filters.update.*` in the filter argument.
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:


```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.
- **pass_update_queue** (`bool`, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (`bool`, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.

- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **message_updates** (bool, optional) – Should “normal” message updates be handled? Default is `None`. DEPRECATED: Please switch to filters for update filtering.
- **channel_post_updates** (bool, optional) – Should channel posts updates be handled? Default is `None`. DEPRECATED: Please switch to filters for update filtering.
- **edited_updates** (bool, optional) – Should “edited” message updates be handled? Default is `None`. DEPRECATED: Please switch to filters for update filtering.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

Raises `ValueError`

check_update (*update*: `Union[str, Update]`) → `Union[bool, Dict[str, Any], None]`

Determines whether an update should be passed to this handlers `callback`.

Parameters *update* (`telegram.Update`) – Incoming telegram update.

Returns `bool`

collect_additional_context (*context*: `CallbackContext`, *update*: `Union[str, Update]`, *dispatcher*: `Dispatcher`, *check_result*: `Union[bool, Dict[str, Any], None]`) → `None`

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (`telegram.ext.CallbackContext`) – The context object.
- **update** (`telegram.Update`) – The update to gather chat/user id from.
- **dispatcher** (`telegram.ext.Dispatcher`) – The calling dispatcher.
- **check_result** – The result (return value) from `check_update`.

`telegram.ext.PollAnswerHandler`

```
class telegram.ext.PollAnswerHandler (callback: Callable[[Union[str, Update], CallbackContext], RT], pass_update_queue: bool = False, pass_job_queue: bool = False, pass_user_data: bool = False, pass_chat_data: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: `telegram.ext.handler.Handler`

Handler class to handle Telegram updates that contain a poll answer.

callback

The callback function for this handler.

Type `callable`

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type `bool`

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type `bool`

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type `bool`

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update*: Union[str, Update]) → bool

Determines whether an update should be passed to this handlers *callback*.

Parameters *update* (*telegram.Update*) – Incoming telegram update.

Returns bool

telegram.ext.PollHandler

```
class telegram.ext.PollHandler(callback: Callable[[Union[str, Update], CallbackContext], RT], pass_update_queue: bool = False,
                               pass_job_queue: bool = False, pass_user_data: bool = False,
                               pass_chat_data: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: telegram.ext.handler.Handler

Handler class to handle Telegram updates that contain a poll.

callback

The callback function for this handler.

Type callable

pass_update_queue

Determines whether *update_queue* will be passed to the callback function.

Type bool

pass_job_queue

Determines whether *job_queue* will be passed to the callback function.

Type bool

pass_user_data

Determines whether *user_data* will be passed to the callback function.

Type bool

pass_chat_data

Determines whether *chat_data* will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Note: *pass_user_data* and *pass_chat_data* determine whether a dict you can use to keep any data in will be sent to the *callback* function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same dict.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting *run_async* to True, you cannot rely on adding custom attributes to *telegram.ext.CallbackContext*. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Union[str, Update]*) → bool

Determines whether an update should be passed to this handlers `callback`.

Parameters *update* (`telegram.Update`) – Incoming telegram update.

Returns bool

telegram.ext.PreCheckoutQueryHandler

```
class telegram.ext.PreCheckoutQueryHandler (callback: Callable[[Union[str, Up-
                                         date], CallbackContext], RT],
                                         pass_update_queue: bool = False,
                                         pass_job_queue: bool = False,
                                         pass_user_data: bool = False,
                                         pass_chat_data: bool = False,
                                         run_async: Union[bool, tele-
                                         gram.utils.helpers.DefaultValue] =
                                         <telegram.utils.helpers.DefaultValue
                                         object>)
```

Bases: `telegram.ext.handler.Handler`

Handler class to handle Telegram PreCheckout callback queries.

callback

The callback function for this handler.

Type callable

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type bool

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type `bool`

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type `bool`

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (`bool`, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` DEPRECATED: Please switch to context based callbacks. instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`.
- **pass_job_queue** (`bool`, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (`bool`, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (`bool`, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (`bool`) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Union[str, Update]*) → bool

Determines whether an update should be passed to this handlers *callback*.

Parameters *update* (*telegram.Update*) – Incoming telegram update.

Returns bool

telegram.ext.PrefixHandler

```
class telegram.ext.PrefixHandler(prefix: Union[str, List[str], Tuple[str, ...]], command: Union[str, List[str], Tuple[str, ...]], callback: Callable[[Union[str, Update], CallbackContext], RT], filters: telegram.ext.filters.BaseFilter = None, pass_args: bool = False, pass_update_queue: bool = False, pass_job_queue: bool = False, pass_user_data: bool = False, pass_chat_data: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: telegram.ext.commandhandler.CommandHandler

Handler class to handle custom prefix commands

This is a intermediate handler between *MessageHandler* and *CommandHandler*. It supports configurable commands with the same options as *CommandHandler*. It will respond to every combination of *prefix* and *command*. It will add a list to the *CallbackContext* named *CallbackContext.args*. It will contain a list of strings, which is the text following the command split on single or consecutive whitespace characters.

Examples:

```
Single prefix and command:

    PrefixHandler('!', 'test', callback) will respond to '!test'.

Multiple prefixes, single command:

    PrefixHandler(['!', '#'], 'test', callback) will respond to '!test' and
    '#test'.

Multiple prefixes and commands:

    PrefixHandler(['!', '#'], ['test', 'help'], callback) will respond to '!
    ↪test',
    '#test', '!help' and '#help'.
```

By default the handler listens to messages as well as edited messages. To change this behavior use ~“*Filters.update.edited_message*”.

callback

The callback function for this handler.

Type callable

filters

Optional. Only allow updates with these Filters.

Type telegram.ext.BaseFilter

pass_args

Determines whether the handler should be passed args.

Type bool

pass_update_queue

Determines whether *update_queue* will be passed to the callback function.

Type bool

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type bool

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type bool

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **prefix** (`telegram.utils.types.SLT[str]`) – The prefix(es) that will precede `command`.
- **command** (`telegram.utils.types.SLT[str]`) – The command or list of commands this handler should listen for.
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **filters** (`telegram.ext.BaseFilter`, optional) – A filter inheriting from `telegram.ext.filters.BaseFilter`. Standard filters can be found in `telegram.ext.filters.Filters`. Filters can be combined using bitwise operators (& for and, | for or, ~ for not).
- **pass_args** (bool, optional) – Determines whether the handler should be passed the arguments passed to the command as a keyword argument called `args`. It will contain a list of strings, which is the text following the command split on single or consecutive whitespace characters. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that

contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.

- **pass_job_queue** (`bool`, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (`bool`, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (`bool`, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (`bool`) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Union[str, Update]*) → Union[bool, Tuple[List[str], Union[bool, Dict[KT, VT], None]], None]

Determines whether an update should be passed to this handlers `callback`.

Parameters *update* (`telegram.Update`) – Incoming telegram update.

Returns The list of args for the handler.

Return type `list`

collect_additional_context (*context: CallbackContext, update: Union[str, Update], dispatcher: Dispatcher, check_result: Union[bool, Tuple[List[str], Optional[bool]], None]*) → None

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (`telegram.ext.CallbackContext`) – The context object.
- **update** (`telegram.Update`) – The update to gather chat/user id from.
- **dispatcher** (`telegram.ext.Dispatcher`) – The calling dispatcher.
- **check_result** – The result (return value) from `check_update`.

command

The list of commands this handler should listen for.

Returns `List[str]`

prefix

The prefixes that will precede `command`.

Returns `List[str]`

telegram.ext.RegexHandler

```
class telegram.ext.RegexHandler (pattern: Union[str, Pattern[AnyStr]], callback:
    Callable[[Union[str, Update], CallbackContext], RT],
    pass_groups: bool = False, pass_groupdict: bool = False,
    pass_update_queue: bool = False, pass_job_queue: bool
    = False, pass_user_data: bool = False, pass_chat_data:
    bool = False, allow_edited: bool = False, mes-
    sage_updates: bool = True, channel_post_updates:
    bool = False, edited_updates: bool = False, run_async:
    Union[bool, telegram.utils.helpers.DefaultValue] =
    <telegram.utils.helpers.DefaultValue object>)
```

Bases: telegram.ext.messagehandler.MessageHandler

Handler class to handle Telegram updates based on a regex.

It uses a regular expression to check text messages. Read the documentation of the `re` module for more information. The `re.match` function is used to determine if an update should be handled by this handler.

pattern

The regex pattern.

Type str|Pattern

callback

The callback function for this handler.

Type callable

pass_groups

Determines whether groups will be passed to the callback function.

Type bool

pass_groupdict

Determines whether groupdict. will be passed to the callback function.

Type bool

pass_update_queue

Determines whether update_queue will be passed to the callback function.

Type bool

pass_job_queue

Determines whether job_queue will be passed to the callback function.

Type bool

pass_user_data

Determines whether user_data will be passed to the callback function.

Type bool

pass_chat_data

Determines whether chat_data will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Note: This handler is being deprecated. For the same use case use: `MessageHandler(Filters.regex(r'pattern'), callback)`

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **pattern** (`str` | `Pattern`) – The regex pattern.
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.
- **pass_groups** (`bool`, optional) – If the callback should be passed the result of `re.match(pattern, data).groups()` as a keyword argument called `groups`. Default is `False`
- **pass_groupdict** (`bool`, optional) – If the callback should be passed the result of `re.match(pattern, data).groupdict()` as a keyword argument called `groupdict`. Default is `False`
- **pass_update_queue** (`bool`, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`.
- **pass_job_queue** (`bool`, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`.
- **pass_user_data** (`bool`, optional) – If set to `True`, a keyword argument called `user_data` will be passed to the callback function. Default is `False`.
- **pass_chat_data** (`bool`, optional) – If set to `True`, a keyword argument called `chat_data` will be passed to the callback function. Default is `False`.
- **message_updates** (`bool`, optional) – Should “normal” message updates be handled? Default is `True`.
- **channel_post_updates** (`bool`, optional) – Should channel posts updates be handled? Default is `True`.
- **edited_updates** (`bool`, optional) – Should “edited” message updates be handled? Default is `False`.
- **run_async** (`bool`) – Determines whether the callback will run asynchronously. Defaults to `False`.

Raises `ValueError`

collect_optional_args (*dispatcher: Dispatcher, update: Union[str, Update] = None, check_result: Union[bool, Dict[str, Any], None] = None*) → `Dict[str, Any]`

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (`telegram.ext.Dispatcher`) – The dispatcher.

- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **check_result** – The result from `check_update`

telegram.ext.ShippingQueryHandler

```
class telegram.ext.ShippingQueryHandler(callback: Callable[[Union[str, Update], CallbackContext], RT], pass_update_queue: bool = False, pass_job_queue: bool = False, pass_user_data: bool = False, pass_chat_data: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: `telegram.ext.handler.Handler`

Handler class to handle Telegram shipping callback queries.

callback

The callback function for this handler.

Type `callable`

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type `bool`

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type `bool`

pass_user_data

Determines whether `user_data` will be passed to the callback function.

Type `bool`

pass_chat_data

Determines whether `chat_data` will be passed to the callback function.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Note: `pass_user_data` and `pass_chat_data` determine whether a `dict` you can use to keep any data in will be sent to the `callback` function. Related to either the user or the chat that the update was sent in. For each update from the same user or in the same chat, it will be the same `dict`.

Note that this is DEPRECATED, and you should use context based callbacks. See <https://git.io/fxJuV> for more info.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **callback** (`callable`) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_update_queue** (bool, optional) – If set to True, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is False. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to True, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is False. DEPRECATED: Please switch to context based callbacks.
- **pass_user_data** (bool, optional) – If set to True, a keyword argument called `user_data` will be passed to the callback function. Default is False. DEPRECATED: Please switch to context based callbacks.
- **pass_chat_data** (bool, optional) – If set to True, a keyword argument called `chat_data` will be passed to the callback function. Default is False. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to False.

check_update (*update: Union[str, Update]*) → bool

Determines whether an update should be passed to this handlers `callback`.

Parameters *update* (`telegram.Update`) – Incoming telegram update.

Returns bool

telegram.ext.StringCommandHandler

```
class telegram.ext.StringCommandHandler(command: str, callback: Callable[[Union[str,
Update], CallbackContext], RT], pass_args:
    bool = False, pass_update_queue: bool =
    False, pass_job_queue: bool =
    False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)
```

Bases: `telegram.ext.handler.Handler`

Handler class to handle string commands. Commands are string updates that start with `/`.

Note: This handler is not used to handle Telegram `telegram.Update`, but strings manually put in the queue. For example to send messages with the bot using command line or API.

Warning: When setting `run_async` to True, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

command

The command this handler should listen for.

Type str

callback

The callback function for this handler.

Type callable

pass_args

Determines whether the handler should be passed `args`.

Type bool

pass_update_queue

Determines whether `update_queue` will be passed to the callback function.

Type bool

pass_job_queue

Determines whether `job_queue` will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type bool

Parameters

- **command** (str) – The command this handler should listen for.
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.

- **pass_args** (bool, optional) – Determines whether the handler should be passed the arguments passed to the command as a keyword argument called `args`. It will contain a list of strings, which is the text following the command split on single or consecutive whitespace characters. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a class: `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Union[str, Update]*) → Optional[List[str]]

Determines whether an update should be passed to this handlers `callback`.

Parameters **update** (str) – An incoming command.

Returns bool

collect_additional_context (*context: CallbackContext, update: Union[str, Update], dispatcher: Dispatcher, check_result: Optional[List[str]]*) → None

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (*telegram.ext.CallbackContext*) – The context object.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **dispatcher** (*telegram.ext.Dispatcher*) – The calling dispatcher.
- **check_result** – The result (return value) from *check_update*.

collect_optional_args (*dispatcher: Dispatcher, update: Union[str, Update] = None, check_result: Optional[List[str]] = None*) → Dict[str, Any]

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (*telegram.ext.Dispatcher*) – The dispatcher.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **check_result** – The result from *check_update*

telegram.ext.StringRegexHandler

class telegram.ext.StringRegexHandler (*pattern: Union[str, Pattern[AnyStr]], callback: Callable[[Union[str, Update], CallbackContext], RT], pass_groups: bool = False, pass_groupdict: bool = False, pass_update_queue: bool = False, pass_job_queue: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>*)

Bases: telegram.ext.handler.Handler

Handler class to handle string updates based on a regex which checks the update content.

Read the documentation of the `re` module for more information. The `re.match` function is used to determine if an update should be handled by this handler.

Note: This handler is not used to handle Telegram *telegram.Update*, but strings manually put in the queue. For example to send messages with the bot using command line or API.

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to *telegram.ext.CallbackContext*. See its docs for more info.

pattern

The regex pattern.

Type str|Pattern

callback

The callback function for this handler.

Type callable

pass_groups

Determines whether groups will be passed to the callback function.

Type `bool`

pass_groupdict

Determines whether groupdict. will be passed to the callback function.

Type `bool`

pass_update_queue

Determines whether update_queue will be passed to the callback function.

Type `bool`

pass_job_queue

Determines whether job_queue will be passed to the callback function.

Type `bool`

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Parameters

- **pattern** (`str` | `Pattern`) – The regex pattern.
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.
- **pass_groups** (`bool`, optional) – If the callback should be passed the result of `re.match(pattern, data).groups()` as a keyword argument called `groups`. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_groupdict** (`bool`, optional) – If the callback should be passed the result of `re.match(pattern, data).groupdict()` as a keyword argument called `groupdict`. Default is `False` DEPRECATED: Please switch to context based callbacks.
- **pass_update_queue** (`bool`, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (`bool`, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (`bool`) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (`update: Union[str, Update]`) → `Optional[Match[AnyStr]]`

Determines whether an update should be passed to this handlers `callback`.

Parameters `update` (`str`) – An incoming command.

Returns `bool`

collect_additional_context (*context: CallbackContext, update: Union[str, Update], dispatcher: Dispatcher, check_result: Optional[Match[AnyStr]]*) → None

Prepares additional arguments for the context. Override if needed.

Parameters

- **context** (*telegram.ext.CallbackContext*) – The context object.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **dispatcher** (*telegram.ext.Dispatcher*) – The calling dispatcher.
- **check_result** – The result (return value) from *check_update*.

collect_optional_args (*dispatcher: Dispatcher, update: Union[str, Update] = None, check_result: Optional[Match[AnyStr]] = None*) → Dict[str, Any]

Prepares the optional arguments. If the handler has additional optional args, it should subclass this method, but remember to call this super method.

DEPRECATED: This method is being replaced by new context based callbacks. Please see <https://git.io/fxJuV> for more info.

Parameters

- **dispatcher** (*telegram.ext.Dispatcher*) – The dispatcher.
- **update** (*telegram.Update*) – The update to gather chat/user id from.
- **check_result** – The result from *check_update*

telegram.ext.TypeHandler

class telegram.ext.**TypeHandler** (*type: Type[CT_co], callback: Callable[[Any, CallbackContext], RT], strict: bool = False, pass_update_queue: bool = False, pass_job_queue: bool = False, run_async: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>)*

Bases: telegram.ext.handler.Handler

Handler class to handle updates of custom types.

type

The type of updates this handler should process.

Type *type*

callback

The callback function for this handler.

Type callable

strict

Use type instead of isinstance. Default is False.

Type bool

pass_update_queue

Determines whether update_queue will be passed to the callback function.

Type bool

pass_job_queue

Determines whether job_queue will be passed to the callback function.

Type bool

run_async

Determines whether the callback will run asynchronously.

Type `bool`

Warning: When setting `run_async` to `True`, you cannot rely on adding custom attributes to `telegram.ext.CallbackContext`. See its docs for more info.

Parameters

- **type** (*type*) – The type of updates this handler should process, as determined by `isinstance`
- **callback** (callable) – The callback function for this handler. Will be called when `check_update` has determined that an update should be processed by this handler. Callback signature for context based API:

```
def callback(update: Update, context: CallbackContext)
```

The return value of the callback is usually ignored except for the special case of `telegram.ext.ConversationHandler`.
- **strict** (bool, optional) – Use type instead of `isinstance`. Default is `False`
- **pass_update_queue** (bool, optional) – If set to `True`, a keyword argument called `update_queue` will be passed to the callback function. It will be the `Queue` instance used by the `telegram.ext.Updater` and `telegram.ext.Dispatcher` that contains new updates which can be used to insert updates. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **pass_job_queue** (bool, optional) – If set to `True`, a keyword argument called `job_queue` will be passed to the callback function. It will be a `telegram.ext.JobQueue` instance created by the `telegram.ext.Updater` which can be used to schedule new jobs. Default is `False`. DEPRECATED: Please switch to context based callbacks.
- **run_async** (bool) – Determines whether the callback will run asynchronously. Defaults to `False`.

check_update (*update: Any*) → bool

Determines whether an update should be passed to this handlers `callback`.

Parameters **update** (`telegram.Update`) – Incoming telegram update.

Returns bool

3.1.12 Persistence

telegram.ext.BasePersistence

```
class telegram.ext.BasePersistence (store_user_data: bool = True, store_chat_data: bool = True, store_bot_data: bool = True)
```

Bases: `abc.ABC`

Interface class for adding persistence to your bot. Subclass this object for different implementations of a persistent bot.

All relevant methods must be overwritten. This means:

- If `store_bot_data` is `True` you must overwrite `get_bot_data()` and `update_bot_data()`.
- If `store_chat_data` is `True` you must overwrite `get_chat_data()` and `update_chat_data()`.

- If `store_user_data` is `True` you must overwrite `get_user_data()` and `update_user_data()`.
- If you want to store conversation data with `telegram.ext.ConversationHandler`, you must overwrite `get_conversations()` and `update_conversation()`.
- `flush()` will be called when the bot is shutdown.

Warning: Persistence will try to replace `telegram.Bot` instances by `REPLACED_BOT` and insert the bot set with `set_bot()` upon loading of the data. This is to ensure that changes to the bot apply to the saved objects, too. If you change the bots token, this may lead to e.g. `Chat not found` errors. For the limitations on replacing bots see `replace_bot()` and `insert_bot()`.

Note: `replace_bot()` and `insert_bot()` are used *independently* of the implementation of the `update/get_*()` methods, i.e. you don't need to worry about it while implementing a custom persistence subclass.

store_user_data

Optional, Whether user_data should be saved by this persistence class.

Type `bool`

store_chat_data

Optional. Whether chat_data should be saved by this persistence class.

Type `bool`

store_bot_data

Optional. Whether bot_data should be saved by this persistence class.

Type `bool`

Parameters

- **store_user_data** (`bool`, optional) – Whether user_data should be saved by this persistence class. Default is `True`.
- **store_chat_data** (`bool`, optional) – Whether chat_data should be saved by this persistence class. Default is `True`.
- **store_bot_data** (`bool`, optional) – Whether bot_data should be saved by this persistence class. Default is `True`.

REPLACED_BOT = `'bot_instance_replaced_by_ptb_persistence'`

Placeholder for `telegram.Bot` instances replaced in saved data.

Type `str`

flush() → `None`

Will be called by `telegram.ext.Updater` upon receiving a stop signal. Gives the persistence a chance to finish up saving or close a database connection gracefully. If this is not of any importance just pass will be sufficient.

get_bot_data() → `Dict[Any, Any]`

“Will be called by `telegram.ext.Dispatcher` upon creation with a persistence object. It should return the bot_data if stored, or an empty dict.

Returns The restored bot data.

Return type `dict`

get_chat_data () → DefaultDict[int, Dict[Any, Any]]

“Will be called by `telegram.ext.Dispatcher` upon creation with a persistence object. It should return the chat_data if stored, or an empty defaultdict (dict).

Returns The restored chat data.

Return type defaultdict

get_conversations (name: str) → Dict[Tuple[int, ...], Optional[object]]

“Will be called by `telegram.ext.Dispatcher` when a `telegram.ext.ConversationHandler` is added if `telegram.ext.ConversationHandler.persistent` is True. It should return the conversations for the handler with *name* or an empty dict

Parameters *name* (str) – The handlers name.

Returns The restored conversations for the handler.

Return type dict

get_user_data () → DefaultDict[int, Dict[Any, Any]]

“Will be called by `telegram.ext.Dispatcher` upon creation with a persistence object. It should return the user_data if stored, or an empty defaultdict (dict).

Returns The restored user data.

Return type defaultdict

insert_bot (obj: object) → object

Replaces all instances of `REPLACED_BOT` that occur within the passed object with bot. Currently, this handles objects of type list, tuple, set, frozenset, dict, defaultdict and objects that have a `__dict__` or `__slot__` attribute, excluding objects that can't be copied with `copy.copy`.

Parameters *obj* (object) – The object

Returns Copy of the object with Bot instances inserted.

Return type obj

classmethod replace_bot (obj: object) → object

Replaces all instances of `telegram.Bot` that occur within the passed object with `REPLACED_BOT`. Currently, this handles objects of type list, tuple, set, frozenset, dict, defaultdict and objects that have a `__dict__` or `__slot__` attribute, excluding objects that can't be copied with `copy.copy`.

Parameters *obj* (object) – The object

Returns Copy of the object with Bot instances replaced.

Return type obj

set_bot (bot: telegram.bot.Bot) → None

Set the Bot to be used by this persistence instance.

Parameters *bot* (`telegram.Bot`) – The bot.

update_bot_data (data: Dict[KT, VT]) → None

Will be called by the `telegram.ext.Dispatcher` after a handler has handled an update.

Parameters *data* (dict) – The `telegram.ext.dispatcher.bot_data`.

update_chat_data (chat_id: int, data: Dict[KT, VT]) → None

Will be called by the `telegram.ext.Dispatcher` after a handler has handled an update.

Parameters

- **chat_id** (int) – The chat the data might have been changed for.
- **data** (dict) – The `telegram.ext.dispatcher.chat_data [chat_id]`.

update_conversation (*name: str, key: Tuple[int, ...], new_state: Optional[object]*) → None
 Will be called when a `telegram.ext.ConversationHandler.update_state` is called.
 This allows the storage of the new state in the persistence.

Parameters

- **name** (`str`) – The handler’s name.
- **key** (`tuple`) – The key the state is changed for.
- **new_state** (`tuple` | `any`) – The new state for the given key.

update_user_data (*user_id: int, data: Dict[KT, VT]*) → None
 Will be called by the `telegram.ext.Dispatcher` after a handler has handled an update.

Parameters

- **user_id** (`int`) – The user the data might have been changed for.
- **data** (`dict`) – The `telegram.ext.dispatcher.user_data [user_id]`.

telegram.ext.PicklePersistence

```
class telegram.ext.PicklePersistence(filename: str, store_user_data: bool = True,
                                     store_chat_data: bool = True, store_bot_data: bool
                                     = True, single_file: bool = True, on_flush: bool =
                                     False)
```

Bases: `telegram.ext.basepersistence.BasePersistence`

Using python’s builtin pickle for making you bot persistent.

Warning: `PicklePersistence` will try to replace `telegram.Bot` instances by `REPLACED_BOT` and insert the bot set with `telegram.ext.BasePersistence.set_bot()` upon loading of the data. This is to ensure that changes to the bot apply to the saved objects, too. If you change the bots token, this may lead to e.g. Chat not found errors. For the limitations on replacing bots see `telegram.ext.BasePersistence.replace_bot()` and `telegram.ext.BasePersistence.insert_bot()`.

filename

The filename for storing the pickle files. When `single_file` is `False` this will be used as a prefix.

Type `str`

store_user_data

Optional. Whether user_data should be saved by this persistence class.

Type `bool`

store_chat_data

Optional. Whether user_data should be saved by this persistence class.

Type `bool`

store_bot_data

Optional. Whether bot_data should be saved by this persistence class.

Type `bool`

single_file

Optional. When `False` will store 3 separate files of `filename_user_data`, `filename_chat_data` and `filename_conversations`. Default is `True`.

Type `bool`

on_flush

When `True` will only save to file when `flush()` is called and keep data in memory until that happens. When `False` will store data on any transaction *and* on call to `flush()`. Default is `False`.

Type `bool`, optional

Parameters

- **filename** (`str`) – The filename for storing the pickle files. When `single_file` is `False` this will be used as a prefix.
- **store_user_data** (`bool`, optional) – Whether user_data should be saved by this persistence class. Default is `True`.
- **store_chat_data** (`bool`, optional) – Whether user_data should be saved by this persistence class. Default is `True`.
- **store_bot_data** (`bool`, optional) – Whether bot_data should be saved by this persistence class. Default is `True`.
- **single_file** (`bool`, optional) – When `False` will store 3 separate files of `filename_user_data`, `filename_chat_data` and `filename_conversations`. Default is `True`.
- **on_flush** (`bool`, optional) – When `True` will only save to file when `flush()` is called and keep data in memory until that happens. When `False` will store data on any transaction *and* on call to `flush()`. Default is `False`.

flush() → `None`

Will save all data in memory to pickle file(s).

get_bot_data() → `Dict[Any, Any]`

Returns the bot_data from the pickle file if it exists or an empty dict.

Returns The restored bot data.

Return type `dict`

get_chat_data() → `DefaultDict[int, Dict[Any, Any]]`

Returns the chat_data from the pickle file if it exists or an empty defaultdict.

Returns The restored chat data.

Return type `defaultdict`

get_conversations (*name: str*) → `Dict[Tuple[int, ...], Optional[object]]`

Returns the conversations from the pickle file if it exists or an empty dict.

Parameters **name** (`str`) – The handlers name.

Returns The restored conversations for the handler.

Return type `dict`

get_user_data() → `DefaultDict[int, Dict[Any, Any]]`

Returns the user_data from the pickle file if it exists or an empty defaultdict.

Returns The restored user data.

Return type `defaultdict`

update_bot_data (*data: Dict[KT, VT]*) → `None`

Will update the bot_data and depending on `on_flush` save the pickle file.

Parameters **data** (`dict`) – The `telegram.ext.dispatcher.bot_data`.

update_chat_data (*chat_id: int, data: Dict[KT, VT]*) → `None`

Will update the chat_data and depending on `on_flush` save the pickle file.

Parameters

- **chat_id** (`int`) – The chat the data might have been changed for.

- **data** (dict) – The `telegram.ext.dispatcher.chat_data [chat_id]`.

update_conversation (*name: str, key: Tuple[int, ...], new_state: Optional[object]*) → None

Will update the conversations for the given handler and depending on *on_flush* save the pickle file.

Parameters

- **name** (str) – The handler’s name.
- **key** (tuple) – The key the state is changed for.
- **new_state** (tuple | any) – The new state for the given key.

update_user_data (*user_id: int, data: Dict[KT, VT]*) → None

Will update the user_data and depending on *on_flush* save the pickle file.

Parameters

- **user_id** (int) – The user the data might have been changed for.
- **data** (dict) – The `telegram.ext.dispatcher.user_data [user_id]`.

telegram.ext.DictPersistence

```
class telegram.ext.DictPersistence (store_user_data: bool = True, store_chat_data: bool
                                   = True, store_bot_data: bool = True, user_data_json:
                                   str = ", chat_data_json: str = ", bot_data_json: str =
                                   ", conversations_json: str = ")
```

Bases: `telegram.ext.basepersistence.BasePersistence`

Using python’s dicts and json for making your bot persistent.

Note: This class does *not* implement a `flush()` method, meaning that data managed by `DictPersistence` is in-memory only and will be lost when the bot shuts down. This is, because `DictPersistence` is mainly intended as starting point for custom persistence classes that need to JSON-serialize the stored data before writing them to file/database.

Warning: `DictPersistence` will try to replace `telegram.Bot` instances by `REPLACED_BOT` and insert the bot set with `telegram.ext.BasePersistence.set_bot()` upon loading of the data. This is to ensure that changes to the bot apply to the saved objects, too. If you change the bots token, this may lead to e.g. Chat not found errors. For the limitations on replacing bots see `telegram.ext.BasePersistence.replace_bot()` and `telegram.ext.BasePersistence.insert_bot()`.

store_user_data

Whether user_data should be saved by this persistence class.

Type bool

store_chat_data

Whether chat_data should be saved by this persistence class.

Type bool

store_bot_data

Whether bot_data should be saved by this persistence class.

Type bool

Parameters

- **store_user_data** (bool, optional) – Whether user_data should be saved by this persistence class. Default is True.

- **store_chat_data** (`bool`, optional) – Whether `user_data` should be saved by this persistence class. Default is `True`.
- **store_bot_data** (`bool`, optional) – Whether `bot_data` should be saved by this persistence class. Default is `True`.
- **user_data_json** (`str`, optional) – Json string that will be used to reconstruct `user_data` on creating this persistence. Default is `""`.
- **chat_data_json** (`str`, optional) – Json string that will be used to reconstruct `chat_data` on creating this persistence. Default is `""`.
- **bot_data_json** (`str`, optional) – Json string that will be used to reconstruct `bot_data` on creating this persistence. Default is `""`.
- **conversations_json** (`str`, optional) – Json string that will be used to reconstruct conversation on creating this persistence. Default is `""`.

bot_data

The `bot_data` as a dict.

Type `dict`

bot_data_json

The `bot_data` serialized as a JSON-string.

Type `str`

chat_data

The `chat_data` as a dict.

Type `dict`

chat_data_json

The `chat_data` serialized as a JSON-string.

Type `str`

conversations

The conversations as a dict.

Type `dict`

conversations_json

The conversations serialized as a JSON-string.

Type `str`

get_bot_data () → `Dict[Any, Any]`

Returns the `bot_data` created from the `bot_data_json` or an empty dict.

Returns The restored bot data.

Return type `dict`

get_chat_data () → `DefaultDict[int, Dict[Any, Any]]`

Returns the `chat_data` created from the `chat_data_json` or an empty `defaultdict`.

Returns The restored chat data.

Return type `defaultdict`

get_conversations (*name: str*) → `Dict[Tuple[int, ...], Optional[object]]`

Returns the conversations created from the `conversations_json` or an empty dict.

Returns The restored conversations data.

Return type `dict`

get_user_data () → `DefaultDict[int, Dict[Any, Any]]`

Returns the `user_data` created from the `user_data_json` or an empty `defaultdict`.

Returns The restored user data.

Return type defaultdict

update_bot_data (*data: Dict[KT, VT]*) → None

Will update the bot_data (if changed).

Parameters **data** (dict) – The telegram.ext.dispatcher.bot_data.

update_chat_data (*chat_id: int, data: Dict[KT, VT]*) → None

Will update the chat_data (if changed).

Parameters

- **chat_id** (int) – The chat the data might have been changed for.
- **data** (dict) – The telegram.ext.dispatcher.chat_data [chat_id].

update_conversation (*name: str, key: Tuple[int, ...], new_state: Optional[object]*) → None

Will update the conversations for the given handler.

Parameters

- **name** (str) – The handler's name.
- **key** (tuple) – The key the state is changed for.
- **new_state** (tuple | any) – The new state for the given key.

update_user_data (*user_id: int, data: Dict[KT, VT]*) → None

Will update the user_data (if changed).

Parameters

- **user_id** (int) – The user the data might have been changed for.
- **data** (dict) – The telegram.ext.dispatcher.user_data [user_id].

user_data

The user_data as a dict.

Type dict

user_data_json

The user_data serialized as a JSON-string.

Type str

3.2 telegram package

3.2.1 telegram.Animation

```
class telegram.Animation (file_id: str, file_unique_id: str, width: int, height: int, duration: int,  
                           thumb: telegram.files.photosize.PhotoSize = None, file_name: str =  
                           None, mime_type: str = None, file_size: int = None, bot: Bot = None,  
                           **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents an animation file (GIF or H.264/MPEG-4 AVC video without sound).

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *file_unique_id* is equal.

file_id

File identifier.

Type str

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

width

Video width as defined by sender.

Type `int`

height

Video height as defined by sender.

Type `int`

duration

Duration of the video in seconds as defined by sender.

Type `int`

thumb

Optional. Animation thumbnail as defined by sender.

Type `telegram.PhotoSize`

file_name

Optional. Original animation filename as defined by sender.

Type `str`

mime_type

Optional. MIME type of the file as defined by sender.

Type `str`

file_size

Optional. File size.

Type `int`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **width** (`int`) – Video width as defined by sender.
- **height** (`int`) – Video height as defined by sender.
- **duration** (`int`) – Duration of the video in seconds as defined by sender.
- **thumb** (`telegram.PhotoSize`, optional) – Animation thumbnail as defined by sender.
- **file_name** (`str`, optional) – Original animation filename as defined by sender.
- **mime_type** (`str`, optional) – MIME type of the file as defined by sender.
- **file_size** (`int`, optional) – File size.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

get_file (*timeout: int = None, api_kwargs: Dict[str, Any] = None*) → File
Convenience wrapper over `telegram.Bot.get_file`

Parameters

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.2 telegram.Audio

class `telegram.Audio` (*file_id: str, file_unique_id: str, duration: int, performer: str = None, title: str = None, mime_type: str = None, file_size: int = None, thumb: telegram.files.photosize.PhotoSize = None, bot: Bot = None, file_name: str = None, **kwargs*)

Bases: `telegram.base.TelegramObject`

This object represents an audio file to be treated as music by the Telegram clients.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

file_id

Identifier for this file.

Type `str`

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

duration

Duration of the audio in seconds.

Type `int`

performer

Optional. Performer of the audio as defined by sender or by audio tags.

Type `str`

title

Optional. Title of the audio as defined by sender or by audio tags.

Type `str`

file_name

Optional. Original filename as defined by sender.

Type `str`

mime_type

Optional. MIME type of the file as defined by sender.

Type `str`

file_size

Optional. File size.

Type `int`

thumb

Optional. Thumbnail of the album cover to which the music file belongs.

Type `telegram.PhotoSize`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **duration** (`int`) – Duration of the audio in seconds as defined by sender.
- **performer** (`str`, optional) – Performer of the audio as defined by sender or by audio tags.
- **title** (`str`, optional) – Title of the audio as defined by sender or by audio tags.
- **file_name** (`str`, optional) – Original filename as defined by sender.
- **mime_type** (`str`, optional) – MIME type of the file as defined by sender.
- **file_size** (`int`, optional) – File size.
- **thumb** (`telegram.PhotoSize`, optional) – Thumbnail of the album cover to which the music file belongs.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

get_file (`timeout: int = None, api_kwargs: Dict[str, Any] = None`) → `File`
Convenience wrapper over `telegram.Bot.get_file`

Parameters

- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.3 telegram.Bot

```
class telegram.Bot (token: str, base_url: str = None, base_file_url: str = None, request: Request  
                   = None, private_key: bytes = None, private_key_password: bytes = None,  
                   defaults: Defaults = None)
```

Bases: `telegram.base.TelegramObject`

This object represents a Telegram Bot.

Parameters

- **token** (`str`) – Bot's unique authentication.
- **base_url** (`str`, optional) – Telegram Bot API service URL.

- **base_file_url** (*str*, optional) – Telegram Bot API file URL.
- **request** (*telegram.utils.request.Request*, optional) – Pre initialized *telegram.utils.request.Request*.
- **private_key** (*bytes*, optional) – Private key for decryption of telegram passport data.
- **private_key_password** (*bytes*, optional) – Password for above private key.
- **defaults** (*telegram.ext.Defaults*, optional) – An object containing default values to be used if not set explicitly in the bot methods.

Note: Most bot methods have the argument `api_kwargs` which allows to pass arbitrary keywords to the Telegram API. This can be used to access new features of the API before they were incorporated into PTB. However, this is not guaranteed to work, i.e. it will fail for passing files.

```
addStickerToSet (user_id: Union[str, int], name: str, emojis: str, png_sticker:
                 Union[str, IO, InputFile, pathlib.Path] = None, mask_position: tele-
                 gram.files.sticker.MaskPosition = None, timeout: float = 20, tgs_sticker:
                 Union[str, IO, InputFile, pathlib.Path] = None, api_kwargs: Dict[str, Any]
                 = None) → bool
```

Alias for `add_sticker_to_set`

```
add_sticker_to_set (user_id: Union[str, int], name: str, emojis: str, png_sticker:
                   Union[str, IO, InputFile, pathlib.Path] = None, mask_position: tele-
                   gram.files.sticker.MaskPosition = None, timeout: float = 20, tgs_sticker:
                   Union[str, IO, InputFile, pathlib.Path] = None, api_kwargs: Dict[str,
                   Any] = None) → bool
```

Use this method to add a new sticker to a set created by the bot. You must use exactly one of the fields `png_sticker` or `tgs_sticker`. Animated stickers can be added to animated sticker sets and only to them. Animated sticker sets can have up to 50 stickers. Static sticker sets can have up to 120 stickers.

Warning: As of API 4.7 `png_sticker` is an optional argument and therefore the order of the arguments had to be changed. Use keyword arguments to make sure that the arguments are passed correctly.

Note: The `png_sticker` and `tgs_sticker` argument can be either a `file_id`, an URL or a file from disk `open(filename, 'rb')`

Parameters

- **user_id** (*int*) – User identifier of created sticker set owner.
- **name** (*str*) – Sticker set name.
- **png_sticker** (*str | filelike object | pathlib.Path*, optional) – PNG image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px. Pass a `file_id` as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **tgs_sticker** (*str | filelike object | pathlib.Path*, optional) – TGS animation with the sticker, uploaded using multipart/form-data. See https://core.telegram.org/animated_stickers#technical-requirements for technical requirements.
- **emojis** (*str*) – One or more emoji corresponding to the sticker.
- **mask_position** (*telegram.MaskPosition*, optional) – Position where the mask should be placed on faces.

- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

answerCallbackQuery (*callback_query_id*: *str*, *text*: *str* = *None*, *show_alert*: *bool* = *False*, *url*: *str* = *None*, *cache_time*: *int* = *None*, *timeout*: *float* = *None*, *api_kwargs*: *Dict*[*str*, *Any*] = *None*) → *bool*

Alias for `answer_callback_query`

answerInlineQuery (*inline_query_id*: *str*, *results*: *List*[*telegram.inline.inlinequeryresult.InlineQueryResult*], *cache_time*: *int* = 300, *is_personal*: *bool* = *None*, *next_offset*: *str* = *None*, *switch_pm_text*: *str* = *None*, *switch_pm_parameter*: *str* = *None*, *timeout*: *float* = *None*, *current_offset*: *str* = *None*, *api_kwargs*: *Dict*[*str*, *Any*] = *None*) → *bool*

Alias for `answer_inline_query`

answerPreCheckoutQuery (*pre_checkout_query_id*: *str*, *ok*: *bool*, *error_message*: *str* = *None*, *timeout*: *float* = *None*, *api_kwargs*: *Dict*[*str*, *Any*] = *None*) → *bool*

Alias for `answer_pre_checkout_query`

answerShippingQuery (*shipping_query_id*: *str*, *ok*: *bool*, *shipping_options*: *List*[*telegram.payment.shippingoption.ShippingOption*] = *None*, *error_message*: *str* = *None*, *timeout*: *float* = *None*, *api_kwargs*: *Dict*[*str*, *Any*] = *None*) → *bool*

Alias for `answer_shipping_query`

answer_callback_query (*callback_query_id*: *str*, *text*: *str* = *None*, *show_alert*: *bool* = *False*, *url*: *str* = *None*, *cache_time*: *int* = *None*, *timeout*: *float* = *None*, *api_kwargs*: *Dict*[*str*, *Any*] = *None*) → *bool*

Use this method to send answers to callback queries sent from inline keyboards. The answer will be displayed to the user as a notification at the top of the chat screen or as an alert. Alternatively, the user can be redirected to the specified Game URL. For this option to work, you must first create a game for your bot via BotFather and accept the terms. Otherwise, you may use links like `t.me/your_bot?start=XXXX` that open your bot with a parameter.

Parameters

- **callback_query_id** (*str*) – Unique identifier for the query to be answered.
- **text** (*str*, optional) – Text of the notification. If not specified, nothing will be shown to the user, 0-200 characters.
- **show_alert** (*bool*, optional) – If `True`, an alert will be shown by the client instead of a notification at the top of the chat screen. Defaults to `False`.
- **url** (*str*, optional) – URL that will be opened by the user's client. If you have created a Game and accepted the conditions via [@BotFather](#), specify the URL that opens your game - note that this will only work if the query comes from a callback game button. Otherwise, you may use links like `t.me/your_bot?start=XXXX` that open your bot with a parameter.
- **cache_time** (*int*, optional) – The maximum amount of time in seconds that the result of the callback query may be cached client-side. Defaults to 0.
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns bool On success, True is returned.

Raises telegram.TelegramError

answer_inline_query (*inline_query_id*: str, *results*: List[telegram.inline.inlinequeryresult.InlineQueryResult], *cache_time*: int = 300, *is_personal*: bool = None, *next_offset*: str = None, *switch_pm_text*: str = None, *switch_pm_parameter*: str = None, *timeout*: float = None, *current_offset*: str = None, *api_kwargs*: Dict[str, Any] = None) → bool

Use this method to send answers to an inline query. No more than 50 results per query are allowed.

Warning: In most use cases `current_offset` should not be passed manually. Instead of calling this method directly, use the shortcut `telegram.InlineQuery.answer()` with `auto_pagination=True`, which will take care of passing the correct value.

Parameters

- **inline_query_id** (str) – Unique identifier for the answered query.
- **results** (List[telegram.InlineQueryResult] | Callable) – A list of results for the inline query. In case `current_offset` is passed, `results` may also be a callable accepts the current page index starting from 0. It must return either a list of telegram.InlineResult instances or None if there are no more results.
- **cache_time** (int, optional) – The maximum amount of time in seconds that the result of the inline query may be cached on the server. Defaults to 300.
- **is_personal** (bool, optional) – Pass True, if results may be cached on the server side only for the user that sent the query. By default, results may be returned to any user who sends the same query.
- **next_offset** (str, optional) – Pass the offset that a client should send in the next query with the same text to receive more results. Pass an empty string if there are no more results or if you don't support pagination. Offset length can't exceed 64 bytes.
- **switch_pm_text** (str, optional) – If passed, clients will display a button with specified text that switches the user to a private chat with the bot and sends the bot a start message with the parameter `switch_pm_parameter`.
- **switch_pm_parameter** (str, optional) – Deep-linking parameter for the /start message sent to the bot when user presses the switch button. 1-64 characters, only A-Z, a-z, 0-9, _ and - are allowed.
- **current_offset** (str, optional) – The `telegram.InlineQuery.offset` of the inline query to answer. If passed, PTB will automatically take care of the pagination for you, i.e. pass the correct `next_offset` and truncate the results list/get the results from the callable you passed.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Example

An inline bot that sends YouTube videos can ask the user to connect the bot to their YouTube account to adapt search results accordingly. To do this, it displays a 'Connect your YouTube account' button above the results, or even before showing any. The user presses the button, switches to a private chat

with the bot and, in doing so, passes a start parameter that instructs the bot to return an oauth link. Once done, the bot can offer a switch_inline button so that the user can easily return to the chat where they wanted to use the bot's inline capabilities.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

answer_pre_checkout_query (*pre_checkout_query_id: str, ok: bool, error_message: str = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `bool`

Once the user has confirmed their payment and shipping details, the Bot API sends the final confirmation in the form of an Update with the field `pre_checkout_query`. Use this method to respond to such pre-checkout queries.

Note: The Bot API must receive an answer within 10 seconds after the pre-checkout query was sent.

Parameters

- **pre_checkout_query_id** (`str`) – Unique identifier for the query to be answered.
- **ok** (`bool`) – Specify `True` if everything is alright (goods are available, etc.) and the bot is ready to proceed with the order. Use `False` if there are any problems.
- **error_message** (`str`, optional) – Required if `ok` is `False`. Error message in human readable form that explains the reason for failure to proceed with the checkout (e.g. “Sorry, somebody just bought the last of our amazing black T-shirts while you were busy filling out your payment details. Please choose a different color or garment!”). Telegram will display this message to the user.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

answer_shipping_query (*shipping_query_id: str, ok: bool, shipping_options: List[telegram.payment.shippingoption.ShippingOption] = None, error_message: str = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `bool`

If you sent an invoice requesting a shipping address and the parameter `is_flexible` was specified, the Bot API will send an Update with a `shipping_query` field to the bot. Use this method to reply to shipping queries.

Parameters

- **shipping_query_id** (`str`) – Unique identifier for the query to be answered.
- **ok** (`bool`) – Specify `True` if delivery to the specified address is possible and `False` if there are any problems (for example, if delivery to the specified address is not possible).

- **shipping_options** (List[[telegram.ShippingOption](#)]) – Required if `ok` is `True`. A JSON-serialized array of available shipping options.
- **error_message** (str, optional) – Required if `ok` is `False`. Error message in human readable form that explains why it is impossible to complete the order (e.g. “Sorry, delivery to your desired address is unavailable”). Telegram will display this message to the user.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type bool

Raises [telegram.TelegramError](#)

can_join_groups

Bot’s `can_join_groups` attribute.

Type bool

can_read_all_group_messages

Bot’s `can_read_all_group_messages` attribute.

Type bool

close() → bool

Use this method to close the bot instance before moving it from one local server to another. You need to delete the webhook before calling this method to ensure that the bot isn’t launched again after server restart. The method will return error 429 in the first 10 minutes after the bot is launched.

Returns On success

Return type True

Raises [telegram.TelegramError](#)

commands

Bot’s commands.

Type List[[BotCommand](#)]

copyMessage (*chat_id*: Union[int, str], *from_chat_id*: Union[str, int], *message_id*: Union[str, int], *caption*: str = None, *parse_mode*: str = None, *caption_entities*: Union[Tuple[[telegram.messageentity.MessageEntity](#), ...], List[[telegram.messageentity.MessageEntity](#)]] = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *allow_sending_without_reply*: bool = False, *reply_markup*: [telegram.replymarkup.ReplyMarkup](#) = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → Optional[[telegram.messageid.MessageId](#)]

Alias for [copy_message](#)

copy_message (*chat_id*: Union[int, str], *from_chat_id*: Union[str, int], *message_id*: Union[str, int], *caption*: str = None, *parse_mode*: str = None, *caption_entities*: Union[Tuple[[telegram.messageentity.MessageEntity](#), ...], List[[telegram.messageentity.MessageEntity](#)]] = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *allow_sending_without_reply*: bool = False, *reply_markup*: [telegram.replymarkup.ReplyMarkup](#) = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → Optional[[telegram.messageid.MessageId](#)]

Use this method to copy messages of any kind. The method is analogous to the method `forwardMes-`

sages, but the copied message doesn't have a link to the original message. Returns the `MessageId` of the sent message on success.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **from_chat_id** (`int` | `str`) – Unique identifier for the chat where the original message was sent (or channel username in the format `@channelusername`).
- **message_id** (`int`) – Message identifier in the chat specified in `from_chat_id`.
- **caption** (`str`, optional) – New caption for media, 0-1024 characters after entities parsing. If not specified, the original caption is kept.
- **parse_mode** (`str`, optional) – Mode for parsing entities in the new caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`telegram.utils.types.SLT[MessageEntity]`) – List of special entities that appear in the new caption, which can be specified instead of `parse_mode`
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success

Return type `telegram.MessageId`

Raises `telegram.TelegramError`

createNewStickerSet (`user_id: Union[str, int]`, `name: str`, `title: str`, `emojis: str`, `png_sticker: Union[str, IO, InputFile, pathlib.Path] = None`, `contains_masks: bool = None`, `mask_position: telegram.files.sticker.MaskPosition = None`, `timeout: float = 20`, `tgs_sticker: Union[str, IO, InputFile, pathlib.Path] = None`, `api_kwargs: Dict[str, Any] = None`) → `bool`

Alias for `create_new_sticker_set`

create_new_sticker_set (`user_id: Union[str, int]`, `name: str`, `title: str`, `emojis: str`, `png_sticker: Union[str, IO, InputFile, pathlib.Path] = None`, `contains_masks: bool = None`, `mask_position: telegram.files.sticker.MaskPosition = None`, `timeout: float = 20`, `tgs_sticker: Union[str, IO, InputFile, pathlib.Path] = None`, `api_kwargs: Dict[str, Any] = None`) → `bool`

Use this method to create new sticker set owned by a user. The bot will be able to edit the created sticker set. You must use exactly one of the fields `png_sticker` or `tgs_sticker`.

Warning: As of API 4.7 `png_sticker` is an optional argument and therefore the order of the arguments had to be changed. Use keyword arguments to make sure that the arguments are passed correctly.

Note: The `png_sticker` and `tgs_sticker` argument can be either a `file_id`, an URL or a file from disk
`open(filename, 'rb')`

Parameters

- **user_id** (`int`) – User identifier of created sticker set owner.
- **name** (`str`) – Short name of sticker set, to be used in `t.me/addstickers/` URLs (e.g., animals). Can contain only english letters, digits and underscores. Must begin with a letter, can't contain consecutive underscores and must end in “_by_<bot username>”. <bot_username> is case insensitive. 1-64 characters.
- **title** (`str`) – Sticker set title, 1-64 characters.
- **png_sticker** (`str` | *filelike object* | `pathlib.Path`, optional) – Png image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px. Pass a `file_id` as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data.
- **tgs_sticker** (`str` | *filelike object* | `pathlib.Path`, optional) – TGS animation with the sticker, uploaded using multipart/form-data. See https://core.telegram.org/animated_stickers#technical-requirements for technical requirements.
- **emojis** (`str`) – One or more emoji corresponding to the sticker.
- **contains_masks** (`bool`, optional) – Pass `True`, if a set of mask stickers should be created.
- **mask_position** (`telegram.MaskPosition`, optional) – Position where the mask should be placed on faces.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

deleteChatPhoto (`chat_id: Union[str, int]`, `timeout: float = None`, `api_kwargs: Dict[str, Any] = None`) → `bool`
 Alias for `delete_chat_photo`

deleteChatStickerSet (`chat_id: Union[str, int]`, `timeout: float = None`, `api_kwargs: Dict[str, Any] = None`) → `bool`
 Alias for `delete_chat_sticker_set`

deleteMessage (`chat_id: Union[str, int]`, `message_id: Union[str, int]`, `timeout: float = None`, `api_kwargs: Dict[str, Any] = None`) → `bool`
 Alias for `delete_message`

deleteStickerFromSet (`sticker: str`, `timeout: float = None`, `api_kwargs: Dict[str, Any] = None`) → `bool`
 Alias for `delete_sticker_from_set`

deleteWebhook (*timeout: float = None, api_kwargs: Dict[str, Any] = None, drop_pending_updates: bool = None*) → bool
Alias for `delete_webhook`

delete_chat_photo (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool

Use this method to delete a chat photo. Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

delete_chat_sticker_set (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool

Use this method to delete a group sticker set from a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `telegram.Chat.can_set_sticker_set` optionally returned in `get_chat` requests to check if the bot can use this method.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

delete_message (*chat_id: Union[str, int], message_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool

Use this method to delete a message, including service messages, with the following limitations:

- A message can only be deleted if it was sent less than 48 hours ago.
- A dice message in a private chat can only be deleted if it was sent more than 24 hours ago.
- Bots can delete outgoing messages in private chats, groups, and supergroups.
- Bots can delete incoming messages in private chats.
- Bots granted can_post_messages permissions can delete outgoing messages in channels.
- If the bot is an administrator of a group, it can delete any message there.
- If the bot has can_delete_messages permission in a supergroup or a channel, it can delete any message there.

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **message_id** (*int*) – Identifier of the message to delete.
- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

delete_sticker_from_set (*sticker: str, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `bool`

Use this method to delete a sticker from a set created by the bot.

Parameters

- **sticker** (*str*) – File identifier of the sticker.
- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

delete_webhook (*timeout: float = None, api_kwargs: Dict[str, Any] = None, drop_pending_updates: bool = None*) → `bool`

Use this method to remove webhook integration if you decide to switch back to `getUpdates`. Requires no parameters.

Parameters

- **drop_pending_updates** (*bool*, optional) – Pass `True`: to drop all pending updates.
- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `bool` On success, `True` is returned.

Raises `telegram.TelegramError`

editMessageCaption (*chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, caption: str = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, parse_mode: str = None, api_kwargs: Dict[str, Any] = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None*) → `Union[telegram.message.Message, bool]`

Alias for `edit_message_caption`

```
editMessageLiveLocation(chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, latitude: float = None, longitude: float = None, location: telegram.files.location.Location = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, horizontal_accuracy: float = None, heading: int = None, proximity_alert_radius: int = None) → Union[telegram.message.Message, None, bool]
```

Alias for `edit_message_live_location`

```
editMessageMedia(chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, media: telegram.files.inputmedia.InputMedia = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None) → Union[telegram.message.Message, bool]
```

Alias for `edit_message_media`

```
editMessageReplyMarkup(chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, reply_markup: Optional[telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup] = None, timeout: float = None, api_kwargs: Dict[str, Any] = None) → Union[telegram.message.Message, bool]
```

Alias for `edit_message_reply_markup`

```
editMessageText(text: str, chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, parse_mode: str = None, disable_web_page_preview: bool = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Union[telegram.message.Message, None, bool]
```

Alias for `edit_message_text`

```
edit_message_caption(chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, caption: str = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, parse_mode: str = None, api_kwargs: Dict[str, Any] = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Union[telegram.message.Message, bool]
```

Use this method to edit captions of messages.

Parameters

- **chat_id** (int | str, optional) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format `@channelusername`)
- **message_id** (int, optional) – Required if `inline_message_id` is not specified. Identifier of the message to edit.
- **inline_message_id** (str, optional) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message.
- **caption** (str, optional) – New caption of the message, 0-1024 characters after entities parsing.

- **parse_mode** (*str*, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (*List[telegram.MessageEntity]*, optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – A JSON-serialized object for an inline keyboard.
- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, if edited message is not an inline message, the edited message is returned, otherwise `True` is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

```
edit_message_live_location(chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, latitude: float = None, longitude: float = None, location: telegram.files.location.Location = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, horizontal_accuracy: float = None, heading: int = None, proximity_alert_radius: int = None) → Union[telegram.message.Message, None, bool]
```

Use this method to edit live location messages sent by the bot or via the bot (for inline bots). A location can be edited until its `live_period` expires or editing is explicitly disabled by a call to `stop_message_live_location`.

Note: You can either supply a `latitude` and `longitude` or a `location`.

Parameters

- **chat_id** (*int | str*, optional) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **message_id** (*int*, optional) – Required if `inline_message_id` is not specified. Identifier of the message to edit.
- **inline_message_id** (*str*, optional) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message.
- **latitude** (*float*, optional) – Latitude of location.
- **longitude** (*float*, optional) – Longitude of location.
- **location** (*telegram.Location*, optional) – The location to send.
- **horizontal_accuracy** (*float*, optional) – The radius of uncertainty for the location, measured in meters; 0-1500.
- **heading** (*int*, optional) – Direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.

- **proximity_alert_radius** (*int*, optional) – Maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – A JSON-serialized object for a new inline keyboard.
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, if edited message is not an inline message, the edited message is returned, otherwise `True` is returned.

Return type *telegram.Message*

```
edit_message_media (chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, media: telegram.files.inputmedia.InputMedia = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None) → Union[telegram.message.Message, bool]
```

Use this method to edit animation, audio, document, photo, or video messages. If a message is part of a message album, then it can be edited only to an audio for audio albums, only to a document for document albums and to a photo or a video otherwise. When an inline message is edited, a new file can't be uploaded. Use a previously uploaded file via its `file_id` or specify a URL.

Parameters

- **chat_id** (*int* | *str*, optional) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **message_id** (*int*, optional) – Required if `inline_message_id` is not specified. Identifier of the message to edit.
- **inline_message_id** (*str*, optional) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message.
- **media** (*telegram.InputMedia*) – An object for a new media content of the message.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – A JSON-serialized object for an inline keyboard.
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise `True` is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

```
edit_message_reply_markup(chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, reply_markup: Optional[telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup] = None, timeout: float = None, api_kwargs: Dict[str, Any] = None) → Union[telegram.message.Message, bool]
```

Use this method to edit only the reply markup of messages sent by the bot or via the bot (for inline bots).

Parameters

- **chat_id** (int | str, optional) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **message_id** (int, optional) – Required if inline_message_id is not specified. Identifier of the message to edit.
- **inline_message_id** (str, optional) – Required if chat_id and message_id are not specified. Identifier of the inline message.
- **reply_markup** ([telegram.InlineKeyboardMarkup](#), optional) – A JSON-serialized object for an inline keyboard.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, if edited message is not an inline message, the edited message is returned, otherwise True is returned.

Return type [telegram.Message](#)

Raises [telegram.TelegramError](#)

```
edit_message_text(text: str, chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, parse_mode: str = None, disable_web_page_preview: bool = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Union[telegram.message.Message, None, bool]
```

Use this method to edit text and game messages.

Parameters

- **chat_id** (int | str, optional) – Required if inline_message_id is not specified. Unique identifier for the target chat or username of the target channel (in the format @channelusername)
- **message_id** (int, optional) – Required if inline_message_id is not specified. Identifier of the message to edit.
- **inline_message_id** (str, optional) – Required if chat_id and message_id are not specified. Identifier of the inline message.
- **text** (str) – New text of the message, 1-4096 characters after entities parsing.
- **parse_mode** (str, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in your bot's message. See the constants in [telegram.ParseMode](#) for the available modes.

- **entities** (List[[telegram.MessageEntity](#)], optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **disable_web_page_preview** (bool, optional) – Disables link previews for links in this message.
- **reply_markup** ([telegram.InlineKeyboardMarkup](#), optional) – A JSON-serialized object for an inline keyboard.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, if edited message is not an inline message, the edited message is returned, otherwise True is returned.

Return type [telegram.Message](#)

Raises [telegram.TelegramError](#)

exportChatInviteLink (*chat_id*: Union[str, int], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → str

Alias for [export_chat_invite_link](#)

export_chat_invite_link (*chat_id*: Union[str, int], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → str

Use this method to generate a new invite link for a chat; any previously generated link is revoked. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns New invite link on success.

Return type str

Raises [telegram.TelegramError](#)

first_name

Bot's first name.

Type str

forwardMessage (*chat_id*: Union[int, str], *from_chat_id*: Union[str, int], *message_id*: Union[str, int], *disable_notification*: bool = False, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → Optional[[telegram.message.Message](#)]

Alias for [forward_message](#)

forward_message (*chat_id*: Union[int, str], *from_chat_id*: Union[str, int], *message_id*: Union[str, int], *disable_notification*: bool = False, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → Optional[[telegram.message.Message](#)]

Use this method to forward messages of any kind.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).

- **from_chat_id** (int | str) – Unique identifier for the chat where the original message was sent (or channel username in the format @channelusername).
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **message_id** (int) – Message identifier in the chat specified in from_chat_id.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

getChat (*chat_id*: Union[str, int], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → telegram.chat.Chat
Alias for `get_chat`

getChatAdministrators (*chat_id*: Union[str, int], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → List[telegram.chatmember.ChatMember]
Alias for `get_chat_administrators`

getChatMember (*chat_id*: Union[str, int], *user_id*: Union[str, int], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → telegram.chatmember.ChatMember
Alias for `get_chat_member`

getChatMembersCount (*chat_id*: Union[str, int], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → int
Alias for `get_chat_members_count`

getFile (*file_id*: Union[str, telegram.files.animation.Animation, telegram.files.audio.Audio, telegram.files.chatphoto.ChatPhoto, telegram.files.document.Document, telegram.files.photosize.PhotoSize, telegram.files.sticker.Sticker, telegram.files.video.Video, telegram.files.videonote.VideoNote, telegram.files.voice.Voice], *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → telegram.files.file.File
Alias for `get_file`

getGameHighScores (*user_id*: Union[int, str], *chat_id*: Union[str, int] = None, *message_id*: Union[str, int] = None, *inline_message_id*: Union[str, int] = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → List[telegram.games.gamehighscore.GameHighScore]
Alias for `get_game_high_scores`

getMe (*timeout*: int = None, *api_kwargs*: Dict[str, Any] = None) → Optional[telegram.user.User]
Alias for `get_me`

getMyCommands (*timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → List[telegram.botcommand.BotCommand]
Alias for `get_my_commands`

getStickerSet (*name*: str, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → telegram.files.sticker.StickerSet
Alias for `get_sticker_set`

getUpdates (*offset*: int = None, *limit*: int = 100, *timeout*: float = 0, *read_latency*: float = 2.0, *allowed_updates*: List[str] = None, *api_kwargs*: Dict[str, Any] = None) → List[telegram.update.Update]
Alias for `get_updates`

getUserProfilePhotos (*user_id: Union[str, int], offset: int = None, limit: int = 100, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → Optional[telegram.userprofilephotos.UserProfilePhotos]

Alias for `get_user_profile_photos`

getWebhookInfo (*timeout: float = None, api_kwargs: Dict[str, Any] = None*) → telegram.webhookinfo.WebhookInfo

Alias for `get_webhook_info`

get_chat (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → telegram.chat.Chat

Use this method to get up to date information about the chat (current name of the user for one-on-one conversations, current username of a user, group or channel, etc.).

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (*int | float, optional*) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict, optional*) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.Chat`

Raises `telegram.TelegramError`

get_chat_administrators (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → List[telegram.chatmember.ChatMember]

Use this method to get a list of administrators in a chat.

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (*int | float, optional*) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict, optional*) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, returns a list of `ChatMember` objects that contains information about all chat administrators except other bots. If the chat is a group or a supergroup and no administrators were appointed, only the creator will be returned.

Return type List[`telegram.ChatMember`]

Raises `telegram.TelegramError`

get_chat_member (*chat_id: Union[str, int], user_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → telegram.chatmember.ChatMember

Use this method to get information about a member of a chat.

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **user_id** (*int*) – Unique identifier of the target user.
- **timeout** (*int | float, optional*) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.ChatMember`

Raises `telegram.TelegramError`

get_chat_members_count (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → int

Use this method to get the number of members in a chat.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns Number of members in the chat.

Return type int

Raises `telegram.TelegramError`

get_file (*file_id: Union[str, telegram.files.animation.Animation, telegram.files.audio.Audio, telegram.files.chatphoto.ChatPhoto, telegram.files.document.Document, telegram.files.photosize.PhotoSize, telegram.files.sticker.Sticker, telegram.files.video.Video, telegram.files.videonote.VideoNote, telegram.files.voice.Voice], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `telegram.files.file.File`

Use this method to get basic info about a file and prepare it for downloading. For the moment, bots can download files of up to 20MB in size. The file can then be downloaded with `telegram.File.download`. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling `get_file` again.

Note: This function may not preserve the original file name and MIME type. You should save the file's MIME type and name (if available) when the File object is received.

Parameters

- **file_id** (str | `telegram.Animation` | `telegram.Audio` | `telegram.ChatPhoto` | `telegram.Document` | `telegram.PhotoSize` | `telegram.Sticker` | `telegram.Video` | `telegram.VideoNote` | `telegram.Voice`) – Either the file identifier or an object that has a `file_id` attribute to get file information about.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

get_game_high_scores (*user_id: Union[int, str], chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → List[`telegram.games.gamehighscore.GameHighScore`]

Use this method to get data for high score tables. Will return the score of the specified user and several of his neighbors in a game.

Parameters

- **user_id** (int) – Target user id.
- **chat_id** (int | str, optional) – Required if inline_message_id is not specified. Unique identifier for the target chat.
- **message_id** (int, optional) – Required if inline_message_id is not specified. Identifier of the sent message.
- **inline_message_id** (str, optional) – Required if chat_id and message_id are not specified. Identifier of the inline message.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns List[*telegram.GameHighScore*]

Raises telegram.TelegramError

get_me (timeout: int = None, api_kwargs: Dict[str, Any] = None) → Optional[telegram.user.User]
A simple method for testing your bot's auth token. Requires no parameters.

Parameters

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns A *telegram.User* instance representing that bot if the credentials are valid, None otherwise.

Return type *telegram.User*

Raises telegram.TelegramError

get_my_commands (timeout: float = None, api_kwargs: Dict[str, Any] = None) → List[telegram.botcommand.BotCommand]
Use this method to get the current list of the bot's commands.

Parameters

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the commands set for the bot

Return type List[telegram.BotCommand]

Raises telegram.TelegramError

get_sticker_set (name: str, timeout: float = None, api_kwargs: Dict[str, Any] = None) → telegram.files.sticker.StickerSet
Use this method to get a sticker set.

Parameters

- **name** (`str`) – Name of the sticker set.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.StickerSet`

Raises `telegram.TelegramError`

get_updates (`offset: int = None, limit: int = 100, timeout: float = 0, read_latency: float = 2.0, allowed_updates: List[str] = None, api_kwargs: Dict[str, Any] = None`) → `List[telegram.update.Update]`

Use this method to receive incoming updates using long polling.

Parameters

- **offset** (`int`, optional) – Identifier of the first update to be returned. Must be greater by one than the highest among the identifiers of previously received updates. By default, updates starting with the earliest unconfirmed update are returned. An update is considered confirmed as soon as `getUpdates` is called with an offset higher than its `update_id`. The negative offset can be specified to retrieve updates starting from -offset update from the end of the updates queue. All previous updates will forgotten.
- **limit** (`int`, optional) – Limits the number of updates to be retrieved. Values between 1-100 are accepted. Defaults to 100.
- **timeout** (`int`, optional) – Timeout in seconds for long polling. Defaults to 0, i.e. usual short polling. Should be positive, short polling should be used for testing purposes only.
- **allowed_updates** (`List[str]`), optional) – A JSON-serialized list the types of updates you want your bot to receive. For example, specify `[“message”, “edited_channel_post”, “callback_query”]` to only receive updates of these types. See `telegram.Update` for a complete list of available update types. Specify an empty list to receive all updates regardless of type (default). If not specified, the previous setting will be used. Please note that this parameter doesn’t affect updates created before the call to the `get_updates`, so unwanted updates may be received for a short period of time.
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Note:

1. This method will not work if an outgoing webhook is set up.
 2. In order to avoid getting duplicate updates, recalculate offset after each server response.
 3. To take full advantage of this library take a look at `telegram.ext.Updater`
-

Returns `List[telegram.Update]`

Raises `telegram.TelegramError`

get_user_profile_photos (`user_id: Union[str, int], offset: int = None, limit: int = 100, timeout: float = None, api_kwargs: Dict[str, Any] = None`) → `Optional[telegram.userprofilephotos.UserProfilePhotos]`

Use this method to get a list of profile pictures for a user.

Parameters

- **user_id** (int) – Unique identifier of the target user.
- **offset** (int, optional) – Sequential number of the first photo to be returned. By default, all photos are returned.
- **limit** (int, optional) – Limits the number of photos to be retrieved. Values between 1-100 are accepted. Defaults to 100.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.UserProfilePhotos`

Raises `telegram.TelegramError`

get_webhook_info (timeout: float = None, api_kwargs: Dict[str, Any] = None) → telegram.webhookinfo.WebhookInfo

Use this method to get current webhook status. Requires no parameters.

If the bot is using getUpdates, will return an object with the url field empty.

Parameters

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.WebhookInfo`

id

Unique identifier for this bot.

Type int

kickChatMember (chat_id: Union[str, int], user_id: Union[str, int], timeout: float = None, until_date: Union[int, datetime.datetime] = None, api_kwargs: Dict[str, Any] = None) → bool

Alias for `kick_chat_member`

kick_chat_member (chat_id: Union[str, int], user_id: Union[str, int], timeout: float = None, until_date: Union[int, datetime.datetime] = None, api_kwargs: Dict[str, Any] = None) → bool

Use this method to kick a user from a group or a supergroup or a channel. In the case of supergroups and channels, the user will not be able to return to the group on their own using invite links, etc., unless unbanned first. The bot must be an administrator in the group for this to work.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **user_id** (int) – Unique identifier of the target user.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **until_date** (int | datetime.datetime, optional) – Date when the user will be unbanned, unix time. If user is banned for more than 366 days or less than 30 seconds from the current time they are considered to be banned forever. For timezone naive datetime.datetime objects, the default timezone of the bot will be used.

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns bool On success, True is returned.

Raises telegram.TelegramError

last_name

Optional. Bot's last name.

Type str

leaveChat (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*)

→ bool
Alias for `leave_chat`

leave_chat (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*)

→ bool
Use this method for your bot to leave a group, supergroup or channel.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns bool On success, True is returned.

Raises telegram.TelegramError

link

Convenience property. Returns the t.me link of the bot.

Type str

logOut () → bool

Alias for `log_out`

log_out () → bool

Use this method to log out from the cloud Bot API server before launching the bot locally. You *must* log out the bot before running it locally, otherwise there is no guarantee that the bot will receive updates. After a successful call, you can immediately log in on a local server, but will not be able to log in back to the cloud Bot API server for 10 minutes.

Returns On success

Return type True

Raises telegram.TelegramError

name

Bot's @username.

Type str

pinChatMessage (*chat_id: Union[str, int], message_id: Union[str, int], disable_notification: bool = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool

Alias for `pin_chat_message`

pin_chat_message (*chat_id: Union[str, int], message_id: Union[str, int], disable_notification: bool = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool

Use this method to add a message to the list of pinned messages in a chat. If the chat is not a private chat, the bot must be an administrator in the chat for this to work and must have the

`can_pin_messages` admin right in a supergroup or `can_edit_messages` admin right in a channel.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **message_id** (`int`) – Identifier of a message to pin.
- **disable_notification** (`bool`, optional) – Pass `True`, if it is not necessary to send a notification to all chat members about the new pinned message. Notifications are always disabled in channels and private chats.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

promoteChatMember (*chat_id: Union[str, int], user_id: Union[str, int], can_change_info: bool = None, can_post_messages: bool = None, can_edit_messages: bool = None, can_delete_messages: bool = None, can_invite_users: bool = None, can_restrict_members: bool = None, can_pin_messages: bool = None, can_promote_members: bool = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, is_anonymous: bool = None*) → `bool`

Alias for `promote_chat_member`

promote_chat_member (*chat_id: Union[str, int], user_id: Union[str, int], can_change_info: bool = None, can_post_messages: bool = None, can_edit_messages: bool = None, can_delete_messages: bool = None, can_invite_users: bool = None, can_restrict_members: bool = None, can_pin_messages: bool = None, can_promote_members: bool = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, is_anonymous: bool = None*) → `bool`

Use this method to promote or demote a user in a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Pass `False` for all boolean parameters to demote a user.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`).
- **user_id** (`int`) – Unique identifier of the target user.
- **is_anonymous** (`bool`, optional) – Pass `True`, if the administrator's presence in the chat is hidden.
- **can_change_info** (`bool`, optional) – Pass `True`, if the administrator can change chat title, photo and other settings.
- **can_post_messages** (`bool`, optional) – Pass `True`, if the administrator can create channel posts, channels only.
- **can_edit_messages** (`bool`, optional) – Pass `True`, if the administrator can edit messages of other users, channels only.
- **can_delete_messages** (`bool`, optional) – Pass `True`, if the administrator can delete messages of other users.

- **can_invite_users** (bool, optional) – Pass `True`, if the administrator can invite new users to the chat.
- **can_restrict_members** (bool, optional) – Pass `True`, if the administrator can restrict, ban or unban chat members.
- **can_pin_messages** (bool, optional) – Pass `True`, if the administrator can pin messages, supergroups only.
- **can_promote_members** (bool, optional) – Pass `True`, if the administrator can add new administrators with a subset of his own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by him).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type bool

Raises telegram.TelegramError

restrictChatMember (*chat_id*: Union[str, int], *user_id*: Union[str, int], *permissions*: telegram.chatpermissions.ChatPermissions, *until_date*: Union[int, datetime.datetime] = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → bool

Alias for `restrict_chat_member`

restrict_chat_member (*chat_id*: Union[str, int], *user_id*: Union[str, int], *permissions*: telegram.chatpermissions.ChatPermissions, *until_date*: Union[int, datetime.datetime] = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → bool

Use this method to restrict a user in a supergroup. The bot must be an administrator in the supergroup for this to work and must have the appropriate admin rights. Pass `True` for all boolean parameters to lift restrictions from a user.

Note: Since Bot API 4.4, `restrict_chat_member` takes the new user permissions in a single argument of type `telegram.ChatPermissions`. The old way of passing parameters will not keep working forever.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`).
- **user_id** (int) – Unique identifier of the target user.
- **until_date** (int | datetime.datetime, optional) – Date when restrictions will be lifted for the user, unix time. If user is restricted for more than 366 days or less than 30 seconds from the current time, they are considered to be restricted forever. For timezone naive `datetime.datetime` objects, the default timezone of the bot will be used.
- **permissions** (`telegram.ChatPermissions`) – A JSON-serialized object for new user permissions.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

sendAnimation (*chat_id*: Union[int, str], *animation*: Union[str, IO, InputFile, pathlib.Path, telegram.files.animation.Animation], *duration*: int = None, *width*: int = None, *height*: int = None, *thumb*: Union[str, IO, InputFile, pathlib.Path] = None, *caption*: str = None, *parse_mode*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for `send_animation`

sendAudio (*chat_id*: Union[int, str], *audio*: Union[str, IO, InputFile, pathlib.Path, telegram.files.audio.Audio], *duration*: int = None, *performer*: str = None, *title*: str = None, *caption*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *parse_mode*: str = None, *thumb*: Union[str, IO, InputFile, pathlib.Path] = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for `send_audio`

sendChatAction (*chat_id*: Union[str, int], *action*: str, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None) → bool

Alias for `send_chat_action`

sendContact (*chat_id*: Union[int, str], *phone_number*: str = None, *first_name*: str = None, *last_name*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *contact*: telegram.files.contact.Contact = None, *vcard*: str = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Alias for `send_contact`

sendDice (*chat_id*: Union[int, str], *disable_notification*: bool = None, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *emoji*: str = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → telegram.message.Message

Alias for `send_dice`

sendDocument (*chat_id*: Union[int, str], *document*: Union[str, IO, InputFile, pathlib.Path, telegram.files.document.Document], *filename*: str = None, *caption*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *parse_mode*: str = None, *thumb*: Union[str, IO, InputFile, pathlib.Path] = None, *api_kwargs*: Dict[str, Any] = None, *disable_content_type_detection*: bool = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for `send_document`

sendGame (*chat_id*: Union[int, str], *game_short_name*: str, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Alias for [send_game](#)

sendInvoice (*chat_id*: Union[int, str], *title*: str, *description*: str, *payload*: str, *provider_token*: str, *start_parameter*: str, *currency*: str, *prices*: List[telegram.payment.labeledprice.LabeledPrice], *photo_url*: str = None, *photo_size*: int = None, *photo_width*: int = None, *photo_height*: int = None, *need_name*: bool = None, *need_phone_number*: bool = None, *need_email*: bool = None, *need_shipping_address*: bool = None, *is_flexible*: bool = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, *provider_data*: Union[str, object] = None, *send_phone_number_to_provider*: bool = None, *send_email_to_provider*: bool = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → telegram.message.Message

Alias for [send_invoice](#)

sendLocation (*chat_id*: Union[int, str], *latitude*: float = None, *longitude*: float = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *location*: telegram.files.location.Location = None, *live_period*: int = None, *api_kwargs*: Dict[str, Any] = None, *horizontal_accuracy*: float = None, *heading*: int = None, *proximity_alert_radius*: int = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Alias for [send_location](#)

sendMediaGroup (*chat_id*: Union[int, str], *media*: List[Union[telegram.files.inputmedia.InputMediaAudio, telegram.files.inputmedia.InputMediaDocument, telegram.files.inputmedia.InputMediaPhoto, telegram.files.inputmedia.InputMediaVideo]], *disable_notification*: bool = None, *reply_to_message_id*: Union[int, str] = None, *timeout*: float = 20, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → List[Optional[telegram.message.Message]]

Alias for [send_media_group](#)

sendMessage (*chat_id*: Union[int, str], *text*: str, *parse_mode*: str = None, *disable_web_page_preview*: bool = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for [send_message](#)

sendPhoto (*chat_id*: int, *photo*: Union[str, telegram.files.photosize.PhotoSize, IO], *caption*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *parse_mode*: str = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for [send_photo](#)

sendPoll (*chat_id*: Union[int, str], *question*: str, *options*: List[str], *is_anonymous*: bool = True, *type*: str = 'regular', *allows_multiple_answers*: bool = False, *correct_option_id*: int = None, *is_closed*: bool = None, *disable_notification*: bool = None, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *explanation*: str = None, *explanation_parse_mode*: Union[str, telegram.utils.helpers.DefaultValue, None] = <telegram.utils.helpers.DefaultValue object>, *open_period*: int = None, *close_date*: Union[int, datetime.datetime] = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *explanation_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → telegram.message.Message

Alias for [send_poll](#)

sendSticker (*chat_id*: Union[int, str], *sticker*: Union[str, IO, InputFile, pathlib.Path, telegram.files.sticker.Sticker], *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Alias for [send_sticker](#)

sendVenue (*chat_id*: Union[int, str], *latitude*: float = None, *longitude*: float = None, *title*: str = None, *address*: str = None, *foursquare_id*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *venue*: telegram.files.venue.Venue = None, *foursquare_type*: str = None, *api_kwargs*: Dict[str, Any] = None, *google_place_id*: str = None, *google_place_type*: str = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Alias for [send_venue](#)

sendVideo (*chat_id*: Union[int, str], *video*: Union[str, IO, InputFile, pathlib.Path, telegram.files.video.Video], *duration*: int = None, *caption*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *width*: int = None, *height*: int = None, *parse_mode*: str = None, *supports_streaming*: bool = None, *thumb*: Union[str, IO, InputFile, pathlib.Path] = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for [send_video](#)

sendVideoNote (*chat_id*: Union[int, str], *video_note*: Union[str, IO, InputFile, pathlib.Path, telegram.files.videonote.VideoNote], *duration*: int = None, *length*: int = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *thumb*: Union[str, IO, InputFile, pathlib.Path] = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Alias for [send_video_note](#)

sendVoice (*chat_id*: Union[int, str], *voice*: Union[str, IO, InputFile, pathlib.Path, telegram.files.voice.Voice], *duration*: int = None, *caption*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *parse_mode*: str = None, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Alias for [send_voice](#)

send_animation (*chat_id*: Union[int, str], *animation*: Union[str, IO, InputFile, pathlib.Path, telegram.files.animation.Animation], *duration*: int = None, *width*: int = None, *height*: int = None, *thumb*: Union[str, IO, InputFile, pathlib.Path] = None, *caption*: str = None, *parse_mode*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None, *caption_entities*: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]

Use this method to send animation files (GIF or H.264/MPEG-4 AVC video without sound). Bots can currently send animation files of up to 50 MB in size, this limit may be changed in the future.

Note: `thumb` will be ignored for small files, for which Telegram can easily generate thumb nails. However, this behaviour is undocumented and might be changed by Telegram.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **animation** (str | filelike object | pathlib.Path | `telegram.Animation`) – Animation to send. Pass a file_id as String to send an animation that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an animation from the Internet, or upload a new animation using multipart/form-data. Lastly you can pass an existing `telegram.Animation` object to send.
- **duration** (int, optional) – Duration of sent animation in seconds.
- **width** (int, optional) – Animation width.
- **height** (int, optional) – Animation height.
- **thumb** (filelike object | pathlib.Path, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **caption** (str, optional) – Animation caption (may also be used when resending animations by file_id), 0-1024 characters after entities parsing.
- **parse_mode** (str, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (List[`telegram.MessageEntity`], optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int | float, optional) – Send file timeout (default: 20 seconds).

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

send_audio (*chat_id: Union[int, str], audio: Union[str, IO, InputFile, pathlib.Path, telegram.files.audio.Audio], duration: int = None, performer: str = None, title: str = None, caption: str = None, disable_notification: bool = False, reply_to_message_id: Union[int, str] = None, reply_markup: telegram.replymarkup.ReplyMarkup = None, timeout: float = 20, parse_mode: str = None, thumb: Union[str, IO, InputFile, pathlib.Path] = None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None*) → Optional[telegram.message.Message]

Use this method to send audio files, if you want Telegram clients to display them in the music player. Your audio must be in the .mp3 or .m4a format.

Bots can currently send audio files of up to 50 MB in size, this limit may be changed in the future.

For sending voice messages, use the `sendVoice` method instead.

Note: The audio argument can be either a `file_id`, an URL or a file from disk `open(filename, 'rb')`

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **audio** (str | filelike object | pathlib.Path | `telegram.Audio`) – Audio file to send. Pass a `file_id` as String to send an audio file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an audio file from the Internet, or upload a new one using multipart/form-data. Lastly you can pass an existing `telegram.Audio` object to send.
- **caption** (str, optional) – Audio caption, 0-1024 characters after entities parsing.
- **parse_mode** (str, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (List[`telegram.MessageEntity`], optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **duration** (int, optional) – Duration of sent audio in seconds.
- **performer** (str, optional) – Performer.
- **title** (str, optional) – Track name.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.

- **reply_markup** (*telegram.ReplyMarkup*, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **thumb** (*filelike object* | *pathlib.Path*, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **timeout** (*int* | *float*, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

send_chat_action (*chat_id: Union[str, int]*, *action: str*, *timeout: float = None*, *api_kwargs: Dict[str, Any] = None*) → bool

Use this method when you need to tell the user that something is happening on the bot's side. The status is set for 5 seconds or less (when a message arrives from your bot, Telegram clients clear its typing status). Telegram only recommends using this method when a response from the bot will take a noticeable amount of time to arrive.

Parameters

- **chat_id** (*int* | *str*) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **action** (*telegram.ChatAction* | *str*) – Type of action to broadcast. Choose one, depending on what the user is about to receive. For convenience look at the constants in *telegram.ChatAction*
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises *telegram.TelegramError*

send_contact (*chat_id: Union[int, str]*, *phone_number: str = None*, *first_name: str = None*, *last_name: str = None*, *disable_notification: bool = False*, *reply_to_message_id: Union[int, str] = None*, *reply_markup: telegram.replymarkup.ReplyMarkup = None*, *timeout: float = None*, *contact: telegram.files.contact.Contact = None*, *vcard: str = None*, *api_kwargs: Dict[str, Any] = None*, *allow_sending_without_reply: bool = None*) → Optional[*telegram.message.Message*]

Use this method to send phone contacts.

Note: You can either supply *contact* or *phone_number* and *first_name* with optionally *last_name* and optionally *vcard*.

Parameters

- **chat_id** (`int | str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **phone_number** (`str`, optional) – Contact’s phone number.
- **first_name** (`str`, optional) – Contact’s first name.
- **last_name** (`str`, optional) – Contact’s last name.
- **vcard** (`str`, optional) – Additional data about the contact in the form of a vCard, 0-2048 bytes.
- **contact** (`telegram.Contact`, optional) – The contact to send.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent `Message` is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

send_dice (`chat_id: Union[int, str]`, `disable_notification: bool = None`, `reply_to_message_id: Union[int, str] = None`, `reply_markup: telegram.replymarkup.ReplyMarkup = None`, `timeout: float = None`, `emoji: str = None`, `api_kwargs: Dict[str, Any] = None`, `allow_sending_without_reply: bool = None`) → `telegram.message.Message`

Use this method to send an animated emoji, which will have a random value. On success, the sent `Message` is returned.

Parameters

- **chat_id** (`int | str`) – Unique identifier for the target private chat.
- **emoji** (`str`, optional) – Emoji on which the dice throw animation is based. Currently, must be one of “🎲”, “🎯”, “🎰”, “🎱”, or “🎳”. Dice can have values 1-6 for “🎲” and “🎱”, values 1-5 for “🎰” and “🎳”, and values 1-64 for “🎯”. Defaults to “🎲”.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.

- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

send_document (`chat_id: Union[int, str]`, `document: Union[str, IO, InputFile, pathlib.Path, telegram.files.document.Document]`, `filename: str = None`, `caption: str = None`, `disable_notification: bool = False`, `reply_to_message_id: Union[int, str] = None`, `reply_markup: telegram.replymarkup.ReplyMarkup = None`, `timeout: float = 20`, `parse_mode: str = None`, `thumb: Union[str, IO, InputFile, pathlib.Path] = None`, `api_kwargs: Dict[str, Any] = None`, `disable_content_type_detection: bool = None`, `allow_sending_without_reply: bool = None`, `caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None`) → Optional[`telegram.message.Message`]

Use this method to send general files.

Bots can currently send files of any type of up to 50 MB in size, this limit may be changed in the future.

Note: The document argument can be either a file_id, an URL or a file from disk open (filename, 'rb')

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **document** (`str` | *filelike object* | `pathlib.Path` | `telegram.Document`) – File to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data. Lastly you can pass an existing `telegram.Document` object to send.
- **filename** (`str`, optional) – File name that shows in telegram message (it is useful when you send file generated by temp module, for example). Undocumented.
- **caption** (`str`, optional) – Document caption (may also be used when resending documents by file_id), 0-1024 characters after entities parsing.
- **disable_content_type_detection** (`bool`, optional) – Disables automatic server-side content type detection for files uploaded using multipart/form-data.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in message text, which can be specified instead of parse_mode.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.

- **allow_sending_without_reply** (*bool*, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (*telegram.ReplyMarkup*, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **thumb** (*filelike object | pathlib.Path*, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **timeout** (*int | float*, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent `Message` is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

send_game (*chat_id: Union[int, str], game_short_name: str, disable_notification: bool = False, reply_to_message_id: Union[int, str] = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None*) → *Optional[telegram.message.Message]*

Use this method to send a game.

Parameters

- **chat_id** (*int | str*) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **game_short_name** (*str*) – Short name of the game, serves as the unique identifier for the game. Set up your games via [@BotFather](#).
- **disable_notification** (*bool*, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (*int*, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (*bool*, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – A JSON-serialized object for a new inline keyboard. If empty, one 'Play game_title' button will be shown. If not empty, the first button must launch the game.
- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent `Message` is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

```
send_invoice(chat_id: Union[int, str], title: str, description: str, payload: str,
              provider_token: str, start_parameter: str, currency: str, prices:
              List[telegram.payment.labeledprice.LabeledPrice], photo_url: str =
              None, photo_size: int = None, photo_width: int = None, photo_height:
              int = None, need_name: bool = None, need_phone_number: bool
              = None, need_email: bool = None, need_shipping_address: bool
              = None, is_flexible: bool = None, disable_notification: bool =
              False, reply_to_message_id: Union[int, str] = None, reply_markup:
              telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None,
              provider_data: Union[str, object] = None, send_phone_number_to_provider:
              bool = None, send_email_to_provider: bool = None, timeout: float = None,
              api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None)
              → telegram.message.Message
```

Use this method to send invoices.

Parameters

- **chat_id** (int | str) – Unique identifier for the target private chat.
- **title** (str) – Product name, 1-32 characters.
- **description** (str) – Product description, 1-255 characters.
- **payload** (str) – Bot-defined invoice payload, 1-128 bytes. This will not be displayed to the user, use for your internal processes.
- **provider_token** (str) – Payments provider token, obtained via [@BotFather](#).
- **start_parameter** (str) – Unique deep-linking parameter that can be used to generate this invoice when used as a start parameter.
- **currency** (str) – Three-letter ISO 4217 currency code.
- **prices** (List[[telegram.LabeledPrice](#)]) – Price breakdown, a JSON-serialized list of components (e.g. product price, tax, discount, delivery cost, delivery tax, bonus, etc.).
- **provider_data** (str | object, optional) – JSON-serialized data about the invoice, which will be shared with the payment provider. A detailed description of required fields should be provided by the payment provider. When an object is passed, it will be encoded as JSON.
- **photo_url** (str, optional) – URL of the product photo for the invoice. Can be a photo of the goods or a marketing image for a service. People like it better when they see what they are paying for.
- **photo_size** (str, optional) – Photo size.
- **photo_width** (int, optional) – Photo width.
- **photo_height** (int, optional) – Photo height.
- **need_name** (bool, optional) – Pass True, if you require the user's full name to complete the order.
- **need_phone_number** (bool, optional) – Pass True, if you require the user's phone number to complete the order.
- **need_email** (bool, optional) – Pass True, if you require the user's email to complete the order.
- **need_shipping_address** (bool, optional) – Pass True, if you require the user's shipping address to complete the order.
- **send_phone_number_to_provider** (bool, optional) – Pass True, if user's phone number should be sent to provider.

- **send_email_to_provider** (bool, optional) – Pass True, if user’s email address should be sent to provider.
- **is_flexible** (bool, optional) – Pass True, if the final price depends on the shipping method.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – A JSON-serialized object for an inline keyboard. If empty, one ‘Pay total price’ button will be shown. If not empty, the first button must be a Pay button.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

send_location (*chat_id: Union[int, str]*, *latitude: float = None*, *longitude: float = None*, *disable_notification: bool = False*, *reply_to_message_id: Union[int, str] = None*, *reply_markup: telegram.replymarkup.ReplyMarkup = None*, *timeout: float = None*, *location: telegram.files.location.Location = None*, *live_period: int = None*, *api_kwargs: Dict[str, Any] = None*, *horizontal_accuracy: float = None*, *heading: int = None*, *proximity_alert_radius: int = None*, *allow_sending_without_reply: bool = None*) → Optional[*telegram.message.Message*]

Use this method to send point on the map.

Note: You can either supply a latitude and longitude or a location.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **latitude** (float, optional) – Latitude of location.
- **longitude** (float, optional) – Longitude of location.
- **location** (*telegram.Location*, optional) – The location to send.
- **horizontal_accuracy** (int, optional) – The radius of uncertainty for the location, measured in meters; 0-1500.
- **live_period** (int, optional) – Period in seconds for which the location will be updated, should be between 60 and 86400.
- **heading** (int, optional) – For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.

- **proximity_alert_radius** (int, optional) – For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (*telegram.ReplyMarkup*, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

send_media_group (*chat_id: Union[int, str]*, *media: List[Union[*telegram.files.inputmedia.InputMediaAudio*, *telegram.files.inputmedia.InputMediaDocument*, *telegram.files.inputmedia.InputMediaPhoto*, *telegram.files.inputmedia.InputMediaVideo*]]*, *disable_notification: bool = None*, *reply_to_message_id: Union[int, str] = None*, *timeout: float = 20*, *api_kwargs: Dict[str, Any] = None*, *allow_sending_without_reply: bool = None*) → List[Optional[*telegram.message.Message*]]

Use this method to send a group of photos or videos as an album.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **media** (List[*telegram.InputMediaAudio*, *telegram.InputMediaDocument*, *telegram.InputMediaPhoto*, *telegram.InputMediaVideo*]) – An array describing messages to be sent, must include 2–10 items.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **timeout** (int | float, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns An array of the sent Messages.

Return type List[*telegram.Message*]

Raises *telegram.TelegramError*

```
send_message(chat_id: Union[int, str], text: str, parse_mode: str = None, disable_web_page_preview: bool = None, disable_notification: bool = False, reply_to_message_id: Union[int, str] = None, reply_markup: telegram.replymarkup.ReplyMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None, entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]
```

Use this method to send text messages.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **text** (str) – Text of the message to be sent. Max 4096 characters after entities parsing. Also found as `telegram.constants.MAX_MESSAGE_LENGTH`.
- **parse_mode** (str) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in your bot's message. See the constants in `telegram.ParseMode` for the available modes.
- **entities** (List[`telegram.MessageEntity`], optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **disable_web_page_preview** (bool, optional) – Disables link previews for links in this message.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent message is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

```
send_photo(chat_id: int, photo: Union[str, telegram.files.photosize.PhotoSize, IO], caption: str = None, disable_notification: bool = False, reply_to_message_id: Union[int, str] = None, reply_markup: telegram.replymarkup.ReplyMarkup = None, timeout: float = 20, parse_mode: str = None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]
```

Use this method to send photos.

Note: The `photo` argument can be either a `file_id`, an URL or a file from disk `open(filename, 'rb')`

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **photo** (`str` | *filelike object* | `pathlib.Path` | `telegram.PhotoSize`) – Photo to send. Pass a `file_id` as `String` to send a photo that exists on the Telegram servers (recommended), pass an HTTP URL as a `String` for Telegram to get a photo from the Internet, or upload a new photo using multipart/form-data. Lastly you can pass an existing `telegram.PhotoSize` object to send.
- **caption** (`str`, optional) – Photo caption (may also be used when resending photos by `file_id`), 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (`int` | `float`, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent `Message` is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

```
send_poll(chat_id: Union[int, str], question: str, options: List[str], is_anonymous:
    bool = True, type: str = 'regular', allows_multiple_answers: bool =
    False, correct_option_id: int = None, is_closed: bool = None, dis-
    able_notification: bool = None, reply_to_message_id: Union[int, str] = None,
    reply_markup: telegram.replymarkup.ReplyMarkup = None, timeout: float =
    None, explanation: str = None, explanation_parse_mode: Union[str, tele-
    gram.utils.helpers.DefaultValue, None] = <telegram.utils.helpers.DefaultValue
    object>, open_period: int = None, close_date: Union[int, datetime.datetime] =
    None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool =
    None, explanation_entities: Union[List[telegram.messageentity.MessageEntity],
    Tuple[telegram.messageentity.MessageEntity, ...]] = None) → tele-
    gram.message.Message
```

Use this method to send a native poll.

Parameters

- **chat_id** (`int | str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **question** (`str`) – Poll question, 1-255 characters.
- **options** (`List[str]`) – List of answer options, 2-10 strings 1-100 characters each.
- **is_anonymous** (`bool`, optional) – True, if the poll needs to be anonymous, defaults to True.
- **type** (`str`, optional) – Poll type, `telegram.Poll.QUIZ` or `telegram.Poll.REGULAR`, defaults to `telegram.Poll.REGULAR`.
- **allows_multiple_answers** (`bool`, optional) – True, if the poll allows multiple answers, ignored for polls in quiz mode, defaults to False.
- **correct_option_id** (`int`, optional) – 0-based identifier of the correct answer option, required for polls in quiz mode.
- **explanation** (`str`, optional) – Text that is shown when a user chooses an incorrect answer or taps on the lamp icon in a quiz-style poll, 0-200 characters with at most 2 line feeds after entities parsing.
- **explanation_parse_mode** (`str`, optional) – Mode for parsing entities in the explanation. See the constants in `telegram.ParseMode` for the available modes.
- **explanation_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **open_period** (`int`, optional) – Amount of time in seconds the poll will be active after creation, 5-600. Can't be used together with `close_date`.
- **close_date** (`int | datetime.datetime`, optional) – Point in time (Unix timestamp) when the poll will be automatically closed. Must be at least 5 and no more than 600 seconds in the future. Can't be used together with `open_period`. For timezone naive `datetime.datetime` objects, the default timezone of the bot will be used.
- **is_closed** (`bool`, optional) – Pass True, if the poll needs to be immediately closed. This can be useful for poll preview.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

send_sticker (*chat_id*: Union[int, str], *sticker*: Union[str, IO, InputFile, pathlib.Path, telegram.files.sticker.Sticker], *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = 20, *api_kwargs*: Dict[str, Any] = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Use this method to send static .WEBP or animated .TGS stickers.

Note: The sticker argument can be either a file_id, an URL or a file from disk open(filename, 'rb')

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **sticker** (str | filelike object | pathlib.Path | *telegram.Sticker*) – Sticker to send. Pass a file_id as String to send a file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get a .webp file from the Internet, or upload a new one using multipart/form-data. Lastly you can pass an existing *telegram.Sticker* object to send.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (*telegram.ReplyMarkup*, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int | float, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

send_venue (*chat_id*: Union[int, str], *latitude*: float = None, *longitude*: float = None, *title*: str = None, *address*: str = None, *foursquare_id*: str = None, *disable_notification*: bool = False, *reply_to_message_id*: Union[int, str] = None, *reply_markup*: telegram.replymarkup.ReplyMarkup = None, *timeout*: float = None, *venue*: telegram.files.venue.Venue = None, *foursquare_type*: str = None, *api_kwargs*: Dict[str, Any] = None, *google_place_id*: str = None, *google_place_type*: str = None, *allow_sending_without_reply*: bool = None) → Optional[telegram.message.Message]

Use this method to send information about a venue.

Note:

- You can either supply venue, or latitude, longitude, title and address and optionally foursquare_id and foursquare_type or optionally google_place_id and google_place_type.
- Foursquare details and Google Place details are mutually exclusive. However, this behaviour is undocumented and might be changed by Telegram.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **latitude** (`float`, optional) – Latitude of venue.
- **longitude** (`float`, optional) – Longitude of venue.
- **title** (`str`, optional) – Name of the venue.
- **address** (`str`, optional) – Address of the venue.
- **foursquare_id** (`str`, optional) – Foursquare identifier of the venue.
- **foursquare_type** (`str`, optional) – Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (`str`, optional) – Google Places identifier of the venue.
- **google_place_type** (`str`, optional) – Google Places type of the venue. (See [supported types](#).)
- **venue** (`telegram.Venue`, optional) – The venue to send.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent `Message` is returned.

Return type `telegram.Message`

Raises `telegram.TelegramError`

send_video (`chat_id`: `Union[int, str]`, `video`: `Union[str, IO, InputFile, pathlib.Path, telegram.files.video.Video]`, `duration`: `int = None`, `caption`: `str = None`, `disable_notification`: `bool = False`, `reply_to_message_id`: `Union[int, str] = None`, `reply_markup`: `telegram.replymarkup.ReplyMarkup = None`, `timeout`: `float = 20`, `width`: `int = None`, `height`: `int = None`, `parse_mode`: `str = None`, `supports_streaming`: `bool = None`, `thumb`: `Union[str, IO, InputFile, pathlib.Path] = None`, `api_kwargs`: `Dict[str, Any] = None`, `allow_sending_without_reply`: `bool = None`, `caption_entities`: `Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None`) $\rightarrow$ `Optional[telegram.message.Message]`

Use this method to send video files, Telegram clients support mp4 videos (other formats may be sent as Document).

Bots can currently send video files of up to 50 MB in size, this limit may be changed in the future.

Note:

- The video argument can be either a `file_id`, an URL or a file from disk `open(filename, 'rb')`
 - `thumb` will be ignored for small video files, for which Telegram can easily generate thumb nails. However, this behaviour is undocumented and might be changed by Telegram.
-

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **video** (`str` | *filelike object* | `pathlib.Path` | `telegram.Video`) – Video file to send. Pass a `file_id` as String to send an video file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an video file from the Internet, or upload a new one using multipart/form-data. Lastly you can pass an existing `telegram.Video` object to send.
- **duration** (`int`, optional) – Duration of sent video in seconds.
- **width** (`int`, optional) – Video width.
- **height** (`int`, optional) – Video height.
- **caption** (`str`, optional) – Video caption (may also be used when resending videos by `file_id`), 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in message text, which can be specified instead of `parse_mode`.
- **supports_streaming** (`bool`, optional) – Pass `True`, if the uploaded video is suitable for streaming.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **thumb** (*filelike object* | `pathlib.Path`, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **timeout** (`int` | `float`, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type `telegram.Message`

Raises telegram.TelegramError

send_video_note (*chat_id: Union[int, str], video_note: Union[str, IO, InputFile, pathlib.Path, telegram.files.videonote.VideoNote], duration: int = None, length: int = None, disable_notification: bool = False, reply_to_message_id: Union[int, str] = None, reply_markup: telegram.replymarkup.ReplyMarkup = None, timeout: float = 20, thumb: Union[str, IO, InputFile, pathlib.Path] = None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None*) → Optional[telegram.message.Message]

As of v.4.0, Telegram clients support rounded square mp4 videos of up to 1 minute long. Use this method to send video messages.

Note:

- The `video_note` argument can be either a `file_id` or a file from disk `open(filename, 'rb')`
 - `thumb` will be ignored for small video files, for which Telegram can easily generate thumb nails. However, this behaviour is undocumented and might be changed by Telegram.
-

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **video_note** (`str` | *filelike object* | `pathlib.Path` | `telegram.VideoNote`) – Video note to send. Pass a `file_id` as String to send a video note that exists on the Telegram servers (recommended) or upload a new video using multipart/form-data. Or you can pass an existing `telegram.VideoNote` object to send. Sending video notes by a URL is currently unsupported.
- **duration** (`int`, optional) – Duration of sent video in seconds.
- **length** (`int`, optional) – Video width and height, i.e. diameter of the video message.
- **disable_notification** (`bool`, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (`int`, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (`bool`, optional) – Pass `True`, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **thumb** (*filelike object* | `pathlib.Path`, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **timeout** (`int` | `float`, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type `telegram.Message`

Raises telegram.TelegramError

```
send_voice(chat_id: Union[int, str], voice: Union[str, IO, InputFile, pathlib.Path, telegram.files.voice.Voice], duration: int = None, caption: str = None, disable_notification: bool = False, reply_to_message_id: Union[int, str] = None, reply_markup: telegram.replymarkup.ReplyMarkup = None, timeout: float = 20, parse_mode: str = None, api_kwargs: Dict[str, Any] = None, allow_sending_without_reply: bool = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None) → Optional[telegram.message.Message]
```

Use this method to send audio files, if you want Telegram clients to display the file as a playable voice message. For this to work, your audio must be in an .ogg file encoded with OPUS (other formats may be sent as Audio or Document). Bots can currently send voice messages of up to 50 MB in size, this limit may be changed in the future.

Note: The voice argument can be either a file_id, an URL or a file from disk open(filename, 'rb')

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **voice** (str | filelike object | pathlib.Path | *telegram.Voice*) – Voice file to send. Pass a file_id as String to send an voice file that exists on the Telegram servers (recommended), pass an HTTP URL as a String for Telegram to get an voice file from the Internet, or upload a new one using multipart/form-data. Lastly you can pass an existing *telegram.Voice* object to send.
- **caption** (str, optional) – Voice message caption, 0-1024 characters after entities parsing.
- **parse_mode** (str, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in *telegram.ParseMode* for the available modes.
- **caption_entities** (List[*telegram.MessageEntity*], optional) – List of special entities that appear in message text, which can be specified instead of parse_mode.
- **duration** (int, optional) – Duration of the voice message in seconds.
- **disable_notification** (bool, optional) – Sends the message silently. Users will receive a notification with no sound.
- **reply_to_message_id** (int, optional) – If the message is a reply, ID of the original message.
- **allow_sending_without_reply** (bool, optional) – Pass True, if the message should be sent even if the specified replied-to message is not found.
- **reply_markup** (*telegram.ReplyMarkup*, optional) – Additional interface options. A JSON-serialized object for an inline keyboard, custom reply keyboard, instructions to remove reply keyboard or to force a reply from the user.
- **timeout** (int | float, optional) – Send file timeout (default: 20 seconds).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the sent Message is returned.

Return type *telegram.Message*

Raises *telegram.TelegramError*

[illegible]Alias for `set_chat_administrator_custom_title`

```
setChatDescription (chat_id: Union[str, int], description: str, timeout: float = None,
                    api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set_chat_description`

```
setChatPermissions (chat_id: Union[str, int], permissions: telegram.chatpermissions.ChatPermissions, timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set_chat_permissions`

```
setChatPhoto (chat_id: Union[str, int], photo: Union[str, IO, InputFile, pathlib.Path], timeout: float = 20, api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set chat photo`

```
setChatStickerSet (chat_id: Union[str, int], sticker_set_name: str, timeout: float = None,
api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set chat sticker set`

```
setChatTitle (chat_id: Union[str, int], title: str, timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set_chat_title`

```
setGameScore (user_id: Union[int, str], score: int, chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, force: bool = None, disable_edit_message: bool = None, timeout: float = None, api_kwargs: Dict[str, Any] = None) → Union[telegram.message.Message, bool]
```

Alias for *set game score*

```
setMyCommands (commands: List[Union[telegram.botcommand.BotCommand, Tuple[str, str]]],
               timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set_my_commands`

```
setPassportDataErrors (user_id: Union[str, int], errors: List[telegram.passport.passportelementerrors.PassportElementError], timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set_passport_data_errors`

```
setStickerPositionInSet (sticker: str, position: int, timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Alias for `set_sticker_position_in_set`

```
setStickerSetThumb (name: str, user_id: Union[str, int], thumb: Union[str, IO, InputFile, path-
lib.Path] = None, timeout: float = None, api_kwargs: Dict[str, Any] =
None) → bool
```

Alias for `set_sticker_set_thumb`

```
setWebhook (url: str = None, certificate: Union[str, IO, InputFile, pathlib.Path] = None, time-
out: float = None, max_connections: int = 40, allowed_updates: List[str] = None,
api_kwargs: Dict[str, Any] = None, ip_address: str = None, drop_pending_updates:
bool = None) → bool
```

Alias for `set webhook`

```
set_chat_administrator_custom_title(chat_id: Union[int, str], user_id: Union[int, str], custom_title: str, timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Use this method to set a custom title for administrators promoted by the bot in a supergroup. The bot must be an administrator for this to work.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target supergroup (in the format *@supergroupusername*).
- **user_id** (int) – Unique identifier of the target administrator.

- **custom_title** (*str*) – emoji are not allowed.
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

set_chat_description (*chat_id*: *Union[str, int]*, *description*: *str*, *timeout*: *float* = *None*, *api_kwargs*: *Dict[str, Any]* = *None*) → `bool`

Use this method to change the description of a group, a supergroup or a channel. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Parameters

- **chat_id** (*int* | *str*) – Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **description** (*str*) – New chat description, 0-255 characters.
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

set_chat_permissions (*chat_id*: *Union[str, int]*, *permissions*: *telegram.chatpermissions.ChatPermissions*, *timeout*: *float* = *None*, *api_kwargs*: *Dict[str, Any]* = *None*) → `bool`

Use this method to set default chat permissions for all members. The bot must be an administrator in the group or a supergroup for this to work and must have the `can_restrict_members` admin rights.

Parameters

- **chat_id** (*int* | *str*) – Unique identifier for the target chat or username of the target supergroup (in the format `@supergroupusername`).
- **permissions** (*telegram.ChatPermissions*) – New default chat permissions.
- **timeout** (*int* | *float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

set_chat_photo (*chat_id*: *Union[str, int]*, *photo*: *Union[str, IO, InputFile, pathlib.Path]*, *timeout*: *float* = 20, *api_kwargs*: *Dict[str, Any]* = *None*) → `bool`

Use this method to set a new profile photo for the chat.

Photos can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **photo** (*filelike object* | `pathlib.Path`) – New chat photo.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

set_chat_sticker_set (*chat_id: Union[str, int], sticker_set_name: str, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `bool`

Use this method to set a new group sticker set for a supergroup. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights. Use the field `telegram.Chat.can_set_sticker_set` optionally returned in `get_chat` requests to check if the bot can use this method.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target supergroup (in the format @supergroupusername).
- **sticker_set_name** (`str`) – Name of the sticker set to be set as the group sticker set.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

set_chat_title (*chat_id: Union[str, int], title: str, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `bool`

Use this method to change the title of a chat. Titles can't be changed for private chats. The bot must be an administrator in the chat for this to work and must have the appropriate admin rights.

Parameters

- **chat_id** (`int` | `str`) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **title** (`str`) – New chat title, 1-255 characters.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, `True` is returned.

Return type `bool`

Raises `telegram.TelegramError`

set_game_score (*user_id: Union[int, str], score: int, chat_id: Union[str, int] = None, message_id: Union[str, int] = None, inline_message_id: Union[str, int] = None, force: bool = None, disable_edit_message: bool = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → Union[telegram.message.Message, bool]

Use this method to set the score of the specified user in a game.

Parameters

- **user_id** (`int`) – User identifier.
- **score** (`int`) – New score, must be non-negative.
- **force** (`bool`, optional) – Pass `True`, if the high score is allowed to decrease. This can be useful when fixing mistakes or banning cheaters.
- **disable_edit_message** (`bool`, optional) – Pass `True`, if the game message should not be automatically edited to include the current scoreboard.
- **chat_id** (`int` | `str`, optional) – Required if `inline_message_id` is not specified. Unique identifier for the target chat.
- **message_id** (`int`, optional) – Required if `inline_message_id` is not specified. Identifier of the sent message.
- **inline_message_id** (`str`, optional) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns The edited message, or if the message wasn't sent by the bot, `True`.

Return type `telegram.Message`

Raises `telegram.TelegramError` – If the new score is not greater than the user's current score in the chat and `force` is `False`.

set_my_commands (*commands: List[Union[telegram.botcommand.BotCommand, Tuple[str, str]]], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `bool`

Use this method to change the list of the bot's commands.

Parameters

- **commands** (`List[BotCommand | (str, str)]`) – A JSON-serialized list of bot commands to be set as the list of the bot's commands. At most 100 commands can be specified.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success

Return type `True`

Raises `telegram.TelegramError`

```
set_passport_data_errors (user_id: Union[str, int], errors: List[telegram.passport.passportelementerrors.PassportElementError],
                           timeout: float = None, api_kwargs: Dict[str, Any] = None) → bool
```

Informs a user that some of the Telegram Passport elements they provided contains errors. The user will not be able to re-submit their Passport to you until the errors are fixed (the contents of the field for which you returned the error must change).

Use this if the data submitted by the user doesn't satisfy the standards your service requires for any reason. For example, if a birthday date seems invalid, a submitted document is blurry, a scan shows evidence of tampering, etc. Supply some details in the error message to make sure the user knows how to correct the issues.

Parameters

- **user_id** (int) – User identifier
- **errors** (List[[PassportElementError](#)]) – A JSON-serialized array describing the errors.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

```
set_sticker_position_in_set (sticker: str, position: int, timeout: float = None,
                              api_kwargs: Dict[str, Any] = None) → bool
```

Use this method to move a sticker in a set created by the bot to a specific position.

Parameters

- **sticker** (str) – File identifier of the sticker.
- **position** (int) – New sticker position in the set, zero-based.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

```
set_sticker_set_thumb (name: str, user_id: Union[str, int], thumb: Union[str, IO, InputFile,
                                                                           pathlib.Path] = None, timeout: float = None,
                        api_kwargs: Dict[str, Any] = None) → bool
```

Use this method to set the thumbnail of a sticker set. Animated thumbnails can be set for animated sticker sets only.

Note: The thumb can be either a file_id, an URL or a file from disk `open(filename, 'rb')`

Parameters

- **name** (str) – Sticker set name

- **user_id** (int) – User identifier of created sticker set owner.
- **thumb** (str | filelike object | pathlib.Path, optional) – A PNG image with the thumbnail, must be up to 128 kilobytes in size and have width and height exactly 100px, or a TGS animation with the thumbnail up to 32 kilobytes in size; see https://core.telegram.org/animated_stickers#technical-requirements for animated sticker technical requirements. Pass a file_id as a String to send a file that already exists on the Telegram servers, pass an HTTP URL as a String for Telegram to get a file from the Internet, or upload a new one using multipart/form-data. Animated sticker set thumbnail can't be uploaded via HTTP URL.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

```
set_webhook(url: str = None, certificate: Union[str, IO, InputFile, pathlib.Path] = None,
            timeout: float = None, max_connections: int = 40, allowed_updates: List[str]
            = None, api_kwargs: Dict[str, Any] = None, ip_address: str = None,
            drop_pending_updates: bool = None) → bool
```

Use this method to specify a url and receive incoming updates via an outgoing webhook. Whenever there is an update for the bot, Telegram will send an HTTPS POST request to the specified url, containing a JSON-serialized Update. In case of an unsuccessful request, Telegram will give up after a reasonable amount of attempts.

If you'd like to make sure that the Webhook request comes from Telegram, Telegram recommends using a secret path in the URL, e.g. <https://www.example.com/<token>>. Since nobody else knows your bot's token, you can be pretty sure it's us.

Note: The certificate argument should be a file from disk `open(filename, 'rb')`.

Parameters

- **url** (str) – HTTPS url to send updates to. Use an empty string to remove webhook integration.
- **certificate** (filelike) – Upload your public key certificate so that the root certificate in use can be checked. See our self-signed guide for details. (<https://goo.gl/rw7w6Y>)
- **ip_address** (str, optional) – The fixed IP address which will be used to send webhook requests instead of the IP address resolved through DNS.
- **max_connections** (int, optional) – Maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery, 1-100. Defaults to 40. Use lower values to limit the load on your bot's server, and higher values to increase your bot's throughput.
- **allowed_updates** (List[str], optional) – A JSON-serialized list the types of updates you want your bot to receive. For example, specify ["message", "edited_channel_post", "callback_query"] to only receive updates of these types. See [telegram.Update](#) for a complete list of available update types. Specify an empty list to receive all updates regardless of type (default). If not specified, the previous setting will be used. Please note that this parameter doesn't affect updates created

before the call to the `set_webhook`, so unwanted updates may be received for a short period of time.

- **drop_pending_updates** (`bool`, optional) – Pass `True` to drop all pending updates.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Note:

1. You will not be able to receive updates using `get_updates` for as long as an outgoing webhook is set up.
2. To use a self-signed certificate, you need to upload your public key certificate using `certificate` parameter. Please upload as `InputFile`, sending a `String` will not work.
3. Ports currently supported for Webhooks: 443, 80, 88, 8443.

If you're having any trouble setting up webhooks, please check out this [guide to Webhooks](#).

Returns `bool` On success, `True` is returned.

Raises `telegram.TelegramError`

```
stopMessageLiveLocation (chat_id: Union[str, int] = None, message_id: Union[str, int] =  
None, inline_message_id: Union[str, int] = None, reply_markup: tele-  
gram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup =  
None, timeout: float = None, api_kwargs: Dict[str, Any] = None)  
→ Union[telegram.message.Message, None, bool]
```

Alias for `stop_message_live_location`

```
stopPoll (chat_id: Union[int, str], message_id: Union[int, str], reply_markup: tele-  
gram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float =  
None, api_kwargs: Dict[str, Any] = None) → telegram.poll.Poll
```

Alias for `stop_poll`

```
stop_message_live_location (chat_id: Union[str, int] = None, message_id:  
Union[str, int] = None, inline_message_id:  
Union[str, int] = None, reply_markup: tele-  
gram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup =  
None, timeout: float = None, api_kwargs: Dict[str, Any] =  
None) → Union[telegram.message.Message, None, bool]
```

Use this method to stop updating a live location message sent by the bot or via the bot (for inline bots) before `live_period` expires.

Parameters

- **chat_id** (`int` | `str`) – Required if `inline_message_id` is not specified. Unique identifier for the target chat or username of the target channel (in the format `@channelusername`).
- **message_id** (`int`, optional) – Required if `inline_message_id` is not specified. Identifier of the sent message with live location to stop.
- **inline_message_id** (`str`, optional) – Required if `chat_id` and `message_id` are not specified. Identifier of the inline message.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – A JSON-serialized object for a new inline keyboard.

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, if edited message is sent by the bot, the sent Message is returned, otherwise True is returned.

Return type `telegram.Message`

stop_poll (*chat_id: Union[int, str], message_id: Union[int, str], reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, timeout: float = None, api_kwargs: Dict[str, Any] = None*) → `telegram.poll.Poll`

Use this method to stop a poll which was sent by the bot.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **message_id** (int) – Identifier of the original message with the poll.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – A JSON-serialized object for a new message inline keyboard.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the stopped Poll with the final results is returned.

Return type `telegram.Poll`

Raises `telegram.TelegramError`

supports_inline_queries

Bot's `supports_inline_queries` attribute.

Type `bool`

unbanChatMember (*chat_id: Union[str, int], user_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None, only_if_banned: bool = None*) → `bool`

Alias for `unban_chat_member`

unban_chat_member (*chat_id: Union[str, int], user_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None, only_if_banned: bool = None*) → `bool`

Use this method to unban a previously kicked user in a supergroup or channel.

The user will *not* return to the group or channel automatically, but will be able to join via link, etc. The bot must be an administrator for this to work. By default, this method guarantees that after the call the user is not a member of the chat, but will be able to join it. So if the user is a member of the chat they will also be *removed* from the chat. If you don't want this, use the parameter `only_if_banned`.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **user_id** (int) – Unique identifier of the target user.
- **only_if_banned** (bool, optional) – Do nothing if the user is not banned.

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns bool On success, True is returned.

Raises telegram.TelegramError

unpinAllChatMessages (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool
Alias for `unpin_all_chat_messages`

unpinChatMessage (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None, message_id: Union[str, int] = None*) → bool
Alias for `unpin_chat_message`

unpin_all_chat_messages (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None*) → bool

Use this method to clear the list of pinned messages in a chat. If the chat is not a private chat, the bot must be an administrator in the chat for this to work and must have the `can_pin_messages` admin right in a supergroup or `can_edit_messages` admin right in a channel.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

unpin_chat_message (*chat_id: Union[str, int], timeout: float = None, api_kwargs: Dict[str, Any] = None, message_id: Union[str, int] = None*) → bool

Use this method to remove a message from the list of pinned messages in a chat. If the chat is not a private chat, the bot must be an administrator in the chat for this to work and must have the `can_pin_messages` admin right in a supergroup or `can_edit_messages` admin right in a channel.

Parameters

- **chat_id** (int | str) – Unique identifier for the target chat or username of the target channel (in the format @channelusername).
- **message_id** (int, optional) – Identifier of a message to unpin. If not specified, the most recent pinned message (by sending date) will be unpinned.
- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, True is returned.

Return type bool

Raises telegram.TelegramError

uploadStickerFile (*user_id: Union[str, int], png_sticker: Union[str, IO, InputFile, pathlib.Path], timeout: float = 20, api_kwargs: Dict[str, Any] = None*) → telegram.files.file.File

Alias for `upload_sticker_file`

upload_sticker_file (*user_id: Union[str, int], png_sticker: Union[str, IO, InputFile, pathlib.Path], timeout: float = 20, api_kwargs: Dict[str, Any] = None*) → telegram.files.file.File

Use this method to upload a .png file with a sticker for later use in `create_new_sticker_set` and `add_sticker_to_set` methods (can be used multiple times).

Note: The `png_sticker` argument can be either a `file_id`, an URL or a file from disk `open(filename, 'rb')`

Parameters

- **user_id** (`int`) – User identifier of sticker file owner.
- **png_sticker** (`str` | *filelike object* | `pathlib.Path`) – Png image with the sticker, must be up to 512 kilobytes in size, dimensions must not exceed 512px, and either width or height must be exactly 512px.
- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns On success, the uploaded File is returned.

Return type `telegram.File`

Raises `telegram.TelegramError`

username

Bot's username.

Type `str`

3.2.4 telegram.BotCommand

class `telegram.BotCommand` (*command: str, description: str, **kwargs*)

Bases: `telegram.base.TelegramObject`

This object represents a bot command.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `command` and `description` are equal.

command

Text of the command.

Type `str`

description

Description of the command.

Type `str`

Parameters

- **command** (`str`) – Text of the command, 1-32 characters. Can contain only lowercase English letters, digits and underscores.

- **description** (*str*) – Description of the command, 3-256 characters.

3.2.5 telegram.CallbackQuery

class telegram.**CallbackQuery** (*id: str, from_user: telegram.user.User, chat_instance: str, message: telegram.message.Message = None, data: str = None, inline_message_id: str = None, game_short_name: str = None, bot: Bot = None, **kwargs*)

Bases: telegram.base.TelegramObject

This object represents an incoming callback query from a callback button in an inline keyboard.

If the button that originated the query was attached to a message sent by the bot, the field *message* will be present. If the button was attached to a message sent via the bot (in inline mode), the field *inline_message_id* will be present.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *id* is equal.

Note:

- In Python *from* is a reserved word, use *from_user* instead.
 - Exactly one of the fields *data* or *game_short_name* will be present.
-

id

Unique identifier for this query.

Type *str*

from_user

Sender.

Type *telegram.User*

chat_instance

Global identifier, uniquely corresponding to the chat to which the message with the callback button was sent.

Type *str*

message

Optional. Message with the callback button that originated the query.

Type *telegram.Message*

data

Optional. Data associated with the callback button.

Type *str*

inline_message_id

Optional. Identifier of the message sent via the bot in inline mode, that originated the query.

Type *str*

game_short_name

Optional. Short name of a Game to be returned.

Type *str*

bot

The Bot to use for instance methods.

Type *telegram.Bot*, optional

Parameters

- **id** (`str`) – Unique identifier for this query.
- **from_user** (`telegram.User`) – Sender.
- **chat_instance** (`str`) – Global identifier, uniquely corresponding to the chat to which the message with the callback button was sent. Useful for high scores in games.
- **message** (`telegram.Message`, optional) – Message with the callback button that originated the query. Note that message content and message date will not be available if the message is too old.
- **data** (`str`, optional) – Data associated with the callback button. Be aware that a bad client can send arbitrary data in this field.
- **inline_message_id** (`str`, optional) – Identifier of the message sent via the bot in inline mode, that originated the query.
- **game_short_name** (`str`, optional) – Short name of a Game to be returned, serves as the unique identifier for the game
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.

Note: After the user presses an inline button, Telegram clients will display a progress bar until you call `answer`. It is, therefore, necessary to react by calling `telegram.Bot.answer_callback_query` even if no notification to the user is needed (e.g., without specifying any of the optional parameters).

answer (`*args, **kwargs`) → `bool`

Shortcut for:

```
bot.answer_callback_query(update.callback_query.id, *args, **kwargs)
```

Returns On success, `True` is returned.

Return type `bool`

copy_message (`chat_id: int, *args, **kwargs`) → `MessageId`

Shortcut for:

```
update.callback_query.message.copy(
    chat_id,
    from_chat_id=update.message.chat_id,
    message_id=update.message.message_id,
    *args,
    **kwargs)
```

Returns On success, returns the `MessageId` of the sent message.

Return type `telegram.MessageId`

delete_message (`*args, **kwargs`) → `Union[telegram.message.Message, bool]`

Shortcut for:

```
update.callback_query.message.delete(*args, **kwargs)
```

Returns On success, `True` is returned.

Return type `bool`

edit_message_caption (*caption: str, *args, **kwargs*) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.edit_caption(caption, *args, **kwargs)
```

or:

```
bot.edit_message_caption(caption=caption
                        inline_message_id=update.callback_query.inline_
↪message_id,
                        *args, **kwargs)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_message_live_location (**args, **kwargs*) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.edit_live_location(*args, **kwargs)
```

or:

```
bot.edit_message_live_location(
    inline_message_id=update.callback_query.inline_message_id,
    *args, **kwargs
)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_message_media (**args, **kwargs*) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.edit_media(*args, **kwargs)
```

or:

```
bot.edit_message_media(inline_message_id=update.callback_query.inline_
↪message_id,
                        *args, **kwargs)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_message_reply_markup (*reply_markup: InlineKeyboardMarkup, *args, **kwargs*) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.edit_reply_markup(
    reply_markup=reply_markup,
    *args,
    **kwargs
)
```

or:

```
bot.edit_message_reply_markup(
    inline_message_id=update.callback_query.inline_message_id,
    reply_markup=reply_markup,
    *args,
    **kwargs
)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type `telegram.Message`

edit_message_text (*text: str, *args, **kwargs*) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.edit_text(text, *args, **kwargs)
```

or:

```
bot.edit_message_text(text, inline_message_id=update.callback_query.inline_
↳message_id,
                        *args, **kwargs)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type `telegram.Message`

get_game_high_scores (**args, **kwargs*) → List[GameHighScore]

Shortcut for either:

```
update.callback_query.message.get_game_high_score(*args, **kwargs)
```

or:

```
bot.get_game_high_scores(inline_message_id=update.callback_query.inline_
↳message_id,
                        *args, **kwargs)
```

Returns List[`telegram.GameHighScore`]

pin_message (**args, **kwargs*) → bool

Shortcut for:

```
bot.pin_chat_message(chat_id=message.chat_id,
                     message_id=message.message_id,
                     *args,
                     **kwargs)
```

Returns On success, True is returned.

Return type bool

set_game_score (**args, **kwargs*) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.set_game_score(*args, **kwargs)
```

or:

```
bot.set_game_score(inline_message_id=update.callback_query.inline_message_id,
→ id,
                    *args, **kwargs)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type `telegram.Message`

stop_message_live_location(*args, **kwargs) → Union[telegram.message.Message, bool]

Shortcut for either:

```
update.callback_query.message.stop_live_location(*args, **kwargs)
```

or:

```
bot.stop_message_live_location(
    inline_message_id=update.callback_query.inline_message_id,
    *args, **kwargs
)
```

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type `telegram.Message`

unpin_message(*args, **kwargs) → bool

Shortcut for:

```
bot.unpin_chat_message(chat_id=message.chat_id,
                        message_id=message.message_id,
                        *args,
                        **kwargs)
```

Returns On success, True is returned.

Return type bool

3.2.6 telegram.Chat

```
class telegram.Chat(id: int, type: str, title: str = None, username: str = None, first_name: str = None, last_name: str = None, bot: Bot = None, photo: telegram.files.chatphoto.ChatPhoto = None, description: str = None, invite_link: str = None, pinned_message: Message = None, permissions: telegram.chatpermissions.ChatPermissions = None, sticker_set_name: str = None, can_set_sticker_set: bool = None, slow_mode_delay: int = None, bio: str = None, linked_chat_id: int = None, location: telegram.chatlocation.ChatLocation = None, **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents a chat.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `id` is equal.

id

Unique identifier for this chat.

Type int

type
Type of chat.
Type `str`

title
Optional. Title, for supergroups, channels and group chats.
Type `str`

username
Optional. Username.
Type `str`

first_name
Optional. First name of the other party in a private chat.
Type `str`

last_name
Optional. Last name of the other party in a private chat.
Type `str`

photo
Optional. Chat photo.
Type `telegram.ChatPhoto`

bio
Optional. Bio of the other party in a private chat. Returned only in `telegram.Bot.get_chat()`.
Type `str`

description
Optional. Description, for groups, supergroups and channel chats.
Type `str`

invite_link
Optional. Chat invite link, for supergroups and channel chats.
Type `str`

pinned_message
Optional. The most recent pinned message (by sending date). Returned only in `telegram.Bot.get_chat()`.
Type `telegram.Message`

permissions
Optional. Default chat member permissions, for groups and supergroups. Returned only in `telegram.Bot.get_chat()`.
Type `telegram.ChatPermissions`

slow_mode_delay
Optional. For supergroups, the minimum allowed delay between consecutive messages sent by each unprivileged user. Returned only in `telegram.Bot.get_chat()`.
Type `int`

sticker_set_name
Optional. For supergroups, name of Group sticker set.
Type `str`

can_set_sticker_set
Optional. True, if the bot can change group the sticker set.
Type `bool`

linked_chat_id

Optional. Unique identifier for the linked chat, i.e. the discussion group identifier for a channel and vice versa; for supergroups and channel chats. Returned only in `telegram.Bot.get_chat()`.

Type `int`

location

Optional. For supergroups, the location to which the supergroup is connected. Returned only in `telegram.Bot.get_chat()`.

Type `telegram.ChatLocation`

Parameters

- **id** (`int`) – Unique identifier for this chat. This number may be greater than 32 bits and some programming languages may have difficulty/silent defects in interpreting it. But it is smaller than 52 bits, so a signed 64 bit integer or double-precision float type are safe for storing this identifier.
- **type** (`str`) – Type of chat, can be either ‘private’, ‘group’, ‘supergroup’ or ‘channel’.
- **title** (`str`, optional) – Title, for supergroups, channels and group chats.
- **username** (`str`, optional) – Username, for private chats, supergroups and channels if available.
- **first_name** (`str`, optional) – First name of the other party in a private chat.
- **last_name** (`str`, optional) – Last name of the other party in a private chat.
- **photo** (`telegram.ChatPhoto`, optional) – Chat photo. Returned only in `telegram.Bot.get_chat()`.
- **bio** (`str`, optional) – Bio of the other party in a private chat. Returned only in `telegram.Bot.get_chat()`.
- **description** (`str`, optional) – Description, for groups, supergroups and channel chats. Returned only in `telegram.Bot.get_chat()`.
- **invite_link** (`str`, optional) – Chat invite link, for groups, supergroups and channel chats. Each administrator in a chat generates their own invite links, so the bot must first generate the link using `export_chat_invite_link()`. Returned only in `telegram.Bot.get_chat()`.
- **pinned_message** (`telegram.Message`, optional) – The most recent pinned message (by sending date). Returned only in `telegram.Bot.get_chat()`.
- **permissions** (`telegram.ChatPermissions`) – Optional. Default chat member permissions, for groups and supergroups. Returned only in `telegram.Bot.get_chat()`.
- **slow_mode_delay** (`int`, optional) – For supergroups, the minimum allowed delay between consecutive messages sent by each unprivileged user. Returned only in `telegram.Bot.get_chat()`.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- **sticker_set_name** (`str`, optional) – For supergroups, name of group sticker set. Returned only in `telegram.Bot.get_chat()`.
- **can_set_sticker_set** (`bool`, optional) – True, if the bot can change group the sticker set. Returned only in `telegram.Bot.get_chat()`.
- **linked_chat_id** (`int`, optional) – Unique identifier for the linked chat, i.e. the discussion group identifier for a channel and vice versa; for supergroups and channel chats. Returned only in `telegram.Bot.get_chat()`.

- **location** (*telegram.ChatLocation*, optional) – For supergroups, the location to which the supergroup is connected. Returned only in *telegram.Bot.get_chat()*.
- ****kwargs** (dict) – Arbitrary keyword arguments.

```
CHANNEL = 'channel'
    telegram.constants.CHAT_CHANNEL

GROUP = 'group'
    telegram.constants.CHAT_GROUP

PRIVATE = 'private'
    telegram.constants.CHAT_PRIVATE

SUPERGROUP = 'supergroup'
    telegram.constants.CHAT_SUPERGROUP
```

copy_message (*args, **kwargs) → MessageId
Shortcut for:

```
bot.copy_message(from_chat_id=update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

get_administrators (*args, **kwargs) → List[ChatMember]
Shortcut for:

```
bot.get_chat_administrators(update.effective_chat.id, *args, **kwargs)
```

Returns A list of administrators in a chat. An Array of *telegram.ChatMember* objects that contains information about all chat administrators except other bots. If the chat is a group or a supergroup and no administrators were appointed, only the creator will be returned.

Return type List[*telegram.ChatMember*]

get_member (*args, **kwargs) → ChatMember
Shortcut for:

```
bot.get_chat_member(update.effective_chat.id, *args, **kwargs)
```

Returns *telegram.ChatMember*

get_members_count (*args, **kwargs) → int
Shortcut for:

```
bot.get_chat_members_count(update.effective_chat.id, *args, **kwargs)
```

Returns int

kick_member (*args, **kwargs) → bool
Shortcut for:

```
bot.kick_chat_member(update.effective_chat.id, *args, **kwargs)
```

Returns If the action was sent successfully.

Return type bool

Note: This method will only work if the *All Members Are Admins* setting is off in the target group. Otherwise members may only be removed by the group's creator or by the member that added them.

leave (*args, **kwargs) → bool

Shortcut for:

```
bot.leave_chat(update.effective_chat.id, *args, **kwargs)
```

Returns bool If the action was sent successfully.

link

Convenience property. If the chat has a *username*, returns a t.me link of the chat.

Type str

pin_message (*args, **kwargs) → bool

Shortcut for:

```
bot.pin_chat_message(chat_id=update.effective_chat.id,
                     *args,
                     **kwargs)
```

Returns On success, True is returned.

Return type bool

send_action (*args, **kwargs) → bool

Alias for *send_chat_action*

send_animation (*args, **kwargs) → Message

Shortcut for:

```
bot.send_animation(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_audio (*args, **kwargs) → Message

Shortcut for:

```
bot.send_audio(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_chat_action (*args, **kwargs) → bool

Shortcut for:

```
bot.send_chat_action(update.effective_chat.id, *args, **kwargs)
```

Returns On success.

Return type True

send_contact (*args, **kwargs) → Message

Shortcut for:

```
bot.send_contact(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_copy (*args, **kwargs) → MessageId

Shortcut for:

```
bot.copy_message(chat_id=update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_dice (*args, **kwargs) → Message

Shortcut for:

```
bot.send_dice(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_document (*args, **kwargs) → Message

Shortcut for:

```
bot.send_document(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_game (*args, **kwargs) → Message

Shortcut for:

```
bot.send_game(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_invoice (*args, **kwargs) → Message

Shortcut for:

```
bot.send_invoice(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_location (*args, **kwargs) → Message

Shortcut for:

```
bot.send_location(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_media_group (*args, **kwargs) → List[Message]

Shortcut for:

```
bot.send_media_group(update.effective_chat.id, *args, **kwargs)
```

Returns] On success, instance representing the message posted.

Return type List[*telegram.Message*]

send_message (*args, **kwargs) → Message

Shortcut for:

```
bot.send_message(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_photo (*args, **kwargs) → Message

Shortcut for:

```
bot.send_photo(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_poll (*args, **kwargs) → Message

Shortcut for:

```
bot.send_poll(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_sticker (*args, **kwargs) → Message

Shortcut for:

```
bot.send_sticker(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_venue (*args, **kwargs) → Message

Shortcut for:

```
bot.send_venue(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_video (*args, **kwargs) → Message

Shortcut for:

```
bot.send_video(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_video_note (*args, **kwargs) → Message

Shortcut for:

```
bot.send_video_note(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_voice (*args, **kwargs) → Message

Shortcut for:

```
bot.send_voice(update.effective_chat.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

set_administrator_custom_title (*args, **kwargs) → bool

Shortcut for:

```
bot.set_chat_administrator_custom_title(update.effective_chat.id, *args, ↵
↪ **kwargs)
```

Returns: bool: If the action was sent successfully.

set_permissions (*args, **kwargs) → bool

Shortcut for:

```
bot.set_chat_permissions(update.effective_chat.id, *args, **kwargs)
```

Returns If the action was sent successfully.

Return type bool

unban_member (*args, **kwargs) → bool

Shortcut for:

```
bot.unban_chat_member(update.effective_chat.id, *args, **kwargs)
```

Returns If the action was sent successfully.

Return type bool

unpin_all_messages (*args, **kwargs) → bool

Shortcut for:

```
bot.unpin_all_chat_messages(chat_id=update.effective_chat.id,
                             *args,
                             **kwargs)
```

Returns On success, True is returned.

Return type bool

unpin_message (*args, **kwargs) → bool

Shortcut for:

```
bot.unpin_chat_message(chat_id=update.effective_chat.id,  
                       *args,  
                       **kwargs)
```

Returns On success, True is returned.

Return type bool

3.2.7 telegram.ChatAction

class telegram.ChatAction

Bases: object

Helper class to provide constants for different chat actions.

```
FIND_LOCATION = 'find_location'  
    telegram.constants.CHATACTION_FIND_LOCATION  
  
RECORD_AUDIO = 'record_audio'  
    telegram.constants.CHATACTION_RECORD_AUDIO  
  
RECORD_VIDEO = 'record_video'  
    telegram.constants.CHATACTION_RECORD_VIDEO  
  
RECORD_VIDEO_NOTE = 'record_video_note'  
    telegram.constants.CHATACTION_RECORD_VIDEO_NOTE  
  
TYPING = 'typing'  
    telegram.constants.CHATACTION_TYPING  
  
UPLOAD_AUDIO = 'upload_audio'  
    telegram.constants.CHATACTION_UPLOAD_AUDIO  
  
UPLOAD_DOCUMENT = 'upload_document'  
    telegram.constants.CHATACTION_UPLOAD_DOCUMENT  
  
UPLOAD_PHOTO = 'upload_photo'  
    telegram.constants.CHATACTION_UPLOAD_PHOTO  
  
UPLOAD_VIDEO = 'upload_video'  
    telegram.constants.CHATACTION_UPLOAD_VIDEO  
  
UPLOAD_VIDEO_NOTE = 'upload_video_note'  
    telegram.constants.CHATACTION_UPLOAD_VIDEO_NOTE
```

3.2.8 telegram.ChatLocation

class telegram.ChatLocation(*location:* telegram.files.location.Location, *address:* str,
 ***kwargs*)

Bases: telegram.base.TelegramObject

This object represents a location to which a chat is connected.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *location* is equal.

location

The location to which the supergroup is connected.

Type telegram.Location

address

Location address, as defined by the chat owner

Type str

Parameters

- **location** (*telegram.Location*) – The location to which the supergroup is connected. Can't be a live location.
- **address** (*str*) – Location address; 1-64 characters, as defined by the chat owner
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

3.2.9 telegram.ChatMember

```
class telegram.ChatMember (user: telegram.user.User, status: str, until_date: datetime.datetime = None, can_be_edited: bool = None, can_change_info: bool = None, can_post_messages: bool = None, can_edit_messages: bool = None, can_delete_messages: bool = None, can_invite_users: bool = None, can_restrict_members: bool = None, can_pin_messages: bool = None, can_promote_members: bool = None, can_send_messages: bool = None, can_send_media_messages: bool = None, can_send_polls: bool = None, can_send_other_messages: bool = None, can_add_web_page_previews: bool = None, is_member: bool = None, custom_title: str = None, is_anonymous: bool = None, **kwargs)
```

Bases: telegram.base.TelegramObject

This object contains information about one member of a chat.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *user* and *status* are equal.

user

Information about the user.

Type *telegram.User*

status

The member's status in the chat.

Type *str*

custom_title

Optional. Custom title for owner and administrators.

Type *str*

is_anonymous

Optional. True, if the user's presence in the chat is hidden.

Type *bool*

until_date

Optional. Date when restrictions will be lifted for this user.

Type *datetime.datetime*

can_be_edited

Optional. If the bot is allowed to edit administrator privileges of that user.

Type *bool*

can_change_info

Optional. If the user can change the chat title, photo and other settings.

Type *bool*

can_post_messages

Optional. If the administrator can post in the channel.

Type `bool`

can_edit_messages

Optional. If the administrator can edit messages of other users.

Type `bool`

can_delete_messages

Optional. If the administrator can delete messages of other users.

Type `bool`

can_invite_users

Optional. If the user can invite new users to the chat.

Type `bool`

can_restrict_members

Optional. If the administrator can restrict, ban or unban chat members.

Type `bool`

can_pin_messages

Optional. If the user can pin messages.

Type `bool`

can_promote_members

Optional. If the administrator can add new administrators.

Type `bool`

is_member

Optional. Restricted only. `True`, if the user is a member of the chat at the moment of the request.

Type `bool`

can_send_messages

Optional. If the user can send text messages, contacts, locations and venues.

Type `bool`

can_send_media_messages

Optional. If the user can send media messages, implies `can_send_messages`.

Type `bool`

can_send_polls

Optional. `True`, if the user is allowed to send polls.

Type `bool`

can_send_other_messages

Optional. If the user can send animations, games, stickers and use inline bots, implies `can_send_media_messages`.

Type `bool`

can_add_web_page_previews

Optional. If user may add web page previews to his messages, implies `can_send_media_messages`

Type `bool`

Parameters

- **user** (`telegram.User`) – Information about the user.
- **status** (`str`) – The member's status in the chat. Can be 'creator', 'administrator', 'member', 'restricted', 'left' or 'kicked'.
- **custom_title** (`str`, optional) – Owner and administrators only. Custom title for this user.

- **is_anonymous** (bool, optional) – Owner and administrators only. True, if the user's presence in the chat is hidden.
- **until_date** (datetime.datetime, optional) – Restricted and kicked only. Date when restrictions will be lifted for this user.
- **can_be_edited** (bool, optional) – Administrators only. True, if the bot is allowed to edit administrator privileges of that user.
- **can_change_info** (bool, optional) – Administrators and restricted only. True, if the user can change the chat title, photo and other settings.
- **can_post_messages** (bool, optional) – Administrators only. True, if the administrator can post in the channel, channels only.
- **can_edit_messages** (bool, optional) – Administrators only. True, if the administrator can edit messages of other users and can pin messages; channels only.
- **can_delete_messages** (bool, optional) – Administrators only. True, if the administrator can delete messages of other users.
- **can_invite_users** (bool, optional) – Administrators and restricted only. True, if the user can invite new users to the chat.
- **can_restrict_members** (bool, optional) – Administrators only. True, if the administrator can restrict, ban or unban chat members.
- **can_pin_messages** (bool, optional) – Administrators and restricted only. True, if the user can pin messages, groups and supergroups only.
- **can_promote_members** (bool, optional) – Administrators only. True, if the administrator can add new administrators with a subset of his own privileges or demote administrators that he has promoted, directly or indirectly (promoted by administrators that were appointed by the user).
- **is_member** (bool, optional) – Restricted only. True, if the user is a member of the chat at the moment of the request.
- **can_send_messages** (bool, optional) – Restricted only. True, if the user can send text messages, contacts, locations and venues.
- **can_send_media_messages** (bool, optional) – Restricted only. True, if the user can send audios, documents, photos, videos, video notes and voice notes.
- **can_send_polls** (bool, optional) – Restricted only. True, if the user is allowed to send polls.
- **can_send_other_messages** (bool, optional) – Restricted only. True, if the user can send animations, games, stickers and use inline bots.
- **can_add_web_page_previews** (bool, optional) – Restricted only. True, if user may add web page previews to his messages.

```
ADMINISTRATOR = 'administrator'  
    telegram.constants.CHATMEMBER_ADMINISTRATOR  
  
CREATOR = 'creator'  
    telegram.constants.CHATMEMBER_CREATOR  
  
KICKED = 'kicked'  
    telegram.constants.CHATMEMBER_KICKED  
  
LEFT = 'left'  
    telegram.constants.CHATMEMBER_LEFT  
  
MEMBER = 'member'  
    telegram.constants.CHATMEMBER_MEMBER
```

```
RESTRICTED = 'restricted'  
telegram.constants.CHATMEMBER_RESTRICTED
```

3.2.10 telegram.ChatPermissions

```
class telegram.ChatPermissions (can_send_messages: bool = None,  
                               can_send_media_messages: bool = None, can_send_polls:  
                               bool = None, can_send_other_messages: bool =  
                               None, can_add_web_page_previews: bool = None,  
                               can_change_info: bool = None, can_invite_users: bool =  
                               None, can_pin_messages: bool = None, **kwargs)  
Bases: telegram.base.TelegramObject
```

Describes actions that a non-administrator user is allowed to take in a chat.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `can_send_messages`, `can_send_media_messages`, `can_send_polls`, `can_send_other_messages`, `can_add_web_page_previews`, `can_change_info`, `can_invite_users` and `can_pin_message` are equal.

Note: Though not stated explicitly in the official docs, Telegram changes not only the permissions that are set, but also sets all the others to `False`. However, since not documented, this behaviour may change unbeknown to PTB.

can_send_messages

Optional. `True`, if the user is allowed to send text messages, contacts, locations and venues.

Type `bool`

can_send_media_messages

Optional. `True`, if the user is allowed to send audios, documents, photos, videos, video notes and voice notes, implies `can_send_messages`.

Type `bool`

can_send_polls

Optional. `True`, if the user is allowed to send polls, implies `can_send_messages`.

Type `bool`

can_send_other_messages

Optional. `True`, if the user is allowed to send animations, games, stickers and use inline bots, implies `can_send_media_messages`.

Type `bool`

can_add_web_page_previews

Optional. `True`, if the user is allowed to add web page previews to their messages, implies `can_send_media_messages`.

Type `bool`

can_change_info

Optional. `True`, if the user is allowed to change the chat title, photo and other settings. Ignored in public supergroups.

Type `bool`

can_invite_users

Optional. `True`, if the user is allowed to invite new users to the chat.

Type `bool`

can_pin_messages

Optional. True, if the user is allowed to pin messages. Ignored in public supergroups.

Type `bool`

Parameters

- **can_send_messages** (`bool`, optional) – True, if the user is allowed to send text messages, contacts, locations and venues.
- **can_send_media_messages** (`bool`, optional) – True, if the user is allowed to send audios, documents, photos, videos, video notes and voice notes, implies `can_send_messages`.
- **can_send_polls** (`bool`, optional) – True, if the user is allowed to send polls, implies `can_send_messages`.
- **can_send_other_messages** (`bool`, optional) – True, if the user is allowed to send animations, games, stickers and use inline bots, implies `can_send_media_messages`.
- **can_add_web_page_previews** (`bool`, optional) – True, if the user is allowed to add web page previews to their messages, implies `can_send_media_messages`.
- **can_change_info** (`bool`, optional) – True, if the user is allowed to change the chat title, photo and other settings. Ignored in public supergroups.
- **can_invite_users** (`bool`, optional) – True, if the user is allowed to invite new users to the chat.
- **can_pin_messages** (`bool`, optional) – True, if the user is allowed to pin messages. Ignored in public supergroups.

3.2.11 telegram.ChatPhoto

```
class telegram.ChatPhoto(small_file_id: str, small_file_unique_id: str, big_file_id: str,  
                        big_file_unique_id: str, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a chat photo.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `small_file_unique_id` and `big_file_unique_id` are equal.

small_file_id

File identifier of small (160x160) chat photo. This `file_id` can be used only for photo download and only for as long as the photo is not changed.

Type `str`

small_file_unique_id

Unique file identifier of small (160x160) chat photo, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

big_file_id

File identifier of big (640x640) chat photo. This `file_id` can be used only for photo download and only for as long as the photo is not changed.

Type `str`

big_file_unique_id

Unique file identifier of big (640x640) chat photo, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

Parameters

- **small_file_id** (`str`) – Unique file identifier of small (160x160) chat photo. This `file_id` can be used only for photo download and only for as long as the photo is not changed.
- **small_file_unique_id** (`str`) – Unique file identifier of small (160x160) chat photo, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **big_file_id** (`str`) – Unique file identifier of big (640x640) chat photo. This `file_id` can be used only for photo download and only for as long as the photo is not changed.
- **big_file_unique_id** (`str`) – Unique file identifier of big (640x640) chat photo, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

get_big_file (`timeout: int = None, **kwargs`) → `File`

Convenience wrapper over `telegram.Bot.get_file` for getting the big (640x640) chat photo

Parameters

- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

get_small_file (`timeout: int = None, **kwargs`) → `File`

Convenience wrapper over `telegram.Bot.get_file` for getting the small (160x160) chat photo

Parameters

- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.12 telegram.constants Module

Constants in the Telegram network.

The following constants were extracted from the [Telegram Bots FAQ](#) and [Telegram Bots API](#).

```
telegram.constants.MAX_MESSAGE_LENGTH
4096
```

Type `int`

```
telegram.constants.MAX_CAPTION_LENGTH
1024
```

Type `int`

`telegram.constants.SUPPORTED_WEBHOOK_PORTS`
[443, 80, 88, 8443]

Type List[int]

`telegram.constants.MAX_FILESIZE_DOWNLOAD`
In bytes (20MB)

Type int

`telegram.constants.MAX_FILESIZE_UPLOAD`
In bytes (50MB)

Type int

`telegram.constants.MAX_PHOTOSIZE_UPLOAD`
In bytes (10MB)

Type int

`telegram.constants.MAX_MESSAGES_PER_SECOND_PER_CHAT`
1. Telegram may allow short bursts that go over this limit, but eventually you'll begin receiving 429 errors.

Type int

`telegram.constants.MAX_MESSAGES_PER_SECOND`
30

Type int

`telegram.constants.MAX_MESSAGES_PER_MINUTE_PER_GROUP`
20

Type int

`telegram.constants.MAX_INLINE_QUERY_RESULTS`
50

Type int

The following constant have been found by experimentation:

`telegram.constants.MAX_MESSAGE_ENTITIES`
100 (Beyond this cap telegram will simply ignore further formatting styles)

Type int

`telegram.constants.ANONYMOUS_ADMIN_ID`
1087968824 (User id in groups for anonymous admin)

Type int

`telegram.constants.SERVICE_CHAT_ID`
777000 (Telegram service chat, that also acts as sender of channel posts forwarded to discussion groups)

Type int

The following constants are related to specific classes and are also available as attributes of those classes:

telegram.Chat:

`telegram.constants.CHAT_PRIVATE`
'private'

Type str

`telegram.constants.CHAT_GROUP`
'group'

Type str

`telegram.constants.CHAT_SUPERGROUP`
'supergroup'

Type str

telegram.constants.CHAT_CHANNEL
‘channel’

Type str

telegram.ChatAction:

telegram.constants.CHATACTION_FIND_LOCATION
‘find_location’

Type str

telegram.constants.CHATACTION_RECORD_AUDIO
‘record_audio’

Type str

telegram.constants.CHATACTION_RECORD_VIDEO
‘record_video’

Type str

telegram.constants.CHATACTION_RECORD_VIDEO_NOTE
‘record_video_note’

Type str

telegram.constants.CHATACTION_TYPING
‘typing’

Type str

telegram.constants.CHATACTION_UPLOAD_AUDIO
‘upload_audio’

Type str

telegram.constants.CHATACTION_UPLOAD_DOCUMENT
‘upload_document’

Type str

telegram.constants.CHATACTION_UPLOAD_PHOTO
‘upload_photo’

Type str

telegram.constants.CHATACTION_UPLOAD_VIDEO
‘upload_video’

Type str

telegram.constants.CHATACTION_UPLOAD_VIDEO_NOTE
‘upload_video_note’

Type str

telegram.ChatMember:

telegram.constants.CHATMEMBER_ADMINISTRATOR
‘administrator’

Type str

telegram.constants.CHATMEMBER_CREATOR
‘creator’

Type str

telegram.constants.CHATMEMBER_KICKED
‘kicked’

```
    Type str
telegram.constants.CHATMEMBER_LEFT
    'left'

    Type str
telegram.constants.CHATMEMBER_MEMBER
    'member'

    Type str
telegram.constants.CHATMEMBER_RESTRICTED
    'restricted'

    Type str
telegram.Dice:
telegram.constants.DICE_DICE
    „

    Type str
telegram.constants.DICE_DARTS
    „

    Type str
telegram.constants.DICE_BASKETBALL
    „

    Type str
telegram.constants.DICE_FOOTBALL
    „

    Type str
telegram.constants.DICE_SLOT_MACHINE
    „

    Type str
telegram.constants.DICE_ALL_EMOJI
    List of all supported base emoji.

    Type List[str]
telegram.MessageEntity:
telegram.constants.MESSAGEENTITY_MENTION
    'mention'

    Type str
telegram.constants.MESSAGEENTITY_HASHTAG
    'hashtag'

    Type str
telegram.constants.MESSAGEENTITY_CASHTAG
    'cashtag'

    Type str
telegram.constants.MESSAGEENTITY_PHONE_NUMBER
    'phone_number'

    Type str
telegram.constants.MESSAGEENTITY_BOT_COMMAND
    'bot_command'
```

Type str

telegram.constants.MESSAGEENTITY_URL
'url'

Type str

telegram.constants.MESSAGEENTITY_EMAIL
'email'

Type str

telegram.constants.MESSAGEENTITY_BOLD
'bold'

Type str

telegram.constants.MESSAGEENTITY_ITALIC
'italic'

Type str

telegram.constants.MESSAGEENTITY_CODE
'code'

Type str

telegram.constants.MESSAGEENTITY_PRE
'pre'

Type str

telegram.constants.MESSAGEENTITY_TEXT_LINK
'text_link'

Type str

telegram.constants.MESSAGEENTITY_TEXT_MENTION
'text_mention'

Type str

telegram.constants.MESSAGEENTITY_UNDERLINE
'underline'

Type str

telegram.constants.MESSAGEENTITY_STRIKETHROUGH
'strikethrough'

Type str

telegram.constants.MESSAGEENTITY_ALL_TYPES
List of all the types of message entity.

Type List[str]

telegram.ParseMode:

telegram.constants.PARSEMODE_MARKDOWN
'Markdown'

Type str

telegram.constants.PARSEMODE_MARKDOWN_V2
'MarkdownV2'

Type str

telegram.constants.PARSEMODE_HTML
'HTML'

Type str

```
telegram.Poll:
telegram.constants.POLL_REGULAR
    'regular'
    Type str
telegram.constants.POLL_QUIZ
    'quiz'
    Type str
telegram.constants.MAX_POLL_QUESTION_LENGTH
    300
    Type int
telegram.constants.MAX_POLL_OPTION_LENGTH
    100
    Type int
telegram.files.MaskPosition:
telegram.constants.STICKER_FOREHEAD
    'forehead'
    Type str
telegram.constants.STICKER_EYES
    'eyes'
    Type str
telegram.constants.STICKER_MOUTH
    'mouth'
    Type str
telegram.constants.STICKER_CHIN
    'chin'
    Type str
```

3.2.13 telegram.Contact

```
class telegram.Contact (phone_number: str, first_name: str, last_name: str = None, user_id: int
                        = None, vcard: str = None, **kwargs)
    Bases: telegram.base.TelegramObject
```

This object represents a phone contact.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `phone_number` is equal.

```
phone_number
    Contact's phone number.
    Type str
first_name
    Contact's first name.
    Type str
last_name
    Optional. Contact's last name.
    Type str
```

user_id

Optional. Contact's user identifier in Telegram.

Type `int`

vcard

Optional. Additional data about the contact in the form of a vCard.

Type `str`

Parameters

- **phone_number** (`str`) – Contact's phone number.
- **first_name** (`str`) – Contact's first name.
- **last_name** (`str`, optional) – Contact's last name.
- **user_id** (`int`, optional) – Contact's user identifier in Telegram.
- **vcard** (`str`, optional) – Additional data about the contact in the form of a vCard.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

3.2.14 telegram.Dice

class `telegram.Dice` (*value: int, emoji: str, **kwargs*)

Bases: `telegram.base.TelegramObject`

This object represents an animated emoji with a random value for currently supported base emoji. (The singular form of “dice” is “die”. However, PTB mimics the Telegram API, which uses the term “dice”.)

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *value* and *emoji* are equal.

Note: If *emoji* is “”, a value of 6 currently represents a bullseye, while a value of 1 indicates that the dartboard was missed. However, this behaviour is undocumented and might be changed by Telegram.

If *emoji* is “”, a value of 4 or 5 currently score a basket, while a value of 1 to 3 indicates that the basket was missed. However, this behaviour is undocumented and might be changed by Telegram.

If *emoji* is “”, a value of 3 to 5 currently scores a goal, while a value of 1 to 3 indicates that the goal was missed. However, this behaviour is undocumented and might be changed by Telegram.

If *emoji* is “”, each value corresponds to a unique combination of symbols, which can be found at our [wiki](#). However, this behaviour is undocumented and might be changed by Telegram.

value

Value of the dice.

Type `int`

emoji

Emoji on which the dice throw animation is based.

Type `str`

Parameters

- **value** (`int`) – Value of the dice. 1-6 for dice and darts, 1-5 for basketball and football/soccer ball, 1-64 for slot machine.
- **emoji** (`str`) – Emoji on which the dice throw animation is based.

ALL_EMOJI = `['', '', '', '', '']`
`telegram.constants.DICE_ALL_EMOJI`

```
BASKETBALL = ''
    telegram.constants.DICE_BASKETBALL
DARTS = ''
    telegram.constants.DICE_DARTS
DICE = ''
    telegram.constants.DICE_DICE
FOOTBALL = ''
    telegram.constants.DICE_FOOTBALL
SLOT_MACHINE = ''
    telegram.constants.DICE_SLOT_MACHINE
```

3.2.15 telegram.Document

```
class telegram.Document (file_id: str, file_unique_id: str, thumb: tele-
    gram.files.photosize.PhotoSize = None, file_name: str = None,
    mime_type: str = None, file_size: int = None, bot: Bot = None,
    **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents a general file (as opposed to photos, voice messages and audio files).

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

file_id

File identifier.

Type str

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type str

thumb

Optional. Document thumbnail.

Type telegram.PhotoSize

file_name

Original filename.

Type str

mime_type

Optional. MIME type of the file.

Type str

file_size

Optional. File size.

Type int

bot

Optional. The Bot to use for instance methods.

Type telegram.Bot

Parameters

- **file_id** (str) – Identifier for this file, which can be used to download or reuse the file.

- **file_unique_id** (*str*) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **thumb** (*telegram.PhotoSize*, optional) – Document thumbnail as defined by sender.
- **file_name** (*str*, optional) – Original filename as defined by sender.
- **mime_type** (*str*, optional) – MIME type of the file as defined by sender.
- **file_size** (*int*, optional) – File size.
- **bot** (*telegram.Bot*, optional) – The Bot to use for instance methods.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

get_file (*timeout: int = None, api_kwargs: Dict[str, Any] = None*) → *File*
Convenience wrapper over *telegram.Bot.get_file*

Parameters

- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (*dict*, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns *telegram.File*

Raises *telegram.TelegramError*

3.2.16 telegram.error module

This module contains an object that represents Telegram errors.

exception *telegram.error.BadRequest* (*message: str*)
Bases: *telegram.error.NetworkError*

exception *telegram.error.ChatMigrated* (*new_chat_id: int*)
Bases: *telegram.error.TelegramError*

Parameters *new_chat_id* (*int*) – The new chat id of the group.

exception *telegram.error.Conflict* (*message: str*)
Bases: *telegram.error.TelegramError*

Raised when a long poll or webhook conflicts with another one.

Parameters *msg* (*str*) – The message from telegrams server.

exception *telegram.error.InvalidToken*
Bases: *telegram.error.TelegramError*

exception *telegram.error.NetworkError* (*message: str*)
Bases: *telegram.error.TelegramError*

exception *telegram.error.RetryAfter* (*retry_after: int*)
Bases: *telegram.error.TelegramError*

Parameters *retry_after* (*int*) – Time in seconds, after which the bot can retry the request.

exception *telegram.error.TelegramError* (*message: str*)
Bases: *Exception*

exception *telegram.error.TimedOut*
Bases: *telegram.error.NetworkError*

exception `telegram.error.Unauthorized` (*message: str*)
Bases: `telegram.error.TelegramError`

3.2.17 telegram.File

class `telegram.File` (*file_id: str, file_unique_id: str, bot: Bot = None, file_size: int = None, file_path: str = None, **kwargs*)
Bases: `telegram.base.TelegramObject`

This object represents a file ready to be downloaded. The file can be downloaded with `download`. It is guaranteed that the link will be valid for at least 1 hour. When the link expires, a new one can be requested by calling `telegram.Bot.get_file()`.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

Note: Maximum file size to download is 20 MB.

file_id
Identifier for this file.

Type `str`

file_unique_id
Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

file_size
Optional. File size.

Type `str`

file_path
Optional. File path. Use `download` to get the file.

Type `str`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **file_size** (`int`, optional) – Optional. File size, if known.
- **file_path** (`str`, optional) – File path. Use `download` to get the file.
- **bot** (`telegram.Bot`, optional) – Bot to use with shortcut method.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

Note: If you obtain an instance of this class from `telegram.PassportFile.get_file`, then it will automatically be decrypted as it downloads when you call `download()`.

download (*custom_path: str = None, out: IO = None, timeout: int = None*) → `Union[str, IO]`
Download this file. By default, the file is saved in the current working directory with its original filename as reported by Telegram. If the file has no filename, it the file ID will be used as filename. If

a `custom_path` is supplied, it will be saved to that path instead. If `out` is defined, the file contents will be saved to that object using the `out.write` method.

Note:

- `custom_path` and `out` are mutually exclusive.
 - If neither `custom_path` nor `out` is provided and `file_path` is the path of a local file (which is the case when a Bot API Server is running in local mode), this method will just return the path.
-

Parameters

- **`custom_path`** (`str`, optional) – Custom path.
- **`out`** (`io.BufferedWriter`, optional) – A file-like object. Must be opened for writing in binary mode, if applicable.
- **`timeout`** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

Returns The same object as `out` if specified. Otherwise, returns the filename downloaded to or the file path of the local file.

Return type `str` | `io.BufferedWriter`

Raises `ValueError` – If both `custom_path` and `out` are passed.

`download_as_bytearray` (*buf*: `bytearray` = `None`) → `bytes`

Download this file and return it as a bytearray.

Parameters **`buf`** (`bytearray`, optional) – Extend the given bytearray with the downloaded data.

Returns The same object as `buf` if it was specified. Otherwise a newly allocated bytearray.

Return type `bytearray`

3.2.18 telegram.ForceReply

class `telegram.ForceReply` (*force_reply*: `bool` = `True`, *selective*: `bool` = `False`, ***kwargs*)

Bases: `telegram.replymarkup.ReplyMarkup`

Upon receiving a message with this object, Telegram clients will display a reply interface to the user (act as if the user has selected the bot's message and tapped 'Reply'). This can be extremely useful if you want to create user-friendly step-by-step interfaces without having to sacrifice privacy mode.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *selective* is equal.

force_reply

Shows reply interface to the user, as if they manually selected the bot's message and tapped 'Reply'.

Type `True`

selective

Optional. Force reply from specific users only.

Type `bool`

Parameters

- **`selective`** (`bool`, optional) – Use this parameter if you want to force reply from specific users only. Targets:

- 1) Users that are @mentioned in the text of the Message object.
 - 2) If the bot's message is a reply (has `reply_to_message_id`), sender of the original message.
- ****kwargs** (dict) – Arbitrary keyword arguments.

3.2.19 telegram.InlineKeyboardButton

```
class telegram.InlineKeyboardButton(text: str, url: str = None, callback_data: str = None, switch_inline_query: str = None, switch_inline_query_current_chat: str = None, callback_game: CallbackGame = None, pay: bool = None, login_url: LoginUrl = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents one button of an inline keyboard.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `text`, `url`, `login_url`, `callback_data`, `switch_inline_query`, `switch_inline_query_current_chat`, `callback_game` and `pay` are equal.

Note: You must use exactly one of the optional fields. Mind that `callback_game` is not working as expected. Putting a game short name in it might, but is not guaranteed to work.

text

Label text on the button.

Type `str`

url

Optional. HTTP or `tg://` url to be opened when button is pressed.

Type `str`

login_url

authorize the user. Can be used as a replacement for the Telegram Login Widget.

Type `telegram.LoginUrl`

callback_data

Optional. Data to be sent in a callback query to the bot when button is pressed, UTF-8 1-64 bytes.

Type `str`

switch_inline_query

Optional. Will prompt the user to select one of their chats, open that chat and insert the bot's username and the specified inline query in the input field. Can be empty, in which case just the bot's username will be inserted.

Type `str`

switch_inline_query_current_chat

Optional. Will insert the bot's username and the specified inline query in the current chat's input field. Can be empty, in which case just the bot's username will be inserted.

Type `str`

callback_game

Optional. Description of the game that will be launched when the user presses the button.

Type `telegram.CallbackGame`

pay

Optional. Specify True, to send a Pay button.

Type `bool`

Parameters

- **text** (`str`) – Label text on the button.
- **url** (`str`) – HTTP or `tg://` url to be opened when button is pressed.
- **login_url** (`telegram.LoginUrl`, optional) – authorize the user. Can be used as a replacement for the Telegram Login Widget.
- **callback_data** (`str`, optional) – Data to be sent in a callback query to the bot when button is pressed, UTF-8 1-64 bytes.
- **switch_inline_query** (`str`, optional) – If set, pressing the button will prompt the user to select one of their chats, open that chat and insert the bot's username and the specified inline query in the input field. Can be empty, in which case just the bot's username will be inserted. This offers an easy way for users to start using your bot in inline mode when they are currently in a private chat with it. Especially useful when combined with `switch_pm*` actions - in this case the user will be automatically returned to the chat they switched from, skipping the chat selection screen.
- **switch_inline_query_current_chat** (`str`, optional) – If set, pressing the button will insert the bot's username and the specified inline query in the current chat's input field. Can be empty, in which case only the bot's username will be inserted. This offers a quick way for the user to open your bot in inline mode in the same chat - good for selecting something from multiple options.
- **callback_game** (`telegram.CallbackGame`, optional) – Description of the game that will be launched when the user presses the button. This type of button must always be the `first` button in the first row.
- **pay** (`bool`, optional) – Specify `True`, to send a Pay button. This type of button must always be the `first` button in the first row.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

3.2.20 telegram.InlineKeyboardMarkup

```
class telegram.InlineKeyboardMarkup (inline_keyboard: List[List[telegram.inline.inlinekeyboardbutton.InlineKeyboardButton],  
                                     **kwargs)
```

Bases: `telegram.replymarkup.ReplyMarkup`

This object represents an inline keyboard that appears right next to the message it belongs to.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their the size of `inline_keyboard` and all the buttons are equal.

inline_keyboard

List of button rows, each represented by a list of `InlineKeyboardButton` objects.

Type `List[List[telegram.InlineKeyboardButton]]`

Parameters

- **inline_keyboard** (`List[List[telegram.InlineKeyboardButton]]`) – List of button rows, each represented by a list of `InlineKeyboardButton` objects.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

```
classmethod from_button (button: telegram.inline.inlinekeyboardbutton.InlineKeyboardButton,  
                        **kwargs) → telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup
```

Shortcut for:

```
InlineKeyboardMarkup([[button]], **kwargs)
```

Return an `InlineKeyboardMarkup` from a single `InlineKeyboardButton`

Parameters

- **button** (`telegram.InlineKeyboardButton`) – The button to use in the markup
- ****kwargs** (dict) – Arbitrary keyword arguments.

classmethod from_column (*button_column: List[telegram.inline.inlinekeyboardbutton.InlineKeyboardButton], **kwargs*) → `telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup`

Shortcut for:

```
InlineKeyboardMarkup([[button] for button in button_column], **kwargs)
```

Return an `InlineKeyboardMarkup` from a single column of `InlineKeyboardButtons`

Parameters

- **button_column** (List[`telegram.InlineKeyboardButton`]) – The button to use in the markup
- ****kwargs** (dict) – Arbitrary keyword arguments.

classmethod from_row (*button_row: List[telegram.inline.inlinekeyboardbutton.InlineKeyboardButton], **kwargs*) → `telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup`

Shortcut for:

```
InlineKeyboardMarkup([button_row], **kwargs)
```

Return an `InlineKeyboardMarkup` from a single row of `InlineKeyboardButtons`

Parameters

- **button_row** (List[`telegram.InlineKeyboardButton`]) – The button to use in the markup
- ****kwargs** (dict) – Arbitrary keyword arguments.

3.2.21 telegram.InputFile

class `telegram.InputFile` (*obj: IO, filename: str = None, attach: bool = None*)

Bases: `object`

This object represents a Telegram `InputFile`.

input_file_content

The binary content of the file to send.

Type `bytes`

filename

Optional. Filename for the file to be sent.

Type `str`

attach

Optional. Attach id for sending multiple files.

Type `str`

Parameters

- **obj** (File handler) – An open file descriptor.
- **filename** (`str`, optional) – Filename for this `InputFile`.

- **attach** (bool, optional) – Whether this should be send as one file or is part of a collection of files.

Raises `TelegramError`

static is_image (*stream: bytes*) → Optional[str]

Check if the content file is an image by analyzing its headers.

Parameters **stream** (bytes) – A byte stream representing the content of a file.

Returns The mime-type of an image, if the input is an image, or None else.

Return type str|None

3.2.22 telegram.InputMedia

class `telegram.InputMedia`

Bases: `telegram.base.TelegramObject`

Base class for Telegram InputMedia Objects.

See `telegram.InputMediaAnimation`, `telegram.InputMediaAudio`, `telegram.InputMediaDocument`, `telegram.InputMediaPhoto` and `telegram.InputMediaVideo` for detailed use.

3.2.23 telegram.InputMediaAnimation

class `telegram.InputMediaAnimation` (*media: Union[str, IO, InputFile, pathlib.Path, telegram.files.animation.Animation]*, *thumb: Union[str, IO, InputFile, pathlib.Path] = None*, *caption: str = None*, *parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>*, *width: int = None*, *height: int = None*, *duration: int = None*, *caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None*)

Bases: `telegram.files.inputmedia.InputMedia`

Represents an animation file (GIF or H.264/MPEG-4 AVC video without sound) to be sent.

type

`animation.`

Type str

media

Animation to send.

Type str|`telegram.InputFile`

caption

Optional. Caption of the document to be sent.

Type str

parse_mode

Optional. The parse mode to use for text formatting.

Type str

caption_entities

Optional. List of special entities that appear in the caption.

Type List[*telegram.MessageEntity*]

thumb

Optional. Thumbnail of the file to send.

Type *telegram.InputFile*

width

Optional. Animation width.

Type int

height

Optional. Animation height.

Type int

duration

Optional. Animation duration.

Type int

Parameters

- **media** (str | filelike object | pathlib.Path | *telegram.Animation*) – File to send. Pass a file_id to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet. Lastly you can pass an existing *telegram.Animation* object to send.
- **thumb** (filelike object | pathlib.Path, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **caption** (str, optional) – Caption of the animation to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (str, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in *telegram.ParseMode* for the available modes.
- **caption_entities** (List[*telegram.MessageEntity*], optional) – List of special entities that appear in the caption, which can be specified instead of parse_mode.
- **width** (int, optional) – Animation width.
- **height** (int, optional) – Animation height.
- **duration** (int, optional) – Animation duration.

Note: When using a *telegram.Animation* for the *media* attribute. It will take the width, height and duration from that video, unless otherwise specified with the optional arguments.

3.2.24 telegram.InputMediaAudio

```
class telegram.InputMediaAudio(media: Union[str, IO, InputFile, pathlib.Path, telegram.files.audio.Audio], thumb: Union[str, IO, InputFile, pathlib.Path] = None, caption: str = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, duration: int = None, performer: str = None, title: str = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None)
```

Bases: telegram.files.inputmedia.InputMedia

Represents an audio file to be treated as music to be sent.

type

audio.

Type str

media

Audio file to send.

Type str | *telegram.InputFile*

caption

Optional. Caption of the document to be sent.

Type str

parse_mode

Optional. The parse mode to use for text formatting.

Type str

caption_entities

Optional. List of special entities that appear in the caption.

Type List[*telegram.MessageEntity*]

duration

Duration of the audio in seconds.

Type int

performer

Optional. Performer of the audio as defined by sender or by audio tags.

Type str

title

Optional. Title of the audio as defined by sender or by audio tags.

Type str

thumb

Optional. Thumbnail of the file to send.

Type *telegram.InputFile*

Parameters

- **media** (str | *filelike object* | *pathlib.Path* | *telegram.Audio*) – File to send. Pass a *file_id* to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet. Lastly you can pass an existing *telegram.Audio* object to send.
- **caption** (str, optional) – Caption of the audio to be sent, 0-1024 characters after entities parsing.

- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **duration** (`int`) – Duration of the audio in seconds as defined by sender.
- **performer** (`str`, optional) – Performer of the audio as defined by sender or by audio tags.
- **title** (`str`, optional) – Title of the audio as defined by sender or by audio tags.
- **thumb** (*filelike object* | `pathlib.Path`, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.

Note: When using a `telegram.Audio` for the `media` attribute. It will take the duration, performer and title from that video, unless otherwise specified with the optional arguments.

3.2.25 telegram.InputMediaDocument

```
class telegram.InputMediaDocument (media: Union[str, IO, InputFile, pathlib.Path,
                                             telegram.files.document.Document], thumb:
                                     Union[str, IO, InputFile, pathlib.Path] =
                                     None, caption: str = None, parse_mode:
                                     Union[str, telegram.utils.helpers.DefaultValue]
                                     = <telegram.utils.helpers.DefaultValue object>,
                                     disable_content_type_detection:
                                     bool = None, caption_entities:
                                     Union[List[telegram.messageentity.MessageEntity],
                                     Tuple[telegram.messageentity.MessageEntity, ...]]
                                     = None)
```

Bases: `telegram.files.inputmedia.InputMedia`

Represents a general file to be sent.

type

`document.`

Type `str`

media

File to send.

Type `str` | `telegram.InputFile`

caption

Optional. Caption of the document to be sent.

Type `str`

parse_mode

Optional. The parse mode to use for text formatting.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption.

Type `List[telegram.MessageEntity]`

thumb

Optional. Thumbnail of the file to send.

Type `telegram.InputFile`

disable_content_type_detection

Optional. Disables automatic server-side content type detection for files uploaded using multipart/form-data. Always true, if the document is sent as part of an album.

Type `bool`

Parameters

- **media** (`str` | *filelike object* | `pathlib.Path` | `telegram.Document`) – File to send. Pass a `file_id` to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet. Lastly you can pass an existing `telegram.Document` object to send.
- **caption** (`str`, optional) – Caption of the document to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **thumb** (*filelike object* | `pathlib.Path`, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.
- **disable_content_type_detection** (`bool`, optional) – Disables automatic server-side content type detection for files uploaded using multipart/form-data. Always true, if the document is sent as part of an album.

3.2.26 telegram.InputMediaPhoto

```
class telegram.InputMediaPhoto (media: Union[str, IO, InputFile, pathlib.Path, telegram.files.photosize.PhotoSize], caption: str = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None)
```

Bases: `telegram.files.inputmedia.InputMedia`

Represents a photo to be sent.

type

`photo.`

Type `str`

media

Photo to send.

Type `str` | `telegram.InputFile`

caption

Optional. Caption of the document to be sent.

Type `str`

parse_mode

Optional. The parse mode to use for text formatting.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption.

Type `List[telegram.MessageEntity]`

Parameters

- **media** (`str` | *filelike object* | `pathlib.Path` | `telegram.PhotoSize`) – File to send. Pass a `file_id` to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet. Lastly you can pass an existing `telegram.PhotoSize` object to send.
- **caption** (`str`, optional) – Caption of the photo to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

3.2.27 telegram.InputMediaVideo

```
class telegram.InputMediaVideo(media: Union[str, IO, InputFile, pathlib.Path, telegram.files.video.Video], caption: str = None, width: int = None, height: int = None, duration: int = None, supports_streaming: bool = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, thumb: Union[str, IO, InputFile, pathlib.Path] = None, caption_entities: Union[List[telegram.messageentity.MessageEntity], Tuple[telegram.messageentity.MessageEntity, ...]] = None)
```

Bases: `telegram.files.inputmedia.InputMedia`

Represents a video to be sent.

type

`video.`

Type `str`

media

Video file to send.

Type `str` | `telegram.InputFile`

caption

Optional. Caption of the document to be sent.

Type `str`

parse_mode

Optional. The parse mode to use for text formatting.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption.

Type List[*telegram.MessageEntity*]

width
Optional. Video width.
Type int

height
Optional. Video height.
Type int

duration
Optional. Video duration.
Type int

supports_streaming
Optional. Pass True, if the uploaded video is suitable for streaming.
Type bool

thumb
Optional. Thumbnail of the file to send.
Type *telegram.InputFile*

Parameters

- **media** (str | *filelike object* | `pathlib.Path` | *telegram.Video*) – File to send. Pass a `file_id` to send a file that exists on the Telegram servers (recommended), pass an HTTP URL for Telegram to get a file from the Internet. Lastly you can pass an existing *telegram.Video* object to send.
- **caption** (str, optional) – Caption of the video to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (str, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in *telegram.ParseMode* for the available modes.
- **caption_entities** (List[*telegram.MessageEntity*], optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **width** (int, optional) – Video width.
- **height** (int, optional) – Video height.
- **duration** (int, optional) – Video duration.
- **supports_streaming** (bool, optional) – Pass True, if the uploaded video is suitable for streaming.
- **thumb** (*filelike object* | `pathlib.Path`, optional) – Thumbnail of the file sent; can be ignored if thumbnail generation for the file is supported server-side. The thumbnail should be in JPEG format and less than 200 kB in size. A thumbnail's width and height should not exceed 320. Ignored if the file is not uploaded using multipart/form-data. Thumbnails can't be reused and can be only uploaded as a new file.

Note:

- When using a *telegram.Video* for the *media* attribute. It will take the width, height and duration from that video, unless otherwise specified with the optional arguments.
 - `thumb` will be ignored for small video files, for which Telegram can easily generate thumb nails. However, this behaviour is undocumented and might be changed by Telegram.
-

3.2.28 telegram.KeyboardButton

```
class telegram.KeyboardButton(text: str, request_contact: bool = None, request_location:  
                               bool = None, request_poll: bool = None, **kwargs)  
    Bases: telegram.base.TelegramObject
```

This object represents one button of the reply keyboard. For simple text buttons String can be used instead of this object to specify text of the button.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *text*, *request_contact*, *request_location* and *request_poll* are equal.

Note: Optional fields are mutually exclusive.

text

Text of the button.

Type `str`

request_contact

Optional. The user's phone number will be sent.

Type `bool`

request_location

Optional. The user's current location will be sent.

Type `bool`

request_poll

Optional. If the user should create a poll.

Type `KeyboardButtonPollType`

Parameters

- **text** (`str`) – Text of the button. If none of the optional fields are used, it will be sent to the bot as a message when the button is pressed.
- **request_contact** (`bool`, optional) – If `True`, the user's phone number will be sent as a contact when the button is pressed. Available in private chats only.
- **request_location** (`bool`, optional) – If `True`, the user's current location will be sent when the button is pressed. Available in private chats only.
- **request_poll** (`KeyboardButtonPollType`, optional) – If specified, the user will be asked to create a poll and send it to the bot when the button is pressed. Available in private chats only.

Note: *request_contact* and *request_location* options will only work in Telegram versions released after 9 April, 2016. Older clients will ignore them.

request_poll option will only work in Telegram versions released after 23 January, 2020. Older clients will receive unsupported message.

3.2.29 telegram.KeyboardButtonPollType

```
class telegram.KeyboardButtonPollType(type: str = None, **kwargs)  
    Bases: telegram.base.TelegramObject
```

This object represents type of a poll, which is allowed to be created and sent when the corresponding button is pressed.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `type` is equal.

type

Optional. If `telegram.Poll.QUIZ` is passed, the user will be allowed to create only polls in the quiz mode. If `telegram.Poll.REGULAR` is passed, only regular polls will be allowed. Otherwise, the user will be allowed to create a poll of any type.

Type `str`

3.2.30 telegram.Location

```
class telegram.Location(longitude: float, latitude: float, horizontal_accuracy: float = None,
                        live_period: int = None, heading: int = None, proximity_alert_radius:
                        int = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a point on the map.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `longitude` and `latitude` are equal.

longitude

Longitude as defined by sender.

Type `float`

latitude

Latitude as defined by sender.

Type `float`

horizontal_accuracy

Optional. The radius of uncertainty for the location, measured in meters.

Type `float`

live_period

Optional. Time relative to the message sending date, during which the location can be updated, in seconds. For active live locations only.

Type `int`

heading

Optional. The direction in which user is moving, in degrees. For active live locations only.

Type `int`

proximity_alert_radius

Optional. Maximum distance for proximity alerts about approaching another chat member, in meters. For sent live locations only.

Type `int`

Parameters

- **longitude** (`float`) – Longitude as defined by sender.
- **latitude** (`float`) – Latitude as defined by sender.
- **horizontal_accuracy** (`float`, optional) – The radius of uncertainty for the location, measured in meters; 0-1500.
- **live_period** (`int`, optional) – Time relative to the message sending date, during which the location can be updated, in seconds. For active live locations only.
- **heading** (`int`, optional) – The direction in which user is moving, in degrees; 1-360. For active live locations only.

- **proximity_alert_radius** (int, optional) – Maximum distance for proximity alerts about approaching another chat member, in meters. For sent live locations only.
- ****kwargs** (dict) – Arbitrary keyword arguments.

3.2.31 telegram.LoginUrl

class telegram.LoginUrl (*url: str, forward_text: bool = None, bot_username: str = None, request_write_access: bool = None, **kwargs*)
Bases: telegram.base.TelegramObject

This object represents a parameter of the inline keyboard button used to automatically authorize a user. Serves as a great replacement for the Telegram Login Widget when the user is coming from Telegram. All the user needs to do is tap/click a button and confirm that they want to log in. Telegram apps support these buttons as of version 5.7.

Sample bot: [@discussbot](#)

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *url* is equal.

url

An HTTP URL to be opened with user authorization data.

Type `str`

forward_text

Optional. New text of the button in forwarded messages.

Type `str`

bot_username

Optional. Username of a bot, which will be used for user authorization.

Type `str`

request_write_access

Optional. Pass `True` to request the permission for your bot to send messages to the user.

Type `bool`

Parameters

- **url** (`str`) – An HTTP URL to be opened with user authorization data added to the query string when the button is pressed. If the user refuses to provide authorization data, the original URL without information about the user will be opened. The data added is the same as described in [Receiving authorization data](#)
- **forward_text** (`str`, optional) – New text of the button in forwarded messages.
- **bot_username** (`str`, optional) – Username of a bot, which will be used for user authorization. See [Setting up a bot](#) for more details. If not specified, the current bot's username will be assumed. The url's domain must be the same as the domain linked with the bot. See [Linking your domain to the bot](#) for more details.
- **request_write_access** (`bool`, optional) – Pass `True` to request the permission for your bot to send messages to the user.

Note: You must always check the hash of the received data to verify the authentication and the integrity of the data as described in [Checking authorization](#)

3.2.32 telegram.Message

```
class telegram.Message (message_id: int, date: datetime.datetime, chat: telegram.chat.Chat,
    from_user: telegram.user.User = None, forward_from: telegram.user.User = None, forward_from_chat: telegram.chat.Chat = None, forward_from_message_id: int = None, forward_date: datetime.datetime = None, reply_to_message: Message = None, edit_date: datetime.datetime = None, text: str = None, entities: List[telegram.messageentity.MessageEntity] = None, caption_entities: List[telegram.messageentity.MessageEntity] = None, audio: telegram.files.audio.Audio = None, document: telegram.files.document.Document = None, game: telegram.games.game.Game = None, photo: List[telegram.files.photosize.PhotoSize] = None, sticker: telegram.files.sticker.Sticker = None, video: telegram.files.video.Video = None, voice: telegram.files.voice.Voice = None, video_note: telegram.files.videonote.VideoNote = None, new_chat_members: List[telegram.user.User] = None, caption: str = None, contact: telegram.files.contact.Contact = None, location: telegram.files.location.Location = None, venue: telegram.files.venue.Venue = None, left_chat_member: telegram.user.User = None, new_chat_title: str = None, new_chat_photo: List[telegram.files.photosize.PhotoSize] = None, delete_chat_photo: bool = False, group_chat_created: bool = False, supergroup_chat_created: bool = False, channel_chat_created: bool = False, migrate_to_chat_id: int = None, migrate_from_chat_id: int = None, pinned_message: Message = None, invoice: telegram.payment.invoice.Invoice = None, successful_payment: telegram.payment.successfulpayment.SuccessfulPayment = None, forward_signature: str = None, author_signature: str = None, media_group_id: str = None, connected_website: str = None, animation: telegram.files.animation.Animation = None, passport_data: telegram.passport.passportdata.PassportData = None, poll: telegram.poll.Poll = None, forward_sender_name: str = None, reply_markup: telegram.inline.inlinekeyboardmarkup.InlineKeyboardMarkup = None, bot: Bot = None, dice: telegram.dice.Dice = None, via_bot: telegram.user.User = None, proximity_alert_triggered: telegram.proximityalertrIGGERED.ProximityAlertTriggered = None, sender_chat: telegram.chat.Chat = None, **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents a message.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `message_id` and `chat` are equal.

Note:

- In Python `from` is a reserved word, use `from_user` instead.
-

`message_id`

Unique message identifier inside this chat.

Type `int`

`from_user`

Optional. Sender.

Type `telegram.User`

sender_chat

Optional. Sender of the message, sent on behalf of a chat. The channel itself for channel messages. The supergroup itself for messages from anonymous group administrators. The linked channel for messages automatically forwarded to the discussion group.

Type `telegram.Chat`

date

Date the message was sent.

Type `datetime.datetime`

chat

Conversation the message belongs to.

Type `telegram.Chat`

forward_from

Optional. Sender of the original message.

Type `telegram.User`

forward_from_chat

Optional. For messages forwarded from channels or from anonymous administrators, information about the original sender chat.

Type `telegram.Chat`

forward_from_message_id

Optional. Identifier of the original message in the channel.

Type `int`

forward_date

Optional. Date the original message was sent.

Type `datetime.datetime`

reply_to_message

Optional. For replies, the original message. Note that the Message object in this field will not contain further `reply_to_message` fields even if it itself is a reply.

Type `telegram.Message`

edit_date

Optional. Date the message was last edited.

Type `datetime.datetime`

media_group_id

Optional. The unique identifier of a media message group this message belongs to.

Type `str`

text

Optional. The actual UTF-8 text of the message.

Type `str`

entities

Optional. Special entities like usernames, URLs, bot commands, etc. that appear in the text. See `Message.parse_entity` and `parse_entities` methods for how to use properly.

Type `List[telegram.MessageEntity]`

caption_entities

Optional. Special entities like usernames, URLs, bot commands, etc. that appear in the caption. See `Message.parse_caption_entity` and `parse_caption_entities` methods for how to use properly.

Type `List[telegram.MessageEntity]`

audio

Optional. Information about the file.

Type `telegram.Audio`

document

Optional. Information about the file.

Type `telegram.Document`

animation

For backward compatibility, when this field is set, the document field will also be set.

Type `telegram.Animation`

game

Optional. Information about the game.

Type `telegram.Game`

photo

Optional. Available sizes of the photo.

Type `List[telegram.PhotoSize]`

sticker

Optional. Information about the sticker.

Type `telegram.Sticker`

video

Optional. Information about the video.

Type `telegram.Video`

voice

Optional. Information about the file.

Type `telegram.Voice`

video_note

Optional. Information about the video message.

Type `telegram.VideoNote`

new_chat_members

Optional. Information about new members to the chat. (the bot itself may be one of these members).

Type `List[telegram.User]`

caption

Optional. Caption for the document, photo or video, 0-1024 characters.

Type `str`

contact

Optional. Information about the contact.

Type `telegram.Contact`

location

Optional. Information about the location.

Type `telegram.Location`

venue

Optional. Information about the venue.

Type `telegram.Venue`

left_chat_member

Optional. Information about the user that left the group. (this member may be the bot itself).

Type *telegram.User*

new_chat_title

Optional. A chat title was changed to this value.

Type *str*

new_chat_photo

Optional. A chat photo was changed to this value.

Type *List[telegram.PhotoSize]*

delete_chat_photo

Optional. The chat photo was deleted.

Type *bool*

group_chat_created

Optional. The group has been created.

Type *bool*

supergroup_chat_created

Optional. The supergroup has been created.

Type *bool*

channel_chat_created

Optional. The channel has been created.

Type *bool*

migrate_to_chat_id

Optional. The group has been migrated to a supergroup with the specified identifier.

Type *int*

migrate_from_chat_id

Optional. The supergroup has been migrated from a group with the specified identifier.

Type *int*

pinned_message

Optional. Specified message was pinned.

Type *telegram.message*

invoice

Optional. Information about the invoice.

Type *telegram.Invoice*

successful_payment

Optional. Information about the payment.

Type *telegram.SuccessfulPayment*

connected_website

Optional. The domain name of the website on which the user has logged in.

Type *str*

forward_signature

Optional. Signature of the post author for messages forwarded from channels.

Type *str*

forward_sender_name

Optional. Sender's name for messages forwarded from users who disallow adding a link to their account in forwarded messages.

Type *str*

author_signature

Optional. Signature of the post author for messages in channels, or the custom title of an anonymous group administrator.

Type `str`

passport_data

Optional. Telegram Passport data.

Type `telegram.PassportData`

poll

Optional. Message is a native poll, information about the poll.

Type `telegram.Poll`

dice

Optional. Message is a dice.

Type `telegram.Dice`

via_bot

Optional. Bot through which the message was sent.

Type `telegram.User`

proximity_alert_triggered

Optional. Service message. A user in the chat triggered another user's proximity alert while sharing Live Location.

Type `telegram.ProximityAlertTriggered`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **message_id** (`int`) – Unique message identifier inside this chat.
- **from_user** (`telegram.User`, optional) – Sender, empty for messages sent to channels.
- **sender_chat** (`telegram.Chat`, optional) – Sender of the message, sent on behalf of a chat. The channel itself for channel messages. The supergroup itself for messages from anonymous group administrators. The linked channel for messages automatically forwarded to the discussion group.
- **date** (`datetime.datetime`) – Date the message was sent in Unix time. Converted to `datetime.datetime`.
- **chat** (`telegram.Chat`) – Conversation the message belongs to.
- **forward_from** (`telegram.User`, optional) – For forwarded messages, sender of the original message.
- **forward_from_chat** (`telegram.Chat`, optional) – For messages forwarded from channels or from anonymous administrators, information about the original sender chat.
- **forward_from_message_id** (`int`, optional) – For forwarded channel posts, identifier of the original message in the channel.

- **forward_sender_name** (`str`, optional) – Sender’s name for messages forwarded from users who disallow adding a link to their account in forwarded messages.
- **forward_date** (`datetime.datetime`, optional) – For forwarded messages, date the original message was sent in Unix time. Converted to `datetime.datetime`.
- **reply_to_message** (`telegram.Message`, optional) – For replies, the original message.
- **edit_date** (`datetime.datetime`, optional) – Date the message was last edited in Unix time. Converted to `datetime.datetime`.
- **media_group_id** (`str`, optional) – The unique identifier of a media message group this message belongs to.
- **text** (`str`, optional) – For text messages, the actual UTF-8 text of the message, 0-4096 characters. Also found as `telegram.constants.MAX_MESSAGE_LENGTH`.
- **entities** (`List[telegram.MessageEntity]`, optional) – For text messages, special entities like usernames, URLs, bot commands, etc. that appear in the text. See `parse_entity` and `parse_entities` methods for how to use properly.
- **caption_entities** (`List[telegram.MessageEntity]`) – Optional. For Messages with a Caption. Special entities like usernames, URLs, bot commands, etc. that appear in the caption. See `Message.parse_caption_entity` and `parse_caption_entities` methods for how to use properly.
- **audio** (`telegram.Audio`, optional) – Message is an audio file, information about the file.
- **document** (`telegram.Document`, optional) – Message is a general file, information about the file.
- **animation** (`telegram.Animation`, optional) – Message is an animation, information about the animation. For backward compatibility, when this field is set, the document field will also be set.
- **game** (`telegram.Game`, optional) – Message is a game, information about the game.
- **photo** (`List[telegram.PhotoSize]`, optional) – Message is a photo, available sizes of the photo.
- **sticker** (`telegram.Sticker`, optional) – Message is a sticker, information about the sticker.
- **video** (`telegram.Video`, optional) – Message is a video, information about the video.
- **voice** (`telegram.Voice`, optional) – Message is a voice message, information about the file.
- **video_note** (`telegram.VideoNote`, optional) – Message is a video note, information about the video message.
- **new_chat_members** (`List[telegram.User]`, optional) – New members that were added to the group or supergroup and information about them (the bot itself may be one of these members).
- **caption** (`str`, optional) – Caption for the animation, audio, document, photo, video or voice, 0-1024 characters.
- **contact** (`telegram.Contact`, optional) – Message is a shared contact, information about the contact.
- **location** (`telegram.Location`, optional) – Message is a shared location, information about the location.

- **venue** (*telegram.Venue*, optional) – Message is a venue, information about the venue. For backward compatibility, when this field is set, the location field will also be set.
- **left_chat_member** (*telegram.User*, optional) – A member was removed from the group, information about them (this member may be the bot itself).
- **new_chat_title** (*str*, optional) – A chat title was changed to this value.
- **new_chat_photo** (*List[telegram.PhotoSize]*, optional) – A chat photo was changed to this value.
- **delete_chat_photo** (*bool*, optional) – Service message: The chat photo was deleted.
- **group_chat_created** (*bool*, optional) – Service message: The group has been created.
- **supergroup_chat_created** (*bool*, optional) – Service message: The supergroup has been created. This field can't be received in a message coming through updates, because bot can't be a member of a supergroup when it is created. It can only be found in *reply_to_message* if someone replies to a very first message in a directly created supergroup.
- **channel_chat_created** (*bool*, optional) – Service message: The channel has been created. This field can't be received in a message coming through updates, because bot can't be a member of a channel when it is created. It can only be found in *reply_to_message* if someone replies to a very first message in a channel.
- **migrate_to_chat_id** (*int*, optional) – The group has been migrated to a supergroup with the specified identifier. This number may be greater than 32 bits and some programming languages may have difficulty/silent defects in interpreting it. But it is smaller than 52 bits, so a signed 64 bit integer or double-precision float type are safe for storing this identifier.
- **migrate_from_chat_id** (*int*, optional) – The supergroup has been migrated from a group with the specified identifier. This number may be greater than 32 bits and some programming languages may have difficulty/silent defects in interpreting it. But it is smaller than 52 bits, so a signed 64 bit integer or double-precision float type are safe for storing this identifier.
- **pinned_message** (*telegram.Message*, optional) – Specified message was pinned. Note that the Message object in this field will not contain further *reply_to_message* fields even if it is itself a reply.
- **invoice** (*telegram.Invoice*, optional) – Message is an invoice for a payment, information about the invoice.
- **successful_payment** (*telegram.SuccessfulPayment*, optional) – Message is a service message about a successful payment, information about the payment.
- **connected_website** (*str*, optional) – The domain name of the website on which the user has logged in.
- **forward_signature** (*str*, optional) – For messages forwarded from channels, signature of the post author if present.
- **author_signature** (*str*, optional) – Signature of the post author for messages in channels, or the custom title of an anonymous group administrator.
- **passport_data** (*telegram.PassportData*, optional) – Telegram Passport data.
- **poll** (*telegram.Poll*, optional) – Message is a native poll, information about the poll.

- **dice** (*telegram.Dice*, optional) – Message is a dice with random value from 1 to 6.
- **via_bot** (*telegram.User*, optional) – Message was sent through an inline bot.
- **proximity_alert_triggered** (*telegram.ProximityAlertTriggered*, optional) – Service message. A user in the chat triggered another user's proximity alert while sharing Live Location.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – Inline keyboard attached to the message. `login_url` buttons are represented as ordinary url buttons.
- **bot** (*telegram.Bot*, optional) – The Bot to use for instance methods.

caption_html

Creates an HTML-formatted string from the markup entities found in the message's caption.

Use this if you want to retrieve the message caption with the caption entities formatted as HTML in the same way the original message was formatted.

Returns Message caption with caption entities formatted as HTML.

Return type `str`

caption_html_urled

Creates an HTML-formatted string from the markup entities found in the message's caption.

Use this if you want to retrieve the message caption with the caption entities formatted as HTML. This also formats *telegram.MessageEntity.URL* as a hyperlink.

Returns Message caption with caption entities formatted as HTML.

Return type `str`

caption_markdown

Creates an Markdown-formatted string from the markup entities found in the message's caption using *telegram.ParseMode.MARKDOWN*.

Use this if you want to retrieve the message caption with the caption entities formatted as Markdown in the same way the original message was formatted.

Note: *telegram.ParseMode.MARKDOWN* is a legacy mode, retained by Telegram for backward compatibility. You should use *caption_markdown_v2()* instead.

Returns Message caption with caption entities formatted as Markdown.

Return type `str`

caption_markdown_urled

Creates an Markdown-formatted string from the markup entities found in the message's caption using *telegram.ParseMode.MARKDOWN*.

Use this if you want to retrieve the message caption with the caption entities formatted as Markdown. This also formats *telegram.MessageEntity.URL* as a hyperlink.

Note: *telegram.ParseMode.MARKDOWN* is a legacy mode, retained by Telegram for backward compatibility. You should use *caption_markdown_v2_urled()* instead.

Returns Message caption with caption entities formatted as Markdown.

Return type `str`

caption_markdown_v2

Creates an Markdown-formatted string from the markup entities found in the message's caption using `telegram.ParseMode.MARKDOWN_V2`.

Use this if you want to retrieve the message caption with the caption entities formatted as Markdown in the same way the original message was formatted.

Returns Message caption with caption entities formatted as Markdown.

Return type `str`

caption_markdown_v2_urled

Creates an Markdown-formatted string from the markup entities found in the message's caption using `telegram.ParseMode.MARKDOWN_V2`.

Use this if you want to retrieve the message caption with the caption entities formatted as Markdown. This also formats `telegram.MessageEntity.URL` as a hyperlink.

Returns Message caption with caption entities formatted as Markdown.

Return type `str`

chat_id

Shortcut for `telegram.Chat.id` for `chat`.

Type `int`

copy (`chat_id: int, *args, **kwargs`) → `MessageId`

Shortcut for:

```
bot.copy_message(chat_id=chat_id,
                 from_chat_id=update.message.chat_id,
                 message_id=update.message.message_id,
                 *args,
                 **kwargs)
```

Returns On success, returns the `MessageId` of the sent message.

Return type `telegram.MessageId`

delete (`*args, **kwargs`) → `bool`

Shortcut for:

```
bot.delete_message(chat_id=message.chat_id,
                   message_id=message.message_id,
                   *args,
                   **kwargs)
```

Returns On success, `True` is returned.

Return type `bool`

edit_caption (`*args, **kwargs`) → `Union[telegram.message.Message, bool]`

Shortcut for:

```
bot.edit_message_caption(chat_id=message.chat_id,
                        message_id=message.message_id,
                        *args,
                        **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_live_location (*args, **kwargs) → Union[telegram.message.Message, bool]

Shortcut for:

```
bot.edit_message_live_location(chat_id=message.chat_id,
                              message_id=message.message_id,
                              *args,
                              **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_media (media: InputMedia, *args, **kwargs) → Union[Message, bool]

Shortcut for:

```
bot.edit_message_media(chat_id=message.chat_id,
                      message_id=message.message_id,
                      *args,
                      **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_reply_markup (*args, **kwargs) → Union[telegram.message.Message, bool]

Shortcut for:

```
bot.edit_message_reply_markup(chat_id=message.chat_id,
                              message_id=message.message_id,
                              *args,
                              **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

edit_text (*args, **kwargs) → Union[telegram.message.Message, bool]

Shortcut for:

```
bot.edit_message_text(chat_id=message.chat_id,
                      message_id=message.message_id,
                      *args,
                      **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

effective_attachment

telegram.Audio or *telegram.Contact* or *telegram.Document* or *telegram.Animation* or *telegram.Game* or *telegram.Invoice* or *telegram.Location* or List[*telegram.PhotoSize*] or *telegram.Sticker* or *telegram.SuccessfulPayment* or *telegram.Venue* or *telegram.Video* or *telegram.VideoNote* or *telegram.Voice*: The attachment that this message was sent with. May be None if no attachment was sent.

forward (chat_id: int, *args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.forward_message(chat_id=chat_id,
                    from_chat_id=update.message.chat_id,
                    message_id=update.message.message_id,
                    *args,
                    **kwargs)
```

Returns On success, instance representing the message forwarded.

Return type *telegram.Message*

get_game_high_scores (*args, **kwargs) → List[GameHighScore]

Shortcut for:

```
bot.get_game_high_scores(chat_id=message.chat_id,
                         message_id=message.message_id,
                         *args,
                         **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns List[*telegram.GameHighScore*]

link

Convenience property. If the chat of the message is not a private chat or normal group, returns a t.me link of the message.

Type str

parse_caption_entities (*types*: *List[str]* = *None*) → Dict[telegram.messageentity.MessageEntity, str]

Returns a dict that maps *telegram.MessageEntity* to *str*. It contains entities from this message's caption filtered by their *telegram.MessageEntity.type* attribute as the key, and the text that each entity belongs to as the value of the dict.

Note: This method should always be used instead of the *caption_entities* attribute, since it calculates the correct substring from the message text based on UTF-16 codepoints. See *parse_entity* for more info.

Parameters *types* (List[str], optional) – List of *telegram.MessageEntity* types as strings. If the *type* attribute of an entity is contained in this list, it will be returned. Defaults to a list of all types. All types can be found as constants in *telegram.MessageEntity*.

Returns A dictionary of entities mapped to the text that belongs to them, calculated based on UTF-16 codepoints.

Return type Dict[*telegram.MessageEntity*, str]

parse_caption_entity (*entity*: telegram.messageentity.MessageEntity) → str

Returns the text from a given *telegram.MessageEntity*.

Note: This method is present because Telegram calculates the offset and length in UTF-16 codepoint pairs, which some versions of Python don't handle automatically. (That is, you can't just slice *Message.caption* with the offset and length.)

Parameters *entity* (*telegram.MessageEntity*) – The entity to extract the text from. It must be an entity that belongs to this message.

Returns The text of the given entity.

Return type str

Raises RuntimeError – If the message has no caption.

parse_entities (*types*: List[str] = None) → Dict[telegram.messageentity.MessageEntity, str]

Returns a dict that maps *telegram.MessageEntity* to *str*. It contains entities from this message filtered by their *telegram.MessageEntity.type* attribute as the key, and the text that each entity belongs to as the value of the dict.

Note: This method should always be used instead of the *entities* attribute, since it calculates the correct substring from the message text based on UTF-16 codepoints. See *parse_entity* for more info.

Parameters *types* (List[str], optional) – List of *telegram.MessageEntity* types as strings. If the *type* attribute of an entity is contained in this list, it will be returned. Defaults to a list of all types. All types can be found as constants in *telegram.MessageEntity*.

Returns A dictionary of entities mapped to the text that belongs to them, calculated based on UTF-16 codepoints.

Return type Dict[*telegram.MessageEntity*, str]

parse_entity (*entity*: telegram.messageentity.MessageEntity) → str

Returns the text from a given *telegram.MessageEntity*.

Note: This method is present because Telegram calculates the offset and length in UTF-16 code-point pairs, which some versions of Python don't handle automatically. (That is, you can't just slice `Message.text` with the offset and length.)

Parameters **entity** (*telegram.MessageEntity*) – The entity to extract the text from. It must be an entity that belongs to this message.

Returns The text of the given entity.

Return type `str`

Raises `RuntimeError` – If the message has no text.

pin (*args, **kwargs) → bool

Shortcut for:

```
bot.pin_chat_message(chat_id=message.chat_id,
                    message_id=message.message_id,
                    *args,
                    **kwargs)
```

Returns On success, `True` is returned.

Return type `bool`

reply_animation (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_animation(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to `True`, the animation is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: `True` in group chats and `False` in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_audio (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_audio(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to `True`, the audio is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: `True` in group chats and `False` in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_contact (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_contact(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to `True`, the contact is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: `True` in group chats and `False` in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_copy (*from_chat_id: int, message_id: int, *args, **kwargs*) → MessageId

Shortcut for:

```
bot.copy_message(chat_id=message.chat.id,
                 from_chat_id=from_chat_id,
                 message_id=message_id,
                 *args,
                 **kwargs)
```

Returns On success, returns the MessageId of the sent message.

Return type *telegram.MessageId*

reply_dice (**args, **kwargs*) → telegram.message.Message

Shortcut for:

```
bot.send_dice(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the dice is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_document (**args, **kwargs*) → telegram.message.Message

Shortcut for:

```
bot.send_document(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the document is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_html (**args, **kwargs*) → telegram.message.Message

Shortcut for:

```
bot.send_message(update.message.chat_id, parse_mode=ParseMode.HTML, *args,
                 ↪ **kwargs)
```

Sends a message with HTML formatting.

Keyword Arguments **quote** (bool, optional) – If set to True, the message is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_location (**args, **kwargs*) → telegram.message.Message

Shortcut for:

```
bot.send_location(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the location is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type `telegram.Message`

reply_markdown (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_message(update.message.chat_id, parse_mode=ParseMode.MARKDOWN,
↳ *args,
**kwargs)
```

Sends a message with Markdown version 1 formatting.

Note: `telegram.ParseMode.MARKDOWN` is a legacy mode, retained by Telegram for backward compatibility. You should use `reply_markdown_v2()` instead.

Keyword Arguments **quote** (bool, optional) – If set to True, the message is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type `telegram.Message`

reply_markdown_v2 (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_message(update.message.chat_id, parse_mode=ParseMode.MARKDOWN_V2,
↳ *args,
**kwargs)
```

Sends a message with markdown version 2 formatting.

Keyword Arguments **quote** (bool, optional) – If set to True, the message is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type `telegram.Message`

reply_media_group (*args, **kwargs) → List[Optional[telegram.message.Message]]

Shortcut for:

```
bot.send_media_group(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the media group is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns An array of the sent Messages.

Return type List[`telegram.Message`]

Raises `telegram.TelegramError`

reply_photo (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_photo(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the photo is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_poll (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_poll(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the poll is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_sticker (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_sticker(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the sticker is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_text (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_message(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the message is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_venue (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_venue(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the venue is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_video (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_video(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the video is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_video_note (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_video_note(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the video note is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

reply_voice (*args, **kwargs) → telegram.message.Message

Shortcut for:

```
bot.send_voice(update.message.chat_id, *args, **kwargs)
```

Keyword Arguments **quote** (bool, optional) – If set to True, the voice note is sent as an actual reply to this message. If `reply_to_message_id` is passed in `kwargs`, this parameter will be ignored. Default: True in group chats and False in private chats.

Returns On success, instance representing the message posted.

Return type *telegram.Message*

set_game_score (*args, **kwargs) → Union[telegram.message.Message, bool]

Shortcut for:

```
bot.set_game_score(chat_id=message.chat_id,
                   message_id=message.message_id,
                   *args,
                   **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

stop_live_location (*args, **kwargs) → Union[telegram.message.Message, bool]

Shortcut for:

```
bot.stop_message_live_location(chat_id=message.chat_id,
                              message_id=message.message_id,
                              *args,
                              **kwargs)
```

Note: You can only edit messages that the bot sent itself (i.e. of the `bot.send_*` family of methods) or channel posts, if the bot is an admin in that channel. However, this behaviour is undocumented and might be changed by Telegram.

Returns On success, if edited message is sent by the bot, the edited Message is returned, otherwise True is returned.

Return type *telegram.Message*

stop_poll (*args, **kwargs) → telegram.poll.Poll

Shortcut for:

```
bot.stop_poll(chat_id=message.chat_id,
              message_id=message.message_id,
              *args,
              **kwargs)
```

Returns On success, the stopped Poll with the final results is returned.

Return type *telegram.Poll*

text_html

Creates an HTML-formatted string from the markup entities found in the message.

Use this if you want to retrieve the message text with the entities formatted as HTML in the same way the original message was formatted.

Returns Message text with entities formatted as HTML.

Return type `str`

text_html_urled

Creates an HTML-formatted string from the markup entities found in the message.

Use this if you want to retrieve the message text with the entities formatted as HTML. This also formats *telegram.MessageEntity.URL* as a hyperlink.

Returns Message text with entities formatted as HTML.

Return type `str`

text_markdown

Creates an Markdown-formatted string from the markup entities found in the message using *telegram.ParseMode.MARKDOWN*.

Use this if you want to retrieve the message text with the entities formatted as Markdown in the same way the original message was formatted.

Note: *telegram.ParseMode.MARKDOWN* is a legacy mode, retained by Telegram for backward compatibility. You should use *text_markdown_v2()* instead.

Returns Message text with entities formatted as Markdown.

Return type `str`

`text_markdown_urled`

Creates an Markdown-formatted string from the markup entities found in the message using `telegram.ParseMode.MARKDOWN`.

Use this if you want to retrieve the message text with the entities formatted as Markdown. This also formats `telegram.MessageEntity.URL` as a hyperlink.

Note: `telegram.ParseMode.MARKDOWN` is a legacy mode, retained by Telegram for back-ward compatibility. You should use `text_markdown_v2_urled()` instead.

Returns Message text with entities formatted as Markdown.

Return type `str`

`text_markdown_v2`

Creates an Markdown-formatted string from the markup entities found in the message using `telegram.ParseMode.MARKDOWN_V2`.

Use this if you want to retrieve the message text with the entities formatted as Markdown in the same way the original message was formatted.

Returns Message text with entities formatted as Markdown.

Return type `str`

`text_markdown_v2_urled`

Creates an Markdown-formatted string from the markup entities found in the message using `telegram.ParseMode.MARKDOWN_V2`.

Use this if you want to retrieve the message text with the entities formatted as Markdown. This also formats `telegram.MessageEntity.URL` as a hyperlink.

Returns Message text with entities formatted as Markdown.

Return type `str`

unpin (**args*, ***kwargs*) → bool

Shortcut for:

```
bot.unpin_chat_message(chat_id=message.chat_id,
                       message_id=message.message_id,
                       *args,
                       **kwargs)
```

Returns On success, True is returned.

Return type `bool`

3.2.33 telegram.MessageId

class `telegram.MessageId` (*message_id: int*, ***kwargs*)

Bases: `telegram.base.TelegramObject`

This object represents a unique message identifier.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `message_id` is equal.

message_id

Unique message identifier

Type `int`

3.2.34 telegram.MessageEntity

class telegram.**MessageEntity** (*type: str, offset: int, length: int, url: str = None, user: telegram.user.User = None, language: str = None, **kwargs*)

Bases: telegram.base.TelegramObject

This object represents one special entity in a text message. For example, hashtags, usernames, URLs, etc.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `type`, `offset` and `length` are equal.

type

Type of the entity.

Type `str`

offset

Offset in UTF-16 code units to the start of the entity.

Type `int`

length

Length of the entity in UTF-16 code units.

Type `int`

url

Optional. Url that will be opened after user taps on the text.

Type `str`

user

Optional. The mentioned user.

Type `telegram.User`

language

Optional. Programming language of the entity text.

Type `str`

Parameters

- **type** (`str`) – Type of the entity. Can be mention (@username), hashtag, bot_command, url, email, phone_number, bold (bold text), italic (italic text), strikethrough, code (monowidth string), pre (monowidth block), text_link (for clickable text URLs), text_mention (for users without usernames).
- **offset** (`int`) – Offset in UTF-16 code units to the start of the entity.
- **length** (`int`) – Length of the entity in UTF-16 code units.
- **url** (`str`, optional) – For `TEXT_LINK` only, url that will be opened after user taps on the text.
- **user** (`telegram.User`, optional) – For `TEXT_MENTION` only, the mentioned user.
- **language** (`str`, optional) – For `PRE` only, the programming language of the entity text.

`ALL_TYPES = ['mention', 'hashtag', 'cashtag', 'phone_number', 'bot_command', 'url', telegram.constants.MESSAGEENTITY_ALL_TYPES]`

List of all the types

```
BOLD = 'bold'
    telegram.constants.MESSAGEENTITY_BOLD

BOT_COMMAND = 'bot_command'
    telegram.constants.MESSAGEENTITY_BOT_COMMAND

CASHTAG = 'cashtag'
    telegram.constants.MESSAGEENTITY_CASHTAG

CODE = 'code'
    telegram.constants.MESSAGEENTITY_CODE

EMAIL = 'email'
    telegram.constants.MESSAGEENTITY_EMAIL

HASHTAG = 'hashtag'
    telegram.constants.MESSAGEENTITY_HASHTAG

ITALIC = 'italic'
    telegram.constants.MESSAGEENTITY_ITALIC

MENTION = 'mention'
    telegram.constants.MESSAGEENTITY_MENTION

PHONE_NUMBER = 'phone_number'
    telegram.constants.MESSAGEENTITY_PHONE_NUMBER

PRE = 'pre'
    telegram.constants.MESSAGEENTITY_PRE

STRIKETHROUGH = 'strikethrough'
    telegram.constants.MESSAGEENTITY_STRIKETHROUGH

TEXT_LINK = 'text_link'
    telegram.constants.MESSAGEENTITY_TEXT_LINK

TEXT_MENTION = 'text_mention'
    telegram.constants.MESSAGEENTITY_TEXT_MENTION

UNDERLINE = 'underline'
    telegram.constants.MESSAGEENTITY_UNDERLINE

URL = 'url'
    telegram.constants.MESSAGEENTITY_URL
```

3.2.35 telegram.ParseMode

class telegram.ParseMode

Bases: object

This object represents a Telegram Message Parse Modes.

```
HTML = 'HTML'
    telegram.constants.PARSEMODE_HTML

MARKDOWN = 'Markdown'
    telegram.constants.PARSEMODE_MARKDOWN
```

Note: `MARKDOWN` is a legacy mode, retained by Telegram for backward compatibility. You should use `MARKDOWN_V2` instead.

```
MARKDOWN_V2 = 'MarkdownV2'
    telegram.constants.PARSEMODE_MARKDOWN_V2
```

3.2.36 telegram.PhotoSize

class telegram.**PhotoSize** (*file_id: str, file_unique_id: str, width: int, height: int, file_size: int = None, bot: Bot = None, **kwargs*)

Bases: telegram.base.TelegramObject

This object represents one size of a photo or a file/sticker thumbnail.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *file_unique_id* is equal.

file_id

Identifier for this file.

Type *str*

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type *str*

width

Photo width.

Type *int*

height

Photo height.

Type *int*

file_size

Optional. File size.

Type *int*

bot

Optional. The Bot to use for instance methods.

Type *telegram.Bot*

Parameters

- **file_id** (*str*) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (*str*) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **width** (*int*) – Photo width.
- **height** (*int*) – Photo height.
- **file_size** (*int*, optional) – File size.
- **bot** (*telegram.Bot*, optional) – The Bot to use for instance methods.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

get_file (*timeout: int = None, api_kwargs: Dict[str, Any] = None*) → File

Convenience wrapper over *telegram.Bot.get_file*

Parameters

- **timeout** (*int | float*, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.37 telegram.Poll

```
class telegram.Poll(id: str, question: str, options: List[telegram.poll.PollOption],
                    total_voter_count: int, is_closed: bool, is_anonymous: bool,
                    type: str, allows_multiple_answers: bool, correct_option_id:
                    int = None, explanation: str = None, explanation_entities:
                    List[telegram.messageentity.MessageEntity] = None, open_period: int
                    = None, close_date: datetime.datetime = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object contains information about a poll.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `id` is equal.

id

Unique poll identifier.

Type `str`

question

Poll question, 1-300 characters.

Type `str`

options

List of poll options.

Type `List[PollOption]`

total_voter_count

Total number of users that voted in the poll.

Type `int`

is_closed

True, if the poll is closed.

Type `bool`

is_anonymous

True, if the poll is anonymous.

Type `bool`

type

Poll type, currently can be `REGULAR` or `QUIZ`.

Type `str`

allows_multiple_answers

True, if the poll allows multiple answers.

Type `bool`

correct_option_id

Optional. Identifier of the correct answer option.

Type `int`

explanation

Optional. Text that is shown when a user chooses an incorrect answer or taps on the lamp icon in a quiz-style poll.

Type `str`

explanation_entities

Optional. Special entities like usernames, URLs, bot commands, etc. that appear in the *explanation*.

Type `List[telegram.MessageEntity]`

open_period

Optional. Amount of time in seconds the poll will be active after creation.

Type `int`

close_date

Optional. Point in time when the poll will be automatically closed.

Type `datetime.datetime`

Parameters

- **id** (`str`) – Unique poll identifier.
- **question** (`str`) – Poll question, 1-300 characters.
- **options** (`List[PollOption]`) – List of poll options.
- **is_closed** (`bool`) – True, if the poll is closed.
- **is_anonymous** (`bool`) – True, if the poll is anonymous.
- **type** (`str`) – Poll type, currently can be *REGULAR* or *QUIZ*.
- **allows_multiple_answers** (`bool`) – True, if the poll allows multiple answers.
- **correct_option_id** (`int`, optional) – 0-based identifier of the correct answer option. Available only for polls in the quiz mode, which are closed, or was sent (not forwarded) by the bot or to the private chat with the bot.
- **explanation** (`str`, optional) – Text that is shown when a user chooses an incorrect answer or taps on the lamp icon in a quiz-style poll, 0-200 characters.
- **explanation_entities** (`List[telegram.MessageEntity]`, optional) – Special entities like usernames, URLs, bot commands, etc. that appear in the *explanation*.
- **open_period** (`int`, optional) – Amount of time in seconds the poll will be active after creation.
- **close_date** (`datetime.datetime`, optional) – Point in time (Unix timestamp) when the poll will be automatically closed. Converted to `datetime.datetime`.

MAX_OPTION_LENGTH = 100

`telegram.constants.MAX_POLL_OPTION_LENGTH`

MAX_QUESTION_LENGTH = 300

`telegram.constants.MAX_POLL_QUESTION_LENGTH`

QUIZ = 'quiz'

`telegram.constants.POLL QUIZ`

REGULAR = 'regular'

`telegram.constants.POLL_REGULAR`

parse_explanation_entities (*types*: *List[str]* = *None*) → *Dict[telegram.messageentity.MessageEntity, str]*

Returns a dict that maps *telegram.MessageEntity* to *str*. It contains entities from this poll's explanation filtered by their *type* attribute as the key, and the text that each entity belongs to as the value of the dict.

Note: This method should always be used instead of the *explanation_entities* attribute, since it calculates the correct substring from the message text based on UTF-16 codepoints. See *parse_explanation_entity* for more info.

Parameters *types* (*List[str]*, optional) – List of *MessageEntity* types as strings. If the *type* attribute of an entity is contained in this list, it will be returned. Defaults to *telegram.MessageEntity.ALL_TYPES*.

Returns A dictionary of entities mapped to the text that belongs to them, calculated based on UTF-16 codepoints.

Return type *Dict[telegram.MessageEntity, str]*

parse_explanation_entity (*entity*: *telegram.messageentity.MessageEntity*) → *str*

Returns the text from a given *telegram.MessageEntity*.

Note: This method is present because Telegram calculates the offset and length in UTF-16 codepoint pairs, which some versions of Python don't handle automatically. (That is, you can't just slice *Message.text* with the offset and length.)

Parameters *entity* (*telegram.MessageEntity*) – The entity to extract the text from. It must be an entity that belongs to this message.

Returns The text of the given entity.

Return type *str*

Raises *RuntimeError* – If the poll has no explanation.

3.2.38 telegram.PollAnswer

class *telegram.PollAnswer* (*poll_id*: *str*, *user*: *telegram.user.User*, *option_ids*: *List[int]*, ***kwargs*)

Bases: *telegram.base.TelegramObject*

This object represents an answer of a user in a non-anonymous poll.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *poll_id*, *user* and *option_ids* are equal.

poll_id

Unique poll identifier.

Type *str*

user

The user, who changed the answer to the poll.

Type *telegram.User*

option_ids

Identifiers of answer options, chosen by the user.

Type *List[int]*

Parameters

- **poll_id** (*str*) – Unique poll identifier.
- **user** (*telegram.User*) – The user, who changed the answer to the poll.
- **option_ids** (*List[int]*) – 0-based identifiers of answer options, chosen by the user. May be empty if the user retracted their vote.

3.2.39 telegram.PollOption

class telegram.PollOption(*text: str, voter_count: int, **kwargs*)

Bases: telegram.base.TelegramObject

This object contains information about one answer option in a poll.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *text* and *voter_count* are equal.

text

Option text, 1-100 characters.

Type *str*

voter_count

Number of users that voted for this option.

Type *int*

Parameters

- **text** (*str*) – Option text, 1-100 characters.
- **voter_count** (*int*) – Number of users that voted for this option.

MAX_LENGTH = 100

telegram.constants.MAX_POLL_OPTION_LENGTH

3.2.40 telegram.ProximityAlertTriggered

class telegram.ProximityAlertTriggered(*traveler: telegram.user.User, watcher: telegram.user.User, distance: int, **kwargs*)

Bases: telegram.base.TelegramObject

This object represents the content of a service message, sent whenever a user in the chat triggers a proximity alert set by another user.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *traveler*, *watcher* and *distance* are equal.

traveler

User that triggered the alert

Type *telegram.User*

watcher

User that set the alert

Type *telegram.User*

distance

The distance between the users

Type *int*

Parameters

- **traveler** (*telegram.User*) – User that triggered the alert
- **watcher** (*telegram.User*) – User that set the alert
- **distance** (*int*) – The distance between the users

3.2.41 telegram.ReplyKeyboardRemove

class telegram.ReplyKeyboardRemove (*selective: bool = False, **kwargs*)

Bases: telegram.replymarkup.ReplyMarkup

Upon receiving a message with this object, Telegram clients will remove the current custom keyboard and display the default letter-keyboard. By default, custom keyboards are displayed until a new keyboard is sent by a bot. An exception is made for one-time keyboards that are hidden immediately after the user presses a button (see *telegram.ReplyKeyboardMarkup*).

remove_keyboard

Requests clients to remove the custom keyboard.

Type `True`

selective

Optional. Use this parameter if you want to remove the keyboard for specific users only.

Type `bool`

Example

A user votes in a poll, bot returns confirmation message in reply to the vote and removes the keyboard for that user, while still showing the keyboard with poll options to users who haven't voted yet.

Parameters

- **selective** (*bool*, optional) – Use this parameter if you want to remove the keyboard for specific users only. Targets:
 - 1) Users that are @mentioned in the text of the *telegram.Message* object.
 - 2) If the bot's message is a reply (has *reply_to_message_id*), sender of the original message.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

Note: User will not be able to summon this keyboard; if you want to hide the keyboard from sight but keep it accessible, use *telegram.ReplyKeyboardMarkup.one_time_keyboard*.

3.2.42 telegram.ReplyKeyboardMarkup

class telegram.ReplyKeyboardMarkup (*keyboard: List[List[Union[str, telegram.keyboardbutton.KeyboardButton]]], resize_keyboard: bool = False, one_time_keyboard: bool = False, selective: bool = False, **kwargs*)

Bases: telegram.replymarkup.ReplyMarkup

This object represents a custom keyboard with reply options.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their the size of *keyboard* and all the buttons are equal.

keyboard

Array of button rows.

Type List[List[*telegram.KeyboardButton* | str]]

resize_keyboard

Optional. Requests clients to resize the keyboard.

Type bool

one_time_keyboard

Optional. Requests clients to hide the keyboard as soon as it's been used.

Type bool

selective

Optional. Show the keyboard to specific users only.

Type bool

Example

A user requests to change the bot's language, bot replies to the request with a keyboard to select the new language. Other users in the group don't see the keyboard.

Parameters

- **keyboard** (List[List[str | *telegram.KeyboardButton*]]) – Array of button rows, each represented by an Array of *telegram.KeyboardButton* objects.
- **resize_keyboard** (bool, optional) – Requests clients to resize the keyboard vertically for optimal fit (e.g., make the keyboard smaller if there are just two rows of buttons). Defaults to `False`, in which case the custom keyboard is always of the same height as the app's standard keyboard.
- **one_time_keyboard** (bool, optional) – Requests clients to hide the keyboard as soon as it's been used. The keyboard will still be available, but clients will automatically display the usual letter-keyboard in the chat - the user can press a special button in the input field to see the custom keyboard again. Defaults to `False`.
- **selective** (bool, optional) – Use this parameter if you want to show the keyboard to specific users only. Targets:
 - 1) Users that are @mentioned in the text of the Message object.
 - 2) If the bot's message is a reply (has `reply_to_message_id`), sender of the original message.Defaults to `False`.
- ****kwargs** (dict) – Arbitrary keyword arguments.

classmethod from_button (*button*: Union[*telegram.keyboardbutton.KeyboardButton*, str], *resize_keyboard*: bool = False, *one_time_keyboard*: bool = False, *selective*: bool = False, **kwargs) → *telegram.replykeyboardmarkup.ReplyKeyboardMarkup*

Shortcut for:

```
ReplyKeyboardMarkup([button], **kwargs)
```

Return a *ReplyKeyboardMarkup* from a single *KeyboardButton*.

Parameters

- **button** (*telegram.KeyboardButton* | str) – The button to use in the markup.

- **resize_keyboard** (`bool`, optional) – Requests clients to resize the keyboard vertically for optimal fit (e.g., make the keyboard smaller if there are just two rows of buttons). Defaults to `False`, in which case the custom keyboard is always of the same height as the app’s standard keyboard.
- **one_time_keyboard** (`bool`, optional) – Requests clients to hide the keyboard as soon as it’s been used. The keyboard will still be available, but clients will automatically display the usual letter-keyboard in the chat - the user can press a special button in the input field to see the custom keyboard again. Defaults to `False`.
- **selective** (`bool`, optional) – Use this parameter if you want to show the keyboard to specific users only. Targets:
 - 1) Users that are @mentioned in the text of the Message object.
 - 2) **If the bot’s message is a reply (has `reply_to_message_id`), sender of the original message.**Defaults to `False`.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

```
classmethod from_column(button_column: List[Union[str, telegram.keyboardbutton.KeyboardButton]], resize_keyboard: bool = False, one_time_keyboard: bool = False, selective: bool = False, **kwargs) → telegram.replykeyboardmarkup.ReplyKeyboardMarkup
```

Shortcut for:

```
ReplyKeyboardMarkup([[button] for button in button_column], **kwargs)
```

Return a `ReplyKeyboardMarkup` from a single column of `KeyboardButtons`.

Parameters

- **button_column** (`List[telegram.KeyboardButton | str]`) – The button to use in the markup.
- **resize_keyboard** (`bool`, optional) – Requests clients to resize the keyboard vertically for optimal fit (e.g., make the keyboard smaller if there are just two rows of buttons). Defaults to `False`, in which case the custom keyboard is always of the same height as the app’s standard keyboard.
- **one_time_keyboard** (`bool`, optional) – Requests clients to hide the keyboard as soon as it’s been used. The keyboard will still be available, but clients will automatically display the usual letter-keyboard in the chat - the user can press a special button in the input field to see the custom keyboard again. Defaults to `False`.
- **selective** (`bool`, optional) – Use this parameter if you want to show the keyboard to specific users only. Targets:
 - 1) Users that are @mentioned in the text of the Message object.
 - 2) **If the bot’s message is a reply (has `reply_to_message_id`), sender of the original message.**Defaults to `False`.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

```
classmethod from_row(button_row: List[Union[str, telegram.keyboardbutton.KeyboardButton]], resize_keyboard: bool = False, one_time_keyboard: bool = False, selective: bool = False, **kwargs) → telegram.replykeyboardmarkup.ReplyKeyboardMarkup
```

Shortcut for:

```
ReplyKeyboardMarkup([button_row], **kwargs)
```

Return a `ReplyKeyboardMarkup` from a single row of `KeyboardButtons`.

Parameters

- **button_row** (List[[`telegram.KeyboardButton`](#) | str]) – The button to use in the markup.
- **resize_keyboard** (bool, optional) – Requests clients to resize the keyboard vertically for optimal fit (e.g., make the keyboard smaller if there are just two rows of buttons). Defaults to `False`, in which case the custom keyboard is always of the same height as the app's standard keyboard.
- **one_time_keyboard** (bool, optional) – Requests clients to hide the keyboard as soon as it's been used. The keyboard will still be available, but clients will automatically display the usual letter-keyboard in the chat - the user can press a special button in the input field to see the custom keyboard again. Defaults to `False`.
- **selective** (bool, optional) – Use this parameter if you want to show the keyboard to specific users only. Targets:
 - 1) Users that are @mentioned in the text of the `Message` object.
 - 2) If the bot's message is a reply (has `reply_to_message_id`), sender of the original message.
 Defaults to `False`.
- ****kwargs** (dict) – Arbitrary keyword arguments.

3.2.43 telegram.ReplyMarkup

class `telegram.ReplyMarkup`

Bases: `telegram.base.TelegramObject`

Base class for Telegram ReplyMarkup Objects.

See [`telegram.ReplyKeyboardMarkup`](#) and [`telegram.InlineKeyboardMarkup`](#) for detailed use.

3.2.44 telegram.TelegramObject

class `telegram.TelegramObject`

Bases: `object`

Base class for most telegram objects.

to_json () → str

Returns str

3.2.45 telegram.Update

```
class telegram.Update(update_id: int, message: telegram.message.Message = None,
    edited_message: telegram.message.Message = None, channel_post: telegram.message.Message = None,
    edited_channel_post: telegram.message.Message = None, inline_query: telegram.inline.inlinequery.InlineQuery = None,
    chosen_inline_result: telegram.choseninlineresult.ChosenInlineResult = None, callback_query: telegram.callbackquery.CallbackQuery = None,
    shipping_query: telegram.payment.shippingquery.ShippingQuery = None, pre_checkout_query: telegram.payment.precheckoutquery.PreCheckoutQuery = None,
    poll: telegram.poll.Poll = None, poll_answer: telegram.poll.PollAnswer = None, **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents an incoming update.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `update_id` is equal.

Note: At most one of the optional parameters can be present in any given update.

update_id

The update's unique identifier.

Type `int`

message

Optional. New incoming message.

Type `telegram.Message`

edited_message

Optional. New version of a message.

Type `telegram.Message`

channel_post

Optional. New incoming channel post.

Type `telegram.Message`

edited_channel_post

Optional. New version of a channel post.

Type `telegram.Message`

inline_query

Optional. New incoming inline query.

Type `telegram.InlineQuery`

chosen_inline_result

Optional. The result of an inline query that was chosen by a user.

Type `telegram.ChosenInlineResult`

callback_query

Optional. New incoming callback query.

Type `telegram.CallbackQuery`

shipping_query

Optional. New incoming shipping query.

Type `telegram.ShippingQuery`

pre_checkout_query

Optional. New incoming pre-checkout query.

Type `telegram.PreCheckoutQuery`

poll

Optional. New poll state. Bots receive only updates about stopped polls and polls, which are sent by the bot.

Type `telegram.Poll`

poll_answer

Optional. A user changed their answer in a non-anonymous poll. Bots receive new votes only in polls that were sent by the bot itself.

Type `telegram.PollAnswer`

Parameters

- **update_id** (`int`) – The update’s unique identifier. Update identifiers start from a certain positive number and increase sequentially. This ID becomes especially handy if you’re using Webhooks, since it allows you to ignore repeated updates or to restore the correct update sequence, should they get out of order. If there are no new updates for at least a week, then identifier of the next update will be chosen randomly instead of sequentially.
- **message** (`telegram.Message`, optional) – New incoming message of any kind - text, photo, sticker, etc.
- **edited_message** (`telegram.Message`, optional) – New version of a message that is known to the bot and was edited.
- **channel_post** (`telegram.Message`, optional) – New incoming channel post of any kind - text, photo, sticker, etc.
- **edited_channel_post** (`telegram.Message`, optional) – New version of a channel post that is known to the bot and was edited.
- **inline_query** (`telegram.InlineQuery`, optional) – New incoming inline query.
- **chosen_inline_result** (`telegram.ChosenInlineResult`, optional) – The result of an inline query that was chosen by a user and sent to their chat partner.
- **callback_query** (`telegram.CallbackQuery`, optional) – New incoming callback query.
- **shipping_query** (`telegram.ShippingQuery`, optional) – New incoming shipping query. Only for invoices with flexible price.
- **pre_checkout_query** (`telegram.PreCheckoutQuery`, optional) – New incoming pre-checkout query. Contains full information about checkout.
- **poll** (`telegram.Poll`, optional) – New poll state. Bots receive only updates about stopped polls and polls, which are sent by the bot.
- **poll_answer** (`telegram.PollAnswer`, optional) – A user changed their answer in a non-anonymous poll. Bots receive new votes only in polls that were sent by the bot itself.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

classmethod `de_json` (*data: Optional[Dict[str, Any]]*, *bot: Bot*) → Optional[Update]

effective_chat

The chat that this update was sent in, no matter what kind of update this is. Will be `None` for `inline_query`, `chosen_inline_result`, `callback_query` from inline messages, `shipping_query`, `pre_checkout_query`, `poll` and `poll_answer`.

Type `telegram.Chat`

effective_message

The message included in this update, no matter what kind of update this is. Will be `None` for `inline_query`, `chosen_inline_result`, `callback_query` from inline messages, `shipping_query`, `pre_checkout_query`, `poll` and `poll_answer`.

Type `telegram.Message`

effective_user

The user that sent this update, no matter what kind of update this is. Will be `None` for `channel_post` and `poll`.

Type `telegram.User`

3.2.46 telegram.User

```
class telegram.User(id: int, first_name: str, is_bot: bool, last_name: str = None, username: str = None, language_code: str = None, can_join_groups: bool = None, can_read_all_group_messages: bool = None, supports_inline_queries: bool = None, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a Telegram user or bot.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `id` is equal.

id

Unique identifier for this user or bot.

Type `int`

is_bot

True, if this user is a bot.

Type `bool`

first_name

User's or bot's first name.

Type `str`

last_name

Optional. User's or bot's last name.

Type `str`

username

Optional. User's or bot's username.

Type `str`

language_code

Optional. IETF language tag of the user's language.

Type `str`

can_join_groups

Optional. True, if the bot can be invited to groups. Returned only in `telegram.Bot.get_me` requests.

Type `str`

can_read_all_group_messages

Optional. True, if privacy mode is disabled for the bot. Returned only in `telegram.Bot.get_me` requests.

Type `str`

supports_inline_queries

Optional. `True`, if the bot supports inline queries. Returned only in `telegram.Bot.get_me` requests.

Type `str`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **id** (`int`) – Unique identifier for this user or bot.
- **is_bot** (`bool`) – `True`, if this user is a bot.
- **first_name** (`str`) – User’s or bot’s first name.
- **last_name** (`str`, optional) – User’s or bot’s last name.
- **username** (`str`, optional) – User’s or bot’s username.
- **language_code** (`str`, optional) – IETF language tag of the user’s language.
- **can_join_groups** (`str`, optional) – `True`, if the bot can be invited to groups. Returned only in `telegram.Bot.get_me` requests.
- **can_read_all_group_messages** (`str`, optional) – `True`, if privacy mode is disabled for the bot. Returned only in `telegram.Bot.get_me` requests.
- **supports_inline_queries** (`str`, optional) – `True`, if the bot supports inline queries. Returned only in `telegram.Bot.get_me` requests.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.

copy_message (**args*, ***kwargs*) → `MessageId`

Shortcut for:

```
bot.copy_message(from_chat_id=update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

full_name

Convenience property. The user’s `first_name`, followed by (if available) `last_name`.

Type `str`

get_profile_photos (**args*, ***kwargs*) → `UserProfilePhotos`

Shortcut for:

```
bot.get_user_profile_photos(update.effective_user.id, *args, **kwargs)
```

link

Convenience property. If `username` is available, returns a t.me link of the user.

Type `str`

mention_html (*name: str = None*) → `str`

Parameters **name** (`str`) – The name used as a link for the user. Defaults to `full_name`.

Returns The inline mention for the user as HTML.

Return type `str`

mention_markdown (*name: str = None*) → str

Note: `telegram.ParseMode.MARKDOWN` is a legacy mode, retained by Telegram for backward compatibility. You should use `mention_markdown_v2()` instead.

Parameters **name** (str) – The name used as a link for the user. Defaults to `full_name`.

Returns The inline mention for the user as markdown (version 1).

Return type str

mention_markdown_v2 (*name: str = None*) → str

Parameters **name** (str) – The name used as a link for the user. Defaults to `full_name`.

Returns The inline mention for the user as markdown (version 2).

Return type str

name

Convenience property. If available, returns the user's `username` prefixed with "@". If `username` is not available, returns `full_name`.

Type str

pin_message (**args, **kwargs*) → bool

Shortcut for:

```
bot.pin_chat_message(chat_id=update.effective_user.id,  
                     *args,  
                     **kwargs)
```

Returns On success, True is returned.

Return type bool

send_action (**args, **kwargs*) → bool

Alias for `send_chat_action`

send_animation (**args, **kwargs*) → Message

Shortcut for:

```
bot.send_animation(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_audio (**args, **kwargs*) → Message

Shortcut for:

```
bot.send_audio(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_chat_action (**args, **kwargs*) → bool

Shortcut for:

```
bot.send_chat_action(update.effective_user.id, *args, **kwargs)
```

Returns On success.

Return type `True`

send_contact (*args, **kwargs) → Message

Shortcut for:

```
bot.send_contact(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_copy (*args, **kwargs) → MessageId

Shortcut for:

```
bot.copy_message(chat_id=update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_dice (*args, **kwargs) → Message

Shortcut for:

```
bot.send_dice(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_document (*args, **kwargs) → Message

Shortcut for:

```
bot.send_document(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_game (*args, **kwargs) → Message

Shortcut for:

```
bot.send_game(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_invoice (*args, **kwargs) → Message

Shortcut for:

```
bot.send_invoice(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type `telegram.Message`

send_location (*args, **kwargs) → Message

Shortcut for:

```
bot.send_location(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_media_group (*args, **kwargs) → List[Message]

Shortcut for:

```
bot.send_media_group(update.effective_user.id, *args, **kwargs)
```

Returns] On success, instance representing the message posted.

Return type List[*telegram.Message*]

send_message (*args, **kwargs) → Message

Shortcut for:

```
bot.send_message(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_photo (*args, **kwargs) → Message

Shortcut for:

```
bot.send_photo(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_poll (*args, **kwargs) → Message

Shortcut for:

```
bot.send_poll(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_sticker (*args, **kwargs) → Message

Shortcut for:

```
bot.send_sticker(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_venue (*args, **kwargs) → Message

Shortcut for:

```
bot.send_venue(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_video (*args, **kwargs) → Message

Shortcut for:

```
bot.send_video(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_video_note (*args, **kwargs) → Message

Shortcut for:

```
bot.send_video_note(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

send_voice (*args, **kwargs) → Message

Shortcut for:

```
bot.send_voice(update.effective_user.id, *args, **kwargs)
```

Returns On success, instance representing the message posted.

Return type *telegram.Message*

unpin_all_messages (*args, **kwargs) → bool

Shortcut for:

```
bot.unpin_all_chat_messages(chat_id=update.effective_user.id,
                             *args,
                             **kwargs)
```

Returns On success, True is returned.

Return type bool

unpin_message (*args, **kwargs) → bool

Shortcut for:

```
bot.unpin_chat_message(chat_id=update.effective_user.id,
                        *args,
                        **kwargs)
```

Returns On success, True is returned.

Return type bool

3.2.47 telegram.UserProfilePhotos

```
class telegram.UserProfilePhotos (total_count: int, photos:
                                   List[List[telegram.files.photosize.PhotoSize]],
                                   **_kwargs)
```

Bases: telegram.base.TelegramObject

This object represent a user's profile pictures.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *total_count* and *photos* are equal.

total_count

Total number of profile pictures.

Type `int`

photos

Requested profile pictures.

Type `List[List[telegram.PhotoSize]]`

Parameters

- **total_count** (`int`) – Total number of profile pictures the target user has.
- **photos** (`List[List[telegram.PhotoSize]]`) – Requested profile pictures (in up to 4 sizes each).

3.2.48 telegram.Venue

```
class telegram.Venue (location: telegram.files.location.Location, title: str, address: str,
                      foursquare_id: str = None, foursquare_type: str = None, google_place_id:
                      str = None, google_place_type: str = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a venue.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *location* and *title* are equal.

Note: Foursquare details and Google Pace details are mutually exclusive. However, this behaviour is undocumented and might be changed by Telegram.

location

Venue location.

Type `telegram.Location`

title

Name of the venue.

Type `str`

address

Address of the venue.

Type `str`

foursquare_id

Optional. Foursquare identifier of the venue.

Type `str`

foursquare_type

Optional. Foursquare type of the venue.

Type `str`

google_place_id

Optional. Google Places identifier of the venue.

Type `str`

google_place_type

Optional. Google Places type of the venue.

Type `str`

Parameters

- **location** (*telegram.Location*) – Venue location.
- **title** (`str`) – Name of the venue.
- **address** (`str`) – Address of the venue.
- **foursquare_id** (`str`, optional) – Foursquare identifier of the venue.
- **foursquare_type** (`str`, optional) – Foursquare type of the venue. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (`str`, optional) – Google Places identifier of the venue.
- **google_place_type** (`str`, optional) – Google Places type of the venue. (See [supported types](#).)
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

3.2.49 telegram.Video

```
class telegram.Video(file_id: str, file_unique_id: str, width: int, height: int, duration: int,  
                    thumb: telegram.files.photosize.PhotoSize = None, mime_type: str = None,  
                    file_size: int = None, bot: Bot = None, file_name: str = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a video file.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *file_unique_id* is equal.

file_id

Identifier for this file.

Type `str`

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

width

Video width as defined by sender.

Type `int`

height

Video height as defined by sender.

Type `int`

duration

Duration of the video in seconds as defined by sender.

Type `int`

thumb

Optional. Video thumbnail.

Type *telegram.PhotoSize*

file_name

Optional. Original filename as defined by sender.

Type `str`

mime_type

Optional. Mime type of a file as defined by sender.

Type `str`

file_size

Optional. File size.

Type `int`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **width** (`int`) – Video width as defined by sender.
- **height** (`int`) – Video height as defined by sender.
- **duration** (`int`) – Duration of the video in seconds as defined by sender.
- **thumb** (`telegram.PhotoSize`, optional) – Video thumbnail.
- **file_name** (`str`, optional) – Original filename as defined by sender.
- **mime_type** (`str`, optional) – Mime type of a file as defined by sender.
- **file_size** (`int`, optional) – File size.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

get_file (*timeout: int = None, api_kwargs: Dict[str, Any] = None*) → `File`

Convenience wrapper over `telegram.Bot.get_file`

Parameters

- **timeout** (`int` | `float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.50 telegram.VideoNote

```
class telegram.VideoNote (file_id: str, file_unique_id: str, length: int, duration: int, thumb: telegram.files.photosize.PhotoSize = None, file_size: int = None, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a video message (available in Telegram apps as of v.4.0).

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

file_id

Identifier for this file.

Type `str`

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

length

Video width and height as defined by sender.

Type `int`

duration

Duration of the video in seconds as defined by sender.

Type `int`

thumb

Optional. Video thumbnail.

Type `telegram.PhotoSize`

file_size

Optional. File size.

Type `int`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **length** (`int`) – Video width and height (diameter of the video message) as defined by sender.
- **duration** (`int`) – Duration of the video in seconds as defined by sender.
- **thumb** (`telegram.PhotoSize`, optional) – Video thumbnail.
- **file_size** (`int`, optional) – File size.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

get_file (*timeout: int = None, api_kwargs: Dict[str, Any] = None*) → File

Convenience wrapper over `telegram.Bot.get_file`

Parameters

- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.51 telegram.Voice

```
class telegram.Voice(file_id: str, file_unique_id: str, duration: int, mime_type: str = None,
                    file_size: int = None, bot: Bot = None, **kwargs)
    Bases: telegram.base.TelegramObject
```

This object represents a voice note.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

file_id

Identifier for this file.

Type `str`

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

duration

Duration of the audio in seconds as defined by sender.

Type `int`

mime_type

Optional. MIME type of the file as defined by sender.

Type `str`

file_size

Optional. File size.

Type `int`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **duration** (`int`, optional) – Duration of the audio in seconds as defined by sender.
- **mime_type** (`str`, optional) – MIME type of the file as defined by sender.
- **file_size** (`int`, optional) – File size.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (dict) – Arbitrary keyword arguments.

get_file (`timeout: int = None`, `api_kwargs: Dict[str, Any] = None`) → File
Convenience wrapper over `telegram.Bot.get_file`

Parameters

- **timeout** (int | float, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (dict, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

3.2.52 telegram.WebhookInfo

```
class telegram.WebhookInfo(url: str, has_custom_certificate: bool, pending_update_count: int,
                           last_error_date: int = None, last_error_message: str = None,
                           max_connections: int = None, allowed_updates: List[str] = None,
                           ip_address: str = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a Telegram WebhookInfo.

Contains information about the current status of a webhook.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `url`, `has_custom_certificate`, `pending_update_count`, `ip_address`, `last_error_date`, `last_error_message`, `max_connections` and `allowed_updates` are equal.

url

Webhook URL.

Type `str`

has_custom_certificate

If a custom certificate was provided for webhook.

Type `bool`

pending_update_count

Number of updates awaiting delivery.

Type `int`

ip_address

Optional. Currently used webhook IP address.

Type `str`

last_error_date

Optional. Unix time for the most recent error that happened.

Type `int`

last_error_message

Optional. Error message in human-readable format.

Type `str`

max_connections

Optional. Maximum allowed number of simultaneous HTTPS connections.

Type `int`

allowed_updates

Optional. A list of update types the bot is subscribed to.

Type `List[str]`

Parameters

- **url** (`str`) – Webhook URL, may be empty if webhook is not set up.
- **has_custom_certificate** (`bool`) – True, if a custom certificate was provided for webhook certificate checks.
- **pending_update_count** (`int`) – Number of updates awaiting delivery.
- **ip_address** (`str`, optional) – Currently used webhook IP address.
- **last_error_date** (`int`, optional) – Unix time for the most recent error that happened when trying to deliver an update via webhook.
- **last_error_message** (`str`, optional) – Error message in human-readable format for the most recent error that happened when trying to deliver an update via webhook.
- **max_connections** (`int`, optional) – Maximum allowed number of simultaneous HTTPS connections to the webhook for update delivery.
- **allowed_updates** (`List[str]`, optional) – A list of update types the bot is subscribed to. Defaults to all update types.

3.2.53 Stickers

telegram.Sticker

```
class telegram.Sticker(file_id: str, file_unique_id: str, width: int, height: int, is_animated: bool,  
                      thumb: telegram.files.photosize.PhotoSize = None, emoji: str = None,  
                      file_size: int = None, set_name: str = None, mask_position: MaskPosi-  
                      tion = None, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a sticker.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

file_id

Identifier for this file.

Type `str`

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

width

Sticker width.

Type `int`

height

Sticker height.

Type `int`

is_animated

True, if the sticker is animated.

Type `bool`

thumb

Optional. Sticker thumbnail in the .webp or .jpg format.

Type `telegram.PhotoSize`

emoji

Optional. Emoji associated with the sticker.

Type `str`

set_name

Optional. Name of the sticker set to which the sticker belongs.

Type `str`

mask_position

Optional. For mask stickers, the position where the mask should be placed.

Type `telegram.MaskPosition`

file_size

Optional. File size.

Type `int`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **width** (`int`) – Sticker width.
- **height** (`int`) – Sticker height.
- **is_animated** (`bool`) – True, if the sticker is animated.
- **thumb** (`telegram.PhotoSize`, optional) – Sticker thumbnail in the .WEBP or .JPG format.
- **emoji** (`str`, optional) – Emoji associated with the sticker
- **set_name** (`str`, optional) – Name of the sticker set to which the sticker belongs.
- **mask_position** (`telegram.MaskPosition`, optional) – For mask stickers, the position where the mask should be placed.
- **file_size** (`int`, optional) – File size.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- **(obj (**kwargs) – dict)**: Arbitrary keyword arguments.

get_file (*timeout: str = None, api_kwargs: Dict[str, Any] = None*) → File

Convenience wrapper over `telegram.Bot.get_file`

Parameters

- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

telegram.StickerSet

```
class telegram.StickerSet(name: str, title: str, is_animated: bool, contains_masks:  
                          bool, stickers: List[telegram.files.sticker.Sticker], thumb: tele-  
                          gram.files.photosize.PhotoSize = None, **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents a sticker set.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *name* is equal.

name

Sticker set name.

Type str

title

Sticker set title.

Type str

is_animated

True, if the sticker set contains animated stickers.

Type bool

contains_masks

True, if the sticker set contains masks.

Type bool

stickers

List of all set stickers.

Type List[*telegram.Sticker*]

thumb

Optional. Sticker set thumbnail in the .WEBP or .TGS format.

Type *telegram.PhotoSize*

Parameters

- **name** (str) – Sticker set name.
- **title** (str) – Sticker set title.
- **is_animated** (bool) – True, if the sticker set contains animated stickers.
- **contains_masks** (bool) – True, if the sticker set contains masks.
- **stickers** (List[*telegram.Sticker*]) – List of all set stickers.
- **thumb** (*telegram.PhotoSize*, optional) – Sticker set thumbnail in the .WEBP or .TGS format.

telegram.MaskPosition

```
class telegram.MaskPosition(point: str, x_shift: float, y_shift: float, scale: float, **kwargs)
```

Bases: telegram.base.TelegramObject

This object describes the position on faces where a mask should be placed by default.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *point*, *x_shift*, *y_shift* and, *scale* are equal.

point

The part of the face relative to which the mask should be placed. One of 'forehead', 'eyes', 'mouth', or 'chin'.

Type str

x_shift

Shift by X-axis measured in widths of the mask scaled to the face size, from left to right.

Type float

y_shift

Shift by Y-axis measured in heights of the mask scaled to the face size, from top to bottom.

Type float

scale

Mask scaling coefficient. For example, 2.0 means double size.

Type float

Note: type should be one of the following: *forehead*, *eyes*, *mouth* or *chin*. You can use the class constants for those.

Parameters

- **point** (str) – The part of the face relative to which the mask should be placed. One of 'forehead', 'eyes', 'mouth', or 'chin'.
- **x_shift** (float) – Shift by X-axis measured in widths of the mask scaled to the face size, from left to right. For example, choosing -1.0 will place mask just to the left of the default mask position.
- **y_shift** (float) – Shift by Y-axis measured in heights of the mask scaled to the face size, from top to bottom. For example, 1.0 will place the mask just below the default mask position.
- **scale** (float) – Mask scaling coefficient. For example, 2.0 means double size.

CHIN = 'chin'

telegram.constants.STICKER_CHIN

EYES = 'eyes'

telegram.constants.STICKER_EYES

FOREHEAD = 'forehead'

telegram.constants.STICKER_FOREHEAD

MOUTH = 'mouth'

telegram.constants.STICKER_MOUTH

3.2.54 Inline Mode

telegram.InlineQuery

class telegram.InlineQuery (*id: str, from_user: telegram.user.User, query: str, offset: str, location: telegram.files.location.Location = None, bot: Bot = None, **kwargs*)

Bases: telegram.base.TelegramObject

This object represents an incoming inline query. When the user sends an empty query, your bot could return some default or trending results.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *id* is equal.

Note:

- In Python *from* is a reserved word, use *from_user* instead.
-

id

Unique identifier for this query.

Type `str`

from_user

Sender.

Type `telegram.User`

location

Optional. Sender location, only for bots that request user location.

Type `telegram.Location`

query

Text of the query (up to 256 characters).

Type `str`

offset

Offset of the results to be returned, can be controlled by the bot.

Type `str`

Parameters

- **id** (`str`) – Unique identifier for this query.
- **from_user** (`telegram.User`) – Sender.
- **location** (`telegram.Location`, optional) – Sender location, only for bots that request user location.
- **query** (`str`) – Text of the query (up to 256 characters).
- **offset** (`str`) – Offset of the results to be returned, can be controlled by the bot.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

answer (**args*, *auto_pagination: bool = False*, ***kwargs*) → `bool`

Shortcut for:

```
bot.answer_inline_query(update.inline_query.id,
                        *args,
                        current_offset=self.offset if auto_pagination else
↪ None,
                        **kwargs)
```

Parameters

- **results** (`List[telegram.InlineQueryResult] | Callable`) – A list of results for the inline query. In case *auto_pagination* is set to `True`, results may also be a callable may also be a callable accepts the current page index starting from 0. It must return either a list of `telegram.InlineResult` instances or `None` if there are no more results.

- **cache_time** (int, optional) – The maximum amount of time in seconds that the result of the inline query may be cached on the server. Defaults to 300.
- **is_personal** (bool, optional) – Pass `True`, if results may be cached on the server side only for the user that sent the query. By default, results may be returned to any user who sends the same query.
- **next_offset** (str, optional) – Pass the offset that a client should send in the next query with the same text to receive more results. Pass an empty string if there are no more results or if you don't support pagination. Offset length can't exceed 64 bytes.
- **switch_pm_text** (str, optional) – If passed, clients will display a button with specified text that switches the user to a private chat with the bot and sends the bot a start message with the parameter `switch_pm_parameter`.
- **switch_pm_parameter** (str, optional) – Deep-linking parameter for the `/start` message sent to the bot when user presses the switch button. 1-64 characters, only A-Z, a-z, 0-9, `_` and `-` are allowed.
- **auto_pagination** (bool, optional) – If set to `True`, `offset` will be passed as `current_offset` to `:meth:telegram.Bot.answer_inline_query`. Defaults to `False`.

telegram.InlineQueryResult

class telegram.InlineQueryResult (*type: str, id: str, **kwargs*)

Bases: telegram.base.TelegramObject

Baseclass for the InlineQueryResult* classes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `id` is equal.

type

Type of the result.

Type str

id

Unique identifier for this result, 1-64 Bytes.

Type str

Parameters

- **type** (str) – Type of the result.
- **id** (str) – Unique identifier for this result, 1-64 Bytes.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InlineQueryResultArticle

class telegram.InlineQueryResultArticle (*id: str, title: str, input_message_content: InputMessageContent, reply_markup: ReplyMarkup = None, url: str = None, hide_url: bool = None, description: str = None, thumb_url: str = None, thumb_width: int = None, thumb_height: int = None, **kwargs*)

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

This object represents a Telegram InlineQueryResultArticle.

type

'article'.

Type `str`

id
Unique identifier for this result, 1-64 Bytes.

Type `str`

title
Title of the result.

Type `str`

input_message_content
Content of the message to be sent.

Type `telegram.InputMessageContent`

reply_markup
Optional. Inline keyboard attached to the message.

Type `telegram.ReplyMarkup`

url
Optional. URL of the result.

Type `str`

hide_url
Optional. Pass `True`, if you don't want the URL to be shown in the message.

Type `bool`

description
Optional. Short description of the result.

Type `str`

thumb_url
Optional. Url of the thumbnail for the result.

Type `str`

thumb_width
Optional. Thumbnail width.

Type `int`

thumb_height
Optional. Thumbnail height.

Type `int`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 Bytes.
- **title** (`str`) – Title of the result.
- **input_message_content** (`telegram.InputMessageContent`) – Content of the message to be sent.
- **reply_markup** (`telegram.ReplyMarkup`, optional) – Inline keyboard attached to the message
- **url** (`str`, optional) – URL of the result.
- **hide_url** (`bool`, optional) – Pass `True`, if you don't want the URL to be shown in the message.
- **description** (`str`, optional) – Short description of the result.
- **thumb_url** (`str`, optional) – Url of the thumbnail for the result.

- **thumb_width** (int, optional) – Thumbnail width.
- **thumb_height** (int, optional) – Thumbnail height.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InlineQueryResultAudio

```
class telegram.InlineQueryResultAudio(id: str, audio_url: str, title: str, performer:
                                     str = None, audio_duration: int = None,
                                     caption: str = None, reply_markup: ReplyMarkup = None, input_message_content:
                                     InputMessageContent = None, parse_mode:
                                     Union[str, telegram.utils.helpers.DefaultValue]
                                     = <telegram.utils.helpers.DefaultValue
                                     object>, caption_entities:
                                     Union[Tuple[telegram.messageentity.MessageEntity,
                                     ...], List[telegram.messageentity.MessageEntity]]
                                     = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to an mp3 audio file. By default, this audio file will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the audio.

type

'audio'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

audio_url

A valid URL for the audio file.

Type str

title

Title.

Type str

performer

Optional. Performer.

Type str

audio_duration

Optional. Audio duration in seconds.

Type str

caption

Optional. Caption, 0-1024 characters after entities parsing.

Type str

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type str

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of *parse_mode*.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the audio.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **audio_url** (`str`) – A valid URL for the audio file.
- **title** (`str`) – Title.
- **performer** (`str`, optional) – Performer.
- **audio_duration** (`str`, optional) – Audio duration in seconds.
- **caption** (`str`, optional) – Caption, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of *parse_mode*.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the audio.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedAudio

```
class telegram.InlineQueryResultCachedAudio(id: str, audio_file_id: str, caption: str
                                             = None, reply_markup: ReplyMarkup
                                             = None, input_message_content:
                                             InputMessageContent = None,
                                             parse_mode: Union[str, telegram.utils.helpers.DefaultValue]
                                             = <telegram.utils.helpers.DefaultValue
                                             object>, caption_entities:
                                             Union[Tuple[telegram.messageentity.MessageEntity,
                                             ...], List[telegram.messageentity.MessageEntity]]
                                             = None, **kwargs)
```

Bases: `telegram.inline.inlinequeryresult.InlineQueryResult`

Represents a link to an mp3 audio file stored on the Telegram servers. By default, this audio file will be sent by the user. Alternatively, you can use *input_message_content* to send a message with the specified content instead of the audio.

type

'audio'.

Type `str`

id

Unique identifier for this result, 1-64 bytes.

Type `str`

audio_file_id

A valid file identifier for the audio file.

Type `str`

caption

Optional. Caption, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the audio.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **audio_file_id** (`str`) – A valid file identifier for the audio file.
- **caption** (`str`, optional) – Caption, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the audio.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedDocument

```
class telegram.InlineQueryResultCachedDocument (id: str, title: str, document_file_id:
                                                str, description: str = None,
                                                caption: str = None, re-
                                                ply_markup: ReplyMarkup =
                                                None, input_message_content:
                                                InputMessageContent = None,
                                                parse_mode: Union[str, tele-
                                                gram.utils.helpers.DefaultValue]
                                                =
                                                <tele-
                                                gram.utils.helpers.DefaultValue
                                                object>, caption_entities:
                                                Union[Tuple[telegram.messageentity.MessageEntity,
                                                ...], List[telegram.messageentity.MessageEntity]]
                                                = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a file stored on the Telegram servers. By default, this file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the file.

type

‘document’.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

title

Title for the result.

Type str

document_file_id

A valid file identifier for the file.

Type str

description

Optional. Short description of the result.

Type str

caption

Optional. Caption of the document to be sent, 0-1024 characters after entities parsing.

Type str

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption.. See the constants in `telegram.ParseMode` for the available modes.

Type str

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type List[`telegram.MessageEntity`]

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the file.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **title** (`str`) – Title for the result.
- **document_file_id** (`str`) – A valid file identifier for the file.
- **description** (`str`, optional) – Short description of the result.
- **caption** (`str`, optional) – Caption of the document to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption.. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the file.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedGif

```
class telegram.InlineQueryResultCachedGif(id: str, gif_file_id: str, title: str
                                           = None, caption: str = None, re-
                                           ply_markup: ReplyMarkup = None,
                                           input_message_content: InputMessage-
                                           Content = None, parse_mode: Union[str,
                                           telegram.utils.helpers.DefaultValue] =
                                           <telegram.utils.helpers.DefaultValue
                                           object>, caption_entities:
                                           Union[Tuple[telegram.messageentity.MessageEntity,
                                           ...], List[telegram.messageentity.MessageEntity]]
                                           = None, **kwargs)
```

Bases: `telegram.inline.inlinequeryresult.InlineQueryResult`

Represents a link to an animated GIF file stored on the Telegram servers. By default, this animated GIF file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with specified content instead of the animation.

type

'gif'.

Type `str`

id

Unique identifier for this result, 1-64 bytes.

Type `str`

gif_file_id

A valid file identifier for the GIF file.

Type `str`

title

Optional. Title for the result.

Type `str`

caption

Optional. Caption of the GIF file to be sent, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the gif.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **gif_file_id** (`str`) – A valid file identifier for the GIF file.
- **title** (`str`, optional) – Title for the result. **caption** (`str`, optional):
- **caption** (`str`, optional) – Caption of the GIF file to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the gif.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedMpeg4Gif

```
class telegram.InlineQueryResultCachedMpeg4Gif(id: str, mpeg4_file_id: str, title:
                                                str = None, caption: str = None,
                                                reply_markup: ReplyMarkup =
                                                None, input_message_content:
                                                InputMessageContent = None,
                                                parse_mode: Union[str, tele-
                                                gram.utils.helpers.DefaultValue]
                                                = <tele-
                                                gram.utils.helpers.DefaultValue
                                                object>, caption_entities:
                                                Union[Tuple[telegram.messageentity.MessageEntity,
                                                ...], List[telegram.messageentity.MessageEntity]]
                                                = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a video animation (H.264/MPEG-4 AVC video without sound) stored on the Telegram servers. By default, this animated MPEG-4 file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the animation.

type

'mpeg4_gif'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

mpeg4_file_id

A valid file identifier for the MP4 file.

Type str

title

Optional. Title for the result.

Type str

caption

Optional. Caption of the MPEG-4 file to be sent, 0-1024 characters after entities parsing.

Type str

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type str

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type List[`telegram.MessageEntity`]

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the MPEG-4 file.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **mpeg4_file_id** (`str`) – A valid file identifier for the MP4 file.
- **title** (`str`, optional) – Title for the result.
- **caption** (`str`, optional) – Caption of the MPEG-4 file to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the MPEG-4 file.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

`telegram.InlineQueryResultCachedPhoto`

```
class telegram.InlineQueryResultCachedPhoto(id: str, photo_file_id: str, title: str = None, description: str = None, caption: str = None, reply_markup: ReplyMarkup = None, input_message_content: InputMessageContent = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, caption_entities: Union[Tuple[telegram.messageentity.MessageEntity, ...], List[telegram.messageentity.MessageEntity]] = None, **kwargs)
```

Bases: `telegram.inline.inlinequeryresult.InlineQueryResult`

Represents a link to a photo stored on the Telegram servers. By default, this photo will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the photo.

type
'photo'.

Type `str`

id
Unique identifier for this result, 1-64 bytes.

Type `str`

photo_file_id
A valid file identifier of the photo.

Type `str`

title
Optional. Title for the result.

Type `str`

description

Optional. Short description of the result.

Type `str`

caption

Optional. Caption of the photo to be sent, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the photo.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **photo_file_id** (`str`) – A valid file identifier of the photo.
- **title** (`str`, optional) – Title for the result.
- **description** (`str`, optional) – Short description of the result.
- **caption** (`str`, optional) – Caption of the photo to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the photo.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedSticker

```
class telegram.InlineQueryResultCachedSticker(id: str, sticker_file_id: str, reply_markup: ReplyMarkup = None, input_message_content: InputMessageContent = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a sticker stored on the Telegram servers. By default, this sticker will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the sticker.

type

'sticker'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

sticker_file_id

A valid file identifier of the sticker.

Type str

reply_markup

Optional. Inline keyboard attached to the message.

Type telegram.InlineKeyboardMarkup

input_message_content

Optional. Content of the message to be sent instead of the sticker.

Type telegram.InputMessageContent

Parameters

- **id** (str) – Unique identifier for this result, 1-64 bytes.
- **sticker_file_id** (str) – A valid file identifier of the sticker.
- **reply_markup** (telegram.InlineKeyboardMarkup, optional) – Inline keyboard attached to the message.
- **input_message_content** (telegram.InputMessageContent, optional) – Content of the message to be sent instead of the sticker.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedVideo

```
class telegram.InlineQueryResultCachedVideo(id: str, video_file_id: str, title: str, description: str = None, caption: str = None, reply_markup: ReplyMarkup = None, input_message_content: InputMessageContent = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, caption_entities: Union[Tuple[telegram.messageentity.MessageEntity, ...], List[telegram.messageentity.MessageEntity]] = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a video file stored on the Telegram servers. By default, this video file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the video.

type

'video'.

Type `str`

id

Unique identifier for this result, 1-64 bytes.

Type `str`

video_file_id

A valid file identifier for the video file.

Type `str`

title

Title for the result.

Type `str`

description

Optional. Short description of the result.

Type `str`

caption

Optional. Caption of the video to be sent, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the video.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **video_file_id** (`str`) – A valid file identifier for the video file.
- **title** (`str`) – Title for the result.
- **description** (`str`, optional) – Short description of the result.
- **caption** (`str`, optional) – Caption of the video to be sent, 0-1024 characters after entities parsing.

- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the video.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultCachedVoice

```
class telegram.InlineQueryResultCachedVoice (id: str, voice_file_id: str, title: str, caption: str = None, reply_markup: ReplyMarkup = None, input_message_content: InputMessageContent = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, caption_entities: Union[Tuple[telegram.messageentity.MessageEntity, ...], List[telegram.messageentity.MessageEntity]] = None, **kwargs)
```

Bases: `telegram.inline.inlinequeryresult.InlineQueryResult`

Represents a link to a voice message stored on the Telegram servers. By default, this voice message will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the voice message.

type

'voice'.

Type `str`

id

Unique identifier for this result, 1-64 bytes.

Type `str`

voice_file_id

A valid file identifier for the voice message.

Type `str`

title

Voice message title.

Type `str`

caption

Optional. Caption, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of *parse_mode*.

Type List[*telegram.MessageEntity*]

reply_markup

Optional. Inline keyboard attached to the message.

Type *telegram.InlineKeyboardMarkup*

input_message_content

Optional. Content of the message to be sent instead of the voice message.

Type *telegram.InputMessageContent*

Parameters

- **id** (*str*) – Unique identifier for this result, 1-64 bytes.
- **voice_file_id** (*str*) – A valid file identifier for the voice message.
- **title** (*str*) – Voice message title.
- **caption** (*str*, optional) – Caption, 0-1024 characters after entities parsing.
- **parse_mode** (*str*, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in *telegram.ParseMode* for the available modes.
- **caption_entities** (List[*telegram.MessageEntity*], optional) – List of special entities that appear in the caption, which can be specified instead of *parse_mode*.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – Inline keyboard attached to the message.
- **input_message_content** (*telegram.InputMessageContent*, optional) – Content of the message to be sent instead of the voice message.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

telegram.InlineQueryResultContact

```
class telegram.InlineQueryResultContact (id: str, phone_number: str, first_name: str,  
                                           last_name: str = None, reply_markup: Re-  
                                           plyMarkup = None, input_message_content:  
                                           InputMessageContent = None, thumb_url:  
                                           str = None, thumb_width: int = None,  
                                           thumb_height: int = None, vcard: str = None,  
                                           **kwargs)
```

Bases: *telegram.inline.inlinequeryresult.InlineQueryResult*

Represents a contact with a phone number. By default, this contact will be sent by the user. Alternatively, you can use *input_message_content* to send a message with the specified content instead of the contact.

type

'contact'.

Type *str*

id

Unique identifier for this result, 1-64 bytes.

Type *str*

phone_number

Contact's phone number.

Type `str`

first_name

Contact's first name.

Type `str`

last_name

Optional. Contact's last name.

Type `str`

vcard

Optional. Additional data about the contact in the form of a vCard, 0-2048 bytes.

Type `str`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the contact.

Type `telegram.InputMessageContent`

thumb_url

Optional. Url of the thumbnail for the result.

Type `str`

thumb_width

Optional. Thumbnail width.

Type `int`

thumb_height

Optional. Thumbnail height.

Type `int`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **phone_number** (`str`) – Contact's phone number.
- **first_name** (`str`) – Contact's first name.
- **last_name** (`str`, optional) – Contact's last name.
- **vcard** (`str`, optional) – Additional data about the contact in the form of a vCard, 0-2048 bytes.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the contact.
- **thumb_url** (`str`, optional) – Url of the thumbnail for the result.
- **thumb_width** (`int`, optional) – Thumbnail width.
- **thumb_height** (`int`, optional) – Thumbnail height.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultDocument

```
class telegram.InlineQueryResultDocument (id: str, document_url: str, title:
                                         str, mime_type: str, caption: str =
                                         None, description: str = None, re-
                                         ply_markup: ReplyMarkup = None,
                                         input_message_content: InputMessage-
                                         Content = None, thumb_url: str = None,
                                         thumb_width: int = None, thumb_height:
                                         int = None, parse_mode: Union[str,
                                         telegram.utils.helpers.DefaultValue] =
                                         <telegram.utils.helpers.DefaultValue
                                         object>, caption_entities:
                                         Union[Tuple[telegram.messageentity.MessageEntity,
                                         ...], List[telegram.messageentity.MessageEntity]]
                                         = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a file. By default, this file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the file. Currently, only .PDF and .ZIP files can be sent using this method.

type

‘document’.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

title

Title for the result.

Type str

caption

Optional. Caption of the document to be sent, 0-1024 characters after entities parsing.

Type str

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type str

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type List[`telegram.MessageEntity`]

document_url

A valid URL for the file.

Type str

mime_type

Mime type of the content of the file, either “application/pdf” or “application/zip”.

Type str

description

Optional. Short description of the result.

Type `str`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the file.

Type `telegram.InputMessageContent`

thumb_url

Optional. URL of the thumbnail (jpeg only) for the file.

Type `str`

thumb_width

Optional. Thumbnail width.

Type `int`

thumb_height

Optional. Thumbnail height.

Type `int`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **title** (`str`) – Title for the result.
- **caption** (`str`, optional) – Caption of the document to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **document_url** (`str`) – A valid URL for the file.
- **mime_type** (`str`) – Mime type of the content of the file, either “application/pdf” or “application/zip”.
- **description** (`str`, optional) – Short description of the result.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the file.
- **thumb_url** (`str`, optional) – URL of the thumbnail (jpeg only) for the file.
- **thumb_width** (`int`, optional) – Thumbnail width.
- **thumb_height** (`int`, optional) – Thumbnail height.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

`telegram.InlineQueryResultGame`

```
class telegram.InlineQueryResultGame (id: str, game_short_name: str, reply_markup: Re-  
plyMarkup = None, **kwargs)
```

Bases: `telegram.inline.inlinequeryresult.InlineQueryResult`

Represents a *telegram.Game*.

type

'game'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

game_short_name

Short name of the game.

Type str

reply_markup

Optional. Inline keyboard attached to the message.

Type *telegram.InlineKeyboardMarkup*

Parameters

- **id** (str) – Unique identifier for this result, 1-64 bytes.
- **game_short_name** (str) – Short name of the game.
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – Inline keyboard attached to the message.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InlineQueryResultGif

```
class telegram.InlineQueryResultGif(id: str, gif_url: str, thumb_url: str, gif_width: int = None, gif_height: int = None, title: str = None, caption: str = None, reply_markup: ReplyMarkup = None, input_message_content: InputMessageContent = None, gif_duration: int = None, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, thumb_mime_type: str = None, caption_entities: Union[Tuple[telegram.messageentity.MessageEntity, ...], List[telegram.messageentity.MessageEntity]] = None, **kwargs)
```

Bases: *telegram.inline.inlinequeryresult.InlineQueryResult*

Represents a link to an animated GIF file. By default, this animated GIF file will be sent by the user with optional caption. Alternatively, you can use *input_message_content* to send a message with the specified content instead of the animation.

type

'gif'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

gif_url

A valid URL for the GIF file. File size must not exceed 1MB.

Type str

gif_width

Optional. Width of the GIF.

Type `int`

gif_height

Optional. Height of the GIF.

Type `int`

gif_duration

Optional. Duration of the GIF.

Type `int`

thumb_url

URL of the static (JPEG or GIF) or animated (MPEG4) thumbnail for the result.

Type `str`

thumb_mime_type

Optional. MIME type of the thumbnail.

Type `str`

title

Optional. Title for the result.

Type `str`

caption

Optional. Caption of the GIF file to be sent, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in [`telegram.ParseMode`](#) for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of [`parse\_mode`](#).

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type [`telegram.InlineKeyboardMarkup`](#)

input_message_content

Optional. Content of the message to be sent instead of the GIF animation.

Type [`telegram.InputMessageContent`](#)

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **gif_url** (`str`) – A valid URL for the GIF file. File size must not exceed 1MB.
- **gif_width** (`int`, optional) – Width of the GIF.
- **gif_height** (`int`, optional) – Height of the GIF.
- **gif_duration** (`int`, optional) – Duration of the GIF
- **thumb_url** (`str`) – URL of the static (JPEG or GIF) or animated (MPEG4) thumbnail for the result.

- **thumb_mime_type** (*str*, optional) – MIME type of the thumbnail, must be one of 'image/jpeg', 'image/gif', or 'video/mp4'. Defaults to 'image/jpeg'.
- **title** (*str*, optional) – Title for the result.
- **caption** (*str*, optional) – Caption of the GIF file to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (*str*, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in [telegram.ParseMode](#) for the available modes.
- **caption_entities** (List[[telegram.MessageEntity](#)], optional) – List of special entities that appear in the caption, which can be specified instead of [parse_mode](#).
- **reply_markup** ([telegram.InlineKeyboardMarkup](#), optional) – Inline keyboard attached to the message.
- **input_message_content** ([telegram.InputMessageContent](#), optional) – Content of the message to be sent instead of the GIF animation.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

telegram.InlineQueryResultLocation

```
class telegram.InlineQueryResultLocation(id: str, latitude: float, longitude: float,
                                          title: str, live_period: int = None, re-
                                          ply_markup: ReplyMarkup = None, in-
                                          put_message_content: InputMessage-
                                          Content = None, thumb_url: str = None,
                                          thumb_width: int = None, thumb_height: int
                                          = None, horizontal_accuracy: float = None,
                                          heading: int = None, proximity_alert_radius:
                                          int = None, **kwargs)
```

Bases: `telegram.inline.inlinequeryresult.InlineQueryResult`

Represents a location on a map. By default, the location will be sent by the user. Alternatively, you can use [input_message_content](#) to send a message with the specified content instead of the location.

type

'location'.

Type `str`

id

Unique identifier for this result, 1-64 bytes.

Type `str`

latitude

Location latitude in degrees.

Type `float`

longitude

Location longitude in degrees.

Type `float`

title

Location title.

Type `str`

horizontal_accuracy

Optional. The radius of uncertainty for the location, measured in meters.

Type `float`

live_period

Optional. Period in seconds for which the location can be updated, should be between 60 and 86400.

Type `int`

heading

Optional. For live locations, a direction in which the user is moving, in degrees.

Type `int`

proximity_alert_radius

Optional. For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters.

Type `int`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the location.

Type `telegram.InputMessageContent`

thumb_url

Optional. Url of the thumbnail for the result.

Type `str`

thumb_width

Optional. Thumbnail width.

Type `int`

thumb_height

Optional. Thumbnail height.

Type `int`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **latitude** (`float`) – Location latitude in degrees.
- **longitude** (`float`) – Location longitude in degrees.
- **title** (`str`) – Location title.
- **horizontal_accuracy** (`float`, optional) – The radius of uncertainty for the location, measured in meters; 0-1500.
- **live_period** (`int`, optional) – Period in seconds for which the location can be updated, should be between 60 and 86400.
- **heading** (`int`, optional) – For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (`int`, optional) – For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.

- **input_message_content** (*telegram.InputMessageContent*, optional) – Content of the message to be sent instead of the location.
- **thumb_url** (*str*, optional) – Url of the thumbnail for the result.
- **thumb_width** (*int*, optional) – Thumbnail width.
- **thumb_height** (*int*, optional) – Thumbnail height.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

telegram.InlineQueryResultMpeg4Gif

```
class telegram.InlineQueryResultMpeg4Gif(id: str, mpeg4_url: str, thumb_url: str,
                                          mpeg4_width: int = None, mpeg4_height:
                                          int = None, title: str = None, caption: str
                                          = None, reply_markup: ReplyMarkup =
                                          None, input_message_content: InputMes-
                                          sageContent = None, mpeg4_duration:
                                          int = None, parse_mode: Union[str,
                                          telegram.utils.helpers.DefaultValue]
                                          =
                                          <telegram.utils.helpers.DefaultValue
                                          object>, thumb_mime_type:
                                          str = None, caption_entities:
                                          Union[Tuple[telegram.messageentity.MessageEntity,
                                          ...], List[telegram.messageentity.MessageEntity]]
                                          = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a video animation (H.264/MPEG-4 AVC video without sound). By default, this animated MPEG-4 file will be sent by the user with optional caption. Alternatively, you can use *input_message_content* to send a message with the specified content instead of the animation.

type

'mpeg4_gif'.

Type *str*

id

Unique identifier for this result, 1-64 bytes.

Type *str*

mpeg4_url

A valid URL for the MP4 file. File size must not exceed 1MB.

Type *str*

mpeg4_width

Optional. Video width.

Type *int*

mpeg4_height

Optional. Video height.

Type *int*

mpeg4_duration

Optional. Video duration.

Type *int*

thumb_url

URL of the static (JPEG or GIF) or animated (MPEG4) thumbnail for the result.

Type *str*

thumb_mime_type

Optional. MIME type of the thumbnail.

Type `str`

title

Optional. Title for the result.

Type `str`

caption

Optional. Caption of the MPEG-4 file to be sent, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the video animation.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **mpeg4_url** (`str`) – A valid URL for the MP4 file. File size must not exceed 1MB.
- **mpeg4_width** (`int`, optional) – Video width.
- **mpeg4_height** (`int`, optional) – Video height.
- **mpeg4_duration** (`int`, optional) – Video duration.
- **thumb_url** (`str`) – URL of the static thumbnail (jpeg or gif) for the result.
- **thumb_mime_type** (`str`) – Optional. MIME type of the thumbnail, must be one of 'image/jpeg', 'image/gif', or 'video/mp4'. Defaults to 'image/jpeg'.
- **title** (`str`, optional) – Title for the result.
- **caption** (`str`, optional) – Caption of the MPEG-4 file to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.

- **input_message_content** (*telegram.InputMessageContent*, optional) – Content of the message to be sent instead of the video animation.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InlineQueryResultPhoto

```
class telegram.InlineQueryResultPhoto(id: str, photo_url: str, thumb_url: str,
                                       photo_width: int = None, photo_height: int
                                       = None, title: str = None, description: str
                                       = None, caption: str = None, reply_markup:
                                       ReplyMarkup = None, input_message_content:
                                       InputMessageContent = None, parse_mode:
                                       Union[str, telegram.utils.helpers.DefaultValue]
                                       = <telegram.utils.helpers.DefaultValue
                                       object>, caption_entities:
                                       Union[Tuple[telegram.messageentity.MessageEntity,
                                       ...], List[telegram.messageentity.MessageEntity]]
                                       = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a photo. By default, this photo will be sent by the user with optional caption. Alternatively, you can use *input_message_content* to send a message with the specified content instead of the photo.

type

'photo'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

photo_url

A valid URL of the photo. Photo must be in jpeg format. Photo size must not exceed 5MB.

Type str

thumb_url

URL of the thumbnail for the photo.

Type str

photo_width

Optional. Width of the photo.

Type int

photo_height

Optional. Height of the photo.

Type int

title

Optional. Title for the result.

Type str

description

Optional. Short description of the result.

Type str

caption

Optional. Caption of the photo to be sent, 0-1024 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the photo.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **photo_url** (`str`) – A valid URL of the photo. Photo must be in jpeg format. Photo size must not exceed 5MB.
- **thumb_url** (`str`) – URL of the thumbnail for the photo.
- **photo_width** (`int`, optional) – Width of the photo.
- **photo_height** (`int`, optional) – Height of the photo.
- **title** (`str`, optional) – Title for the result.
- **description** (`str`, optional) – Short description of the result.
- **caption** (`str`, optional) – Caption of the photo to be sent, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the photo.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InlineQueryResultVenue

```
class telegram.InlineQueryResultVenue(id: str, latitude: float, longitude: float, title: str, address: str, foursquare_id: str = None, foursquare_type: str = None, reply_markup: ReplyMarkup = None, input_message_content: InputMessageContent = None, thumb_url: str = None, thumb_width: int = None, thumb_height: int = None, google_place_id: str = None, google_place_type: str = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a venue. By default, the venue will be sent by the user. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the venue.

Note: Foursquare details and Google Place details are mutually exclusive. However, this behaviour is undocumented and might be changed by Telegram.

type

'venue'.

Type `str`

id

Unique identifier for this result, 1-64 Bytes.

Type `str`

latitude

Latitude of the venue location in degrees.

Type `float`

longitude

Longitude of the venue location in degrees.

Type `float`

title

Title of the venue.

Type `str`

address

Address of the venue.

Type `str`

foursquare_id

Optional. Foursquare identifier of the venue if known.

Type `str`

foursquare_type

Optional. Foursquare type of the venue, if known.

Type `str`

google_place_id

Optional. Google Places identifier of the venue.

Type `str`

google_place_type

Optional. Google Places type of the venue.

Type `str`

reply_markup

Optional. Inline keyboard attached to the message.

Type *telegram.InlineKeyboardMarkup*

input_message_content

Optional. Content of the message to be sent instead of the venue.

Type *telegram.InputMessageContent*

thumb_url

Optional. Url of the thumbnail for the result.

Type *str*

thumb_width

Optional. Thumbnail width.

Type *int*

thumb_height

Optional. Thumbnail height.

Type *int*

Parameters

- **id** (*str*) – Unique identifier for this result, 1-64 Bytes.
- **latitude** (*float*) – Latitude of the venue location in degrees.
- **longitude** (*float*) – Longitude of the venue location in degrees.
- **title** (*str*) – Title of the venue.
- **address** (*str*) – Address of the venue.
- **foursquare_id** (*str*, optional) – Foursquare identifier of the venue if known.
- **foursquare_type** (*str*, optional) – Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (*str*, optional) – Google Places identifier of the venue.
- **google_place_type** (*str*, optional) – Google Places type of the venue. (See [supported types](#).)
- **reply_markup** (*telegram.InlineKeyboardMarkup*, optional) – Inline keyboard attached to the message.
- **input_message_content** (*telegram.InputMessageContent*, optional) – Content of the message to be sent instead of the location.
- **thumb_url** (*str*, optional) – Url of the thumbnail for the result.
- **thumb_width** (*int*, optional) – Thumbnail width.
- **thumb_height** (*int*, optional) – Thumbnail height.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

telegram.InlineQueryResultVideo

```
class telegram.InlineQueryResultVideo(id: str, video_url: str, mime_type: str,
                                     thumb_url: str, title: str, caption: str =
                                     None, video_width: int = None, video_height:
                                     int = None, video_duration: int = None,
                                     description: str = None, reply_markup: Re-
                                     plyMarkup = None, input_message_content:
                                     InputMessageContent = None, parse_mode:
                                     Union[str, telegram.utils.helpers.DefaultValue]
                                     = <telegram.utils.helpers.DefaultValue
                                     object>, caption_entities:
                                     Union[Tuple[telegram.messageentity.MessageEntity,
                                     ...], List[telegram.messageentity.MessageEntity]]
                                     = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a page containing an embedded video player or a video file. By default, this video file will be sent by the user with an optional caption. Alternatively, you can use `input_message_content` to send a message with the specified content instead of the video.

Note: If an `InlineQueryResultVideo` message contains an embedded video (e.g., YouTube), you must replace its content using `input_message_content`.

type

'video'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

video_url

A valid URL for the embedded video player or video file.

Type str

mime_type

Mime type of the content of video url, "text/html" or "video/mp4".

Type str

thumb_url

URL of the thumbnail (jpeg only) for the video.

Type str

title

Title for the result.

Type str

caption

Optional. Caption of the video to be sent, 0-1024 characters after entities parsing.

Type str

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.

Type str

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of *parse_mode*.

Type `List[telegram.MessageEntity]`

video_width

Optional. Video width.

Type `int`

video_height

Optional. Video height.

Type `int`

video_duration

Optional. Video duration in seconds.

Type `int`

description

Optional. Short description of the result.

Type `str`

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the video. This field is required if *InlineQueryResultVideo* is used to send an HTML-page as a result (e.g., a YouTube video).

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **video_url** (`str`) – A valid URL for the embedded video player or video file.
- **mime_type** (`str`) – Mime type of the content of video url, “text/html” or “video/mp4”.
- **thumb_url** (`str`) – URL of the thumbnail (jpeg only) for the video.
- **title** (`str`) – Title for the result.
- **caption** (`str`, optional) – Caption, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in *telegram.ParseMode* for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of *parse_mode*.
- **video_width** (`int`, optional) – Video width.
- **video_height** (`int`, optional) – Video height.
- **video_duration** (`int`, optional) – Video duration in seconds.
- **description** (`str`, optional) – Short description of the result.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.

- **input_message_content** (*telegram.InputMessageContent*, optional) – Content of the message to be sent instead of the video. This field is required if *InlineQueryResultVideo* is used to send an HTML-page as a result (e.g., a YouTube video).
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InlineQueryResultVoice

```
class telegram.InlineQueryResultVoice(id: str, voice_url: str, title: str, voice_duration:
                                     int = None, caption: str = None, reply_markup:
                                     ReplyMarkup = None, input_message_content:
                                     InputMessageContent = None, parse_mode:
                                     Union[str, telegram.utils.helpers.DefaultValue]
                                     = <telegram.utils.helpers.DefaultValue
                                     object>, caption_entities:
                                     Union[Tuple[telegram.messageentity.MessageEntity,
                                     ...], List[telegram.messageentity.MessageEntity]]
                                     = None, **kwargs)
```

Bases: telegram.inline.inlinequeryresult.InlineQueryResult

Represents a link to a voice recording in an .ogg container encoded with OPUS. By default, this voice recording will be sent by the user. Alternatively, you can use *input_message_content* to send a message with the specified content instead of the the voice message.

type

'voice'.

Type str

id

Unique identifier for this result, 1-64 bytes.

Type str

voice_url

A valid URL for the voice recording.

Type str

title

Recording title.

Type str

caption

Optional. Caption, 0-1024 characters after entities parsing.

Type str

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in *telegram.ParseMode* for the available modes.

Type str

caption_entities

Optional. List of special entities that appear in the caption, which can be specified instead of *parse_mode*.

Type List[*telegram.MessageEntity*]

voice_duration

Optional. Recording duration in seconds.

Type int

reply_markup

Optional. Inline keyboard attached to the message.

Type `telegram.InlineKeyboardMarkup`

input_message_content

Optional. Content of the message to be sent instead of the voice recording.

Type `telegram.InputMessageContent`

Parameters

- **id** (`str`) – Unique identifier for this result, 1-64 bytes.
- **voice_url** (`str`) – A valid URL for the voice recording.
- **title** (`str`) – Recording title.
- **caption** (`str`, optional) – Caption, 0-1024 characters after entities parsing.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in the media caption. See the constants in `telegram.ParseMode` for the available modes.
- **caption_entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **voice_duration** (`int`, optional) – Recording duration in seconds.
- **reply_markup** (`telegram.InlineKeyboardMarkup`, optional) – Inline keyboard attached to the message.
- **input_message_content** (`telegram.InputMessageContent`, optional) – Content of the message to be sent instead of the voice recording.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InputMessageContent**class telegram.InputMessageContent**

Bases: `telegram.base.TelegramObject`

Base class for Telegram InputMessageContent Objects.

See: `telegram.InputContactMessageContent`, `telegram.InputLocationMessageContent`, `telegram.InputTextMessageContent` and `telegram.InputVenueMessageContent` for more details.

telegram.InputTextMessageContent

```
class telegram.InputTextMessageContent (message_text: str, parse_mode: Union[str, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, disable_web_page_preview: Union[bool, telegram.utils.helpers.DefaultValue] = <telegram.utils.helpers.DefaultValue object>, entities: Union[Tuple[telegram.messageentity.MessageEntity, ...], List[telegram.messageentity.MessageEntity]] = None, **kwargs)
```

Bases: `telegram.inline.inputmessagecontent.InputMessageContent`

Represents the content of a text message to be sent as the result of an inline query.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `message_text` is equal.

message_text

Text of the message to be sent, 1-4096 characters after entities parsing.

Type `str`

parse_mode

Optional. Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in your bot's message. See the constants in `telegram.ParseMode` for the available modes.

Type `str`

entities

Optional. List of special entities that appear in the caption, which can be specified instead of `parse_mode`.

Type `List[telegram.MessageEntity]`

disable_web_page_preview

Optional. Disables link previews for links in the sent message.

Type `bool`

Parameters

- **message_text** (`str`) – Text of the message to be sent, 1-4096 characters after entities parsing. Also found as `telegram.constants.MAX_MESSAGE_LENGTH`.
- **parse_mode** (`str`, optional) – Send Markdown or HTML, if you want Telegram apps to show bold, italic, fixed-width text or inline URLs in your bot's message. See the constants in `telegram.ParseMode` for the available modes.
- **entities** (`List[telegram.MessageEntity]`, optional) – List of special entities that appear in the caption, which can be specified instead of `parse_mode`.
- **disable_web_page_preview** (`bool`, optional) – Disables link previews for links in the sent message.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.InputLocationMessageContent

```
class telegram.InputLocationMessageContent (latitude: float, longitude: float,
                                             live_period: int = None, horizon-
                                             tal_accuracy: float = None, heading: int
                                             = None, proximity_alert_radius: int =
                                             None, **kwargs)
```

Bases: `telegram.inline.inputmessagecontent.InputMessageContent`

Represents the content of a location message to be sent as the result of an inline query.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `latitude` and `longitude` are equal.

latitude

Latitude of the location in degrees.

Type `float`

longitude

Longitude of the location in degrees.

Type `float`

horizontal_accuracy

Optional. The radius of uncertainty for the location, measured in meters.

Type float

live_period

Optional. Period in seconds for which the location can be updated.

Type int

heading

Optional. For live locations, a direction in which the user is moving, in degrees.

Type int

proximity_alert_radius

Optional. For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters.

Type int

Parameters

- **latitude** (float) – Latitude of the location in degrees.
- **longitude** (float) – Longitude of the location in degrees.
- **horizontal_accuracy** (float, optional) – The radius of uncertainty for the location, measured in meters; 0-1500.
- **live_period** (int, optional) – Period in seconds for which the location can be updated, should be between 60 and 86400.
- **heading** (int, optional) – For live locations, a direction in which the user is moving, in degrees. Must be between 1 and 360 if specified.
- **proximity_alert_radius** (int, optional) – For live locations, a maximum distance for proximity alerts about approaching another chat member, in meters. Must be between 1 and 100000 if specified.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InputVenueMessageContent

```
class telegram.InputVenueMessageContent(latitude: float, longitude: float, title: str,  
address: str, foursquare_id: str = None,  
foursquare_type: str = None, google_place_id:  
str = None, google_place_type: str = None,  
**kwargs)
```

Bases: telegram.inline.inputmessagecontent.InputMessageContent

Represents the content of a venue message to be sent as the result of an inline query.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *latitude*, *longitude* and *title* are equal.

Note: Foursquare details and Google Pace details are mutually exclusive. However, this behaviour is undocumented and might be changed by Telegram.

latitude

Latitude of the location in degrees.

Type float

longitude

Longitude of the location in degrees.

Type float

title
Name of the venue.

Type str

address
Address of the venue.

Type str

foursquare_id
Optional. Foursquare identifier of the venue, if known.

Type str

foursquare_type
Optional. Foursquare type of the venue, if known.

Type str

google_place_id
Optional. Google Places identifier of the venue.

Type str

google_place_type
Optional. Google Places type of the venue.

Type str

Parameters

- **latitude** (float) – Latitude of the location in degrees.
- **longitude** (float) – Longitude of the location in degrees.
- **title** (str) – Name of the venue.
- **address** (str) – Address of the venue.
- **foursquare_id** (str, optional) – Foursquare identifier of the venue, if known.
- **foursquare_type** (str, optional) – Foursquare type of the venue, if known. (For example, “arts_entertainment/default”, “arts_entertainment/aquarium” or “food/icecream”.)
- **google_place_id** (str, optional) – Google Places identifier of the venue.
- **google_place_type** (str, optional) – Google Places type of the venue. (See [supported types](#).)
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.InputContactMessageContent

```
class telegram.InputContactMessageContent (phone_number: str, first_name: str,  
                                           last_name: str = None, vcard: str = None,  
                                           **kwargs)
```

Bases: telegram.inline.inputmessagecontent.InputMessageContent

Represents the content of a contact message to be sent as the result of an inline query.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `phone_number` is equal.

phone_number
Contact’s phone number.

Type `str`

first_name

Contact's first name.

Type `str`

last_name

Optional. Contact's last name.

Type `str`

vcard

Optional. Additional data about the contact in the form of a vCard, 0-2048 bytes.

Type `str`

Parameters

- **phone_number** (`str`) – Contact's phone number.
- **first_name** (`str`) – Contact's first name.
- **last_name** (`str`, optional) – Contact's last name.
- **vcard** (`str`, optional) – Additional data about the contact in the form of a vCard, 0-2048 bytes.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.ChosenInlineResult

```
class telegram.ChosenInlineResult(result_id: str, from_user: telegram.user.User, query: str, location: telegram.files.location.Location = None, inline_message_id: str = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

Represents a result of an inline query that was chosen by the user and sent to their chat partner.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `result_id` is equal.

Note: In Python `from` is a reserved word, use `from_user` instead.

result_id

The unique identifier for the result that was chosen.

Type `str`

from_user

The user that chose the result.

Type `telegram.User`

location

Optional. Sender location.

Type `telegram.Location`

inline_message_id

Optional. Identifier of the sent inline message.

Type `str`

query

The query that was used to obtain the result.

Type `str`

Parameters

- **result_id** (*str*) – The unique identifier for the result that was chosen.
- **from_user** (*telegram.User*) – The user that chose the result.
- **location** (*telegram.Location*, optional) – Sender location, only for bots that require user location.
- **inline_message_id** (*str*, optional) – Identifier of the sent inline message. Available only if there is an inline keyboard attached to the message. Will be also received in callback queries and can be used to edit the message.
- **query** (*str*) – The query that was used to obtain the result.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

Note: It is necessary to enable inline feedback via [@Botfather](#) in order to receive these objects in updates.

3.2.55 Payments

telegram.LabeledPrice

class telegram.LabeledPrice (*label: str, amount: int, **kwargs*)

Bases: telegram.base.TelegramObject

This object represents a portion of the price for goods or services.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *label* and *amount* are equal.

label

Portion label.

Type *str*

amount

Price of the product in the smallest units of the currency.

Type *int*

Parameters

- **label** (*str*) – Portion label.
- **amount** (*int*) – Price of the product in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass `amount = 145`. See the `exp` parameter in [currencies.json](#), it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

telegram.Invoice

class telegram.Invoice (*title: str, description: str, start_parameter: str, currency: str, total_amount: int, **kwargs*)

Bases: telegram.base.TelegramObject

This object contains basic information about an invoice.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *title*, *description*, *start_parameter*, *currency* and *total_amount* are equal.

title

Product name.

Type `str`

description

Product description.

Type `str`

start_parameter

Unique bot deep-linking parameter.

Type `str`

currency

Three-letter ISO 4217 currency code.

Type `str`

total_amount

Total price in the smallest units of the currency.

Type `int`

Parameters

- **title** (`str`) – Product name.
- **description** (`str`) – Product description.
- **start_parameter** (`str`) – Unique bot deep-linking parameter that can be used to generate this invoice.
- **currency** (`str`) – Three-letter ISO 4217 currency code.
- **total_amount** (`int`) – Total price in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass `amount = 145`. See the `exp` parameter in [currencies.json](#), it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.ShippingAddress

```
class telegram.ShippingAddress(country_code: str, state: str, city: str, street_line1: str,  
                                street_line2: str, post_code: str, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a Telegram `ShippingAddress`.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `country_code`, `state`, `city`, `street_line1`, `street_line2` and `post_cod` are equal.

country_code

ISO 3166-1 alpha-2 country code.

Type `str`

state

State, if applicable.

Type `str`

city

City.

Type `str`

street_line1

First line for the address.

Type `str`

street_line2

Second line for the address.

Type `str`

post_code

Address post code.

Type `str`

Parameters

- **country_code** (`str`) – ISO 3166-1 alpha-2 country code.
- **state** (`str`) – State, if applicable.
- **city** (`str`) – City.
- **street_line1** (`str`) – First line for the address.
- **street_line2** (`str`) – Second line for the address.
- **post_code** (`str`) – Address post code.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.OrderInfo

```
class telegram.OrderInfo(name: str = None, phone_number: str = None, email: str = None,  
                           shipping_address: str = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents information about an order.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *name*, *phone_number*, *email* and *shipping_address* are equal.

name

Optional. User name.

Type `str`

phone_number

Optional. User's phone number.

Type `str`

email

Optional. User email.

Type `str`

shipping_address

Optional. User shipping address.

Type `telegram.ShippingAddress`

Parameters

- **name** (`str`, optional) – User name.
- **phone_number** (`str`, optional) – User's phone number.
- **email** (`str`, optional) – User email.

- **shipping_address** (*telegram.ShippingAddress*, optional) – User shipping address.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.ShippingOption

class telegram.**ShippingOption** (*id: str, title: str, prices: List[LabeledPrice], **_kwargs*)

Bases: telegram.base.TelegramObject

This object represents one shipping option.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *id* is equal.

id

Shipping option identifier.

Type str

title

Option title.

Type str

prices

List of price portions.

Type List[*telegram.LabeledPrice*]

Parameters

- **id** (str) – Shipping option identifier.
- **title** (str) – Option title.
- **prices** (List[*telegram.LabeledPrice*]) – List of price portions.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.SuccessfulPayment

class telegram.**SuccessfulPayment** (*currency: str, total_amount: int, invoice_payload: str, telegram_payment_charge_id: str, provider_payment_charge_id: str, shipping_option_id: str = None, order_info: telegram.payment.orderinfo.OrderInfo = None, **_kwargs*)

Bases: telegram.base.TelegramObject

This object contains basic information about a successful payment.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *telegram_payment_charge_id* and *provider_payment_charge_id* are equal.

currency

Three-letter ISO 4217 currency code.

Type str

total_amount

Total price in the smallest units of the currency.

Type int

invoice_payload

Bot specified invoice payload.

Type `str`

shipping_option_id

Optional. Identifier of the shipping option chosen by the user.

Type `str`

order_info

Optional. Order info provided by the user.

Type `telegram.OrderInfo`

telegram_payment_charge_id

Telegram payment identifier.

Type `str`

provider_payment_charge_id

Provider payment identifier.

Type `str`

Parameters

- **currency** (`str`) – Three-letter ISO 4217 currency code.
- **total_amount** (`int`) – Total price in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass `amount = 145`. See the `exp` parameter in [currencies.json](#), it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).
- **invoice_payload** (`str`) – Bot specified invoice payload.
- **shipping_option_id** (`str`, optional) – Identifier of the shipping option chosen by the user.
- **order_info** (`telegram.OrderInfo`, optional) – Order info provided by the user.
- **telegram_payment_charge_id** (`str`) – Telegram payment identifier.
- **provider_payment_charge_id** (`str`) – Provider payment identifier.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.ShippingQuery

```
class telegram.ShippingQuery (id: str, from_user: telegram.user.User, invoice_payload: str, shipping_address: telegram.payment.shippingaddress.ShippingAddress, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object contains information about an incoming shipping query.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `id` is equal.

Note:

- In Python `from` is a reserved word, use `from_user` instead.
-

id

Unique query identifier.

Type `str`

from_user

User who sent the query.

Type `telegram.User`

invoice_payload

Bot specified invoice payload.

Type `str`

shipping_address

User specified shipping address.

Type `telegram.ShippingAddress`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **id** (`str`) – Unique query identifier.
- **from_user** (`telegram.User`) – User who sent the query.
- **invoice_payload** (`str`) – Bot specified invoice payload.
- **shipping_address** (`telegram.ShippingAddress`) – User specified shipping address.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

answer (**args*, ***kwargs*) → `bool`

Shortcut for:

```
bot.answer_shipping_query(update.shipping_query.id, *args, **kwargs)
```

Parameters

- **ok** (`bool`) – Specify `True` if delivery to the specified address is possible and `False` if there are any problems (for example, if delivery to the specified address is not possible).
- **shipping_options** (`List[telegram.ShippingOption]`, optional) – Required if `ok` is `True`. A JSON-serialized array of available shipping options.
- **error_message** (`str`, optional) – Required if `ok` is `False`. Error message in human readable form that explains why it is impossible to complete the order (e.g. “Sorry, delivery to your desired address is unavailable”). Telegram will display this message to the user.

telegram.PreCheckoutQuery

```
class telegram.PreCheckoutQuery (id: str, from_user: telegram.user.User, currency: str, total_amount: int, invoice_payload: str, shipping_option_id: str = None, order_info: telegram.payment.orderinfo.OrderInfo = None, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object contains information about an incoming pre-checkout query.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *id* is equal.

Note:

- In Python *from* is a reserved word, use *from_user* instead.
-

id

Unique query identifier.

Type `str`

from_user

User who sent the query.

Type `telegram.User`

currency

Three-letter ISO 4217 currency code.

Type `str`

total_amount

Total price in the smallest units of the currency.

Type `int`

invoice_payload

Bot specified invoice payload.

Type `str`

shipping_option_id

Optional. Identifier of the shipping option chosen by the user.

Type `str`

order_info

Optional. Order info provided by the user.

Type `telegram.OrderInfo`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **id** (`str`) – Unique query identifier.
- **from_user** (`telegram.User`) – User who sent the query.
- **currency** (`str`) – Three-letter ISO 4217 currency code.
- **total_amount** (`int`) – Total price in the smallest units of the currency (integer, not float/double). For example, for a price of US\$ 1.45 pass `amount = 145`. See the `exp` parameter in `currencies.json`, it shows the number of digits past the decimal point for each currency (2 for the majority of currencies).
- **invoice_payload** (`str`) – Bot specified invoice payload.
- **shipping_option_id** (`str`, optional) – Identifier of the shipping option chosen by the user.
- **order_info** (`telegram.OrderInfo`, optional) – Order info provided by the user.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

answer (*args, **kwargs) → bool

Shortcut for:

```
bot.answer_pre_checkout_query(update.pre_checkout_query.id, *args,   
↪ **kwargs)
```

Parameters

- **ok** (bool) – Specify `True` if everything is alright (goods are available, etc.) and the bot is ready to proceed with the order. Use `False` if there are any problems.
- **error_message** (str, optional) – Required if `ok` is `False`. Error message in human readable form that explains the reason for failure to proceed with the check-out (e.g. “Sorry, somebody just bought the last of our amazing black T-shirts while you were busy filling out your payment details. Please choose a different color or garment!”). Telegram will display this message to the user.
- ****kwargs** (dict) – Arbitrary keyword arguments.

3.2.56 Games

telegram.Game

```
class telegram.Game(title: str, description: str, photo: List[telegram.files.photosize.PhotoSize],  
                    text: str = None, text_entities: List[telegram.messageentity.MessageEntity] =  
                    None, animation: telegram.files.animation.Animation = None, **kwargs)
```

Bases: telegram.base.TelegramObject

This object represents a game. Use [BotFather](#) to create and edit games, their short names will act as unique identifiers.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *title*, *description* and *photo* are equal.

title

Title of the game.

Type str

description

Description of the game.

Type str

photo

Photo that will be displayed in the game message in chats.

Type List[[telegram.PhotoSize](#)]

text

Optional. Brief description of the game or high scores included in the game message. Can be automatically edited to include current high scores for the game when the bot calls [telegram.Bot.set_game_score\(\)](#), or manually edited using [telegram.Bot.edit_message_text\(\)](#).

Type str

text_entities

Optional. Special entities that appear in text, such as usernames, URLs, bot commands, etc.

Type List[[telegram.MessageEntity](#)]

animation

Optional. Animation that will be displayed in the game message in chats. Upload via [BotFather](#).

Type [telegram.Animation](#)

Parameters

- **title** (`str`) – Title of the game.
- **description** (`str`) – Description of the game.
- **photo** (`List[telegram.PhotoSize]`) – Photo that will be displayed in the game message in chats.
- **text** (`str`, optional) – Brief description of the game or high scores included in the game message. Can be automatically edited to include current high scores for the game when the bot calls `telegram.Bot.set_game_score()`, or manually edited using `telegram.Bot.edit_message_text()`. 1-4096 characters. Also found as `telegram.constants.MAX_MESSAGE_LENGTH`.
- **text_entities** (`List[telegram.MessageEntity]`, optional) – Special entities that appear in text, such as usernames, URLs, bot commands, etc.
- **animation** (`telegram.Animation`, optional) – Animation that will be displayed in the game message in chats. Upload via [BotFather](#).

parse_text_entities (*types: List[str] = None*) → `Dict[telegram.messageentity.MessageEntity, str]`

Returns a dict that maps `telegram.MessageEntity` to `str`. It contains entities from this message filtered by their `type` attribute as the key, and the text that each entity belongs to as the value of the dict.

Note: This method should always be used instead of the `text_entities` attribute, since it calculates the correct substring from the message text based on UTF-16 codepoints. See [parse_text_entity](#) for more info.

Parameters types (`List[str]`, optional) – List of `MessageEntity` types as strings. If the `type` attribute of an entity is contained in this list, it will be returned. Defaults to `telegram.MessageEntity.ALL_TYPES`.

Returns A dictionary of entities mapped to the text that belongs to them, calculated based on UTF-16 codepoints.

Return type `Dict[telegram.MessageEntity, str]`

parse_text_entity (*entity: telegram.messageentity.MessageEntity*) → `str`

Returns the text from a given `telegram.MessageEntity`.

Note: This method is present because Telegram calculates the offset and length in UTF-16 codepoint pairs, which some versions of Python don't handle automatically. (That is, you can't just slice `Message.text` with the offset and length.)

Parameters entity (`telegram.MessageEntity`) – The entity to extract the text from. It must be an entity that belongs to this message.

Returns The text of the given entity.

Return type `str`

Raises `RuntimeError` – If this game has no text.

telegram.Callbackgame

class `telegram.CallbackGame`

Bases: `telegram.base.TelegramObject`

A placeholder, currently holds no information. Use BotFather to set up your game.

telegram.GameHighScore

class telegram.**GameHighScore** (*position: int, user: telegram.user.User, score: int*)

Bases: telegram.base.TelegramObject

This object represents one row of the high scores table for a game.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *position*, *user* and *score* are equal.

position

Position in high score table for the game.

Type int

user

User.

Type *telegram.User*

score

Score.

Type int

Parameters

- **position** (int) – Position in high score table for the game.
- **user** (*telegram.User*) – User.
- **score** (int) – Score.

3.2.57 Passport

telegram.PassportElementError

class telegram.**PassportElementError** (*source: str, type: str, message: str, **kwargs*)

Bases: telegram.base.TelegramObject

Baseclass for the PassportElementError* classes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their *source* and *type* are equal.

source

Error source.

Type str

type

The section of the user's Telegram Passport which has the error.

Type str

message

Error message.

Type str

Parameters

- **source** (str) – Error source.
- **type** (str) – The section of the user's Telegram Passport which has the error.

- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.PassportElementErrorFile

```
class telegram.PassportElementErrorFile(type: str, file_hash: str, message: str,  
                                         **kwargs)
```

Bases: telegram.passport.passportelementerrors.PassportElementError

Represents an issue with a document scan. The error is considered resolved when the file with the document scan changes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their source, *type*, *file_hash*, *data_hash* and *message* are equal.

type

The section of the user's Telegram Passport which has the issue, one of "utility_bill", "bank_statement", "rental_agreement", "passport_registration", "temporary_registration".

Type str

file_hash

Base64-encoded file hash.

Type str

message

Error message.

Type str

Parameters

- **type** (str) – The section of the user's Telegram Passport which has the issue, one of "utility_bill", "bank_statement", "rental_agreement", "passport_registration", "temporary_registration".
- **file_hash** (str) – Base64-encoded file hash.
- **message** (str) – Error message.
- ****kwargs** (dict) – Arbitrary keyword arguments.

telegram.PassportElementErrorReverseSide

```
class telegram.PassportElementErrorReverseSide(type: str, file_hash: str, message:  
                                                str, **kwargs)
```

Bases: telegram.passport.passportelementerrors.PassportElementError

Represents an issue with the front side of a document. The error is considered resolved when the file with the reverse side of the document changes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their source, *type*, *file_hash*, *data_hash* and *message* are equal.

type

The section of the user's Telegram Passport which has the issue, one of "passport", "driver_license", "identity_card", "internal_passport".

Type str

file_hash

Base64-encoded hash of the file with the reverse side of the document.

Type str

message

Error message.

Type `str`

Parameters

- **type** (`str`) – The section of the user’s Telegram Passport which has the issue, one of “driver_license”, “identity_card”.
- **file_hash** (`str`) – Base64-encoded hash of the file with the reverse side of the document.
- **message** (`str`) – Error message.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.PassportElementErrorFrontSide

```
class telegram.PassportElementErrorFrontSide (type: str, file_hash: str, message: str,  
                                              **kwargs)
```

Bases: telegram.passport.passportelementerrors.PassportElementError

Represents an issue with the front side of a document. The error is considered resolved when the file with the front side of the document changes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their source, `type`, `file_hash`, `data_hash` and `message` are equal.

type

The section of the user’s Telegram Passport which has the issue, one of “passport”, “driver_license”, “identity_card”, “internal_passport”.

Type `str`

file_hash

Base64-encoded hash of the file with the front side of the document.

Type `str`

message

Error message.

Type `str`

Parameters

- **type** (`str`) – The section of the user’s Telegram Passport which has the issue, one of “passport”, “driver_license”, “identity_card”, “internal_passport”.
- **file_hash** (`str`) – Base64-encoded hash of the file with the front side of the document.
- **message** (`str`) – Error message.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.PassportElementErrorFiles

```
class telegram.PassportElementErrorFiles (type: str, file_hashes: str, message: str,  
                                          **kwargs)
```

Bases: telegram.passport.passportelementerrors.PassportElementError

Represents an issue with a list of scans. The error is considered resolved when the file with the document scan changes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their source, `type`, `file_hashes`, `data_hash` and `message` are equal.

type

The section of the user's Telegram Passport which has the issue, one of "utility_bill", "bank_statement", "rental_agreement", "passport_registration", "temporary_registration".

Type `str`

file_hashes

List of base64-encoded file hashes.

Type `List[str]`

message

Error message.

Type `str`

Parameters

- **type** (`str`) – The section of the user's Telegram Passport which has the issue, one of "utility_bill", "bank_statement", "rental_agreement", "passport_registration", "temporary_registration".
- **file_hashes** (`List[str]`) – List of base64-encoded file hashes.
- **message** (`str`) – Error message.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

telegram.PassportElementErrorDataField

```
class telegram.PassportElementErrorDataField(type: str, field_name: str, data_hash:  
                                              str, message: str, **kwargs)
```

Bases: `telegram.passport.passportelementerrors.PassportElementError`

Represents an issue in one of the data fields that was provided by the user. The error is considered resolved when the field's value changes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their source, `type`, `field_name`, `data_hash` and `message` are equal.

type

The section of the user's Telegram Passport which has the error, one of "personal_details", "passport", "driver_license", "identity_card", "internal_passport", "address".

Type `str`

field_name

Name of the data field which has the error.

Type `str`

data_hash

Base64-encoded data hash.

Type `str`

message

Error message.

Type `str`

Parameters

- **type** (`str`) – The section of the user's Telegram Passport which has the error, one of "personal_details", "passport", "driver_license", "identity_card", "internal_passport", "address".
- **field_name** (`str`) – Name of the data field which has the error.

- **data_hash** (*str*) – Base64-encoded data hash.
- **message** (*str*) – Error message.
- ****kwargs** (*dict*) – Arbitrary keyword arguments.

telegram.Credentials

```
class telegram.Credentials(secure_data: SecureData, nonce: str, bot: Bot = None,  
                           **kwargs)  
    Bases: telegram.base.TelegramObject  
  
    secure_data  
        Credentials for encrypted data  
  
        Type telegram.SecureData  
  
    nonce  
        Bot-specified nonce  
  
        Type str
```

telegram.DataCredentials

```
class telegram.DataCredentials(data_hash: str, secret: str, **kwargs)  
    Bases: telegram.passport.credentials._CredentialsBase  
  
    These credentials can be used to decrypt encrypted data from the data field in EncryptedPassportData.  
  
    Parameters  
  
    • data_hash (str) – Checksum of encrypted data  
    • secret (str) – Secret of encrypted data  
  
    hash  
        Checksum of encrypted data  
  
        Type str  
  
    secret  
        Secret of encrypted data  
  
        Type str
```

telegram.SecureData

```
class telegram.SecureData(personal_details: SecureValue = None, passport: SecureValue  
                          = None, internal_passport: SecureValue = None, driver_license:  
                          SecureValue = None, identity_card: SecureValue = None, ad-  
                          dress: SecureValue = None, utility_bill: SecureValue = None,  
                          bank_statement: SecureValue = None, rental_agreement: Se-  
                          cureValue = None, passport_registration: SecureValue = None,  
                          temporary_registration: SecureValue = None, bot: Bot = None,  
                          **kwargs)  
    Bases: telegram.base.TelegramObject  
  
    This object represents the credentials that were used to decrypt the encrypted data. All fields are optional  
    and depend on fields that were requested.  
  
    personal_details  
        Credentials for encrypted personal details.  
  
        Type telegram.SecureValue, optional
```

passport

Credentials for encrypted passport.

Type telegram.SecureValue, optional

internal_passport

Credentials for encrypted internal passport.

Type telegram.SecureValue, optional

driver_license

Credentials for encrypted driver license.

Type telegram.SecureValue, optional

identity_card

Credentials for encrypted ID card

Type telegram.SecureValue, optional

address

Credentials for encrypted residential address.

Type telegram.SecureValue, optional

utility_bill

Credentials for encrypted utility bill.

Type telegram.SecureValue, optional

bank_statement

Credentials for encrypted bank statement.

Type telegram.SecureValue, optional

rental_agreement

Credentials for encrypted rental agreement.

Type telegram.SecureValue, optional

passport_registration

Credentials for encrypted registration from internal passport.

Type telegram.SecureValue, optional

temporary_registration

Credentials for encrypted temporary registration.

Type telegram.SecureValue, optional

telegram.FileCredentials

class telegram.**FileCredentials** (*file_hash: str, secret: str, **kwargs*)

Bases: telegram.passport.credentials._CredentialsBase

These credentials can be used to decrypt encrypted files from the front_side, reverse_side, selfie and files fields in EncryptedPassportData.

Parameters

- **file_hash** (*str*) – Checksum of encrypted file
- **secret** (*str*) – Secret of encrypted file

hash

Checksum of encrypted file

Type *str*

secret

Secret of encrypted file

Type `str`

telegram.IdDocumentData

```
class telegram.IdDocumentData (document_no: str, expiry_date: str, bot: Bot = None,  
                                **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents the data of an identity document.

document_no

Document number.

Type `str`

expiry_date

Optional. Date of expiry, in DD.MM.YYYY format.

Type `str`

telegram.PersonalDetails

```
class telegram.PersonalDetails (first_name: str, last_name: str, birth_date: str, gen-  
                                der: str, country_code: str, residence_country_code: str,  
                                first_name_native: str = None, last_name_native: str =  
                                None, middle_name: str = None, middle_name_native: str  
                                = None, bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents personal details.

first_name

First Name.

Type `str`

middle_name

Optional. First Name.

Type `str`

last_name

Last Name.

Type `str`

birth_date

Date of birth in DD.MM.YYYY format.

Type `str`

gender

Gender, male or female.

Type `str`

country_code

Citizenship (ISO 3166-1 alpha-2 country code).

Type `str`

residence_country_code

Country of residence (ISO 3166-1 alpha-2 country code).

Type `str`

first_name_native

First Name in the language of the user's country of residence.

Type `str`

middle_name_native

Optional. Middle Name in the language of the user's country of residence.

Type `str`

last_name_native

Last Name in the language of the user's country of residence.

Type `str`

telegram.ResidentialAddress

```
class telegram.ResidentialAddress (street_line1: str, street_line2: str, city: str, state: str,  
                                   country_code: str, post_code: str, bot: Bot = None,  
                                   **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a residential address.

street_line1

First line for the address.

Type `str`

street_line2

Optional. Second line for the address.

Type `str`

city

City.

Type `str`

state

Optional. State.

Type `str`

country_code

ISO 3166-1 alpha-2 country code.

Type `str`

post_code

Address post code.

Type `str`

telegram.PassportData

```
class telegram.PassportData (data: List[telegram.passport.encryptedpassportelement.EncryptedPassportElement],  
                             credentials: telegram.passport.credentials.EncryptedCredentials,  
                             bot: Bot = None, **kwargs)
```

Bases: `telegram.base.TelegramObject`

Contains information about Telegram Passport data shared with the bot by the user.

data

Array with encrypted information about documents and other Telegram Passport elements that was shared with the bot.

Type `List[telegram.EncryptedPassportElement]`

credentials

Encrypted credentials.

Type `telegram.EncryptedCredentials`

bot

The Bot to use for instance methods.

Type `telegram.Bot`, optional

Parameters

- **data** (List[`telegram.EncryptedPassportElement`]) – Array with encrypted information about documents and other Telegram Passport elements that was shared with the bot.
- **credentials** (`telegram.EncryptedCredentials`) – Encrypted credentials.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (dict) – Arbitrary keyword arguments.

Note: To be able to decrypt this object, you must pass your `private_key` to either `telegram.Updater` or `telegram.Bot`. Decrypted data is then found in `decrypted_data` and the payload can be found in `decrypted_credentials`'s attribute `telegram.Credentials.payload`.

decrypted_credentials

Lazily decrypt and return credentials that were used to decrypt the data. This object also contains the user specified payload as `decrypted_data.payload`.

Raises `telegram.TelegramDecryptionError` – Decryption failed. Usually due to bad private/public key but can also suggest malformed/tampered data.

Type `telegram.Credentials`

decrypted_data

Lazily decrypt and return information about documents and other Telegram Passport elements which were shared with the bot.

Raises `telegram.TelegramDecryptionError` – Decryption failed. Usually due to bad private/public key but can also suggest malformed/tampered data.

Type List[`telegram.EncryptedPassportElement`]

telegram.PassportFile

```
class telegram.PassportFile(file_id: str, file_unique_id: str, file_date: int, file_size: int =
                             None, bot: Bot = None, credentials: FileCredentials = None,
                             **kwargs)
```

Bases: `telegram.base.TelegramObject`

This object represents a file uploaded to Telegram Passport. Currently all Telegram Passport files are in JPEG format when decrypted and don't exceed 10MB.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `file_unique_id` is equal.

file_id

Identifier for this file.

Type `str`

file_unique_id

Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.

Type `str`

file_size

File size.

Type `int`

file_date

Unix time when the file was uploaded.

Type `int`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **file_id** (`str`) – Identifier for this file, which can be used to download or reuse the file.
- **file_unique_id** (`str`) – Unique identifier for this file, which is supposed to be the same over time and for different bots. Can't be used to download or reuse the file.
- **file_size** (`int`) – File size.
- **file_date** (`int`) – Unix time when the file was uploaded.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

get_file (*timeout*: `int = None`, *api_kwargs*: `Dict[str, Any] = None`) → `File`

Wrapper over `telegram.Bot.get_file`. Will automatically assign the correct credentials to the returned `telegram.File` if originating from `telegram.PassportData.decrypted_data`.

Parameters

- **timeout** (`int | float`, optional) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **api_kwargs** (`dict`, optional) – Arbitrary keyword arguments to be passed to the Telegram API.

Returns `telegram.File`

Raises `telegram.TelegramError`

telegram.EncryptedPassportElement

```
class telegram.EncryptedPassportElement (type: str, data: telegram.passport.data.PersonalDetails
                                         = None, phone_number: str =
                                         None, email: str = None, files:
                                         List[telegram.passport.passportfile.PassportFile]
                                         = None, front_side: telegram.
                                         passport.passportfile.PassportFile
                                         = None, reverse_side: telegram.
                                         passport.passportfile.PassportFile
                                         = None, selfie: telegram.
                                         passport.passportfile.PassportFile
                                         = None, translation:
                                         List[telegram.passport.passportfile.PassportFile]
                                         = None, hash: str = None, bot: Bot = None,
                                         credentials: Credentials = None, **kwargs)
```

Bases: telegram.base.TelegramObject

Contains information about documents or other Telegram Passport elements shared with the bot by the user. The data has been automatically decrypted by python-telegram-bot.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `type`, `data`, `phone_number`, `email`, `files`, `front_side`, `reverse_side` and `selfie` are equal.

type

Element type. One of “personal_details”, “passport”, “driver_license”, “identity_card”, “internal_passport”, “address”, “utility_bill”, “bank_statement”, “rental_agreement”, “passport_registration”, “temporary_registration”, “phone_number”, “email”.

Type `str`

data

Optional. Decrypted or encrypted data, available for “personal_details”, “passport”, “driver_license”, “identity_card”, “identity_passport” and “address” types.

Type `telegram.PersonalDetails` | `telegram.IdDocument` | `telegram.ResidentialAddress` | `str`

phone_number

Optional. User’s verified phone number, available only for “phone_number” type.

Type `str`

email

Optional. User’s verified email address, available only for “email” type.

Type `str`

files

Optional. Array of encrypted/decrypted files with documents provided by the user, available for “utility_bill”, “bank_statement”, “rental_agreement”, “passport_registration” and “temporary_registration” types.

Type `List[telegram.PassportFile]`

front_side

Optional. Encrypted/decrypted file with the front side of the document, provided by the user. Available for “passport”, “driver_license”, “identity_card” and “internal_passport”.

Type `telegram.PassportFile`

reverse_side

Optional. Encrypted/decrypted file with the reverse side of the document, provided by the user. Available for “driver_license” and “identity_card”.

Type `telegram.PassportFile`

selfie

Optional. Encrypted/decrypted file with the selfie of the user holding a document, provided by the user; available for “passport”, “driver_license”, “identity_card” and “internal_passport”.

Type `telegram.PassportFile`

translation

Optional. Array of encrypted/decrypted files with translated versions of documents provided by the user. Available if requested for “passport”, “driver_license”, “identity_card”, “internal_passport”, “utility_bill”, “bank_statement”, “rental_agreement”, “passport_registration” and “temporary_registration” types.

Type `List[telegram.PassportFile]`

hash

Base64-encoded element hash for using in `telegram.PassportElementErrorUnspecified`.

Type `str`

bot

Optional. The Bot to use for instance methods.

Type `telegram.Bot`

Parameters

- **type** (`str`) – Element type. One of “personal_details”, “passport”, “driver_license”, “identity_card”, “internal_passport”, “address”, “utility_bill”, “bank_statement”, “rental_agreement”, “passport_registration”, “temporary_registration”, “phone_number”, “email”.
- **data** (`telegram.PersonalDetails` | `telegram.IdDocument` | `telegram.ResidentialAddress` | `str`, optional) – Decrypted or encrypted data, available for “personal_details”, “passport”, “driver_license”, “identity_card”, “identity_passport” and “address” types.
- **phone_number** (`str`, optional) – User’s verified phone number, available only for “phone_number” type.
- **email** (`str`, optional) – User’s verified email address, available only for “email” type.
- **files** (`List[telegram.PassportFile]`, optional) – Array of encrypted/decrypted files with documents provided by the user, available for “utility_bill”, “bank_statement”, “rental_agreement”, “passport_registration” and “temporary_registration” types.
- **front_side** (`telegram.PassportFile`, optional) – Encrypted/decrypted file with the front side of the document, provided by the user. Available for “passport”, “driver_license”, “identity_card” and “internal_passport”.
- **reverse_side** (`telegram.PassportFile`, optional) – Encrypted/decrypted file with the reverse side of the document, provided by the user. Available for “driver_license” and “identity_card”.
- **selfie** (`telegram.PassportFile`, optional) – Encrypted/decrypted file with the selfie of the user holding a document, provided by the user; available for “passport”, “driver_license”, “identity_card” and “internal_passport”.
- **translation** (`List[telegram.PassportFile]`, optional) – Array of encrypted/decrypted files with translated versions of documents provided by the user. Available if requested for “passport”, “driver_license”, “identity_card”, “internal_passport”, “utility_bill”, “bank_statement”, “rental_agreement”, “passport_registration” and “temporary_registration” types.

- **hash** (`str`) – Base64-encoded element hash for using in telegram. `PassportElementErrorUnspecified`.
- **bot** (`telegram.Bot`, optional) – The Bot to use for instance methods.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

Note: This object is decrypted only when originating from `telegram.PassportData.decrypted_data`.

telegram.EncryptedCredentials

class telegram.**EncryptedCredentials** (*data: str, hash: str, secret: str, bot: Bot = None, **kwargs*)
Bases: telegram.base.TelegramObject

Contains data required for decrypting and authenticating `EncryptedPassportElement`. See the Telegram Passport Documentation for a complete description of the data decryption and authentication processes.

Objects of this class are comparable in terms of equality. Two objects of this class are considered equal, if their `data`, `hash` and `secret` are equal.

data

Decrypted data with unique user's nonce, data hashes and secrets used for `EncryptedPassportElement` decryption and authentication or base64 encrypted data.

Type `telegram.Credentials` or `str`

hash

Base64-encoded data hash for data authentication.

Type `str`

secret

Decrypted or encrypted secret used for decryption.

Type `str`

Parameters

- **data** (`telegram.Credentials` or `str`) – Decrypted data with unique user's nonce, data hashes and secrets used for `EncryptedPassportElement` decryption and authentication or base64 encrypted data.
- **hash** (`str`) – Base64-encoded data hash for data authentication.
- **secret** (`str`) – Decrypted or encrypted secret used for decryption.
- ****kwargs** (`dict`) – Arbitrary keyword arguments.

Note: This object is decrypted only when originating from `telegram.PassportData.decrypted_credentials`.

decrypted_data

Lazily decrypt and return credentials data. This object also contains the user specified nonce as `decrypted_data.nonce`.

Raises telegram.TelegramDecryptionError – Decryption failed. Usually due to bad private/public key but can also suggest malformed/tampered data.

Type `telegram.Credentials`

decrypted_secret

Lazily decrypt and return secret.

Raises telegram.TelegramDecryptionError – Decryption failed. Usually due to bad private/public key but can also suggest malformed/tampered data.

Type str

3.3 telegram.utils package

3.3.1 telegram.utils.helpers Module

This module contains helper functions.

telegram.utils.helpers.DEFAULT_FALSE = <telegram.utils.helpers.DefaultValue object>
Default *False*

Type *DefaultValue*

telegram.utils.helpers.DEFAULT_NONE = <telegram.utils.helpers.DefaultValue object>
Default *None*

Type *DefaultValue*

class telegram.utils.helpers.DefaultValue (value: Any = None)
Bases: object

Wrapper for immutable default arguments that allows to check, if the default value was set explicitly. Usage:

```
DefaultOne = DefaultValue(1)
def f(arg=DefaultOne):
    if arg is DefaultOne:
        print('\`arg\` is the default')
        arg = arg.value
    else:
        print('\`arg\` was set explicitly')
    print('\`arg\` = ' + str(arg))
```

This yields:

```
>>> f()
\`arg\` is the default
\`arg\` = 1
>>> f(1)
\`arg\` was set explicitly
\`arg\` = 1
>>> f(2)
\`arg\` was set explicitly
\`arg\` = 2
```

Also allows to evaluate truthiness:

```
default = DefaultValue(value)
if default:
    ...
```

is equivalent to:

```
default = DefaultValue(value)
if value:
    ...
```

value

The value of the default argument

Type `obj`

Parameters **value** (`obj`) – The value of the default argument

`telegram.utils.helpers.create_deep_linked_url` (*bot_username: str, payload: str = None, group: bool = False*) → `str`
Creates a deep-linked URL for this `bot_username` with the specified payload. See <https://core.telegram.org/bots#deep-linking> to learn more.

The payload may consist of the following characters: A-Z, a-z, 0-9, `_`, `-`

Note: Works well in conjunction with `CommandHandler("start", callback, filters = Filters.regex('payload'))`

Examples

```
create_deep_linked_url(bot.get_me().username, "some-params")
```

Parameters

- **bot_username** (`str`) – The username to link to
- **payload** (`str`, optional) – Parameters to encode in the created URL
- **group** (`bool`, optional) – If `True` the user is prompted to select a group to add the bot to. If `False`, opens a one-on-one conversation with the bot. Defaults to `False`.

Returns An URL to start the bot with specific parameters

Return type `str`

`telegram.utils.helpers.decode_conversations_from_json` (*json_string: str*) → `Dict[str, Dict[Tuple, Any]]`

Helper method to decode a conversations dict (that uses tuples as keys) from a JSON-string created with `_encode_conversations_to_json`.

Parameters **json_string** (`str`) – The conversations dict as JSON string.

Returns The conversations dict after decoding

Return type `dict`

`telegram.utils.helpers.decode_user_chat_data_from_json` (*data: str*) → `DefaultDict[int, Dict[Any, Any]]`

Helper method to decode chat or user data (that uses ints as keys) from a JSON-string.

Parameters **data** (`str`) – The user/chat_data dict as JSON string.

Returns The user/chat_data defaultdict after decoding

Return type `dict`

`telegram.utils.helpers.effective_message_type` (*entity: Union[Message, Update]*) → `Optional[str]`

Extracts the type of message as a string identifier from a `telegram.Message` or a `telegram.Update`.

Parameters **entity** (`Update | Message`) –

Returns One of `Message.MESSAGE_TYPES`

Return type `str`

`telegram.utils.helpers.encode_conversations_to_json` (*conversations: Dict[str, Dict[Tuple, Any]]*) → `str`

Helper method to encode a conversations dict (that uses tuples as keys) to a JSON-serializable way. Use `_decode_conversations_from_json` to decode.

Parameters `conversations` (`dict`) – The conversations dict to transform to JSON.

Returns The JSON-serialized conversations dict

Return type `str`

`telegram.utils.helpers.escape_markdown` (*text: str, version: int = 1, entity_type: str = None*) → `str`

Helper function to escape telegram markup symbols.

Parameters

- **text** (`str`) – The text.
- **version** (`int` | `str`) – Use to specify the version of telegrams Markdown. Either 1 or 2. Defaults to 1.
- **entity_type** (`str`, optional) – For the entity types `PRE`, `CODE` and the link part of `TEXT_LINKS`, only certain characters need to be escaped in MarkdownV2. See the official API documentation for details. Only valid in combination with `version=2`, will be ignored else.

`telegram.utils.helpers.from_timestamp` (*unixtime: Optional[int], tzinfo: datetime.tzinfo = <UTC>*) → `Optional[datetime.datetime]`

Converts an (integer) unix timestamp to a timezone aware datetime object. None's are left alone (i.e. ``from_timestamp(None)`` is None).

Parameters

- **unixtime** (`int`) – Integer POSIX timestamp.
- **tzinfo** (`datetime.tzinfo`, optional) – The timezone, the timestamp is to be converted to. Defaults to UTC.

Returns timezone aware equivalent `datetime.datetime` value if timestamp is not None; else None

`telegram.utils.helpers.get_signal_name` (*signum: int*) → `str`

Returns the signal name of the given signal number.

`telegram.utils.helpers.is_local_file` (*obj: Union[str, pathlib.Path, None]*) → `bool`

Checks if a given string is a file on local system.

Parameters `obj` (`str`) – The string to check.

`telegram.utils.helpers.mention_html` (*user_id: Union[int, str], name: str*) → `str`

Parameters

- **user_id** (`int`) –
- **name** (`str`) –

Returns The inline mention for the user as html.

Return type `str`

`telegram.utils.helpers.mention_markdown` (*user_id: Union[int, str], name: str, version: int = 1*) → `str`

Parameters

- **user_id** (`int`) –
- **name** (`str`) –

- **version** (`int` | `str`) – Use to specify the version of telegrams Markdown. Either 1 or 2. Defaults to 1

Returns The inline mention for the user as markdown.

Return type `str`

`telegram.utils.helpers.parse_file_input` (*file_input: Union[str, IO, InputFile, pathlib.Path, TelegramObject], tg_type: Type[TelegramObject] = None, attach: bool = None, filename: str = None*) → Union[str, InputFile, Any]

Parses input for sending files:

- For string input, if the input is an absolute path of a local file, adds the `file://` prefix. If the input is a relative path of a local file, computes the absolute path and adds the `file://` prefix. Returns the input unchanged, otherwise.
- `pathlib.Path` objects are treated the same way as strings.
- For IO input, returns an `telegram.InputFile`.
- If `tg_type` is specified and the input is of that type, returns the `file_id` attribute.

Parameters

- **file_input** (`str` | *filelike object* | Telegram media object) – The input to parse.
- **tg_type** (`type`, optional) – The Telegram media type the input can be. E.g. `telegram.Animation`.
- **attach** (`bool`, optional) – Whether this file should be send as one file or is part of a collection of files. Only relevant in case an `telegram.InputFile` is returned.
- **filename** (`str`, optional) – The filename. Only relevant in case an `telegram.InputFile` is returned.

Returns

The parsed input or the untouched `file_input`, in case it's no valid file input.

Return type `str` | `telegram.InputFile` | object

`telegram.utils.helpers.to_float_timestamp` (*time_object: Union[int, float, datetime.timedelta, datetime.datetime, datetime.time], reference_timestamp: float = None, tzinfo: pytz.tzinfo.BaseTzInfo = None*) → float

Converts a given time object to a float POSIX timestamp. Used to convert different time specifications to a common format. The time object can be relative (i.e. indicate a time increment, or a time of day) or absolute. Any objects from the `datetime` module that are timezone-naive will be assumed to be in UTC, if `bot` is not passed or `bot.defaults` is `None`.

Parameters

- **time_object** (`int` | `float` | `datetime.timedelta` | `datetime.datetime` | `datetime.time`) – Time value to convert. The semantics of this parameter will depend on its type:
 - `int` or `float` will be interpreted as “seconds from `reference_t`”
 - `datetime.timedelta` will be interpreted as “time increment from `reference_t`”
 - `datetime.datetime` will be interpreted as an absolute date/time value
 - `datetime.time` will be interpreted as a specific time of day

- **reference_timestamp** (*float, optional*) – POSIX timestamp that indicates the absolute time from which relative calculations are to be performed (e.g. when `t` is given as an `int`, indicating “seconds from `reference_t`”). Defaults to now (the time at which this function is called).

If `t` is given as an absolute representation of date & time (i.e. a `datetime.datetime` object), `reference_timestamp` is not relevant and so its value should be `None`. If this is not the case, a `ValueError` will be raised.

- **tzinfo** (`datetime.tzinfo`, optional) – If `t` is a naive object from the `datetime` module, it will be interpreted as this timezone. Defaults to `pytz.utc`.

Returns

(float | None) The return value depends on the type of argument `t`. If `t` is given as a time increment (i.e. as a obj:`int`, `float` or `datetime.timedelta`), then the return value will be `reference_t + t`.

Else if it is given as an absolute date/time value (i.e. a `datetime.datetime` object), the equivalent value as a POSIX timestamp will be returned.

Finally, if it is a time of the day without date (i.e. a `datetime.time` object), the return value is the nearest future occurrence of that time of day.

Raises `TypeError` – if `t`’s type is not one of those described above

```
telegram.utils.helpers.to_timestamp(dt_obj: Union[int, float, datetime.timedelta,
                                             datetime.datetime, datetime.time, None],
                                     reference_timestamp: float = None, tzinfo:
                                     pytz.tzinfo.BaseTzInfo = None) → Optional[int]
```

Wrapper over `to_float_timestamp()` which returns an integer (the float value truncated down to the nearest integer).

See the documentation for `to_float_timestamp()` for more details.

3.3.2 telegram.utils.promise.Promise

```
class telegram.utils.promise.Promise(pooled_function: Callable[..., RT], args:
                                     Union[List[T], Tuple], kwargs: Dict[str, Any], up-
                                     date: Union[str, Update] = None, error_handling:
                                     bool = True)
```

Bases: `object`

A simple Promise implementation for use with the `run_async` decorator, `DelayQueue` etc.

Parameters

- **pooled_function** (callable) – The callable that will be called concurrently.
- **args** (`list` | `tuple`) – Positional arguments for `pooled_function`.
- **kwargs** (`dict`) – Keyword arguments for `pooled_function`.
- **update** (`telegram.Update`, optional) – The update this promise is associated with.
- **error_handling** (`bool`, optional) – Whether exceptions raised by `func` may be handled by error handlers. Defaults to `True`.

pooled_function

The callable that will be called concurrently.

Type callable

args

Positional arguments for `pooled_function`.

Type `list` | `tuple`

kwargs

Keyword arguments for *pooled_function*.

Type dict

done

Is set when the result is available.

Type threading.Event

update

Optional. The update this promise is associated with.

Type *telegram.Update*

error_handling

Optional. Whether exceptions raised by *func* may be handled by error handlers. Defaults to True.

Type bool

exception

The exception raised by *pooled_function* or None if no exception has been raised (yet).

result (*timeout: float = None*) → Optional[RT]

Return the result of the Promise.

Parameters **timeout** (*float*, optional) – Maximum time in seconds to wait for the result to be calculated. None means indefinite. Default is None.

Returns Returns the return value of *pooled_function* or None if the timeout expires.

Raises Any exception raised by *pooled_function*.

run () → None

Calls the *pooled_function* callable.

3.3.3 telegram.utils.request.Request

```
class telegram.utils.request.Request (con_pool_size: int = 1, proxy_url: str = None, url-  
lib3_proxy_kwargs: Dict[str, Any] = None, con-  
nect_timeout: float = 5.0, read_timeout: float =  
5.0)
```

Bases: object

Helper class for python-telegram-bot which provides methods to perform POST & GET towards telegram servers.

Parameters

- **con_pool_size** (*int*) – Number of connections to keep in the connection pool.
- **proxy_url** (*str*) – The URL to the proxy server. For example: *http://127.0.0.1:3128*.
- **urllib3_proxy_kwargs** (*dict*) – Arbitrary arguments passed as-is to *urllib3.ProxyManager*. This value will be ignored if *proxy_url* is not set.
- **connect_timeout** (*int | float*) – The maximum amount of time (in seconds) to wait for a connection attempt to a server to succeed. None will set an infinite timeout for connection attempts. (default: 5.)
- **read_timeout** (*int | float*) – The maximum amount of time (in seconds) to wait between consecutive read operations for a response from the server. None will set an infinite timeout. This value is usually overridden by the various *telegram.Bot* methods. (default: 5.)

con_pool_size

The size of the connection pool used.

download (*url: str, filename: str, timeout: float = None*) → None

Download a file by its URL.

Parameters

- **url** (*str*) – The web location we want to retrieve.
- **timeout** (*int | float*) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).
- **filename** (*str*) – The filename within the path to download the file.

post (*url: str, data: Dict[str, Any], timeout: float = None*) → Union[Dict[str, Any], bool]

Request an URL.

Parameters

- **url** (*str*) – The web location we want to retrieve.
- **data** (*dict[str, str | int], optional*) – A dict of key/value pairs.
- **timeout** (*int | float, optional*) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

Returns A JSON object.

retrieve (*url: str, timeout: float = None*) → bytes

Retrieve the contents of a file by its URL.

Parameters

- **url** (*str*) – The web location we want to retrieve.
- **timeout** (*int | float*) – If this value is specified, use it as the read timeout from the server (instead of the one specified during creation of the connection pool).

3.3.4 telegram.utils.types Module

This module contains custom typing aliases.

`telegram.utils.types.ConversationDict = typing.Dict[typing.Tuple[int, ...], typing.Union[Dict[str, Any], str]]`
 Dicts as maintained by the `telegram.ext.ConversationHandler`.

`telegram.utils.types.FileInput = typing.Union[str, typing.IO, ForwardRef('InputFile')]`
 Valid input for passing files to Telegram. Either a file id as string, a file like object or a local file path as string or `pathlib.Path`.

`telegram.utils.types.FileLike = typing.Union[typing.IO, ForwardRef('InputFile')]`
 Either an open file handler or a `telegram.InputFile`.

`telegram.utils.types.HandlerArg = typing.Union[str, ForwardRef('Update')]`
 The argument that handlers parse for `telegram.ext.handler.check_update()` etc.

`telegram.utils.types.JSONDict = typing.Dict[str, typing.Any]`
 Dictionary containing response from Telegram or data to send to the API.

`telegram.utils.types.SLT = typing.Union[~RT, typing.List[~RT], typing.Tuple[~RT, ...]]`
 Single instance or list/tuple of instances.

3.4 Changelog

3.4.1 Changelog

Version 13.1

Released 2020-11-29

Major Changes:

- Full support of Bot API 5.0 (#2181, #2186, #2190, #2189, #2183, #2184, #2188, #2185, #2192, #2196, #2193, #2223, #2199, #2187, #2147, #2205)

New Features:

- Add `Defaults.run_async` (#2210)
- Improve and Expand `CallbackQuery` Shortcuts (#2172)
- Add XOR Filters and make `Filters.name` a Property (#2179)
- Add `Filters.document.file_extension` (#2169)
- Add `Filters.caption_regex` (#2163)
- Add `Filters.chat_type` (#2128)
- Handle Non-Binary File Input (#2202)

Bug Fixes:

- Improve Handling of Custom Objects in `BasePersistence.insert/replace_bot` (#2151)
- Fix bugs in `replace/insert_bot` (#2218)

Minor changes, CI improvements, doc fixes and type hinting:

- Improve Type hinting (#2204, #2118, #2167, #2136)
- Doc Fixes & Extensions (#2201, #2161)
- Use F-Strings Where Possible (#2222)
- Rename kwargs to `_kwargs` where possible (#2182)
- Comply with PEP561 (#2168)
- Improve Code Quality (#2131)
- Switch Code Formatting to Black (#2122, #2159, #2158)
- Update Wheel Settings (#2142)
- Update `timerbot.py` to v13.0 (#2149)
- Overhaul Constants (#2137)
- Add Python 3.9 to Test Matrix (#2132)
- Switch Codecov to GitHub Action (#2127)
- Specify Required `pytz` Version (#2121)

Version 13.0

Released 2020-10-07

For a detailed guide on how to migrate from v12 to v13, see [this wiki page](#).

Major Changes:

- Deprecate old-style callbacks, i.e. `set use_context=True` by default (#2050)
- Refactor Handling of Message VS Update Filters (#2032)
- Deprecate `Message.default_quote` (#1965)
- Refactor persistence of Bot instances (#1994)
- Refactor `JobQueue` (#1981)
- Refactor handling of kwargs in Bot methods (#1924)
- Refactor `Dispatcher.run_async`, deprecating the `@run_async` decorator (#2051)

New Features:

- Type Hinting (#1920)
- Automatic Pagination for `answer_inline_query` (#2072)
- `Defaults.tzinfo` (#2042)
- Extend rich comparison of objects (#1724)
- Add `Filters.via_bot` (#2009)
- Add missing shortcuts (#2043)
- Allow `DispatcherHandlerStop` in `ConversationHandler` (#2059)
- Make Errors picklable (#2106)

Minor changes, CI improvements, doc fixes or bug fixes:

- Fix Webhook not working on Windows with Python 3.8+ (#2067)
- Fix setting thumbs with `send_media_group` (#2093)
- Make `MessageHandler` filter for `Filters.update` first (#2085)
- Fix `PicklePersistence.flush()` with only `bot_data` (#2017)
- Add test for clean argument of `Updater.start_polling/webhook` (#2002)
- Doc fixes, refinements and additions (#2005, #2008, #2089, #2094, #2090)
- CI fixes (#2018, #2061)
- Refine `pollbot.py` example (#2047)
- Refine Filters in examples (#2027)
- Rename `echobot` examples (#2025)
- Use Lock-Bot to lock old threads (#2048, #2052, #2049, #2053)

Version 12.8

Released 2020-06-22

Major Changes:

- Remove Python 2 support (#1715)
- Bot API 4.9 support (#1980)
- IDs/Usernames of `Filters.user` and `Filters.chat` can now be updated (#1757)

Minor changes, CI improvements, doc fixes or bug fixes:

- Update contribution guide and stale bot (#1937)
- Remove `NullHandlers` (#1913)
- Improve and expand examples (#1943, #1995, #1983, #1997)

- Doc fixes (#1940, #1962)
- Add `User.send_poll()` shortcut (#1968)
- Ignore private attributes en `TelegramObject.to_dict()` (#1989)
- Stabilize CI (#2000)

Version 12.7

Released 2020-05-02

Major Changes:

- Bot API 4.8 support. **Note:** The `Dice` object now has a second positional argument `emoji`. This is relevant, if you instantiate `Dice` objects manually. (#1917)
- Added `tzinfo` argument to `helpers.from_timestamp`. It now returns an timezone aware object. This is relevant for `Message.{date, forward_date, edit_date}`, `Poll.close_date` and `ChatMember.until_date` (#1621)

New Features:

- New method `run_monthly` for the `JobQueue` (#1705)
- `Job.next_t` now gives the datetime of the jobs next execution (#1685)

Minor changes, CI improvements, doc fixes or bug fixes:

- Stabalize CI (#1919, #1931)
- Use ABCs `@abstractmethod` instead of raising `NotImplementedError` for `Handler`, `BasePersistence` and `BaseFilter` (#1905)
- Doc fixes (#1914, #1902, #1910)

Version 12.6.1

Released 2020-04-11

Bug fixes:

- Fix serialization of `reply_markup` in media messages (#1889)

Version 12.6

Released 2020-04-10

Major Changes:

- Bot API 4.7 support. **Note:** In `Bot.create_new_sticker_set` and `Bot.add_sticker_to_set`, the order of the parameters had be changed, as the `png_sticker` parameter is now optional. (#1858)

Minor changes, CI improvements or bug fixes:

- Add tests for `swtich_inline_query(_current_chat)` with empty string (#1635)
- Doc fixes (#1854, #1874, #1884)
- Update issue templates (#1880)
- Favor concrete types over “Iterable” (#1882)
- Pass last valid `CallbackContext` to `TIMEOUT` handlers of `ConversationHandler` (#1826)
- Tweak handling of persistence and update persistence after job calls (#1827)

- Use `checkout@v2` for GitHub actions (#1887)

Version 12.5.1

Released 2020-03-30

Minor changes, doc fixes or bug fixes:

- Add missing docs for *PollHandler* and *PollAnswerHandler* (#1853)
- Fix wording in *Filters* docs (#1855)
- Reorder tests to make them more stable (#1835)
- Make *ConversationHandler* attributes immutable (#1756)
- Make *PrefixHandler* attributes *command* and *prefix* editable (#1636)
- Fix UTC as default *tzinfo* for *Job* (#1696)

Version 12.5

Released 2020-03-29

New Features:

- *Bot.link* gives the *t.me* link of the bot (#1770)

Major Changes:

- Bot API 4.5 and 4.6 support. (#1508, #1723)

Minor changes, CI improvements or bug fixes:

- Remove legacy CI files (#1783, #1791)
- Update pre-commit config file (#1787)
- Remove builtin names (#1792)
- CI improvements (#1808, #1848)
- Support Python 3.8 (#1614, #1824)
- Use stale bot for auto closing stale issues (#1820, #1829, #1840)
- Doc fixes (#1778, #1818)
- Fix typo in *edit_message_media* (#1779)
- In examples, answer *CallbackQueries* and use *edit_message_text* shortcut (#1721)
- Revert accidental change in vendored *urllib3* (#1775)

Version 12.4.2

Released 2020-02-10

Bug Fixes

- Pass correct *parse_mode* to *InlineResults* if *bot.defaults* is *None* (#1763)
- Make sure PP can read files that dont have *bot_data* (#1760)

Version 12.4.1

Released 2020-02-08

This is a quick release for [#1744](#) which was accidentally left out of v12.4.0 though mentioned in the release notes.

Version 12.4.0

Released 2020-02-08

New features:

- Set default values for arguments appearing repeatedly. We also have a [wiki page for the new defaults](#). ([#1490](#))
- Store data in `CallbackContext.bot_data` to access it in every callback. Also persists. ([#1325](#))
- `Filters.poll` allows only messages containing a poll ([#1673](#))

Major changes:

- `Filters.text` now accepts messages that start with a slash, because `CommandHandler` checks for `MessageEntity.BOT_COMMAND` since v12. This might lead to your `MessageHandlers` receiving more updates than before ([#1680](#)).
- `Filters.command` now checks for `MessageEntity.BOT_COMMAND` instead of just a leading slash. Also by `Filters.command(False)` you can now filter for messages containing a command *anywhere* in the text ([#1744](#)).

Minor changes, CI improvements or bug fixes:

- Add `dispatcher` argument to `Updater` to allow passing a customized `Dispatcher` ([#1484](#))
- Add missing names for `Filters` ([#1632](#))
- Documentation fixes ([#1624](#), [#1647](#), [#1669](#), [#1703](#), [#1718](#), [#1734](#), [#1740](#), [#1642](#), [#1739](#), [#1746](#))
- CI improvements ([#1716](#), [#1731](#), [#1738](#), [#1748](#), [#1749](#), [#1750](#), [#1752](#))
- Fix spelling issue for `encode_conversations_to_json` ([#1661](#))
- Remove double assignment of `Dispatcher.job_queue` ([#1698](#))
- Expose dispatcher as property for `CallbackContext` ([#1684](#))
- Fix None check in `JobQueue._put()` ([#1707](#))
- Log datetimes correctly in `JobQueue` ([#1714](#))
- Fix false `Message.link` creation for private groups ([#1741](#))
- Add option `--with-upstream-urllib3` to `setup.py` to allow using non-vendored version ([#1725](#))
- Fix persistence for nested `ConversationHandlers` ([#1679](#))
- Improve handling of non-decodable server responses ([#1623](#))
- Fix download for files without `file_path` ([#1591](#))
- `test_webhook_invalid_posts` is now considered flaky and retried on failure ([#1758](#))

Version 12.3.0

Released 2020-01-11

New features:

- `Filters.caption` allows only messages with caption ([#1631](#)).

- Filter for exact messages/captions with new capability of *Filters.text* and *Filters.caption*. Especially useful in combination with *ReplyKeyboardMarkup*. (#1631).

Major changes:

- Fix inconsistent handling of naive datetimes (#1506).

Minor changes, CI improvements or bug fixes:

- Documentation fixes (#1558, #1569, #1579, #1572, #1566, #1577, #1656).
- Add mutex protection on *ConversationHandler* (#1533).
- Add *MAX_PHOTOSIZE_UPLOAD* constant (#1560).
- Add args and kwargs to *Message.forward()* (#1574).
- Transfer to GitHub Actions CI (#1555, #1556, #1605, #1606, #1607, #1612, #1615, #1645).
- Fix deprecation warning with Py3.8 by vendored urllib3 (#1618).
- Simplify assignments for optional arguments (#1600)
- Allow private groups for *Message.link* (#1619).
- Fix wrong signature call for *ConversationHandler.TIMEOUT* handlers (#1653).

Version 12.2.0

Released 2019-10-14

New features:

- Nested *ConversationHandlers* (#1512).

Minor changes, CI improvements or bug fixes:

- Fix CI failures due to non-backward compat attrs dependency (#1540).
- travis.yaml: TEST_OFFICIAL removed from allowed_failures.
- Fix typos in examples (#1537).
- Fix Bot.to_dict to use proper first_name (#1525).
- Refactor test_commandhandler.py (#1408).
- Add Python 3.8 (RC version) to Travis testing matrix (#1543).
- test_bot.py: Add to_dict test (#1544).
- Flake config moved into setup.cfg (#1546).

Version 12.1.1

Released 2019-09-18

Hot fix release

Fixed regression in the vendored urllib3 (#1517).

Version 12.1.0

Released 2019-09-13

Major changes:

- Bot API 4.4 support (#1464, #1510)

- Add `get_file` method to *Animation* & *ChatPhoto*. Add, `get_small_file` & `get_big_file` methods to *ChatPhoto* (#1489)
- Tools for deep linking (#1049)

Minor changes and/or bug fixes:

- Documentation fixes (#1500, #1499)
- Improved examples (#1502)

Version 12.0.0

Released 2019-08-29

Well... This felt like decades. But here we are with a new release.

Expect minor releases soon (mainly complete Bot API 4.4 support)

Major and/or breaking changes:

- Context based callbacks
- Persistence
- PrefixHandler added (Handler overhaul)
- Deprecation of RegexHandler and `edited_messages`, `channel_post`, etc. arguments (Filter overhaul)
- Various ConversationHandler changes and fixes
- Bot API 4.1, 4.2, 4.3 support
- Python 3.4 is no longer supported
- Error Handler now handles all types of exceptions (#1485)
- Return UTC from `from_timestamp()` (#1485)

See the wiki page at <https://git.io/fxJuV> for a detailed guide on how to migrate from version 11 to version 12.

Context based callbacks (#1100)

- Use of `pass_` in handlers is deprecated.
- Instead use `use_context=True` on `Updater` or `Dispatcher` and change callback from (bot, update, others...) to (update, context).
- This also applies to error handlers `Dispatcher.add_error_handler` and `JobQueue` jobs (change (bot, job) to (context) here).
- For users with custom handlers subclassing `Handler`, this is mostly backwards compatible, but to use the new context based callbacks you need to implement the new `collect_additional_context` method.
- Passing bot to `JobQueue.__init__` is deprecated. Use `JobQueue.set_dispatcher` with a dispatcher instead.
- Dispatcher makes sure to use a single *CallbackContext* for a entire update. This means that if an update is handled by multiple handlers (by using the group argument), you can add custom arguments to the *CallbackContext* in a lower group handler and use it in higher group handler. NOTE: Never use with `@run_async`, see docs for more info. (#1283)
- If you have custom handlers they will need to be updated to support the changes in this release.
- Update all examples to use context based callbacks.

Persistence (#1017)

- Added PicklePersistence and DictPersistence for adding persistence to your bots.
- BasePersistence can be subclassed for all your persistence needs.
- Add a new example that shows a persistent ConversationHandler bot

Handler overhaul (#1114)

- CommandHandler now only triggers on actual commands as defined by telegram servers (everything that the clients mark as a tabable link).
- PrefixHandler can be used if you need to trigger on prefixes (like all messages starting with a “/” (old CommandHandler behaviour) or even custom prefixes like “#” or “!”).

Filter overhaul (#1221)

- RegexHandler is deprecated and should be replaced with a MessageHandler with a regex filter.
- Use update filters to filter update types instead of arguments (message_updates, channel_post_updates and edited_updates) on the handlers.
- Completely remove allow_edited argument - it has been deprecated for a while.
- data_filters now exist which allows filters that return data into the callback function. This is how the regex filter is implemented.
- All this means that it no longer possible to use a list of filters in a handler. Use bitwise operators instead!

ConversationHandler

- Remove run_async_timeout and timed_out_behavior arguments (#1344)
- Replace with WAITING constant and behavior from states (#1344)
- Only emit one warning for multiple CallbackQueryHandlers in a ConversationHandler (#1319)
- Use warnings.warn for ConversationHandler warnings (#1343)
- Fix unresolvable promises (#1270)

Bug fixes & improvements

- Handlers should be faster due to deduped logic.
- Avoid compiling compiled regex in regex filter. (#1314)
- Add missing left_chat_member to Message.MESSAGE_TYPES (#1336)
- Make custom timeouts actually work properly (#1330)
- Add convenience classmethods (from_button, from_row and from_column) to InlineKeyboardMarkup
- Small typo fix in setup.py (#1306)
- Add Conflict error (HTTP error code 409) (#1154)
- Change MAX_CAPTION_LENGTH to 1024 (#1262)
- Remove some unnecessary clauses (#1247, #1239)
- Allow filenames without dots in them when sending files (#1228)

- Fix uploading files with unicode filenames (#1214)
- Replace http.server with Tornado (#1191)
- Allow SOCKSConnection to parse username and password from URL (#1211)
- Fix for arguments in passport/data.py (#1213)
- Improve message entity parsing by adding text_mention (#1206)
- Documentation fixes (#1348, #1397, #1436)
- Merged filters short-circuit (#1350)
- Fix webhook listen with tornado (#1383)
- Call task_done() on update queue after update processing finished (#1428)
- Fix send_location() - latitude may be 0 (#1437)
- Make MessageEntity objects comparable (#1465)
- Add prefix to thread names (#1358)

Buf fixes since v12.0.0b1

- Fix setting bot on ShippingQuery (#1355)
- Fix _trigger_timeout() missing 1 required positional argument: 'job' (#1367)
- Add missing message.text check in PrefixHandler check_update (#1375)
- Make updates persist even on DispatcherHandlerStop (#1463)
- Dispatcher force updating persistence object's chat data attribute (#1462)

Internal improvements

- Finally fix our CI builds mostly (too many commits and PRs to list)
- Use multiple bots for CI to improve testing times significantly.
- Allow pypy to fail in CI.
- Remove the last CamelCase CheckUpdate methods from the handlers we missed earlier.
- test_official is now executed in a different job

Version 11.1.0

Released 2018-09-01

Fixes and updates for Telegram Passport: (#1198)

- Fix passport decryption failing at random times
- Added support for middle names.
- Added support for translations for documents
- Add errors for translations for documents
- Added support for requesting names in the language of the user's country of residence
- Replaced the payload parameter with the new parameter nonce
- Add hash to EncryptedPassportElement

Version 11.0.0

Released 2018-08-29

Fully support Bot API version 4.0! (also some bugfixes :))

Telegram Passport (#1174):

- **Add full support for telegram passport.**
 - New types: PassportData, PassportFile, EncryptedPassportElement, EncryptedCredentials, PassportElementError, PassportElementErrorDataField, PassportElementErrorFrontSide, PassportElementErrorReverseSide, PassportElementErrorSelfie, PassportElementErrorFile and PassportElementErrorFiles.
 - New bot method: set_passport_data_errors
 - New filter: Filters.passport_data
 - Field passport_data field on Message
 - PassportData can be easily decrypted.
 - PassportFiles are automatically decrypted if originating from decrypted PassportData.
- See new passportbot.py example for details on how to use, or go to [our telegram passport wiki page](#) for more info
- NOTE: Passport decryption requires new dependency *cryptography*.

Inputfile rework (#1184):

- Change how Inputfile is handled internally
- This allows support for specifying the thumbnails of photos and videos using the thumb= argument in the different send_ methods.
- Also allows Bot.send_media_group to actually finally send more than one media.
- Add thumb to Audio, Video and Videonote
- Add Bot.edit_message_media together with InputMediaAnimation, InputMediaAudio, and InputMediaDocument.

Other Bot API 4.0 changes:

- Add forusquare_type to Venue, InlineQueryResultVenue, InputVenueMessageContent, and Bot.send_venue. (#1170)
- Add vCard support by adding vcard field to Contact, InlineQueryResultContact, InputContactMessageContent, and Bot.send_contact. (#1166)
- **Support new message entities: CASHTAG and PHONE_NUMBER. (#1179)**
 - Cashtag seems to be things like \$USD and \$GBP, but it seems telegram doesn't currently send them to bots.
 - Phone number also seems to have limited support for now
- Add Bot.send_animation, add width, height, and duration to Animation, and add Filters.animation. (#1172)

Non Bot API 4.0 changes:

- Minor integer comparison fix (#1147)
- Fix Filters.regex failing on non-text message (#1158)
- Fix ProcessLookupError if process finishes before we kill it (#1126)
- Add t.me links for User, Chat and Message if available and update User.mention_* (#1092)
- Fix mention_markdown/html on py2 (#1112)

Version 10.1.0

Released 2018-05-02

Fixes changing previous behaviour:

- Add urllib3 fix for socks5h support (#1085)
- Fix send_sticker() timeout=20 (#1088)

Fixes:

- Add a caption_entity filter for filtering caption entities (#1068)
- Inputfile encode filenames (#1086)
- InputFile: Fix proper naming of file when reading from subprocess.PIPE (#1079)
- Remove pytest-catchlog from requirements (#1099)
- Documentation fixes (#1061, #1078, #1081, #1096)

Version 10.0.2

Released 2018-04-17

Important fix:

- Handle utf8 decoding errors (#1076)

New features:

- Added Filter.regex (#1028)
- Filters for Category and file types (#1046)
- Added video note filter (#1067)

Fixes:

- Fix in telegram.Message (#1042)
- Make chat_id a positional argument inside shortcut methods of Chat and User classes (#1050)
- Make Bot.full_name return a unicode object. (#1063)
- CommandHandler faster check (#1074)
- Correct documentation of Dispatcher.add_handler (#1071)
- Various small fixes to documentation.

Version 10.0.1

Released 2018-03-05

Fixes:

- Fix conversationhandler timeout (PR #1032)
- Add missing docs utils (PR #912)

Version 10.0.0

Released 2018-03-02

Non backward compatible changes and changed defaults

- JobQueue: Remove deprecated prevent_autostart & put() (PR #1012)

- Bot, Updater: Remove deprecated `network_delay` (PR #1012)
- Remove deprecated `Message.new_chat_member` (PR #1012)
- Retry bootstrap phase indefinitely (by default) on network errors (PR #1018)

New Features

- Support v3.6 API (PR #1006)
- `User.full_name` convenience property (PR #949)
- Add `send_phone_number_to_provider` and `send_email_to_provider` arguments to `send_invoice` (PR #986)
- Bot: Add shortcut methods `reply_{markdown,html}` (PR #827)
- Bot: Add shortcut method `reply_media_group` (PR #994)
- Added `utils.helpers.effective_message_type` (PR #826)
- `Bot.get_file` now allows passing a file in addition to `file_id` (PR #963)
- Add `.get_file()` to `Audio`, `Document`, `PhotoSize`, `Sticker`, `Video`, `VideoNote` and `Voice` (PR #963)
- Add `.send_*`() methods to `User` and `Chat` (PR #963)
- Get jobs by name (PR #1011)
- Add `Message` caption `html/markdown` methods (PR #1013)
- `File.download_as_bytearray` - new method to get a d/led file as bytearray (PR #1019)
- `File.download()`: Now returns a meaningful return value (PR #1019)
- Added conversation timeout in `ConversationHandler` (PR #895)

Changes

- Store bot in `PreCheckoutQuery` (PR #953)
- Updater: Issue INFO log upon received signal (PR #951)
- `JobQueue`: Thread safety fixes (PR #977)
- `WebhookHandler`: Fix exception thrown during error handling (PR #985)
- Explicitly check `update.effective_chat` in `ConversationHandler.check_update` (PR #959)
- Updater: Better handling of timeouts during `get_updates` (PR #1007)
- Remove unnecessary `to_dict()` (PR #834)
- `CommandHandler` - ignore strings in entities and “/” followed by whitespace (PR #1020)
- Documentation & style fixes (PR #942, PR #956, PR #962, PR #980, PR #983)

Version 9.0.0

Released 2017-12-08

Breaking changes (possibly)

- Drop support for python 3.3 (PR #930)

New Features

- Support Bot API 3.5 (PR #920)

Changes

- Fix race condition in dispatcher start/stop (#887)
- Log error trace if there is no error handler registered (#694)
- Update examples with consistent string formatting (#870)

- Various changes and improvements to the docs.

Version 8.1.1

Released 2017-10-15

- Fix Commandhandler crashing on single character messages (PR #873).

Version 8.1.0

Released 2017-10-14

New features - Support Bot API 3.4 (PR #865).

Changes - MessageHandler & RegexHandler now consider channel_updates. - Fix command not recognized if it is directly followed by a newline (PR #869). - Removed Bot._message_wrapper (PR #822). - Unitests are now also running on AppVeyor (Windows VM). - Various unittest improvements. - Documentation fixes.

Version 8.0.0

Released 2017-09-01

New features

- Fully support Bot Api 3.3 (PR #806).
- DispatcherHandlerStop ([see docs](#)).
- Regression fix for text_html & text_markdown (PR #777).
- Added effective_attachment to message (PR #766).

Non backward compatible changes

- Removed Botan support from the library (PR #776).
- Fully support Bot Api 3.3 (PR #806).
- Remove de_json() (PR #789).

Changes

- Sane defaults for tcp socket options on linux (PR #754).
- Add RESTRICTED as constant to ChatMember (PR #761).
- Add rich comparison to CallbackQuery (PR #764).
- Fix get_game_high_scores (PR #771).
- Warn on small con_pool_size during custom initialization of Updater (PR #793).
- Catch exceptions in error handler for errors that happen during polling (PR #810).
- For testing we switched to pytest (PR #788).
- Lots of small improvements to our tests and documentation.

Version 7.0.1

Released 2017-07-28

- Fix TypeError exception in RegexHandler (PR #751).
- Small documentation fix (PR #749).

Version 7.0.0

Released 2017-07-25

- Fully support Bot API 3.2.
- New filters for handling messages from specific chat/user id (PR #677).
- Add the possibility to add objects as arguments to `send_*` methods (PR #742).
- Fixed download of URLs with UTF-8 chars in path (PR #688).
- Fixed URL parsing for `Message` text properties (PR #689).
- Fixed args dispatching in `MessageQueue`'s decorator (PR #705).
- Fixed regression preventing IPv6 only hosts from connecting to Telegram servers (Issue #720).
- `ConversationHandler` - check if a user exist before using it (PR #699).
- Removed deprecated `telegram.Emoji`.
- Removed deprecated `Botan` import from `utils` (`Botan` is still available through `contrib`).
- Removed deprecated `ReplyKeyboardHide`.
- Removed deprecated `edit_message` argument of `bot.set_game_score`.
- Internal restructure of files.
- Improved documentation.
- Improved unitests.

Pre-version 7.0

2017-06-18

Released 6.1.0

- Fully support Bot API 3.0
- Add more fine-grained filters for status updates
- Bug fixes and other improvements

2017-05-29

Released 6.0.3

- Faulty PyPI release

2017-05-29

Released 6.0.2

- Avoid confusion with user's `urllib3` by renaming vendored `urllib3` to `ptb_urllib3`

2017-05-19

Released 6.0.1

- Add support for `User.language_code`
- Fix `Message.text_html` and `Message.text_markdown` for messages with emoji

2017-05-19

Released 6.0.0

- Add support for Bot API 2.3.1
- Add support for `deleteMessage` API method

- New, simpler API for `JobQueue` - <https://github.com/python-telegram-bot/python-telegram-bot/pull/484>
- Download files into file-like objects - <https://github.com/python-telegram-bot/python-telegram-bot/pull/459>
- Use vendor `urllib3` to address issues with timeouts - The default timeout for messages is now 5 seconds. For sending media, the default timeout is now 20 seconds.
- String attributes that are not set are now `None` by default, instead of empty strings
- Add `text_markdown` and `text_html` properties to `Message` - <https://github.com/python-telegram-bot/python-telegram-bot/pull/507>
- Add support for Socks5 proxy - <https://github.com/python-telegram-bot/python-telegram-bot/pull/518>
- Add support for filters in `CommandHandler` - <https://github.com/python-telegram-bot/python-telegram-bot/pull/536>
- Add the ability to invert (not) filters - <https://github.com/python-telegram-bot/python-telegram-bot/pull/552>
- Add `Filters.group` and `Filters.private`
- Compatibility with GAE via `urllib3.contrib` package - <https://github.com/python-telegram-bot/python-telegram-bot/pull/583>
- Add equality rich comparison operators to telegram objects - <https://github.com/python-telegram-bot/python-telegram-bot/pull/604>
- Several bugfixes and other improvements
- Remove some deprecated code

2017-04-17

Released 5.3.1

- Hotfix release due to bug introduced by `urllib3` version 1.21

2016-12-11

Released 5.3

- Implement API changes of November 21st (Bot API 2.3)
- `JobQueue` now supports `datetime.timedelta` in addition to seconds
- `JobQueue` now supports running jobs only on certain days
- New `Filters.reply` filter
- Bugfix for `Message.edit_reply_markup`
- Other bugfixes

2016-10-25

Released 5.2

- Implement API changes of October 3rd (games update)
- Add `Message.edit_*` methods
- Filters for the `MessageHandler` can now be combined using bitwise operators (`&` and `|`)
- Add a way to save user- and chat-related data temporarily
- Other bugfixes and improvements

2016-09-24

Released 5.1

- Drop Python 2.6 support
- Deprecate `telegram.Emoji`

- Use `ujson` if available
- Add instance methods to `Message`, `Chat`, `User`, `InlineQuery` and `CallbackQuery`
- `RegEx` filtering for `CallbackQueryHandler` and `InlineQueryHandler`
- New `MessageHandler` filters: `forwarded` and `entity`
- Add `Message.get_entity` to correctly handle UTF-16 codepoints and `MessageEntity` offsets
- Fix bug in `ConversationHandler` when first handler ends the conversation
- Allow multiple `Dispatcher` instances
- Add `ChatMigratedException`
- Properly split and handle arguments in `CommandHandler`

2016-07-15

Released 5.0

- Rework `JobQueue`
- Introduce `ConversationHandler`
- Introduce `telegram.constants` - <https://github.com/python-telegram-bot/python-telegram-bot/pull/342>

2016-07-12

Released 4.3.4

- Fix proxy support with `urllib3` when proxy requires auth

2016-07-08

Released 4.3.3

- Fix proxy support with `urllib3`

2016-07-04

Released 4.3.2

- Fix: Use `timeout` parameter in all API methods

2016-06-29

Released 4.3.1

- Update wrong requirement: `urllib3>=1.10`

2016-06-28

Released 4.3

- Use `urllib3.PoolManager` for connection re-use
- Rewrite `run_async` decorator to re-use threads
- New requirements: `urllib3` and `certifi`

2016-06-10

Released 4.2.1

- Fix `CallbackQuery.to_dict()` bug (thanks to @jlmadurga)
- Fix `editMessageText` exception when receiving a `CallbackQuery`

2016-05-28

Released 4.2

- Implement Bot API 2.1

- Move `botan` module to `telegram.contrib`
- New exception type: `BadRequest`

2016-05-22

Released 4.1.2

- Fix `MessageEntity` decoding with Bot API 2.1 changes

2016-05-16

Released 4.1.1

- Fix deprecation warning in `Dispatcher`

2016-05-15

Released 4.1

- Implement API changes from May 6, 2016
- Fix bug when `start_polling` with `clean=True`
- Methods now have `snake_case` equivalent, for example `telegram.Bot.send_message` is the same as `telegram.Bot.sendMessage`

2016-05-01

Released 4.0.3

- Add missing attribute `location` to `InlineQuery`

2016-04-29

Released 4.0.2

- Bugfixes
- `KeyboardReplyMarkup` now accepts `str` again

2016-04-27

Released 4.0.1

- Implement Bot API 2.0
- Almost complete recode of `Dispatcher`
- Please read the [Transition Guide to 4.0](#)
- **Changes from 4.0rc1**
 - The syntax of filters for `MessageHandler` (upper/lower cases)
 - Handler groups are now identified by `int` only, and ordered
- **Note:** v4.0 has been skipped due to a PyPI accident

2016-04-22

Released 4.0rc1

- Implement Bot API 2.0
- Almost complete recode of `Dispatcher`
- Please read the [Transistion Guide to 4.0](#)

2016-03-22

Released 3.4

- Move `Updater`, `Dispatcher` and `JobQueue` to new `telegram.ext` submodule (thanks to @rahiel)
- Add `disable_notification` parameter (thanks to @aidarbiktimirov)

- Fix bug where commands sent by Telegram Web would not be recognized (thanks to @shelomentsevd)
- Add option to skip old updates on bot startup
- Send files from `BufferedReader`

2016-02-28

Released 3.3

- Inline bots
- Send any file by URL
- Specialized exceptions: `Unauthorized`, `InvalidToken`, `NetworkError` and `TimedOut`
- Integration for botan.io (thanks to @ollmer)
- HTML Parsemode (thanks to @jlmadurga)
- Bugfixes and under-the-hood improvements

Very special thanks to Noam Meltzer (@tsnoam) for all of his work!

2016-01-09

Released 3.3b1

- Implement inline bots (beta)

2016-01-05

Released 3.2.0

- Introducing `JobQueue` (original author: @franciscod)
- Streamlining all exceptions to `TelegramError` (Special thanks to @tsnoam)
- Proper locking of `Updater` and `Dispatcher` start and stop methods
- Small bugfixes

2015-12-29

Released 3.1.2

- Fix custom path for file downloads
- Don't stop the dispatcher thread on uncaught errors in handlers

2015-12-21

Released 3.1.1

- Fix a bug where asynchronous handlers could not have additional arguments
- Add `groups` and `groupdict` as additional arguments for regex-based handlers

2015-12-16

Released 3.1.0

- The `chat`-field in `Message` is now of type `Chat`. (API update Oct 8 2015)
- `Message` now contains the optional fields `supergroup_chat_created`, `migrate_to_chat_id`, `migrate_from_chat_id` and `channel_chat_created`. (API update Nov 2015)

2015-12-08

Released 3.0.0

- Introducing the `Updater` and `Dispatcher` classes

2015-11-11

Released 2.9.2

- Error handling on request timeouts has been improved

2015-11-10

Released 2.9.1

- Add parameter `network_delay` to `Bot.getUpdates` for slow connections

2015-11-10

Released 2.9

- Emoji class now uses `bytes_to_native_str` from future 3rd party lib
- Make `user_from` optional to work with channels
- Raise exception if Telegram times out on long-polling

Special thanks to @jh0ker for all hard work

2015-10-08

Released 2.8.7

- Type as optional for `GroupChat` class

2015-10-08

Released 2.8.6

- Adds type to `User` and `GroupChat` classes (pre-release Telegram feature)

2015-09-24

Released 2.8.5

- Handles HTTP Bad Gateway (503) errors on request
- Fixes regression on `Audio` and `Document` for unicode fields

2015-09-20

Released 2.8.4

- `getFile` and `File.download` is now fully supported

2015-09-10

Released 2.8.3

- Moved `Bot._requestURL` to its own class (`telegram.utils.request`)
- Much better, such wow, Telegram Objects tests
- Add consistency for `str` properties on Telegram Objects
- Better design to test if `chat_id` is invalid
- Add ability to set custom filename on `Bot.sendDocument(..., filename='')`
- Fix Sticker as `InputFile`
- Send JSON requests over urlencoded post data
- Markdown support for `Bot.sendMessage(..., parse_mode=ParseMode.MARKDOWN)`
- Refactor of `TelegramError` class (no more handling `IOError` or `URLError`)

2015-09-05

Released 2.8.2

- Fix regression on Telegram `ReplyMarkup`
- Add certificate to `is_inputfile` method

2015-09-05*Released 2.8.1*

- Fix regression on Telegram objects with thumb properties

2015-09-04*Released 2.8*

- TelegramError when chat_id is empty for send* methods
- setWebhook now supports sending self-signed certificate
- Huge redesign of existing Telegram classes
- Added support for PyPy
- Added docstring for existing classes

2015-08-19*Released 2.7.1*

- Fixed JSON serialization for message

2015-08-17*Released 2.7*

- Added support for Voice object and sendVoice method
- Due backward compatibility performer or/and title will be required for sendAudio
- Fixed JSON serialization when forwarded message

2015-08-15*Released 2.6.1*

- Fixed parsing image header issue on < Python 2.7.3

2015-08-14*Released 2.6.0*

- Depreciation of require_authentication and clearCredentials methods
- Giving AUTHORS the proper credits for their contribution for this project
- Message.date and Message.forward_date are now datetime objects

2015-08-12*Released 2.5.3*

- telegram.Bot now supports to be unpickled

2015-08-11*Released 2.5.2*

- New changes from Telegram Bot API have been applied
- telegram.Bot now supports to be pickled
- Return empty str instead None when message.text is empty

2015-08-10*Released 2.5.1*

- Moved from GPLv2 to LGPLv3

2015-08-09*Released 2.5*

- Fixes logging calls in API

2015-08-08

Released 2.4

- Fixes `Emoji` class for Python 3
- PEP8 improvements

2015-08-08

Released 2.3

- Fixes `ForceReply` class
- Remove `logging.basicConfig` from library

2015-07-25

Released 2.2

- Allows `debug=True` when initializing `telegram.Bot`

2015-07-20

Released 2.1

- Fix `to_dict` for `Document` and `Video`

2015-07-19

Released 2.0

- Fixes bugs
- Improves `__str__` over `to_json()`
- Creates abstract class `TelegramObject`

2015-07-15

Released 1.9

- Python 3 officially supported
- PEP8 improvements

2015-07-12

Released 1.8

- Fixes crash when replying an unicode text message (special thanks to JRoot3D)

2015-07-11

Released 1.7

- Fixes crash when `username` is not defined on `chat` (special thanks to JRoot3D)

2015-07-10

Released 1.6

- Improvements for GAE support

2015-07-10

Released 1.5

- Fixes randomly unicode issues when using `InputFile`

2015-07-10

Released 1.4

- `requests` lib is no longer required

- Google App Engine (GAE) is supported

2015-07-10

Released 1.3

- Added support to `setWebhook` (special thanks to macrojames)

2015-07-09

Released 1.2

- `CustomKeyboard` classes now available
- Emojis available
- PEP8 improvements

2015-07-08

Released 1.1

- PyPi package now available

2015-07-08

Released 1.0

- Initial checkin of python-telegram-bot

t

- `telegram.constants`, [152](#)
- `telegram.error`, [160](#)
- `telegram.ext.filters`, [12](#)
- `telegram.utils.helpers`, [283](#)
- `telegram.utils.types`, [289](#)

Symbols

`__call__()` (*telegram.ext.DelayQueue* method), 34
`__call__()` (*telegram.ext.MessageQueue* method), 32
`__init__()` (*telegram.ext.DelayQueue* method), 34
`__init__()` (*telegram.ext.MessageQueue* method), 33
`__weakref__` (*telegram.ext.MessageQueue* attribute), 33

A

`add_bot_ids()` (*telegram.ext.filters.Filters.via_bot* method), 24
`add_chat_ids()` (*telegram.ext.filters.Filters.chat* method), 14
`add_chat_ids()` (*telegram.ext.filters.Filters.sender_chat* method), 20
`add_error_handler()` (*telegram.ext.Dispatcher* method), 9
`add_handler()` (*telegram.ext.Dispatcher* method), 10
`add_sticker_to_set()` (*telegram.Bot* method), 81
`add_user_ids()` (*telegram.ext.filters.Filters.user* method), 23
`add_usernames()` (*telegram.ext.filters.Filters.chat* method), 14
`add_usernames()` (*telegram.ext.filters.Filters.sender_chat* method), 20
`add_usernames()` (*telegram.ext.filters.Filters.user* method), 23
`add_usernames()` (*telegram.ext.filters.Filters.via_bot* method), 24
`address` (*telegram.ChatLocation* attribute), 146
`address` (*telegram.InlineQueryResultVenue* attribute), 251
`address` (*telegram.InputVenueMessageContent* attribute), 259
`address` (*telegram.SecureData* attribute), 275
`address` (*telegram.Venue* attribute), 214
`addStickerToSet()` (*telegram.Bot* method), 81

`ADMINISTRATOR` (*telegram.ChatMember* attribute), 149
`all` (*telegram.ext.filters.Filters* attribute), 12
`ALL_EMOJI` (*telegram.Dice* attribute), 158
`ALL_TYPES` (*telegram.MessageEntity* attribute), 195
`allow_edited` (*telegram.ext.CommandHandler* attribute), 47
`allow_empty` (*telegram.ext.filters.Filters.chat* attribute), 13
`allow_empty` (*telegram.ext.filters.Filters.sender_chat* attribute), 19
`allow_empty` (*telegram.ext.filters.Filters.user* attribute), 22
`allow_empty` (*telegram.ext.filters.Filters.via_bot* attribute), 24
`allow_reentry` (*telegram.ext.ConversationHandler* attribute), 45
`allow_sending_without_reply` (*telegram.ext.Defaults* attribute), 36
`allowed_updates` (*telegram.WebhookInfo* attribute), 219
`allows_multiple_answers` (*telegram.Poll* attribute), 198
`amount` (*telegram.LabeledPrice* attribute), 261
`Animation` (class in *telegram*), 77
`animation` (*telegram.ext.filters.Filters* attribute), 12
`animation` (*telegram.Game* attribute), 268
`animation` (*telegram.Message* attribute), 178
`ANONYMOUS_ADMIN_ID` (in module *telegram.constants*), 153
`answer()` (*telegram.CallbackQuery* method), 135
`answer()` (*telegram.InlineQuery* method), 224
`answer()` (*telegram.PreCheckoutQuery* method), 268
`answer()` (*telegram.ShippingQuery* method), 266
`answer_callback_query()` (*telegram.Bot* method), 82
`answer_inline_query()` (*telegram.Bot* method), 83
`answer_pre_checkout_query()` (*telegram.Bot* method), 84
`answer_shipping_query()` (*telegram.Bot* method), 84

- `answerCallbackQuery()` (*telegram.Bot* method), 82
- `answerInlineQuery()` (*telegram.Bot* method), 82
- `answerPreCheckoutQuery()` (*telegram.Bot* method), 82
- `answerShippingQuery()` (*telegram.Bot* method), 82
- `apk` (*telegram.ext.filters.Filters* attribute), 16
- `application` (*telegram.ext.filters.Filters* attribute), 16
- `args` (*telegram.ext.CallbackContext* attribute), 35
- `args` (*telegram.utils.promise.Promise* attribute), 287
- `async_args` (*telegram.ext.CallbackContext* attribute), 35
- `async_kwargs` (*telegram.ext.CallbackContext* attribute), 35
- `attach` (*telegram.InputFile* attribute), 165
- `Audio` (class in *telegram*), 79
- `audio` (*telegram.ext.filters.Filters* attribute), 12, 16
- `audio` (*telegram.Message* attribute), 178
- `audio_duration` (*telegram.InlineQueryResultAudio* attribute), 227
- `audio_file_id` (*telegram.InlineQueryResultCachedAudio* attribute), 229
- `audio_url` (*telegram.InlineQueryResultAudio* attribute), 227
- `author_signature` (*telegram.Message* attribute), 179
- B**
- `BadRequest`, 160
- `bank_statement` (*telegram.SecureData* attribute), 275
- `BaseFilter` (class in *telegram.ext.filters*), 24
- `BasePersistence` (class in *telegram.ext*), 70
- `BASKETBALL` (*telegram.Dice* attribute), 158
- `basketball` (*telegram.ext.filters.Filters* attribute), 15
- `big_file_id` (*telegram.ChatPhoto* attribute), 151
- `big_file_unique_id` (*telegram.ChatPhoto* attribute), 151
- `bio` (*telegram.Chat* attribute), 139
- `birth_date` (*telegram.PersonalDetails* attribute), 276
- `BOLD` (*telegram.MessageEntity* attribute), 195
- `Bot` (class in *telegram*), 80
- `bot` (*telegram.Animation* attribute), 78
- `bot` (*telegram.Audio* attribute), 80
- `bot` (*telegram.CallbackQuery* attribute), 134
- `bot` (*telegram.Document* attribute), 159
- `bot` (*telegram.EncryptedPassportElement* attribute), 281
- `bot` (*telegram.ext.CallbackContext* attribute), 36
- `bot` (*telegram.ext.Dispatcher* attribute), 8
- `bot` (*telegram.ext.JobQueue* attribute), 28
- `bot` (*telegram.ext.Updater* attribute), 5
- `bot` (*telegram.Message* attribute), 180
- `bot` (*telegram.PassportData* attribute), 278
- `bot` (*telegram.PassportFile* attribute), 279
- `bot` (*telegram.PhotoSize* attribute), 197
- `bot` (*telegram.PreCheckoutQuery* attribute), 267
- `bot` (*telegram.ShippingQuery* attribute), 266
- `bot` (*telegram.Sticker* attribute), 221
- `bot` (*telegram.User* attribute), 209
- `bot` (*telegram.Video* attribute), 216
- `bot` (*telegram.VideoNote* attribute), 217
- `bot` (*telegram.Voice* attribute), 218
- `BOT_COMMAND` (*telegram.MessageEntity* attribute), 196
- `bot_data` (*telegram.ext.CallbackContext* attribute), 35
- `bot_data` (*telegram.ext.DictPersistence* attribute), 76
- `bot_data` (*telegram.ext.Dispatcher* attribute), 9
- `bot_data_json` (*telegram.ext.DictPersistence* attribute), 76
- `bot_ids` (*telegram.ext.filters.Filters.via_bot* attribute), 23
- `bot_username` (*telegram.LoginUrl* attribute), 175
- `BotCommand` (class in *telegram*), 133
- `burst_limit` (*telegram.ext.DelayQueue* attribute), 33
- C**
- `callback` (*telegram.ext.CallbackQueryHandler* attribute), 40
- `callback` (*telegram.ext.ChosenInlineResultHandler* attribute), 42
- `callback` (*telegram.ext.CommandHandler* attribute), 47
- `callback` (*telegram.ext.Handler* attribute), 38
- `callback` (*telegram.ext.InlineQueryHandler* attribute), 50
- `callback` (*telegram.ext.Job* attribute), 27
- `callback` (*telegram.ext.MessageHandler* attribute), 52
- `callback` (*telegram.ext.PollAnswerHandler* attribute), 54
- `callback` (*telegram.ext.PollHandler* attribute), 56
- `callback` (*telegram.ext.PreCheckoutQueryHandler* attribute), 57
- `callback` (*telegram.ext.PrefixHandler* attribute), 59
- `callback` (*telegram.ext.RegexHandler* attribute), 62
- `callback` (*telegram.ext.ShippingQueryHandler* attribute), 64
- `callback` (*telegram.ext.StringCommandHandler* attribute), 65
- `callback` (*telegram.ext.StringRegexHandler* attribute), 67
- `callback` (*telegram.ext.TypeHandler* attribute), 69
- `callback_data` (*telegram.InlineKeyboardButton* attribute), 163
- `callback_game` (*telegram.InlineKeyboardButton* attribute), 163
- `callback_query` (*telegram.Update* attribute), 206

- CallbackContext (class in telegram.ext), 34
- CallbackGame (class in telegram), 269
- CallbackQuery (class in telegram), 134
- CallbackQueryHandler (class in telegram.ext), 40
- can_add_web_page_previews (telegram.ChatMember attribute), 148
- can_add_web_page_previews (telegram.ChatPermissions attribute), 150
- can_be_edited (telegram.ChatMember attribute), 147
- can_change_info (telegram.ChatMember attribute), 147
- can_change_info (telegram.ChatPermissions attribute), 150
- can_delete_messages (telegram.ChatMember attribute), 148
- can_edit_messages (telegram.ChatMember attribute), 148
- can_invite_users (telegram.ChatMember attribute), 148
- can_invite_users (telegram.ChatPermissions attribute), 150
- can_join_groups (telegram.Bot attribute), 85
- can_join_groups (telegram.User attribute), 208
- can_pin_messages (telegram.ChatMember attribute), 148
- can_pin_messages (telegram.ChatPermissions attribute), 150
- can_post_messages (telegram.ChatMember attribute), 147
- can_promote_members (telegram.ChatMember attribute), 148
- can_read_all_group_messages (telegram.Bot attribute), 85
- can_read_all_group_messages (telegram.User attribute), 208
- can_restrict_members (telegram.ChatMember attribute), 148
- can_send_media_messages (telegram.ChatMember attribute), 148
- can_send_media_messages (telegram.ChatPermissions attribute), 150
- can_send_messages (telegram.ChatMember attribute), 148
- can_send_messages (telegram.ChatPermissions attribute), 150
- can_send_other_messages (telegram.ChatMember attribute), 148
- can_send_other_messages (telegram.ChatPermissions attribute), 150
- can_send_polls (telegram.ChatMember attribute), 148
- can_send_polls (telegram.ChatPermissions attribute), 150
- can_set_sticker_set (telegram.Chat attribute), 139
- caption (telegram.ext.filters.Filters attribute), 12
- caption (telegram.InlineQueryResultAudio attribute), 227
- caption (telegram.InlineQueryResultCachedAudio attribute), 229
- caption (telegram.InlineQueryResultCachedDocument attribute), 230
- caption (telegram.InlineQueryResultCachedGif attribute), 232
- caption (telegram.InlineQueryResultCachedMpeg4Gif attribute), 233
- caption (telegram.InlineQueryResultCachedPhoto attribute), 235
- caption (telegram.InlineQueryResultCachedVideo attribute), 237
- caption (telegram.InlineQueryResultCachedVoice attribute), 238
- caption (telegram.InlineQueryResultDocument attribute), 241
- caption (telegram.InlineQueryResultGif attribute), 244
- caption (telegram.InlineQueryResultMpeg4Gif attribute), 248
- caption (telegram.InlineQueryResultPhoto attribute), 249
- caption (telegram.InlineQueryResultVideo attribute), 253
- caption (telegram.InlineQueryResultVoice attribute), 255
- caption (telegram.InputMediaAnimation attribute), 166
- caption (telegram.InputMediaAudio attribute), 168
- caption (telegram.InputMediaDocument attribute), 169
- caption (telegram.InputMediaPhoto attribute), 170
- caption (telegram.InputMediaVideo attribute), 171
- caption (telegram.Message attribute), 178
- caption_entities (telegram.InlineQueryResultAudio attribute), 227
- caption_entities (telegram.InlineQueryResultCachedAudio attribute), 229
- caption_entities (telegram.InlineQueryResultCachedDocument attribute), 230
- caption_entities (telegram.InlineQueryResultCachedGif attribute), 232
- caption_entities (telegram.InlineQueryResultCachedMpeg4Gif attribute), 233
- caption_entities (telegram.InlineQueryResultCachedPhoto attribute), 235
- caption_entities (telegram.InlineQueryResultCachedVideo attribute), 237
- caption_entities (telegram.InlineQueryResultVoice attribute), 255

`gram.InlineQueryResultCachedVoice` (attribute), 238

`caption_entities` (`telegram.InlineQueryResultDocument` attribute), 241

`caption_entities` (`telegram.InlineQueryResultGif` attribute), 244

`caption_entities` (`telegram.InlineQueryResultMpeg4Gif` attribute), 248

`caption_entities` (`telegram.InlineQueryResultPhoto` attribute), 250

`caption_entities` (`telegram.InlineQueryResultVideo` attribute), 253

`caption_entities` (`telegram.InlineQueryResultVoice` attribute), 255

`caption_entities` (`telegram.InputMediaAnimation` attribute), 166

`caption_entities` (`telegram.InputMediaAudio` attribute), 168

`caption_entities` (`telegram.InputMediaDocument` attribute), 169

`caption_entities` (`telegram.InputMediaPhoto` attribute), 171

`caption_entities` (`telegram.InputMediaVideo` attribute), 171

`caption_entities` (`telegram.Message` attribute), 177

`caption_html` (`telegram.Message` attribute), 183

`caption_html_urled` (`telegram.Message` attribute), 183

`caption_markdown` (`telegram.Message` attribute), 183

`caption_markdown_urled` (`telegram.Message` attribute), 183

`caption_markdown_v2` (`telegram.Message` attribute), 183

`caption_markdown_v2_urled` (`telegram.Message` attribute), 184

`CASHTAG` (`telegram.MessageEntity` attribute), 196

`category` (`telegram.ext.filters.Filters` attribute), 15

`CHANNEL` (`telegram.Chat` attribute), 141

`channel` (`telegram.ext.filters.Filters` attribute), 14

`channel` (`telegram.ext.filters.Filters.sender_chat` attribute), 20

`channel_chat_created` (`telegram.Message` attribute), 179

`channel_post` (`telegram.ext.filters.Filters` attribute), 22

`channel_post` (`telegram.Update` attribute), 206

`channel_post_updates` (`telegram.ext.MessageHandler` attribute), 53

`channel_posts` (`telegram.ext.filters.Filters` attribute), 22

`Chat` (class in `telegram`), 138

`chat` (`telegram.Message` attribute), 177

`CHAT_CHANNEL` (in module `telegram.constants`), 154

`chat_created` (`telegram.ext.filters.Filters` attribute), 21

`chat_data` (`telegram.ext.CallbackContext` attribute), 35

`chat_data` (`telegram.ext.DictPersistence` attribute), 76

`chat_data` (`telegram.ext.Dispatcher` attribute), 9

`chat_data_json` (`telegram.ext.DictPersistence` attribute), 76

`CHAT_GROUP` (in module `telegram.constants`), 153

`chat_id` (`telegram.Message` attribute), 184

`chat_ids` (`telegram.ext.filters.Filters.chat` attribute), 13

`chat_ids` (`telegram.ext.filters.Filters.sender_chat` attribute), 19

`chat_instance` (`telegram.CallbackQuery` attribute), 134

`CHAT_PRIVATE` (in module `telegram.constants`), 153

`CHAT_SUPERGROUP` (in module `telegram.constants`), 153

`chat_type` (`telegram.ext.filters.Filters` attribute), 14

`ChatAction` (class in `telegram`), 146

`CHATACTION_FIND_LOCATION` (in module `telegram.constants`), 154

`CHATACTION_RECORD_AUDIO` (in module `telegram.constants`), 154

`CHATACTION_RECORD_VIDEO` (in module `telegram.constants`), 154

`CHATACTION_RECORD_VIDEO_NOTE` (in module `telegram.constants`), 154

`CHATACTION_TYPING` (in module `telegram.constants`), 154

`CHATACTION_UPLOAD_AUDIO` (in module `telegram.constants`), 154

`CHATACTION_UPLOAD_DOCUMENT` (in module `telegram.constants`), 154

`CHATACTION_UPLOAD_PHOTO` (in module `telegram.constants`), 154

`CHATACTION_UPLOAD_VIDEO` (in module `telegram.constants`), 154

`CHATACTION_UPLOAD_VIDEO_NOTE` (in module `telegram.constants`), 154

`ChatLocation` (class in `telegram`), 146

`ChatMember` (class in `telegram`), 147

`CHATMEMBER_ADMINISTRATOR` (in module `telegram.constants`), 154

`CHATMEMBER_CREATOR` (in module `telegram.constants`), 154

`CHATMEMBER_KICKED` (in module `telegram.constants`), 154

`CHATMEMBER_LEFT` (in module `telegram.constants`), 155

`CHATMEMBER_MEMBER` (in module `tele-`

- `gram.constants`), 155
- `CHATMEMBER_RESTRICTED` (in module `telegram.constants`), 155
- `ChatMigrated`, 160
- `ChatPermissions` (class in `telegram`), 150
- `ChatPhoto` (class in `telegram`), 151
- `check_update()` (`telegram.ext.CallbackQueryHandler` method), 41
- `check_update()` (`telegram.ext.ChosenInlineResultHandler` method), 43
- `check_update()` (`telegram.ext.CommandHandler` method), 49
- `check_update()` (`telegram.ext.ConversationHandler` method), 46
- `check_update()` (`telegram.ext.Handler` method), 39
- `check_update()` (`telegram.ext.InlineQueryHandler` method), 51
- `check_update()` (`telegram.ext.MessageHandler` method), 54
- `check_update()` (`telegram.ext.PollAnswerHandler` method), 55
- `check_update()` (`telegram.ext.PollHandler` method), 57
- `check_update()` (`telegram.ext.PreCheckoutQueryHandler` method), 58
- `check_update()` (`telegram.ext.PrefixHandler` method), 61
- `check_update()` (`telegram.ext.ShippingQueryHandler` method), 65
- `check_update()` (`telegram.ext.StringCommandHandler` method), 66
- `check_update()` (`telegram.ext.StringRegexHandler` method), 68
- `check_update()` (`telegram.ext.TypeHandler` method), 70
- `CHIN` (`telegram.MaskPosition` attribute), 223
- `chosen_inline_result` (`telegram.Update` attribute), 206
- `ChosenInlineResult` (class in `telegram`), 260
- `ChosenInlineResultHandler` (class in `telegram.ext`), 42
- `city` (`telegram.ResidentialAddress` attribute), 277
- `city` (`telegram.ShippingAddress` attribute), 262
- `close()` (`telegram.Bot` method), 85
- `close_date` (`telegram.Poll` attribute), 199
- `CODE` (`telegram.MessageEntity` attribute), 196
- `collect_additional_context()` (`telegram.ext.CallbackQueryHandler` method), 42
- `collect_additional_context()` (`telegram.ext.CommandHandler` method), 49
- `collect_additional_context()` (`telegram.ext.Handler` method), 39
- `collect_additional_context()` (`telegram.ext.InlineQueryHandler` method), 51
- `collect_additional_context()` (`telegram.ext.MessageHandler` method), 54
- `collect_additional_context()` (`telegram.ext.PrefixHandler` method), 61
- `collect_additional_context()` (`telegram.ext.StringCommandHandler` method), 66
- `collect_additional_context()` (`telegram.ext.StringRegexHandler` method), 68
- `collect_optional_args()` (`telegram.ext.CallbackQueryHandler` method), 42
- `collect_optional_args()` (`telegram.ext.CommandHandler` method), 49
- `collect_optional_args()` (`telegram.ext.Handler` method), 39
- `collect_optional_args()` (`telegram.ext.InlineQueryHandler` method), 52
- `collect_optional_args()` (`telegram.ext.RegexHandler` method), 63
- `collect_optional_args()` (`telegram.ext.StringCommandHandler` method), 67
- `collect_optional_args()` (`telegram.ext.StringRegexHandler` method), 69
- `command` (`telegram.BotCommand` attribute), 133
- `command` (`telegram.ext.CommandHandler` attribute), 47
- `command` (`telegram.ext.filters.Filters` attribute), 14
- `command` (`telegram.ext.PrefixHandler` attribute), 61
- `command` (`telegram.ext.StringCommandHandler` attribute), 65
- `CommandHandler` (class in `telegram.ext`), 47
- `commands` (`telegram.Bot` attribute), 85
- `con_pool_size` (`telegram.utils.request.Request` attribute), 288
- `Conflict`, 160
- `connected_website` (`telegram.ext.filters.Filters` attribute), 21
- `connected_website` (`telegram.Message` attribute), 179
- `Contact` (class in `telegram`), 157
- `contact` (`telegram.ext.filters.Filters` attribute), 15
- `contact` (`telegram.Message` attribute), 178
- `contains_masks` (`telegram.StickerSet` attribute), 222
- `context` (`telegram.ext.Job` attribute), 27
- `conversation_timeout` (tele-

gram.ext.ConversationHandler attribute), 45

ConversationDict (in module *telegram.utils.types*), 289

ConversationHandler (class in *telegram.ext*), 44

conversations (*telegram.ext.DictPersistence* attribute), 76

conversations_json (*telegram.ext.DictPersistence* attribute), 76

copy() (*telegram.Message* method), 184

copy_message() (*telegram.Bot* method), 85

copy_message() (*telegram.CallbackQuery* method), 135

copy_message() (*telegram.Chat* method), 141

copy_message() (*telegram.User* method), 209

copyMessage() (*telegram.Bot* method), 85

correct_option_id (*telegram.Poll* attribute), 198

country_code (*telegram.PersonalDetails* attribute), 276

country_code (*telegram.ResidentialAddress* attribute), 277

country_code (*telegram.ShippingAddress* attribute), 262

create_deep_linked_url() (in module *telegram.utils.helpers*), 284

create_new_sticker_set() (*telegram.Bot* method), 86

createNewStickerSet() (*telegram.Bot* method), 86

CREATOR (*telegram.ChatMember* attribute), 149

Credentials (class in *telegram*), 274

credentials (*telegram.PassportData* attribute), 278

currency (*telegram.Invoice* attribute), 262

currency (*telegram.PreCheckoutQuery* attribute), 267

currency (*telegram.SuccessfulPayment* attribute), 264

custom_title (*telegram.ChatMember* attribute), 147

D

DARTS (*telegram.Dice* attribute), 159

darts (*telegram.ext.filters.Filters* attribute), 15

data (*telegram.CallbackQuery* attribute), 134

data (*telegram.EncryptedCredentials* attribute), 282

data (*telegram.EncryptedPassportElement* attribute), 280

data (*telegram.PassportData* attribute), 277

data_filter (*telegram.ext.filters.BaseFilter* attribute), 25

data_filter (*telegram.ext.filters.MessageFilter* attribute), 25

data_filter (*telegram.ext.filters.UpdateFilter* attribute), 26

data_hash (*telegram.PassportElementErrorDataField* attribute), 273

DataCredentials (class in *telegram*), 274

date (*telegram.Message* attribute), 177

de_json() (*telegram.Update* class method), 207

decode_conversations_from_json() (in module *telegram.utils.helpers*), 284

decode_user_chat_data_from_json() (in module *telegram.utils.helpers*), 284

decrypted_credentials (*telegram.PassportData* attribute), 278

decrypted_data (*telegram.EncryptedCredentials* attribute), 282

decrypted_data (*telegram.PassportData* attribute), 278

decrypted_secret (*telegram.EncryptedCredentials* attribute), 283

DEFAULT_FALSE (in module *telegram.utils.helpers*), 283

DEFAULT_NONE (in module *telegram.utils.helpers*), 283

Defaults (class in *telegram.ext*), 36

DefaultValue (class in *telegram.utils.helpers*), 283

DelayQueue (class in *telegram.ext*), 33

delete() (*telegram.Message* method), 184

delete_chat_photo (*telegram.ext.filters.Filters* attribute), 21

delete_chat_photo (*telegram.Message* attribute), 179

delete_chat_photo() (*telegram.Bot* method), 88

delete_chat_sticker_set() (*telegram.Bot* method), 88

delete_message() (*telegram.Bot* method), 88

delete_message() (*telegram.CallbackQuery* method), 135

delete_sticker_from_set() (*telegram.Bot* method), 89

delete_webhook() (*telegram.Bot* method), 89

deleteChatPhoto() (*telegram.Bot* method), 87

deleteChatStickerSet() (*telegram.Bot* method), 87

deleteMessage() (*telegram.Bot* method), 87

deleteStickerFromSet() (*telegram.Bot* method), 87

deleteWebhook() (*telegram.Bot* method), 88

description (*telegram.BotCommand* attribute), 133

description (*telegram.Chat* attribute), 139

description (*telegram.Game* attribute), 268

description (*telegram.InlineQueryResultArticle* attribute), 226

description (*telegram.InlineQueryResultCachedDocument* attribute), 230

description (*telegram.InlineQueryResultCachedPhoto* attribute), 235

description (*telegram.InlineQueryResultCachedVideo* attribute), 237

- `description` (*telegram.InlineQueryResultDocument* attribute), 241
 - `description` (*telegram.InlineQueryResultPhoto* attribute), 249
 - `description` (*telegram.InlineQueryResultVideo* attribute), 254
 - `description` (*telegram.Invoice* attribute), 262
 - `Dice` (class in *telegram*), 158
 - `DICE` (*telegram.Dice* attribute), 159
 - `dice` (*telegram.ext.filters.Filters* attribute), 15
 - `dice` (*telegram.Message* attribute), 180
 - `DICE_ALL_EMOJI` (in module *telegram.constants*), 155
 - `DICE_BASKETBALL` (in module *telegram.constants*), 155
 - `DICE_DARTS` (in module *telegram.constants*), 155
 - `DICE_DICE` (in module *telegram.constants*), 155
 - `DICE_FOOTBALL` (in module *telegram.constants*), 155
 - `DICE_SLOT_MACHINE` (in module *telegram.constants*), 155
 - `DictPersistence` (class in *telegram.ext*), 75
 - `disable_content_type_detection` (*telegram.InputMediaDocument* attribute), 170
 - `disable_notification` (*telegram.ext.Defaults* attribute), 36
 - `disable_web_page_preview` (*telegram.ext.Defaults* attribute), 36
 - `disable_web_page_preview` (*telegram.InputTextMessageContent* attribute), 257
 - `dispatch_error()` (*telegram.ext.Dispatcher* method), 10
 - `Dispatcher` (class in *telegram.ext*), 8
 - `dispatcher` (*telegram.ext.CallbackContext* attribute), 36
 - `dispatcher` (*telegram.ext.Updater* attribute), 6
 - `DispatcherHandlerStop` (class in *telegram.ext*), 12
 - `distance` (*telegram.ProximityAlertTriggered* attribute), 201
 - `doc` (*telegram.ext.filters.Filters* attribute), 16
 - `Document` (class in *telegram*), 159
 - `document` (*telegram.ext.filters.Filters* attribute), 15
 - `document` (*telegram.Message* attribute), 178
 - `document_file_id` (*telegram.InlineQueryResultCachedDocument* attribute), 230
 - `document_no` (*telegram.IdDocumentData* attribute), 276
 - `document_url` (*telegram.InlineQueryResultDocument* attribute), 241
 - `docx` (*telegram.ext.filters.Filters* attribute), 16
 - `done` (*telegram.utils.promise.Promise* attribute), 288
 - `download()` (*telegram.File* method), 161
 - `download()` (*telegram.utils.request.Request* method), 289
 - `download_as_bytearray()` (*telegram.File* method), 162
 - `driver_license` (*telegram.SecureData* attribute), 275
 - `duration` (*telegram.Animation* attribute), 78
 - `duration` (*telegram.Audio* attribute), 79
 - `duration` (*telegram.InputMediaAnimation* attribute), 167
 - `duration` (*telegram.InputMediaAudio* attribute), 168
 - `duration` (*telegram.InputMediaVideo* attribute), 172
 - `duration` (*telegram.Video* attribute), 215
 - `duration` (*telegram.VideoNote* attribute), 217
 - `duration` (*telegram.Voice* attribute), 218
- ## E
- `edit_caption()` (*telegram.Message* method), 184
 - `edit_date` (*telegram.Message* attribute), 177
 - `edit_live_location()` (*telegram.Message* method), 185
 - `edit_media()` (*telegram.Message* method), 185
 - `edit_message_caption()` (*telegram.Bot* method), 90
 - `edit_message_caption()` (*telegram.CallbackQuery* method), 135
 - `edit_message_live_location()` (*telegram.Bot* method), 91
 - `edit_message_live_location()` (*telegram.CallbackQuery* method), 136
 - `edit_message_media()` (*telegram.Bot* method), 92
 - `edit_message_media()` (*telegram.CallbackQuery* method), 136
 - `edit_message_reply_markup()` (*telegram.Bot* method), 92
 - `edit_message_reply_markup()` (*telegram.CallbackQuery* method), 136
 - `edit_message_text()` (*telegram.Bot* method), 93
 - `edit_message_text()` (*telegram.CallbackQuery* method), 137
 - `edit_reply_markup()` (*telegram.Message* method), 185
 - `edit_text()` (*telegram.Message* method), 185
 - `edited_channel_post` (*telegram.ext.filters.Filters* attribute), 22
 - `edited_channel_post` (*telegram.Update* attribute), 206
 - `edited_message` (*telegram.ext.filters.Filters* attribute), 22
 - `edited_message` (*telegram.Update* attribute), 206
 - `edited_updates` (*telegram.ext.MessageHandler* attribute), 53
 - `editMessageCaption()` (*telegram.Bot* method), 89
 - `editMessageLiveLocation()` (*telegram.Bot* method), 90
 - `editMessageMedia()` (*telegram.Bot* method), 90

`editMessageReplyMarkup()` (*telegram.Bot method*), 90

`editMessageText()` (*telegram.Bot method*), 90

`effective_attachment` (*telegram.Message attribute*), 186

`effective_chat` (*telegram.Update attribute*), 207

`effective_message` (*telegram.Update attribute*), 208

`effective_message_type()` (*in module telegram.utils.helpers*), 284

`effective_user` (*telegram.Update attribute*), 208

`email` (*telegram.EncryptedPassportElement attribute*), 280

`EMAIL` (*telegram.MessageEntity attribute*), 196

`email` (*telegram.OrderInfo attribute*), 263

`emoji` (*telegram.Dice attribute*), 158

`emoji` (*telegram.Sticker attribute*), 220

`enabled` (*telegram.ext.Job attribute*), 28

`encode_conversations_to_json()` (*in module telegram.utils.helpers*), 285

`EncryptedCredentials` (*class in telegram*), 282

`EncryptedPassportElement` (*class in telegram*), 280

`END` (*telegram.ext.ConversationHandler attribute*), 46

`entities` (*telegram.InputTextMessageContent attribute*), 257

`entities` (*telegram.Message attribute*), 177

`entry_points` (*telegram.ext.ConversationHandler attribute*), 44

`error` (*telegram.ext.CallbackContext attribute*), 35

`error_handlers` (*telegram.ext.Dispatcher attribute*), 10

`error_handling` (*telegram.utils.promise.Promise attribute*), 288

`escape_markdown()` (*in module telegram.utils.helpers*), 285

`exc_route` (*telegram.ext.DelayQueue attribute*), 33

`exception` (*telegram.utils.promise.Promise attribute*), 288

`exe` (*telegram.ext.filters.Filters attribute*), 16

`expiry_date` (*telegram.IdDocumentData attribute*), 276

`explanation` (*telegram.Poll attribute*), 198

`explanation_entities` (*telegram.Poll attribute*), 199

`export_chat_invite_link()` (*telegram.Bot method*), 94

`exportChatInviteLink()` (*telegram.Bot method*), 94

`EYES` (*telegram.MaskPosition attribute*), 223

F

`fallbacks` (*telegram.ext.ConversationHandler attribute*), 44

`field_name` (*telegram.PassportElementErrorDataField attribute*), 273

`File` (*class in telegram*), 161

`file_date` (*telegram.PassportFile attribute*), 279

`file_extension` (*telegram.ext.filters.Filters attribute*), 17

`file_hash` (*telegram.PassportElementErrorFile attribute*), 271

`file_hash` (*telegram.PassportElementErrorFrontSide attribute*), 272

`file_hash` (*telegram.PassportElementErrorReverseSide attribute*), 271

`file_hashes` (*telegram.PassportElementErrorFiles attribute*), 273

`file_id` (*telegram.Animation attribute*), 77

`file_id` (*telegram.Audio attribute*), 79

`file_id` (*telegram.Document attribute*), 159

`file_id` (*telegram.File attribute*), 161

`file_id` (*telegram.PassportFile attribute*), 278

`file_id` (*telegram.PhotoSize attribute*), 197

`file_id` (*telegram.Sticker attribute*), 220

`file_id` (*telegram.Video attribute*), 215

`file_id` (*telegram.VideoNote attribute*), 217

`file_id` (*telegram.Voice attribute*), 218

`file_name` (*telegram.Animation attribute*), 78

`file_name` (*telegram.Audio attribute*), 79

`file_name` (*telegram.Document attribute*), 159

`file_name` (*telegram.Video attribute*), 215

`file_path` (*telegram.File attribute*), 161

`file_size` (*telegram.Animation attribute*), 78

`file_size` (*telegram.Audio attribute*), 79

`file_size` (*telegram.Document attribute*), 159

`file_size` (*telegram.File attribute*), 161

`file_size` (*telegram.PassportFile attribute*), 279

`file_size` (*telegram.PhotoSize attribute*), 197

`file_size` (*telegram.Sticker attribute*), 221

`file_size` (*telegram.Video attribute*), 216

`file_size` (*telegram.VideoNote attribute*), 217

`file_size` (*telegram.Voice attribute*), 218

`file_unique_id` (*telegram.Animation attribute*), 77

`file_unique_id` (*telegram.Audio attribute*), 79

`file_unique_id` (*telegram.Document attribute*), 159

`file_unique_id` (*telegram.File attribute*), 161

`file_unique_id` (*telegram.PassportFile attribute*), 279

`file_unique_id` (*telegram.PhotoSize attribute*), 197

`file_unique_id` (*telegram.Sticker attribute*), 220

`file_unique_id` (*telegram.Video attribute*), 215

`file_unique_id` (*telegram.VideoNote attribute*), 217

`file_unique_id` (*telegram.Voice attribute*), 218

`FileCredentials` (*class in telegram*), 275

`FileInput` (*in module telegram.utils.types*), 289

`FileLike` (*in module telegram.utils.types*), 289

`filename` (*telegram.ext.PicklePersistence attribute*), 73

`filename` (*telegram.InputFile attribute*), 165

`files` (*telegram.EncryptedPassportElement attribute*), 280

- `filter()` (*telegram.ext.filters.InvertedFilter method*), 26
 - `filter()` (*telegram.ext.filters.MergedFilter method*), 26
 - `filter()` (*telegram.ext.filters.MessageFilter method*), 25
 - `filter()` (*telegram.ext.filters.UpdateFilter method*), 26
 - `filter()` (*telegram.ext.filters.XORFilter method*), 27
 - `Filters` (*class in telegram.ext.filters*), 12
 - `filters` (*telegram.ext.CommandHandler attribute*), 47
 - `filters` (*telegram.ext.MessageHandler attribute*), 52
 - `filters` (*telegram.ext.PrefixHandler attribute*), 59
 - `Filters.caption_entity` (*class in telegram.ext.filters*), 12
 - `Filters.caption_regex` (*class in telegram.ext.filters*), 13
 - `Filters.chat` (*class in telegram.ext.filters*), 13
 - `Filters.entity` (*class in telegram.ext.filters*), 17
 - `Filters.language` (*class in telegram.ext.filters*), 18
 - `Filters.regex` (*class in telegram.ext.filters*), 18
 - `Filters.sender_chat` (*class in telegram.ext.filters*), 19
 - `Filters.user` (*class in telegram.ext.filters*), 22
 - `Filters.via_bot` (*class in telegram.ext.filters*), 23
 - `FIND_LOCATION` (*telegram.ChatAction attribute*), 146
 - `first_name` (*telegram.Bot attribute*), 94
 - `first_name` (*telegram.Chat attribute*), 139
 - `first_name` (*telegram.Contact attribute*), 157
 - `first_name` (*telegram.InlineQueryResultContact attribute*), 240
 - `first_name` (*telegram.InputContactMessageContent attribute*), 260
 - `first_name` (*telegram.PersonalDetails attribute*), 276
 - `first_name` (*telegram.User attribute*), 208
 - `first_name_native` (*telegram.PersonalDetails attribute*), 277
 - `flush()` (*telegram.ext.BasePersistence method*), 71
 - `flush()` (*telegram.ext.PicklePersistence method*), 74
 - `FOOTBALL` (*telegram.Dice attribute*), 159
 - `football` (*telegram.ext.filters.Filters attribute*), 15
 - `force_reply` (*telegram.ForceReply attribute*), 162
 - `ForceReply` (*class in telegram*), 162
 - `FOREHEAD` (*telegram.MaskPosition attribute*), 223
 - `forward()` (*telegram.Message method*), 186
 - `forward_date` (*telegram.Message attribute*), 177
 - `forward_from` (*telegram.Message attribute*), 177
 - `forward_from_chat` (*telegram.Message attribute*), 177
 - `forward_from_message_id` (*telegram.Message attribute*), 177
 - `forward_message()` (*telegram.Bot method*), 94
 - `forward_sender_name` (*telegram.Message attribute*), 179
 - `forward_signature` (*telegram.Message attribute*), 179
 - `forward_text` (*telegram.LoginUrl attribute*), 175
 - `forwarded` (*telegram.ext.filters.Filters attribute*), 18
 - `forwardMessage()` (*telegram.Bot method*), 94
 - `foursquare_id` (*telegram.InlineQueryResultVenue attribute*), 251
 - `foursquare_id` (*telegram.InputVenueMessageContent attribute*), 259
 - `foursquare_id` (*telegram.Venue attribute*), 214
 - `foursquare_type` (*telegram.InlineQueryResultVenue attribute*), 251
 - `foursquare_type` (*telegram.InputVenueMessageContent attribute*), 259
 - `foursquare_type` (*telegram.Venue attribute*), 214
 - `from_button()` (*telegram.InlineKeyboardMarkup class method*), 164
 - `from_button()` (*telegram.ReplyKeyboardMarkup class method*), 203
 - `from_column()` (*telegram.InlineKeyboardMarkup class method*), 165
 - `from_column()` (*telegram.ReplyKeyboardMarkup class method*), 204
 - `from_row()` (*telegram.InlineKeyboardMarkup class method*), 165
 - `from_row()` (*telegram.ReplyKeyboardMarkup class method*), 204
 - `from_timestamp()` (*in module telegram.utils.helpers*), 285
 - `from_user` (*telegram.CallbackQuery attribute*), 134
 - `from_user` (*telegram.ChosenInlineResult attribute*), 260
 - `from_user` (*telegram.InlineQuery attribute*), 224
 - `from_user` (*telegram.Message attribute*), 176
 - `from_user` (*telegram.PreCheckoutQuery attribute*), 267
 - `from_user` (*telegram.ShippingQuery attribute*), 265
 - `front_side` (*telegram.EncryptedPassportElement attribute*), 280
 - `full_name` (*telegram.User attribute*), 209
- ## G
- `Game` (*class in telegram*), 268
 - `game` (*telegram.ext.filters.Filters attribute*), 18
 - `game` (*telegram.Message attribute*), 178
 - `game_short_name` (*telegram.CallbackQuery attribute*), 134
 - `game_short_name` (*telegram.InlineQueryResultGame attribute*), 243
 - `GameHighScore` (*class in telegram*), 270
 - `gender` (*telegram.PersonalDetails attribute*), 276
 - `get_administrators()` (*telegram.Chat method*), 141

`get_big_file()` (*telegram.ChatPhoto* method), 152

`get_bot_data()` (*telegram.ext.BasePersistence* method), 71

`get_bot_data()` (*telegram.ext.DictPersistence* method), 76

`get_bot_data()` (*telegram.ext.PicklePersistence* method), 74

`get_chat()` (*telegram.Bot* method), 96

`get_chat_administrators()` (*telegram.Bot* method), 96

`get_chat_data()` (*telegram.ext.BasePersistence* method), 71

`get_chat_data()` (*telegram.ext.DictPersistence* method), 76

`get_chat_data()` (*telegram.ext.PicklePersistence* method), 74

`get_chat_member()` (*telegram.Bot* method), 96

`get_chat_members_count()` (*telegram.Bot* method), 97

`get_conversations()` (*telegram.ext.BasePersistence* method), 72

`get_conversations()` (*telegram.ext.DictPersistence* method), 76

`get_conversations()` (*telegram.ext.PicklePersistence* method), 74

`get_file()` (*telegram.Animation* method), 79

`get_file()` (*telegram.Audio* method), 80

`get_file()` (*telegram.Bot* method), 97

`get_file()` (*telegram.Document* method), 160

`get_file()` (*telegram.PassportFile* method), 279

`get_file()` (*telegram.PhotoSize* method), 197

`get_file()` (*telegram.Sticker* method), 221

`get_file()` (*telegram.Video* method), 216

`get_file()` (*telegram.VideoNote* method), 217

`get_file()` (*telegram.Voice* method), 218

`get_game_high_scores()` (*telegram.Bot* method), 97

`get_game_high_scores()` (*telegram.CallbackQuery* method), 137

`get_game_high_scores()` (*telegram.Message* method), 186

`get_instance()` (*telegram.ext.Dispatcher* class method), 10

`get_jobs_by_name()` (*telegram.ext.JobQueue* method), 28

`get_me()` (*telegram.Bot* method), 98

`get_member()` (*telegram.Chat* method), 141

`get_members_count()` (*telegram.Chat* method), 141

`get_my_commands()` (*telegram.Bot* method), 98

`get_profile_photos()` (*telegram.User* method), 209

`get_signal_name()` (in module *telegram.utils.helpers*), 285

`get_small_file()` (*telegram.ChatPhoto* method), 152

`get_sticker_set()` (*telegram.Bot* method), 98

`get_updates()` (*telegram.Bot* method), 99

`get_user_data()` (*telegram.ext.BasePersistence* method), 72

`get_user_data()` (*telegram.ext.DictPersistence* method), 76

`get_user_data()` (*telegram.ext.PicklePersistence* method), 74

`get_user_profile_photos()` (*telegram.Bot* method), 99

`get_webhook_info()` (*telegram.Bot* method), 100

`getChat()` (*telegram.Bot* method), 95

`getChatAdministrators()` (*telegram.Bot* method), 95

`getChatMember()` (*telegram.Bot* method), 95

`getChatMembersCount()` (*telegram.Bot* method), 95

`getFile()` (*telegram.Bot* method), 95

`getGameHighScores()` (*telegram.Bot* method), 95

`getMe()` (*telegram.Bot* method), 95

`getMyCommands()` (*telegram.Bot* method), 95

`getStickerSet()` (*telegram.Bot* method), 95

`getUpdates()` (*telegram.Bot* method), 95

`getUserProfilePhotos()` (*telegram.Bot* method), 95

`getWebhookInfo()` (*telegram.Bot* method), 96

`gif` (*telegram.ext.filters.Filters* attribute), 16

`gif_duration` (*telegram.InlineQueryResultGif* attribute), 244

`gif_file_id` (*telegram.InlineQueryResultCachedGif* attribute), 231

`gif_height` (*telegram.InlineQueryResultGif* attribute), 244

`gif_url` (*telegram.InlineQueryResultGif* attribute), 243

`gif_width` (*telegram.InlineQueryResultGif* attribute), 243

`google_place_id` (*telegram.InlineQueryResultVenue* attribute), 251

`google_place_id` (*telegram.InputVenueMessageContent* attribute), 259

`google_place_id` (*telegram.Venue* attribute), 214

`google_place_type` (*telegram.InlineQueryResultVenue* attribute), 251

`google_place_type` (*telegram.InputVenueMessageContent* attribute), 259

`google_place_type` (*telegram.Venue* attribute), 214

`GROUP` (*telegram.Chat* attribute), 141

`group` (*telegram.ext.filters.Filters* attribute), 14, 18

`group_chat_created` (*telegram.Message* attribute), 179

`groups` (*telegram.ext.Dispatcher* attribute), 10

`groups` (*telegram.ext.filters.Filters* attribute), 14

H

- `handle_update()` (*telegram.ext.ConversationHandler* method), 46
- `handle_update()` (*telegram.ext.Handler* method), 39
- `Handler` (class in *telegram.ext*), 38
- `HandlerArg` (in module *telegram.utils.types*), 289
- `handlers` (*telegram.ext.Dispatcher* attribute), 10
- `has_custom_certificate` (*telegram.WebhookInfo* attribute), 219
- `hash` (*telegram.DataCredentials* attribute), 274
- `hash` (*telegram.EncryptedCredentials* attribute), 282
- `hash` (*telegram.EncryptedPassportElement* attribute), 281
- `hash` (*telegram.FileCredentials* attribute), 275
- `HASHTAG` (*telegram.MessageEntity* attribute), 196
- `heading` (*telegram.InlineQueryResultLocation* attribute), 246
- `heading` (*telegram.InputLocationMessageContent* attribute), 258
- `heading` (*telegram.Location* attribute), 174
- `height` (*telegram.Animation* attribute), 78
- `height` (*telegram.InputMediaAnimation* attribute), 167
- `height` (*telegram.InputMediaVideo* attribute), 172
- `height` (*telegram.PhotoSize* attribute), 197
- `height` (*telegram.Sticker* attribute), 220
- `height` (*telegram.Video* attribute), 215
- `hide_url` (*telegram.InlineQueryResultArticle* attribute), 226
- `horizontal_accuracy` (*telegram.InlineQueryResultLocation* attribute), 245
- `horizontal_accuracy` (*telegram.InputLocationMessageContent* attribute), 257
- `horizontal_accuracy` (*telegram.Location* attribute), 174
- `HTML` (*telegram.ParseMode* attribute), 196
- I
- `id` (*telegram.Bot* attribute), 100
- `id` (*telegram.CallbackQuery* attribute), 134
- `id` (*telegram.Chat* attribute), 138
- `id` (*telegram.InlineQuery* attribute), 224
- `id` (*telegram.InlineQueryResult* attribute), 225
- `id` (*telegram.InlineQueryResultArticle* attribute), 226
- `id` (*telegram.InlineQueryResultAudio* attribute), 227
- `id` (*telegram.InlineQueryResultCachedAudio* attribute), 229
- `id` (*telegram.InlineQueryResultCachedDocument* attribute), 230
- `id` (*telegram.InlineQueryResultCachedGif* attribute), 231
- `id` (*telegram.InlineQueryResultCachedMpeg4Gif* attribute), 233
- `id` (*telegram.InlineQueryResultCachedPhoto* attribute), 234
- `id` (*telegram.InlineQueryResultCachedSticker* attribute), 236
- `id` (*telegram.InlineQueryResultCachedVideo* attribute), 237
- `id` (*telegram.InlineQueryResultCachedVoice* attribute), 238
- `id` (*telegram.InlineQueryResultContact* attribute), 239
- `id` (*telegram.InlineQueryResultDocument* attribute), 241
- `id` (*telegram.InlineQueryResultGame* attribute), 243
- `id` (*telegram.InlineQueryResultGif* attribute), 243
- `id` (*telegram.InlineQueryResultLocation* attribute), 245
- `id` (*telegram.InlineQueryResultMpeg4Gif* attribute), 247
- `id` (*telegram.InlineQueryResultPhoto* attribute), 249
- `id` (*telegram.InlineQueryResultVenue* attribute), 251
- `id` (*telegram.InlineQueryResultVideo* attribute), 253
- `id` (*telegram.InlineQueryResultVoice* attribute), 255
- `id` (*telegram.Poll* attribute), 198
- `id` (*telegram.PreCheckoutQuery* attribute), 267
- `id` (*telegram.ShippingOption* attribute), 264
- `id` (*telegram.ShippingQuery* attribute), 265
- `id` (*telegram.User* attribute), 208
- `IdDocumentData` (class in *telegram*), 276
- `identity_card` (*telegram.SecureData* attribute), 275
- `idle()` (*telegram.ext.Updater* method), 7
- `image` (*telegram.ext.filters.Filters* attribute), 16
- `inline_keyboard` (*telegram.InlineKeyboardMarkup* attribute), 164
- `inline_message_id` (*telegram.CallbackQuery* attribute), 134
- `inline_message_id` (*telegram.ChosenInlineResult* attribute), 260
- `inline_query` (*telegram.Update* attribute), 206
- `InlineKeyboardButton` (class in *telegram*), 163
- `InlineKeyboardMarkup` (class in *telegram*), 164
- `InlineQuery` (class in *telegram*), 223
- `InlineQueryHandler` (class in *telegram.ext*), 50
- `InlineQueryResult` (class in *telegram*), 225
- `InlineQueryResultArticle` (class in *telegram*), 225
- `InlineQueryResultAudio` (class in *telegram*), 227
- `InlineQueryResultCachedAudio` (class in *telegram*), 228
- `InlineQueryResultCachedDocument` (class in *telegram*), 230
- `InlineQueryResultCachedGif` (class in *telegram*), 231
- `InlineQueryResultCachedMpeg4Gif` (class in *telegram*), 233
- `InlineQueryResultCachedPhoto` (class in *telegram*), 234

`InlineQueryResultCachedSticker` (class in `telegram`), 236

`InlineQueryResultCachedVideo` (class in `telegram`), 236

`InlineQueryResultCachedVoice` (class in `telegram`), 238

`InlineQueryResultContact` (class in `telegram`), 239

`InlineQueryResultDocument` (class in `telegram`), 241

`InlineQueryResultGame` (class in `telegram`), 242

`InlineQueryResultGif` (class in `telegram`), 243

`InlineQueryResultLocation` (class in `telegram`), 245

`InlineQueryResultMpeg4Gif` (class in `telegram`), 247

`InlineQueryResultPhoto` (class in `telegram`), 249

`InlineQueryResultVenue` (class in `telegram`), 251

`InlineQueryResultVideo` (class in `telegram`), 253

`InlineQueryResultVoice` (class in `telegram`), 255

`input_file_content` (`telegram.InputFile` attribute), 165

`input_message_content` (`telegram.InlineQueryResultArticle` attribute), 226

`input_message_content` (`telegram.InlineQueryResultAudio` attribute), 228

`input_message_content` (`telegram.InlineQueryResultCachedAudio` attribute), 229

`input_message_content` (`telegram.InlineQueryResultCachedDocument` attribute), 231

`input_message_content` (`telegram.InlineQueryResultCachedGif` attribute), 232

`input_message_content` (`telegram.InlineQueryResultCachedMpeg4Gif` attribute), 233

`input_message_content` (`telegram.InlineQueryResultCachedPhoto` attribute), 235

`input_message_content` (`telegram.InlineQueryResultCachedSticker` attribute), 236

`input_message_content` (`telegram.InlineQueryResultCachedVideo` attribute), 237

`input_message_content` (`telegram.InlineQueryResultCachedVoice` attribute), 239

`input_message_content` (`telegram.InlineQueryResultContact` attribute), 240

`input_message_content` (`telegram.InlineQueryResultDocument` attribute), 242

`input_message_content` (`telegram.InlineQueryResultGif` attribute), 244

`input_message_content` (`telegram.InlineQueryResultLocation` attribute), 246

`input_message_content` (`telegram.InlineQueryResultMpeg4Gif` attribute), 248

`input_message_content` (`telegram.InlineQueryResultPhoto` attribute), 250

`input_message_content` (`telegram.InlineQueryResultVenue` attribute), 252

`input_message_content` (`telegram.InlineQueryResultVideo` attribute), 254

`input_message_content` (`telegram.InlineQueryResultVoice` attribute), 256

`InputContactMessageContent` (class in `telegram`), 259

`InputFile` (class in `telegram`), 165

`InputLocationMessageContent` (class in `telegram`), 257

`InputMedia` (class in `telegram`), 166

`InputMediaAnimation` (class in `telegram`), 166

`InputMediaAudio` (class in `telegram`), 168

`InputMediaDocument` (class in `telegram`), 169

`InputMediaPhoto` (class in `telegram`), 170

`InputMediaVideo` (class in `telegram`), 171

`InputMessageContent` (class in `telegram`), 256

`InputTextMessageContent` (class in `telegram`), 256

`InputVenueMessageContent` (class in `telegram`), 258

`insert_bot()` (`telegram.ext.BasePersistence` method), 72

`internal_passport` (`telegram.SecureData` attribute), 275

`InvalidToken`, 160

`InvertedFilter` (class in `telegram.ext.filters`), 26

`invite_link` (`telegram.Chat` attribute), 139

`Invoice` (class in `telegram`), 261

`invoice` (`telegram.ext.filters.Filters` attribute), 18

`invoice` (`telegram.Message` attribute), 179

`invoice_payload` (`telegram.PreCheckoutQuery` attribute), 267

`invoice_payload` (`telegram.ShippingQuery` attribute), 266

`invoice_payload` (`telegram.SuccessfulPayment` attribute), 264

`ip_address` (`telegram.WebhookInfo` attribute), 219

- `is_animated` (*telegram.Sticker* attribute), 220
 - `is_animated` (*telegram.StickerSet* attribute), 222
 - `is_anonymous` (*telegram.ChatMember* attribute), 147
 - `is_anonymous` (*telegram.Poll* attribute), 198
 - `is_bot` (*telegram.User* attribute), 208
 - `is_closed` (*telegram.Poll* attribute), 198
 - `is_image()` (*telegram.InputFile* static method), 166
 - `is_local_file()` (in module *telegram.utils.helpers*), 285
 - `is_member` (*telegram.ChatMember* attribute), 148
 - ITALIC* (*telegram.MessageEntity* attribute), 196
- ## J
- `Job` (class in *telegram.ext*), 27
 - `job` (*telegram.ext.CallbackContext* attribute), 36
 - `job` (*telegram.ext.Job* attribute), 27
 - `job_queue` (*telegram.ext.CallbackContext* attribute), 36
 - `job_queue` (*telegram.ext.Dispatcher* attribute), 8
 - `job_queue` (*telegram.ext.Job* attribute), 27
 - `job_queue` (*telegram.ext.Updater* attribute), 5
 - `JobQueue` (class in *telegram.ext*), 28
 - `jobs()` (*telegram.ext.JobQueue* method), 28
 - `jpg` (*telegram.ext.filters.Filters* attribute), 16
 - JSONDict* (in module *telegram.utils.types*), 289
- ## K
- `keyboard` (*telegram.ReplyKeyboardMarkup* attribute), 202
 - `KeyboardButton` (class in *telegram*), 173
 - `KeyboardButtonPollType` (class in *telegram*), 173
 - `kick_chat_member()` (*telegram.Bot* method), 100
 - `kick_member()` (*telegram.Chat* method), 141
 - `kickChatMember()` (*telegram.Bot* method), 100
 - KICKED* (*telegram.ChatMember* attribute), 149
 - `kwargs` (*telegram.utils.promise.Promise* attribute), 288
- ## L
- `label` (*telegram.LabeledPrice* attribute), 261
 - `LabeledPrice` (class in *telegram*), 261
 - `language` (*telegram.MessageEntity* attribute), 195
 - `language_code` (*telegram.User* attribute), 208
 - `last_error_date` (*telegram.WebhookInfo* attribute), 219
 - `last_error_message` (*telegram.WebhookInfo* attribute), 219
 - `last_name` (*telegram.Bot* attribute), 101
 - `last_name` (*telegram.Chat* attribute), 139
 - `last_name` (*telegram.Contact* attribute), 157
 - `last_name` (*telegram.InlineQueryResultContact* attribute), 240
 - `last_name` (*telegram.InputContactMessageContent* attribute), 260
 - `last_name` (*telegram.PersonalDetails* attribute), 276
 - `last_name` (*telegram.User* attribute), 208
 - `last_name_native` (*telegram.PersonalDetails* attribute), 277
 - `latitude` (*telegram.InlineQueryResultLocation* attribute), 245
 - `latitude` (*telegram.InlineQueryResultVenue* attribute), 251
 - `latitude` (*telegram.InputLocationMessageContent* attribute), 257
 - `latitude` (*telegram.InputVenueMessageContent* attribute), 258
 - `latitude` (*telegram.Location* attribute), 174
 - `leave()` (*telegram.Chat* method), 142
 - `leave_chat()` (*telegram.Bot* method), 101
 - `leaveChat()` (*telegram.Bot* method), 101
 - LEFT* (*telegram.ChatMember* attribute), 149
 - `left_chat_member` (*telegram.ext.filters.Filters* attribute), 21
 - `left_chat_member` (*telegram.Message* attribute), 178
 - `length` (*telegram.MessageEntity* attribute), 195
 - `length` (*telegram.VideoNote* attribute), 217
 - `link` (*telegram.Bot* attribute), 101
 - `link` (*telegram.Chat* attribute), 142
 - `link` (*telegram.Message* attribute), 186
 - `link` (*telegram.User* attribute), 209
 - `linked_chat_id` (*telegram.Chat* attribute), 140
 - `live_period` (*telegram.InlineQueryResultLocation* attribute), 246
 - `live_period` (*telegram.InputLocationMessageContent* attribute), 258
 - `live_period` (*telegram.Location* attribute), 174
 - `Location` (class in *telegram*), 174
 - `location` (*telegram.Chat* attribute), 140
 - `location` (*telegram.ChatLocation* attribute), 146
 - `location` (*telegram.ChosenInlineResult* attribute), 260
 - `location` (*telegram.ext.filters.Filters* attribute), 18
 - `location` (*telegram.InlineQuery* attribute), 224
 - `location` (*telegram.Message* attribute), 178
 - `location` (*telegram.Venue* attribute), 214
 - `log_out()` (*telegram.Bot* method), 101
 - `login_url` (*telegram.InlineKeyboardButton* attribute), 163
 - `LoginUrl` (class in *telegram*), 175
 - `logout()` (*telegram.Bot* method), 101
 - `longitude` (*telegram.InlineQueryResultLocation* attribute), 245
 - `longitude` (*telegram.InlineQueryResultVenue* attribute), 251
 - `longitude` (*telegram.InputLocationMessageContent* attribute), 257
 - `longitude` (*telegram.InputVenueMessageContent* attribute), 258
 - `longitude` (*telegram.Location* attribute), 174
- ## M
- `map_to_parent` (*telegram.ext.ConversationHandler*

- attribute*), 45
- MARKDOWN (*telegram.ParseMode attribute*), 196
- MARKDOWN_V2 (*telegram.ParseMode attribute*), 196
- mask_position (*telegram.Sticker attribute*), 221
- MaskPosition (*class in telegram*), 222
- match (*telegram.ext.CallbackContext attribute*), 36
- matches (*telegram.ext.CallbackContext attribute*), 35
- MAX_CAPTION_LENGTH (*in module telegram.constants*), 152
- max_connections (*telegram.WebhookInfo attribute*), 219
- MAX_FILESIZE_DOWNLOAD (*in module telegram.constants*), 153
- MAX_FILESIZE_UPLOAD (*in module telegram.constants*), 153
- MAX_INLINE_QUERY_RESULTS (*in module telegram.constants*), 153
- MAX_LENGTH (*telegram.PollOption attribute*), 201
- MAX_MESSAGE_ENTITIES (*in module telegram.constants*), 153
- MAX_MESSAGE_LENGTH (*in module telegram.constants*), 152
- MAX_MESSAGES_PER_MINUTE_PER_GROUP (*in module telegram.constants*), 153
- MAX_MESSAGES_PER_SECOND (*in module telegram.constants*), 153
- MAX_MESSAGES_PER_SECOND_PER_CHAT (*in module telegram.constants*), 153
- MAX_OPTION_LENGTH (*telegram.Poll attribute*), 199
- MAX_PHOTOSIZE_UPLOAD (*in module telegram.constants*), 153
- MAX_POLL_OPTION_LENGTH (*in module telegram.constants*), 157
- MAX_POLL_QUESTION_LENGTH (*in module telegram.constants*), 157
- MAX_QUESTION_LENGTH (*telegram.Poll attribute*), 199
- media (*telegram.InputMediaAnimation attribute*), 166
- media (*telegram.InputMediaAudio attribute*), 168
- media (*telegram.InputMediaDocument attribute*), 169
- media (*telegram.InputMediaPhoto attribute*), 170
- media (*telegram.InputMediaVideo attribute*), 171
- media_group_id (*telegram.Message attribute*), 177
- MEMBER (*telegram.ChatMember attribute*), 149
- MENTION (*telegram.MessageEntity attribute*), 196
- mention_html() (*in module telegram.utils.helpers*), 285
- mention_html() (*telegram.User method*), 209
- mention_markdown() (*in module telegram.utils.helpers*), 285
- mention_markdown() (*telegram.User method*), 209
- mention_markdown_v2() (*telegram.User method*), 210
- MergedFilter (*class in telegram.ext.filters*), 26
- Message (*class in telegram*), 176
- message (*telegram.CallbackQuery attribute*), 134
- message (*telegram.ext.filters.Filters attribute*), 22
- message (*telegram.PassportElementError attribute*), 270
- message (*telegram.PassportElementErrorDataField attribute*), 273
- message (*telegram.PassportElementErrorFile attribute*), 271
- message (*telegram.PassportElementErrorFiles attribute*), 273
- message (*telegram.PassportElementErrorFrontSide attribute*), 272
- message (*telegram.PassportElementErrorReverseSide attribute*), 271
- message (*telegram.Update attribute*), 206
- message_id (*telegram.Message attribute*), 176
- message_id (*telegram.MessageId attribute*), 194
- message_text (*telegram.InputTextMessageContent attribute*), 257
- message_updates (*telegram.ext.MessageHandler attribute*), 52
- MessageEntity (*class in telegram*), 195
- MESSAGEENTITY_ALL_TYPES (*in module telegram.constants*), 156
- MESSAGEENTITY_BOLD (*in module telegram.constants*), 156
- MESSAGEENTITY_BOT_COMMAND (*in module telegram.constants*), 155
- MESSAGEENTITY_CASHTAG (*in module telegram.constants*), 155
- MESSAGEENTITY_CODE (*in module telegram.constants*), 156
- MESSAGEENTITY_EMAIL (*in module telegram.constants*), 156
- MESSAGEENTITY_HASHTAG (*in module telegram.constants*), 155
- MESSAGEENTITY_ITALIC (*in module telegram.constants*), 156
- MESSAGEENTITY_MENTION (*in module telegram.constants*), 155
- MESSAGEENTITY_PHONE_NUMBER (*in module telegram.constants*), 155
- MESSAGEENTITY_PRE (*in module telegram.constants*), 156
- MESSAGEENTITY_STRIKETHROUGH (*in module telegram.constants*), 156
- MESSAGEENTITY_TEXT_LINK (*in module telegram.constants*), 156
- MESSAGEENTITY_TEXT_MENTION (*in module telegram.constants*), 156
- MESSAGEENTITY_UNDERLINE (*in module telegram.constants*), 156
- MESSAGEENTITY_URL (*in module telegram.constants*), 156
- MessageFilter (*class in telegram.ext.filters*), 25
- MessageHandler (*class in telegram.ext*), 52
- MessageId (*class in telegram*), 194
- MessageQueue (*class in telegram.ext*), 32
- messages (*telegram.ext.filters.Filters attribute*), 22
- middle_name (*telegram.PersonalDetails attribute*),

276

`middle_name_native` (*telegram.PersonalDetails attribute*), 277`migrate` (*telegram.ext.filters.Filters attribute*), 21`migrate_from_chat_id` (*telegram.Message attribute*), 179`migrate_to_chat_id` (*telegram.Message attribute*), 179`mime_type` (*telegram.Animation attribute*), 78`mime_type` (*telegram.Audio attribute*), 79`mime_type` (*telegram.Document attribute*), 159`mime_type` (*telegram.ext.filters.Filters attribute*), 16`mime_type` (*telegram.InlineQueryResultDocument attribute*), 241`mime_type` (*telegram.InlineQueryResultVideo attribute*), 253`mime_type` (*telegram.Video attribute*), 216`mime_type` (*telegram.Voice attribute*), 218`MOUTH` (*telegram.MaskPosition attribute*), 223`mp3` (*telegram.ext.filters.Filters attribute*), 17`mpeg4_duration` (*telegram.InlineQueryResultMpeg4Gif attribute*), 247`mpeg4_file_id` (*telegram.InlineQueryResultCachedMpeg4Gif attribute*), 233`mpeg4_height` (*telegram.InlineQueryResultMpeg4Gif attribute*), 247`mpeg4_url` (*telegram.InlineQueryResultMpeg4Gif attribute*), 247`mpeg4_width` (*telegram.InlineQueryResultMpeg4Gif attribute*), 247

N

`name` (*telegram.Bot attribute*), 101`name` (*telegram.ext.ConversationHandler attribute*), 45`name` (*telegram.ext.DelayQueue attribute*), 33`name` (*telegram.ext.filters.BaseFilter attribute*), 25`name` (*telegram.ext.filters.MessageFilter attribute*), 25`name` (*telegram.ext.filters.UpdateFilter attribute*), 26`name` (*telegram.ext.Job attribute*), 27`name` (*telegram.OrderInfo attribute*), 263`name` (*telegram.StickerSet attribute*), 222`name` (*telegram.User attribute*), 210`NetworkError`, 160`new_chat_members` (*telegram.ext.filters.Filters attribute*), 21`new_chat_members` (*telegram.Message attribute*), 178`new_chat_photo` (*telegram.ext.filters.Filters attribute*), 21`new_chat_photo` (*telegram.Message attribute*), 179`new_chat_title` (*telegram.ext.filters.Filters attribute*), 21`new_chat_title` (*telegram.Message attribute*), 179`next_t` (*telegram.ext.Job attribute*), 28`nonce` (*telegram.Credentials attribute*), 274

O

`offset` (*telegram.InlineQuery attribute*), 224`offset` (*telegram.MessageEntity attribute*), 195`on_flush` (*telegram.ext.PicklePersistence attribute*), 73`one_time_keyboard` (*telegram.ReplyKeyboardMarkup attribute*), 203`open_period` (*telegram.Poll attribute*), 199`option_ids` (*telegram.PollAnswer attribute*), 200`options` (*telegram.Poll attribute*), 198`order_info` (*telegram.PreCheckoutQuery attribute*), 267`order_info` (*telegram.SuccessfulPayment attribute*), 265`OrderInfo` (class in *telegram*), 263

P

`parse_caption_entities()` (*telegram.Message method*), 186`parse_caption_entity()` (*telegram.Message method*), 187`parse_entities()` (*telegram.Message method*), 187`parse_entity()` (*telegram.Message method*), 187`parse_explanation_entities()` (*telegram.Poll method*), 199`parse_explanation_entity()` (*telegram.Poll method*), 200`parse_file_input()` (in module *telegram.utils.helpers*), 286`parse_mode` (*telegram.ext.Defaults attribute*), 36`parse_mode` (*telegram.InlineQueryResultAudio attribute*), 227`parse_mode` (*telegram.InlineQueryResultCachedAudio attribute*), 229`parse_mode` (*telegram.InlineQueryResultCachedDocument attribute*), 230`parse_mode` (*telegram.InlineQueryResultCachedGif attribute*), 232`parse_mode` (*telegram.InlineQueryResultCachedMpeg4Gif attribute*), 233`parse_mode` (*telegram.InlineQueryResultCachedPhoto attribute*), 235`parse_mode` (*telegram.InlineQueryResultCachedVideo attribute*), 237`parse_mode` (*telegram.InlineQueryResultCachedVoice attribute*), 238`parse_mode` (*telegram.InlineQueryResultDocument attribute*), 241`parse_mode` (*telegram.InlineQueryResultGif attribute*), 244`parse_mode` (*telegram.InlineQueryResultMpeg4Gif attribute*), 248`parse_mode` (*telegram.InlineQueryResultPhoto attribute*), 250

`parse_mode` (*telegram.InlineQueryResultVideo* attribute), 253

`parse_mode` (*telegram.InlineQueryResultVoice* attribute), 255

`parse_mode` (*telegram.InputMediaAnimation* attribute), 166

`parse_mode` (*telegram.InputMediaAudio* attribute), 168

`parse_mode` (*telegram.InputMediaDocument* attribute), 169

`parse_mode` (*telegram.InputMediaPhoto* attribute), 171

`parse_mode` (*telegram.InputMediaVideo* attribute), 171

`parse_mode` (*telegram.InputTextMessageContent* attribute), 257

`parse_text_entities()` (*telegram.Game* method), 269

`parse_text_entity()` (*telegram.Game* method), 269

`ParseMode` (class in *telegram*), 196

`PARSEMODE_HTML` (in module *telegram.constants*), 156

`PARSEMODE_MARKDOWN` (in module *telegram.constants*), 156

`PARSEMODE_MARKDOWN_V2` (in module *telegram.constants*), 156

`pass_args` (*telegram.ext.CommandHandler* attribute), 47

`pass_args` (*telegram.ext.PrefixHandler* attribute), 59

`pass_args` (*telegram.ext.StringCommandHandler* attribute), 66

`pass_chat_data` (*telegram.ext.CallbackQueryHandler* attribute), 40

`pass_chat_data` (*telegram.ext.ChosenInlineResultHandler* attribute), 43

`pass_chat_data` (*telegram.ext.CommandHandler* attribute), 48

`pass_chat_data` (*telegram.ext.Handler* attribute), 38

`pass_chat_data` (*telegram.ext.InlineQueryHandler* attribute), 50

`pass_chat_data` (*telegram.ext.MessageHandler* attribute), 52

`pass_chat_data` (*telegram.ext.PollAnswerHandler* attribute), 55

`pass_chat_data` (*telegram.ext.PollHandler* attribute), 56

`pass_chat_data` (*telegram.ext.PreCheckoutQueryHandler* attribute), 58

`pass_chat_data` (*telegram.ext.PrefixHandler* attribute), 60

`pass_chat_data` (*telegram.ext.RegexHandler* attribute), 62

`pass_chat_data` (*telegram.ext.ShippingQueryHandler* attribute), 64

`pass_groupdict` (*telegram.ext.CallbackQueryHandler* attribute), 40

`pass_groupdict` (*telegram.ext.InlineQueryHandler* attribute), 50

`pass_groupdict` (*telegram.ext.RegexHandler* attribute), 62

`pass_groupdict` (*telegram.ext.StringRegexHandler* attribute), 68

`pass_groups` (*telegram.ext.CallbackQueryHandler* attribute), 40

`pass_groups` (*telegram.ext.InlineQueryHandler* attribute), 50

`pass_groups` (*telegram.ext.RegexHandler* attribute), 62

`pass_groups` (*telegram.ext.StringRegexHandler* attribute), 67

`pass_job_queue` (*telegram.ext.CallbackQueryHandler* attribute), 40

`pass_job_queue` (*telegram.ext.ChosenInlineResultHandler* attribute), 42

`pass_job_queue` (*telegram.ext.CommandHandler* attribute), 47

`pass_job_queue` (*telegram.ext.Handler* attribute), 38

`pass_job_queue` (*telegram.ext.InlineQueryHandler* attribute), 50

`pass_job_queue` (*telegram.ext.MessageHandler* attribute), 52

`pass_job_queue` (*telegram.ext.PollAnswerHandler* attribute), 54

`pass_job_queue` (*telegram.ext.PollHandler* attribute), 56

`pass_job_queue` (*telegram.ext.PreCheckoutQueryHandler* attribute), 57

`pass_job_queue` (*telegram.ext.PrefixHandler* attribute), 60

`pass_job_queue` (*telegram.ext.RegexHandler* attribute), 62

`pass_job_queue` (*telegram.ext.ShippingQueryHandler* attribute), 64

`pass_job_queue` (*telegram.ext.StringCommandHandler* attribute), 66

`pass_job_queue` (*telegram.ext.StringRegexHandler* attribute), 68

`pass_job_queue` (*telegram.ext.TypeHandler attribute*), 69
`pass_update_queue` (*telegram.ext.CallbackQueryHandler attribute*), 40
`pass_update_queue` (*telegram.ext.ChosenInlineResultHandler attribute*), 42
`pass_update_queue` (*telegram.ext.CommandHandler attribute*), 47
`pass_update_queue` (*telegram.ext.Handler attribute*), 38
`pass_update_queue` (*telegram.ext.InlineQueryHandler attribute*), 50
`pass_update_queue` (*telegram.ext.MessageHandler attribute*), 52
`pass_update_queue` (*telegram.ext.PollAnswerHandler attribute*), 54
`pass_update_queue` (*telegram.ext.PollHandler attribute*), 56
`pass_update_queue` (*telegram.ext.PreCheckoutQueryHandler attribute*), 57
`pass_update_queue` (*telegram.ext.PrefixHandler attribute*), 59
`pass_update_queue` (*telegram.ext.RegexHandler attribute*), 62
`pass_update_queue` (*telegram.ext.ShippingQueryHandler attribute*), 64
`pass_update_queue` (*telegram.ext.StringCommandHandler attribute*), 66
`pass_update_queue` (*telegram.ext.StringRegexHandler attribute*), 68
`pass_update_queue` (*telegram.ext.TypeHandler attribute*), 69
`pass_user_data` (*telegram.ext.CallbackQueryHandler attribute*), 40
`pass_user_data` (*telegram.ext.ChosenInlineResultHandler attribute*), 43
`pass_user_data` (*telegram.ext.CommandHandler attribute*), 47
`pass_user_data` (*telegram.ext.Handler attribute*), 38
`pass_user_data` (*telegram.ext.InlineQueryHandler attribute*), 50
`pass_user_data` (*telegram.ext.MessageHandler attribute*), 52
`pass_user_data` (*telegram.ext.PollAnswerHandler attribute*), 55
`pass_user_data` (*telegram.ext.PollHandler attribute*), 56
`pass_user_data` (*telegram.ext.PreCheckoutQueryHandler attribute*), 58
`pass_user_data` (*telegram.ext.PrefixHandler attribute*), 60
`pass_user_data` (*telegram.ext.RegexHandler attribute*), 62
`pass_user_data` (*telegram.ext.ShippingQueryHandler attribute*), 64
`passport` (*telegram.SecureData attribute*), 274
`passport_data` (*telegram.ext.filters.Filters attribute*), 18
`passport_data` (*telegram.Message attribute*), 180
`passport_registration` (*telegram.SecureData attribute*), 275
`PassportData` (*class in telegram*), 277
`PassportElementError` (*class in telegram*), 270
`PassportElementErrorDataField` (*class in telegram*), 273
`PassportElementErrorFile` (*class in telegram*), 271
`PassportElementErrorFiles` (*class in telegram*), 272
`PassportElementErrorFrontSide` (*class in telegram*), 272
`PassportElementErrorReverseSide` (*class in telegram*), 271
`PassportFile` (*class in telegram*), 278
`pattern` (*telegram.ext.CallbackQueryHandler attribute*), 40
`pattern` (*telegram.ext.InlineQueryHandler attribute*), 50
`pattern` (*telegram.ext.RegexHandler attribute*), 62
`pattern` (*telegram.ext.StringRegexHandler attribute*), 67
`pay` (*telegram.InlineKeyboardButton attribute*), 163
`pdf` (*telegram.ext.filters.Filters attribute*), 17
`pending_update_count` (*telegram.WebhookInfo attribute*), 219
`per_chat` (*telegram.ext.ConversationHandler attribute*), 45
`per_message` (*telegram.ext.ConversationHandler attribute*), 45
`per_user` (*telegram.ext.ConversationHandler attribute*), 45
`performer` (*telegram.Audio attribute*), 79
`performer` (*telegram.InlineQueryResultAudio attribute*), 227
`performer` (*telegram.InputMediaAudio attribute*), 168
`permissions` (*telegram.Chat attribute*), 139
`persistence` (*telegram.ext.Dispatcher attribute*), 9
`persistence` (*telegram.ext.Updater attribute*), 6
`persistent` (*telegram.ext.ConversationHandler attribute*), 45

- `personal_details` (*telegram.SecureData* attribute), 274
- `PersonalDetails` (class in *telegram*), 276
- `phone_number` (*telegram.Contact* attribute), 157
- `phone_number` (*telegram.EncryptedPassportElement* attribute), 280
- `phone_number` (*telegram.InlineQueryResultContact* attribute), 239
- `phone_number` (*telegram.InputContactMessageContent* attribute), 259
- `PHONE_NUMBER` (*telegram.MessageEntity* attribute), 196
- `phone_number` (*telegram.OrderInfo* attribute), 263
- `photo` (*telegram.Chat* attribute), 139
- `photo` (*telegram.ext.filters.Filters* attribute), 18
- `photo` (*telegram.Game* attribute), 268
- `photo` (*telegram.Message* attribute), 178
- `photo_file_id` (*telegram.InlineQueryResultCachedPhoto* attribute), 234
- `photo_height` (*telegram.InlineQueryResultPhoto* attribute), 249
- `photo_url` (*telegram.InlineQueryResultPhoto* attribute), 249
- `photo_width` (*telegram.InlineQueryResultPhoto* attribute), 249
- `photos` (*telegram.UserProfilePhotos* attribute), 214
- `PhotoSize` (class in *telegram*), 197
- `PicklePersistence` (class in *telegram.ext*), 73
- `pin()` (*telegram.Message* method), 188
- `pin_chat_message()` (*telegram.Bot* method), 101
- `pin_message()` (*telegram.CallbackQuery* method), 137
- `pin_message()` (*telegram.Chat* method), 142
- `pin_message()` (*telegram.User* method), 210
- `pinChatMessage()` (*telegram.Bot* method), 101
- `pinned_message` (*telegram.Chat* attribute), 139
- `pinned_message` (*telegram.ext.filters.Filters* attribute), 21
- `pinned_message` (*telegram.Message* attribute), 179
- `point` (*telegram.MaskPosition* attribute), 222
- `Poll` (class in *telegram*), 198
- `poll` (*telegram.ext.filters.Filters* attribute), 18
- `poll` (*telegram.Message* attribute), 180
- `poll` (*telegram.Update* attribute), 207
- `poll_answer` (*telegram.Update* attribute), 207
- `poll_id` (*telegram.PollAnswer* attribute), 200
- `POLL_QUIZ` (in module *telegram.constants*), 157
- `POLL_REGULAR` (in module *telegram.constants*), 157
- `PollAnswer` (class in *telegram*), 200
- `PollAnswerHandler` (class in *telegram.ext*), 54
- `PollHandler` (class in *telegram.ext*), 56
- `PollOption` (class in *telegram*), 201
- `pooled_function` (*telegram.utils.promise.Promise* attribute), 287
- `position` (*telegram.GameHighScore* attribute), 270
- `post()` (*telegram.utils.request.Request* method), 289
- `post_code` (*telegram.ResidentialAddress* attribute), 277
- `post_code` (*telegram.ShippingAddress* attribute), 263
- `PRE` (*telegram.MessageEntity* attribute), 196
- `pre_checkout_query` (*telegram.Update* attribute), 206
- `PreCheckoutQuery` (class in *telegram*), 266
- `PreCheckoutQueryHandler` (class in *telegram.ext*), 57
- `prefix` (*telegram.ext.PrefixHandler* attribute), 61
- `PrefixHandler` (class in *telegram.ext*), 59
- `prices` (*telegram.ShippingOption* attribute), 264
- `PRIVATE` (*telegram.Chat* attribute), 141
- `private` (*telegram.ext.filters.Filters* attribute), 14, 18
- `process_update()` (*telegram.ext.Dispatcher* method), 10
- `Promise` (class in *telegram.utils.promise*), 287
- `promote_chat_member()` (*telegram.Bot* method), 102
- `promoteChatMember()` (*telegram.Bot* method), 102
- `provider_payment_charge_id` (*telegram.SuccessfulPayment* attribute), 265
- `proximity_alert_radius` (*telegram.InlineQueryResultLocation* attribute), 246
- `proximity_alert_radius` (*telegram.InputLocationMessageContent* attribute), 258
- `proximity_alert_radius` (*telegram.Location* attribute), 174
- `proximity_alert_triggered` (*telegram.ext.filters.Filters* attribute), 21
- `proximity_alert_triggered` (*telegram.Message* attribute), 180
- `ProximityAlertTriggered` (class in *telegram*), 201
- `py` (*telegram.ext.filters.Filters* attribute), 17

Q

- `query` (*telegram.ChosenInlineResult* attribute), 260
- `query` (*telegram.InlineQuery* attribute), 224
- `question` (*telegram.Poll* attribute), 198
- `QUIZ` (*telegram.Poll* attribute), 199
- `quote` (*telegram.ext.Defaults* attribute), 37

R

- `RECORD_AUDIO` (*telegram.ChatAction* attribute), 146
- `RECORD_VIDEO` (*telegram.ChatAction* attribute), 146
- `RECORD_VIDEO_NOTE` (*telegram.ChatAction* attribute), 146
- `RegexHandler` (class in *telegram.ext*), 62
- `REGULAR` (*telegram.Poll* attribute), 199
- `remove_bot_ids()` (*telegram.ext.filters.Filters.via_bot* method), 24

`remove_chat_ids()` (*telegram.ext.filters.Filters.chat method*), 14
`remove_chat_ids()` (*telegram.ext.filters.Filters.sender_chat method*), 20
`remove_error_handler()` (*telegram.ext.Dispatcher method*), 11
`remove_handler()` (*telegram.ext.Dispatcher method*), 11
`remove_keyboard` (*telegram.ReplyKeyboardRemove attribute*), 202
`remove_user_ids()` (*telegram.ext.filters.Filters.user method*), 23
`remove_usernames()` (*telegram.ext.filters.Filters.chat method*), 14
`remove_usernames()` (*telegram.ext.filters.Filters.sender_chat method*), 20
`remove_usernames()` (*telegram.ext.filters.Filters.user method*), 23
`remove_usernames()` (*telegram.ext.filters.Filters.via_bot method*), 24
`removed` (*telegram.ext.Job attribute*), 28
`rental_agreement` (*telegram.SecureData attribute*), 275
`replace_bot()` (*telegram.ext.BasePersistence class method*), 72
`REPLACED_BOT` (*telegram.ext.BasePersistence attribute*), 71
`reply` (*telegram.ext.filters.Filters attribute*), 19
`reply_animation()` (*telegram.Message method*), 188
`reply_audio()` (*telegram.Message method*), 188
`reply_contact()` (*telegram.Message method*), 188
`reply_copy()` (*telegram.Message method*), 189
`reply_dice()` (*telegram.Message method*), 189
`reply_document()` (*telegram.Message method*), 189
`reply_html()` (*telegram.Message method*), 189
`reply_location()` (*telegram.Message method*), 189
`reply_markdown()` (*telegram.Message method*), 190
`reply_markdown_v2()` (*telegram.Message method*), 190
`reply_markup` (*telegram.InlineQueryResultArticle attribute*), 226
`reply_markup` (*telegram.InlineQueryResultAudio attribute*), 228
`reply_markup` (*telegram.InlineQueryResultCachedAudio attribute*), 229
`reply_markup` (*telegram.InlineQueryResultCachedDocument attribute*), 230
`reply_markup` (*telegram.InlineQueryResultCachedGif attribute*), 232
`reply_markup` (*telegram.InlineQueryResultCachedMpeg4Gif attribute*), 233
`reply_markup` (*telegram.InlineQueryResultCachedPhoto attribute*), 235
`reply_markup` (*telegram.InlineQueryResultCachedSticker attribute*), 236
`reply_markup` (*telegram.InlineQueryResultCachedVideo attribute*), 237
`reply_markup` (*telegram.InlineQueryResultCachedVoice attribute*), 239
`reply_markup` (*telegram.InlineQueryResultContact attribute*), 240
`reply_markup` (*telegram.InlineQueryResultDocument attribute*), 242
`reply_markup` (*telegram.InlineQueryResultGame attribute*), 243
`reply_markup` (*telegram.InlineQueryResultGif attribute*), 244
`reply_markup` (*telegram.InlineQueryResultLocation attribute*), 246
`reply_markup` (*telegram.InlineQueryResultMpeg4Gif attribute*), 248
`reply_markup` (*telegram.InlineQueryResultPhoto attribute*), 250
`reply_markup` (*telegram.InlineQueryResultVenue attribute*), 251
`reply_markup` (*telegram.InlineQueryResultVideo attribute*), 254
`reply_markup` (*telegram.InlineQueryResultVoice attribute*), 255
`reply_markup` (*telegram.Message attribute*), 180
`reply_media_group()` (*telegram.Message method*), 190
`reply_photo()` (*telegram.Message method*), 191
`reply_poll()` (*telegram.Message method*), 191
`reply_sticker()` (*telegram.Message method*), 191
`reply_text()` (*telegram.Message method*), 191
`reply_to_message` (*telegram.Message attribute*), 177
`reply_venue()` (*telegram.Message method*), 191
`reply_video()` (*telegram.Message method*), 192
`reply_video_note()` (*telegram.Message method*), 192
`reply_voice()` (*telegram.Message method*), 192
`ReplyKeyboardMarkup` (*class in telegram*), 202
`ReplyKeyboardRemove` (*class in telegram*), 202

ReplyMarkup (class in telegram), 205
Request (class in telegram.utils.request), 288
request_contact (telegram.KeyboardButton attribute), 173
request_location (telegram.KeyboardButton attribute), 173
request_poll (telegram.KeyboardButton attribute), 173
request_write_access (telegram.LoginUrl attribute), 175
residence_country_code (telegram.PersonalDetails attribute), 276
ResidentialAddress (class in telegram), 277
resize_keyboard (telegram.ReplyKeyboardMarkup attribute), 203
restrict_chat_member() (telegram.Bot method), 103
restrictChatMember() (telegram.Bot method), 103
RESTRICTED (telegram.ChatMember attribute), 149
result() (telegram.utils.promise.Promise method), 288
result_id (telegram.ChosenInlineResult attribute), 260
retrieve() (telegram.utils.request.Request method), 289
RetryAfter, 160
reverse_side (telegram.EncryptedPassportElement attribute), 280
run() (telegram.ext.DelayQueue method), 34
run() (telegram.ext.Job method), 28
run() (telegram.utils.promise.Promise method), 288
run_async (telegram.ext.CallbackQueryHandler attribute), 40
run_async (telegram.ext.ChosenInlineResultHandler attribute), 43
run_async (telegram.ext.CommandHandler attribute), 48
run_async (telegram.ext.Defaults attribute), 37
run_async (telegram.ext.Handler attribute), 38
run_async (telegram.ext.InlineQueryHandler attribute), 50
run_async (telegram.ext.MessageHandler attribute), 53
run_async (telegram.ext.PollAnswerHandler attribute), 55
run_async (telegram.ext.PollHandler attribute), 56
run_async (telegram.ext.PreCheckoutQueryHandler attribute), 58
run_async (telegram.ext.PrefixHandler attribute), 60
run_async (telegram.ext.RegexHandler attribute), 62
run_async (telegram.ext.ShippingQueryHandler attribute), 64
run_async (telegram.ext.StringCommandHandler

attribute), 66
run_async (telegram.ext.StringRegexHandler attribute), 68
run_async (telegram.ext.TypeHandler attribute), 69
run_async() (telegram.ext.Dispatcher method), 11
run_custom() (telegram.ext.JobQueue method), 28
run_daily() (telegram.ext.JobQueue method), 29
run_monthly() (telegram.ext.JobQueue method), 29
run_once() (telegram.ext.JobQueue method), 30
run_repeating() (telegram.ext.JobQueue method), 30
running (telegram.ext.Dispatcher attribute), 11
running (telegram.ext.Updater attribute), 6

S

scale (telegram.MaskPosition attribute), 223
schedule_removal() (telegram.ext.Job method), 28
scheduler (telegram.ext.JobQueue attribute), 28
score (telegram.GameHighScore attribute), 270
secret (telegram.DataCredentials attribute), 274
secret (telegram.EncryptedCredentials attribute), 282
secret (telegram.FileCredentials attribute), 275
secure_data (telegram.Credentials attribute), 274
SecureData (class in telegram), 274
selective (telegram.ForceReply attribute), 162
selective (telegram.ReplyKeyboardMarkup attribute), 203
selective (telegram.ReplyKeyboardRemove attribute), 202
selfie (telegram.EncryptedPassportElement attribute), 281
send_action() (telegram.Chat method), 142
send_action() (telegram.User method), 210
send_animation() (telegram.Bot method), 106
send_animation() (telegram.Chat method), 142
send_animation() (telegram.User method), 210
send_audio() (telegram.Bot method), 108
send_audio() (telegram.Chat method), 142
send_audio() (telegram.User method), 210
send_chat_action() (telegram.Bot method), 109
send_chat_action() (telegram.Chat method), 142
send_chat_action() (telegram.User method), 210
send_contact() (telegram.Bot method), 109
send_contact() (telegram.Chat method), 142
send_contact() (telegram.User method), 211
send_copy() (telegram.Chat method), 143
send_copy() (telegram.User method), 211
send_dice() (telegram.Bot method), 110
send_dice() (telegram.Chat method), 143
send_dice() (telegram.User method), 211
send_document() (telegram.Bot method), 111
send_document() (telegram.Chat method), 143
send_document() (telegram.User method), 211

- `send_game()` (*telegram.Bot method*), 112
- `send_game()` (*telegram.Chat method*), 143
- `send_game()` (*telegram.User method*), 211
- `send_invoice()` (*telegram.Bot method*), 112
- `send_invoice()` (*telegram.Chat method*), 143
- `send_invoice()` (*telegram.User method*), 211
- `send_location()` (*telegram.Bot method*), 114
- `send_location()` (*telegram.Chat method*), 143
- `send_location()` (*telegram.User method*), 211
- `send_media_group()` (*telegram.Bot method*), 115
- `send_media_group()` (*telegram.Chat method*), 143
- `send_media_group()` (*telegram.User method*), 212
- `send_message()` (*telegram.Bot method*), 115
- `send_message()` (*telegram.Chat method*), 144
- `send_message()` (*telegram.User method*), 212
- `send_photo()` (*telegram.Bot method*), 116
- `send_photo()` (*telegram.Chat method*), 144
- `send_photo()` (*telegram.User method*), 212
- `send_poll()` (*telegram.Bot method*), 117
- `send_poll()` (*telegram.Chat method*), 144
- `send_poll()` (*telegram.User method*), 212
- `send_sticker()` (*telegram.Bot method*), 118
- `send_sticker()` (*telegram.Chat method*), 144
- `send_sticker()` (*telegram.User method*), 212
- `send_venue()` (*telegram.Bot method*), 119
- `send_venue()` (*telegram.Chat method*), 144
- `send_venue()` (*telegram.User method*), 212
- `send_video()` (*telegram.Bot method*), 120
- `send_video()` (*telegram.Chat method*), 144
- `send_video()` (*telegram.User method*), 213
- `send_video_note()` (*telegram.Bot method*), 122
- `send_video_note()` (*telegram.Chat method*), 145
- `send_video_note()` (*telegram.User method*), 213
- `send_voice()` (*telegram.Bot method*), 122
- `send_voice()` (*telegram.Chat method*), 145
- `send_voice()` (*telegram.User method*), 213
- `sendAnimation()` (*telegram.Bot method*), 104
- `sendAudio()` (*telegram.Bot method*), 104
- `sendChatAction()` (*telegram.Bot method*), 104
- `sendContact()` (*telegram.Bot method*), 104
- `sendDice()` (*telegram.Bot method*), 104
- `sendDocument()` (*telegram.Bot method*), 104
- `sender_chat` (*telegram.Message attribute*), 176
- `sendGame()` (*telegram.Bot method*), 104
- `sendInvoice()` (*telegram.Bot method*), 105
- `sendLocation()` (*telegram.Bot method*), 105
- `sendMediaGroup()` (*telegram.Bot method*), 105
- `sendMessage()` (*telegram.Bot method*), 105
- `sendPhoto()` (*telegram.Bot method*), 105
- `sendPoll()` (*telegram.Bot method*), 105
- `sendSticker()` (*telegram.Bot method*), 106
- `sendVenue()` (*telegram.Bot method*), 106
- `sendVideo()` (*telegram.Bot method*), 106
- `sendVideoNote()` (*telegram.Bot method*), 106
- `sendVoice()` (*telegram.Bot method*), 106
- `SERVICE_CHAT_ID` (*in module telegram.constants*), 153
- `set_administrator_custom_title()` (*telegram.Chat method*), 145
- `set_bot()` (*telegram.ext.BasePersistence method*), 72
- `set_chat_administrator_custom_title()` (*telegram.Bot method*), 124
- `set_chat_description()` (*telegram.Bot method*), 125
- `set_chat_permissions()` (*telegram.Bot method*), 125
- `set_chat_photo()` (*telegram.Bot method*), 125
- `set_chat_sticker_set()` (*telegram.Bot method*), 126
- `set_chat_title()` (*telegram.Bot method*), 126
- `set_dispatcher()` (*telegram.ext.JobQueue method*), 31
- `set_game_score()` (*telegram.Bot method*), 127
- `set_game_score()` (*telegram.CallbackQuery method*), 137
- `set_game_score()` (*telegram.Message method*), 192
- `set_my_commands()` (*telegram.Bot method*), 127
- `set_name` (*telegram.Sticker attribute*), 221
- `set_passport_data_errors()` (*telegram.Bot method*), 127
- `set_permissions()` (*telegram.Chat method*), 145
- `set_sticker_position_in_set()` (*telegram.Bot method*), 128
- `set_sticker_set_thumb()` (*telegram.Bot method*), 128
- `set_webhook()` (*telegram.Bot method*), 129
- `setChatAdministratorCustomTitle()` (*telegram.Bot method*), 123
- `setChatDescription()` (*telegram.Bot method*), 124
- `setChatPermissions()` (*telegram.Bot method*), 124
- `setChatPhoto()` (*telegram.Bot method*), 124
- `setChatStickerSet()` (*telegram.Bot method*), 124
- `setChatTitle()` (*telegram.Bot method*), 124
- `setGameScore()` (*telegram.Bot method*), 124
- `setMyCommands()` (*telegram.Bot method*), 124
- `setPassportDataErrors()` (*telegram.Bot method*), 124
- `setStickerPositionInSet()` (*telegram.Bot method*), 124
- `setStickerSetThumb()` (*telegram.Bot method*), 124
- `setWebhook()` (*telegram.Bot method*), 124
- `shipping_address` (*telegram.OrderInfo attribute*), 263
- `shipping_address` (*telegram.ShippingQuery attribute*), 266
- `shipping_option_id` (*telegram.PreCheckoutQuery attribute*), 267

shipping_option_id (*telegram.SuccessfulPayment* attribute), 265
shipping_query (*telegram.Update* attribute), 206
ShippingAddress (*class in telegram*), 262
ShippingOption (*class in telegram*), 264
ShippingQuery (*class in telegram*), 265
ShippingQueryHandler (*class in telegram.ext*), 64
single_file (*telegram.ext.PicklePersistence* attribute), 73
SLOT_MACHINE (*telegram.Dice* attribute), 159
slot_machine (*telegram.ext.filters.Filters* attribute), 15
slow_mode_delay (*telegram.Chat* attribute), 139
SLT (*in module telegram.utils.types*), 289
small_file_id (*telegram.ChatPhoto* attribute), 151
small_file_unique_id (*telegram.ChatPhoto* attribute), 151
source (*telegram.PassportElementError* attribute), 270
start() (*telegram.ext.Dispatcher* method), 11
start() (*telegram.ext.JobQueue* method), 32
start() (*telegram.ext.MessageQueue* method), 33
start_parameter (*telegram.Invoice* attribute), 262
start_polling() (*telegram.ext.Updater* method), 7
start_webhook() (*telegram.ext.Updater* method), 7
state (*telegram.ext.DispatcherHandlerStop* attribute), 12
state (*telegram.ResidentialAddress* attribute), 277
state (*telegram.ShippingAddress* attribute), 262
states (*telegram.ext.ConversationHandler* attribute), 44
status (*telegram.ChatMember* attribute), 147
status_update (*telegram.ext.filters.Filters* attribute), 20
Sticker (*class in telegram*), 220
sticker (*telegram.ext.filters.Filters* attribute), 21
sticker (*telegram.Message* attribute), 178
STICKER_CHIN (*in module telegram.constants*), 157
STICKER_EYES (*in module telegram.constants*), 157
sticker_file_id (*telegram.InlineQueryResultCachedSticker* attribute), 236
STICKER_FOREHEAD (*in module telegram.constants*), 157
STICKER_MOUTH (*in module telegram.constants*), 157
sticker_set_name (*telegram.Chat* attribute), 139
stickers (*telegram.StickerSet* attribute), 222
StickerSet (*class in telegram*), 222
stop() (*telegram.ext.DelayQueue* method), 34
stop() (*telegram.ext.Dispatcher* method), 11
stop() (*telegram.ext.JobQueue* method), 32
stop() (*telegram.ext.MessageQueue* method), 33
stop() (*telegram.ext.Updater* method), 8
stop_live_location() (*telegram.Message* method), 192
stop_message_live_location() (*telegram.Bot* method), 130
stop_message_live_location() (*telegram.CallbackQuery* method), 138
stop_poll() (*telegram.Bot* method), 131
stop_poll() (*telegram.Message* method), 193
stopMessageLiveLocation() (*telegram.Bot* method), 130
stopPoll() (*telegram.Bot* method), 130
store_bot_data (*telegram.ext.BasePersistence* attribute), 71
store_bot_data (*telegram.ext.DictPersistence* attribute), 75
store_bot_data (*telegram.ext.PicklePersistence* attribute), 73
store_chat_data (*telegram.ext.BasePersistence* attribute), 71
store_chat_data (*telegram.ext.DictPersistence* attribute), 75
store_chat_data (*telegram.ext.PicklePersistence* attribute), 73
store_user_data (*telegram.ext.BasePersistence* attribute), 71
store_user_data (*telegram.ext.DictPersistence* attribute), 75
store_user_data (*telegram.ext.PicklePersistence* attribute), 73
street_line1 (*telegram.ResidentialAddress* attribute), 277
street_line1 (*telegram.ShippingAddress* attribute), 262
street_line2 (*telegram.ResidentialAddress* attribute), 277
street_line2 (*telegram.ShippingAddress* attribute), 263
strict (*telegram.ext.TypeHandler* attribute), 69
STRIKETHROUGH (*telegram.MessageEntity* attribute), 196
StringCommandHandler (*class in telegram.ext*), 65
StringRegexHandler (*class in telegram.ext*), 67
successful_payment (*telegram.ext.filters.Filters* attribute), 21
successful_payment (*telegram.Message* attribute), 179
SuccessfulPayment (*class in telegram*), 264
super_group (*telegram.ext.filters.Filters.sender_chat* attribute), 20
SUPERGROUP (*telegram.Chat* attribute), 141
supergroup (*telegram.ext.filters.Filters* attribute), 14
supergroup_chat_created (*telegram.Message* attribute), 179
SUPPORTED_WEBHOOK_PORTS (*in module telegram.constants*), 152

- `supports_inline_queries` (*telegram.Bot* attribute), 131
 - `supports_inline_queries` (*telegram.User* attribute), 209
 - `supports_streaming` (*telegram.InputMediaVideo* attribute), 172
 - `svg` (*telegram.ext.filters.Filters* attribute), 17
 - `switch_inline_query` (*telegram.InlineKeyboardButton* attribute), 163
 - `switch_inline_query_current_chat` (*telegram.InlineKeyboardButton* attribute), 163
- T**
- `targz` (*telegram.ext.filters.Filters* attribute), 17
 - `telegram.constants` (module), 152
 - `telegram.error` (module), 160
 - `telegram.ext.filters` (module), 12
 - `telegram.utils.helpers` (module), 283
 - `telegram.utils.types` (module), 289
 - `telegram_payment_charge_id` (*telegram.SuccessfulPayment* attribute), 265
 - `TelegramError`, 160
 - `TelegramObject` (class in *telegram*), 205
 - `temporary_registration` (*telegram.SecureData* attribute), 275
 - `text` (*telegram.ext.filters.Filters* attribute), 16, 21
 - `text` (*telegram.Game* attribute), 268
 - `text` (*telegram.InlineKeyboardButton* attribute), 163
 - `text` (*telegram.KeyboardButton* attribute), 173
 - `text` (*telegram.Message* attribute), 177
 - `text` (*telegram.PollOption* attribute), 201
 - `text_entities` (*telegram.Game* attribute), 268
 - `text_html` (*telegram.Message* attribute), 193
 - `text_html_urled` (*telegram.Message* attribute), 193
 - `TEXT_LINK` (*telegram.MessageEntity* attribute), 196
 - `text_markdown` (*telegram.Message* attribute), 193
 - `text_markdown_urled` (*telegram.Message* attribute), 194
 - `text_markdown_v2` (*telegram.Message* attribute), 194
 - `text_markdown_v2_urled` (*telegram.Message* attribute), 194
 - `TEXT_MENTION` (*telegram.MessageEntity* attribute), 196
 - `thumb` (*telegram.Animation* attribute), 78
 - `thumb` (*telegram.Audio* attribute), 79
 - `thumb` (*telegram.Document* attribute), 159
 - `thumb` (*telegram.InputMediaAnimation* attribute), 167
 - `thumb` (*telegram.InputMediaAudio* attribute), 168
 - `thumb` (*telegram.InputMediaDocument* attribute), 170
 - `thumb` (*telegram.InputMediaVideo* attribute), 172
 - `thumb` (*telegram.Sticker* attribute), 220
 - `thumb` (*telegram.StickerSet* attribute), 222
 - `thumb` (*telegram.Video* attribute), 215
 - `thumb` (*telegram.VideoNote* attribute), 217
 - `thumb_height` (*telegram.InlineQueryResultArticle* attribute), 226
 - `thumb_height` (*telegram.InlineQueryResultContact* attribute), 240
 - `thumb_height` (*telegram.InlineQueryResultDocument* attribute), 242
 - `thumb_height` (*telegram.InlineQueryResultLocation* attribute), 246
 - `thumb_height` (*telegram.InlineQueryResultVenue* attribute), 252
 - `thumb_mime_type` (*telegram.InlineQueryResultGif* attribute), 244
 - `thumb_mime_type` (*telegram.InlineQueryResultMpeg4Gif* attribute), 247
 - `thumb_url` (*telegram.InlineQueryResultArticle* attribute), 226
 - `thumb_url` (*telegram.InlineQueryResultContact* attribute), 240
 - `thumb_url` (*telegram.InlineQueryResultDocument* attribute), 242
 - `thumb_url` (*telegram.InlineQueryResultGif* attribute), 244
 - `thumb_url` (*telegram.InlineQueryResultLocation* attribute), 246
 - `thumb_url` (*telegram.InlineQueryResultMpeg4Gif* attribute), 247
 - `thumb_url` (*telegram.InlineQueryResultPhoto* attribute), 249
 - `thumb_url` (*telegram.InlineQueryResultVenue* attribute), 252
 - `thumb_url` (*telegram.InlineQueryResultVideo* attribute), 253
 - `thumb_width` (*telegram.InlineQueryResultArticle* attribute), 226
 - `thumb_width` (*telegram.InlineQueryResultContact* attribute), 240
 - `thumb_width` (*telegram.InlineQueryResultDocument* attribute), 242
 - `thumb_width` (*telegram.InlineQueryResultLocation* attribute), 246
 - `thumb_width` (*telegram.InlineQueryResultVenue* attribute), 252
 - `time_limit` (*telegram.ext.DelayQueue* attribute), 33
 - `TimedOut`, 160
 - `TIMEOUT` (*telegram.ext.ConversationHandler* attribute), 46
 - `timeout` (*telegram.ext.Defaults* attribute), 37
 - `title` (*telegram.Audio* attribute), 79
 - `title` (*telegram.Chat* attribute), 139
 - `title` (*telegram.Game* attribute), 268
 - `title` (*telegram.InlineQueryResultArticle* attribute), 226
 - `title` (*telegram.InlineQueryResultAudio* attribute), 227

title (telegram.InlineQueryResultCachedDocument attribute), 230	225
title (telegram.InlineQueryResultCachedGif attribute), 232	type (telegram.InlineQueryResultAudio attribute), 227
title (telegram.InlineQueryResultCachedMpeg4Gif attribute), 233	type (telegram.InlineQueryResultCachedAudio attribute), 228
title (telegram.InlineQueryResultCachedPhoto attribute), 234	type (telegram.InlineQueryResultCachedDocument attribute), 230
title (telegram.InlineQueryResultCachedVideo attribute), 237	type (telegram.InlineQueryResultCachedGif attribute), 231
title (telegram.InlineQueryResultCachedVoice attribute), 238	type (telegram.InlineQueryResultCachedMpeg4Gif attribute), 233
title (telegram.InlineQueryResultDocument attribute), 241	type (telegram.InlineQueryResultCachedPhoto attribute), 234
title (telegram.InlineQueryResultGif attribute), 244	type (telegram.InlineQueryResultCachedSticker attribute), 236
title (telegram.InlineQueryResultLocation attribute), 245	type (telegram.InlineQueryResultCachedVideo attribute), 237
title (telegram.InlineQueryResultMpeg4Gif attribute), 248	type (telegram.InlineQueryResultCachedVoice attribute), 238
title (telegram.InlineQueryResultPhoto attribute), 249	type (telegram.InlineQueryResultContact attribute), 239
title (telegram.InlineQueryResultVenue attribute), 251	type (telegram.InlineQueryResultDocument attribute), 241
title (telegram.InlineQueryResultVideo attribute), 253	type (telegram.InlineQueryResultGame attribute), 243
title (telegram.InlineQueryResultVoice attribute), 255	type (telegram.InlineQueryResultGif attribute), 243
title (telegram.InputMediaAudio attribute), 168	type (telegram.InlineQueryResultLocation attribute), 245
title (telegram.InputVenueMessageContent attribute), 259	type (telegram.InlineQueryResultMpeg4Gif attribute), 247
title (telegram.Invoice attribute), 261	type (telegram.InlineQueryResultPhoto attribute), 249
title (telegram.ShippingOption attribute), 264	type (telegram.InlineQueryResultVenue attribute), 251
title (telegram.StickerSet attribute), 222	type (telegram.InlineQueryResultVideo attribute), 253
title (telegram.Venue attribute), 214	type (telegram.InlineQueryResultVoice attribute), 255
to_float_timestamp() (in module telegram.utils.helpers), 286	type (telegram.InputMediaAnimation attribute), 166
to_json() (telegram.TelegramObject method), 205	type (telegram.InputMediaAudio attribute), 168
to_timestamp() (in module telegram.utils.helpers), 287	type (telegram.InputMediaDocument attribute), 169
total_amount (telegram.Invoice attribute), 262	type (telegram.InputMediaPhoto attribute), 170
total_amount (telegram.PreCheckoutQuery attribute), 267	type (telegram.InputMediaVideo attribute), 171
total_amount (telegram.SuccessfulPayment attribute), 264	type (telegram.KeyboardButtonPollType attribute), 174
total_count (telegram.UserProfilePhotos attribute), 214	type (telegram.MessageEntity attribute), 195
total_voter_count (telegram.Poll attribute), 198	type (telegram.PassportElementError attribute), 270
translation (telegram.EncryptedPassportElement attribute), 281	type (telegram.PassportElementErrorDataField attribute), 273
traveler (telegram.ProximityAlertTriggered attribute), 201	type (telegram.PassportElementErrorFile attribute), 271
txt (telegram.ext.filters.Filters attribute), 17	type (telegram.PassportElementErrorFiles attribute), 272
type (telegram.Chat attribute), 138	type (telegram.PassportElementErrorFrontSide attribute), 272
type (telegram.EncryptedPassportElement attribute), 280	type (telegram.PassportElementErrorReverseSide attribute), 271
type (telegram.ext.TypeHandler attribute), 69	type (telegram.Poll attribute), 198
type (telegram.InlineQueryResult attribute), 225	TypeHandler (class in telegram.ext), 69
type (telegram.InlineQueryResultArticle attribute),	

TYPING (*telegram.ChatAction* attribute), 146
 tzinfo (*telegram.ext.Defaults* attribute), 37

U

Unauthorized, 160

unban_chat_member() (*telegram.Bot* method), 131

unban_member() (*telegram.Chat* method), 145

unbanChatMember() (*telegram.Bot* method), 131

UNDERLINE (*telegram.MessageEntity* attribute), 196

unpin() (*telegram.Message* method), 194

unpin_all_chat_messages() (*telegram.Bot* method), 132

unpin_all_messages() (*telegram.Chat* method), 145

unpin_all_messages() (*telegram.User* method), 213

unpin_chat_message() (*telegram.Bot* method), 132

unpin_message() (*telegram.CallbackQuery* method), 138

unpin_message() (*telegram.Chat* method), 145

unpin_message() (*telegram.User* method), 213

unpinAllChatMessages() (*telegram.Bot* method), 132

unpinChatMessage() (*telegram.Bot* method), 132

until_date (*telegram.ChatMember* attribute), 147

Update (class in *telegram*), 206

update (*telegram.ext.filters.Filters* attribute), 22

update (*telegram.utils.promise.Promise* attribute), 288

update_bot_data() (*telegram.ext.BasePersistence* method), 72

update_bot_data() (*telegram.ext.DictPersistence* method), 77

update_bot_data() (*telegram.ext.PicklePersistence* method), 74

update_chat_data() (*telegram.ext.BasePersistence* method), 72

update_chat_data() (*telegram.ext.DictPersistence* method), 77

update_chat_data() (*telegram.ext.PicklePersistence* method), 74

update_conversation() (*telegram.ext.BasePersistence* method), 72

update_conversation() (*telegram.ext.DictPersistence* method), 77

update_conversation() (*telegram.ext.PicklePersistence* method), 75

update_id (*telegram.Update* attribute), 206

update_persistence() (*telegram.ext.Dispatcher* method), 11

update_queue (*telegram.ext.CallbackContext* attribute), 36

update_queue (*telegram.ext.Dispatcher* attribute), 8

update_queue (*telegram.ext.Updater* attribute), 5

update_user_data() (*telegram.ext.BasePersistence* method), 73

update_user_data() (*telegram.ext.DictPersistence* method), 77

update_user_data() (*telegram.ext.PicklePersistence* method), 75

UpdateFilter (class in *telegram.ext.filters*), 25

Updater (class in *telegram.ext*), 5

UPLOAD_AUDIO (*telegram.ChatAction* attribute), 146

UPLOAD_DOCUMENT (*telegram.ChatAction* attribute), 146

UPLOAD_PHOTO (*telegram.ChatAction* attribute), 146

upload_sticker_file() (*telegram.Bot* method), 133

UPLOAD_VIDEO (*telegram.ChatAction* attribute), 146

UPLOAD_VIDEO_NOTE (*telegram.ChatAction* attribute), 146

uploadStickerFile() (*telegram.Bot* method), 132

url (*telegram.InlineKeyboardButton* attribute), 163

url (*telegram.InlineQueryResultArticle* attribute), 226

url (*telegram.LoginUrl* attribute), 175

URL (*telegram.MessageEntity* attribute), 196

url (*telegram.MessageEntity* attribute), 195

url (*telegram.WebhookInfo* attribute), 219

use_context (*telegram.ext.Updater* attribute), 6

User (class in *telegram*), 208

user (*telegram.ChatMember* attribute), 147

user (*telegram.GameHighScore* attribute), 270

user (*telegram.MessageEntity* attribute), 195

user (*telegram.PollAnswer* attribute), 200

user_data (*telegram.ext.CallbackContext* attribute), 35

user_data (*telegram.ext.DictPersistence* attribute), 77

user_data (*telegram.ext.Dispatcher* attribute), 9

user_data_json (*telegram.ext.DictPersistence* attribute), 77

user_id (*telegram.Contact* attribute), 157

user_ids (*telegram.ext.filters.Filters.user* attribute), 22

user_sig_handler (*telegram.ext.Updater* attribute), 5

username (*telegram.Bot* attribute), 133

username (*telegram.Chat* attribute), 139

username (*telegram.User* attribute), 208

usernames (*telegram.ext.filters.Filters.chat* attribute), 13

usernames (*telegram.ext.filters.Filters.sender_chat* attribute), 19

usernames (*telegram.ext.filters.Filters.user* attribute), 22

usernames (*telegram.ext.filters.Filters.via_bot* attribute), 23

UserProfilePhotos (class in *telegram*), 213

utility_bill (*telegram.SecureData* attribute), 275

V

value (*telegram.Dice* attribute), 158
value (*telegram.utils.helpers.DefaultValue* attribute), 283
vcard (*telegram.Contact* attribute), 158
vcard (*telegram.InlineQueryResultContact* attribute), 240
vcard (*telegram.InputContactMessageContent* attribute), 260
Venue (class in *telegram*), 214
venue (*telegram.ext.filters.Filters* attribute), 23
venue (*telegram.Message* attribute), 178
via_bot (*telegram.Message* attribute), 180
Video (class in *telegram*), 215
video (*telegram.ext.filters.Filters* attribute), 16, 24
video (*telegram.Message* attribute), 178
video_duration (*telegram.InlineQueryResultVideo* attribute), 254
video_file_id (*telegram.InlineQueryResultCachedVideo* attribute), 237
video_height (*telegram.InlineQueryResultVideo* attribute), 254
video_note (*telegram.ext.filters.Filters* attribute), 24
video_note (*telegram.Message* attribute), 178
video_url (*telegram.InlineQueryResultVideo* attribute), 253
video_width (*telegram.InlineQueryResultVideo* attribute), 254
VideoNote (class in *telegram*), 216
Voice (class in *telegram*), 218
voice (*telegram.ext.filters.Filters* attribute), 24
voice (*telegram.Message* attribute), 178
voice_duration (*telegram.InlineQueryResultVoice* attribute), 255
voice_file_id (*telegram.InlineQueryResultCachedVoice* attribute), 238
voice_url (*telegram.InlineQueryResultVoice* attribute), 255
voter_count (*telegram.PollOption* attribute), 201

W

WAITING (*telegram.ext.ConversationHandler* attribute), 46
watcher (*telegram.ProximityAlertTriggered* attribute), 201
wav (*telegram.ext.filters.Filters* attribute), 17
WebhookInfo (class in *telegram*), 219
width (*telegram.Animation* attribute), 78
width (*telegram.InputMediaAnimation* attribute), 167
width (*telegram.InputMediaVideo* attribute), 172
width (*telegram.PhotoSize* attribute), 197
width (*telegram.Sticker* attribute), 220
width (*telegram.Video* attribute), 215

workers (*telegram.ext.Dispatcher* attribute), 8

X

x_shift (*telegram.MaskPosition* attribute), 223
xml (*telegram.ext.filters.Filters* attribute), 17
XORFilter (class in *telegram.ext.filters*), 26

Y

y_shift (*telegram.MaskPosition* attribute), 223

Z

zip (*telegram.ext.filters.Filters* attribute), 17